

# Technical Memorandum *Appendix*



## **Heroes Tunnel Project Ventilation Study**

*State Project No. 167-108*

October 2019


*Prepared for:*  
**Connecticut  
Department of  
Transportation**



# Appendix A

## Existing Tunnel Plans

This page intentionally left blank.



# CONNECTICUT STATE HIGHWAY DEPARTMENT PLAN FOR CONSTRUCTION


OF  
A TWIN BORE TUNNEL THRU WEST ROCK AND GRADING  
AND DRAINAGE OF A SECTION OF WILBUR CROSS PARKWAY  
IN THE TOWNS OF

NEW HAVEN - WOODBRIDGE - HAMDEN

FROM STA. SEE TO STA. BELOW

LENGTH SEE BELOW FT.

SCALES { PLAN 1 IN. = 40 FT.  
PROFILE HOR. 1 IN. = 40 FT. VERT. 1 IN. = 4 FT.  
CROSS SECTIONS 1 IN. = 5 FT.  
1 IN. = 10 FT.



1947 SPECIFICATIONS FORM 807 GOVERN

ALL ELEVATIONS ON THIS PROJECT ARE BASED ON U.S.C&G. SURVEY DATUM  
TO BE MAINTAINED BY THE STATE

TOWN NO. 185  
PROJECT NO. 90


ROADWAY SECTION { FROM STA. 689+00 TO STA. 708+65 } LENGTH 2560 FT.  
" " 720+65 " " 722+35  
" " 724+75 " " 729+00

TUNNEL SECTION FROM STA. 708+65 TO STA. 720+65 LENGTH 1200 FT.

CONSTRUCTION STARTED: March 10, 1948  
CONSTRUCTION COMPLETED: Oct. 22, 1949  
PLANS REVISED BY: J.M. McCarthy DATE: Oct. 1950  
PLANS CHECKED BY: A. Dozier DATE: Nov. 1950

LIST OF DRAWINGS	
SHEET NO.	TITLE
1	Title sheet
2	Small Scale Plan & Profile
3	Detail Estimate Sheet
4	Typical Cross Sections
5	Details of Type "P" catch Basin
6 thru 13	Plans & Profiles Sta. 689+00 to Sta. 729+00
14 thru 57	Details of West Rock Tunnel Sta. 721+15 to 728+15
58 thru 69	Wilbur Cross Parkway cross sections Sta. 689+10 to 708+10 & Sta. 721+25 to 729+10
70 thru 73	Pond Lily Ave. Ramp Cross Sections
~ STANDARD DRAWINGS ~	
221E	Rein. Conc. Pipe, Perf. A.C.C.M. Pipe Foundation Underdrain
221F	Endwalls
222A	Curbs
223	Manhole
225	Curb Type Catch Basin
226	A.C.C.M. Pipe Elbows
228	Type "C" Catch Basin, Type E.S. Catch Basin, Type C.S. Drop Inlet
241D	Standard Paving Details
242	Load Transfer Units & Metal Plate Shield for Transfer Joints
248	Standard Expanded Metal Mesh Reinforcement for Conc. Pavement
249	Standard Fabric Reinforcement for Conc. Pavement
250	Standard Bar Mat Reinforcement for Concrete Pavement

### STANDARD CONVENTIONS




THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


APPROVED Nov 20 1947  
Ernest J. Peckins  
ENGINEER OF HIGHWAY DESIGN  
APPROVED Nov 20 1947  
D. H. S. Starn  
ENGINEER OF LOCATION & DESIGN  
APPROVED Nov 20 1947  
James M. Crocker  
DIRECTOR OF ENGINEERING & CONSTRUCTION

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	New Haven & Woodbridge		1947		2	73


WILBUR CROSS PARKWAY PROJECT 185-90



INDEX PLAN  
SCALE 1 INCH = 200 FEET



SCALE  
HORT. 1 IN = 200 FT.  
VERT. 1 IN = 20 FT.



THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

PLAN	PROFILE
Surveyed	Surveyed
Plotted	Plotted
Alignment	Grades Plotted
Traced	Traced
New Const. Noted	New Const. Noted
Designed	Designed
NOTE BOOK NO.	NOTE BOOK NO.

BY	DATE	CHECKED BY	DATE

BY	DATE	CHECKED BY	DATE



# TYPICAL CROSS SECTIONS

NOT TO SCALE

PUR. ROAD DIV. NO.	STATE	TOWN	FED. AID PROJ. NO.	PROJ. NO.	YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
1	CONN.	WOODBRIIDGE, NEW HAVEN AND HAMDEN		185-90	1947		4	73

WILBUR CROSS PARKWAY

PROJECT NO. 185-90

Revised Sept 9<sup>th</sup> 1948  
To show raised median strip.

## STAGE CONSTRUCTION

THIS SHEET NOT CORRECTED


Note A:  
For Rock Cut - 0' to 12' 0"; Normal Width of 5' 0"  
For Rock Cut over 12' 0"; Minimum Width of 10' 0"  
or as directed

Note: For details of Rock Slope adjacent to East & West Portals - see Special Cross Section Sheets.


Where Rock is removed to a Flat Slope, it shall be excavated 12" below the normal Slope or as directed. Top of Slope to be rounded as shown or as directed.

ALL LOAM TO BE PLACED BY STATE FORCES

Width of Median Strip, Back to Back of Curbs, varies as shown in detailed instructions on Construction Plans.




## TYPICAL NORMAL SECTION




SKETCH SHOWING TYPICAL SHOULDER TREATMENT IN EARTH CUT

SKETCH SHOWING TREATMENT OF 6'-0" MEDIAN STRIP-NORMAL SECTION




HALF SECTION AT STA. 707+0 & 722+50



### COMBINATION 12" PERF. A.C.C.M.P. & FOUNDATION UNDERDRAIN

Note:  
Where Rock is encountered in constructing "Combination 12" Perf. A.C.C.M.P. & Foundation Underdrain", the Trench shall be excavated to a depth of one foot below the Flow Line and back filled with impervious material. Cost of material to be included in underdrain item.




HALF SECTION AT STA. 708+65 & 720+65  
SHOWING SPECIAL MANNER OF BANKING

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

- NOTES -

For Frame and Grate, see Standard Sheet No. 228.

In such cases and at such locations as the Engineer may direct, on projects where grading only is called for, Type "P" Catch Basin shall be constructed to Line X-X. The Frame and Grate shall be furnished and set securely in mortar, in a manner satisfactory to the Engineer, at this elevation so as to permit the proper drainage of the area intended. The Class "A" Concrete Top and Curb shall be omitted.




TYPICAL SECTION  
POND LILY AVE. RAMP


THIS SHEET NOT CORRECTED

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WILBUR CROSS		1947		5	73


WILBUR CROSS PARKWAY  
Project No. 185-90



SECTION A-A






CURB & TOP  
PLAN  
Scale 1"=1'-0"




SECTION B-B


BAR BILL				
Bar	Size	Length	No.	Total Wt.
A	1/2" φ	5'-10 3/8"	4	15.7 lbs
B	1/2" φ	4'-4"	2	5.8 lbs
C	1/2" φ	1'-0"	10	6.7 lbs
D	1/2" φ	1'-11 1/2"	4	5.3 lbs
TOTAL				33.5 lbs



BAR DETAILS



LONGITUDINAL SECTION



CROSS SECTION

Walls shall be built of Brick, Precast Concrete Units or Class "A" Concrete at the option of the Contractor. Sand Mortar - 1:2 mix. Joints to be not over 1/8" on inside face. Brick Walls are to be plastered outside with 1:2 cement mortar 1/2" thick. Bricks must be wet when mortar is applied.

Pipe to be cut flush with inside of Catch Basin. Work to be included in cost of Catch Basin.

BASE  
Scale 3/4"=1'-0"

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

REVISIONS		
NO.	DATE	DESCRIPTION

CONNECTICUT  
STATE HIGHWAY DEPARTMENT  
**TYPE "P"**  
CATCH BASIN

DESIGNED BY *W.S. Bissell*

SCALES *As Noted*

MADE BY *W.S. Bissell* DATE *6/24/47*

CHECKED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO.	
BRIDGE SHEET NO.	
OF	




**WILBUR CROSS PARKWAY**  
PROJECT 185-90

CENTER PARK TRANSITION -					
STA.	ft to CurbFace	STA.	ft to CurbFace	STA.	ft to CurbFace
689	3.58	692	4.39	695	6.82
750	3.60	750	4.63	750	7.39
690	3.67	693	5.02	696	8.00
750	3.78	750	5.40		
691	3.94	694	5.83		
750	4.14	750	6.31		

**CURVE DATA**  
ALONG FACE OF CURBS  
 $\Delta = 0^{\circ}-48'-01.95''$   
 $D = 0^{\circ}-06'-11.88''$   
 $R = 55468.2$   
 $T = 387.50$   
 $L = 774.99$

**BEGINNING OF PROJECT**  
STA. 689+00



**GENERAL CONSTRUCTION NOTES**

Remove all existing drainage culverts where and as directed.

All proposed drainage may be varied by the Engineer to fit conditions found in the field.

All buildings within the limits of the right of way are to be removed under separate contract.

If so directed, all underdrains, gravel fill, and subbase may be varied as to depth length and location, according to conditions found in the field, or they may be entirely eliminated.


Where buildings have been removed to clear the way for construction or where old foundations and cellar or other holes exist, the removal as directed of the cellar walls and other concrete and masonry to 2 feet below the directed finished grading and the filling of the cellar or other holes will be paid for as per section 2.02.

Type "C-5" Catch Basins shall conform to Std. Drawing #228 except that the open throats adjacent to the inlet grate shall be omitted.

BY	DATE	CHECKED BY	DATE
Surveyed			
Plotted			
Traced			
Designed			
New Const. noted			

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


WILBUR CROSS PARKWAY  
PROJ. 185-90



DATE	
BY	
SURVEYED	
PLOTTED	
GRADES PLOTTED	
GRADES CHECKED	
B. ME. NOTED	
NOTE BOOK NO.	
PROFILE	

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

Slope Rights Required



LOCATION OF WEST PORTAL  
Sta. 708+65

DOMINICK CELOTTO  
Sta. 708+15


**CURVE DATA**  
ALONG FACE OF CURBS  
 $\Delta = 0^\circ - 48' - 01.95''$   
 $D = 0^\circ - 06' - 11.68''$   
 $R = 55468.2$   
 $T = 387.50$   
 $L = 774.99$

CENTER PARK TRANSITION					
STA.	E. to Curbs Face	STA.	E. to Curbs Face	STA.	E. to Curbs Face
696	8.00	+50	14.23	705	16.90
+50	8.66	+74.99	14.58	+50	19.19
+74.99	8.99	701	14.92	706	19.44
697	9.34	+50	15.57	+50	19.64
+50	10.04	702	16.20	707	19.80
698	10.74	+50	16.76	+50	19.91
+50	11.44	703	17.27	708	19.98
699	12.14	+50	17.75	+4998	20.00
+50	12.84	704	18.18		
700	13.54	+50	18.56		

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

PLAN	NO.	BY	DATE	CHECKED BY	DATE
Surveys					
Plotted					
Line plotted					
Traced					
Structures noted					

WILBUR CROSS PARKWAY  
TUNNEL  
185-90



PROFILE NOTE BOOK NO.

Sta. 689+0 to Sta. 707+50 - 8" Subbase as directed


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

100' 140'  
Sta. 707+50 to  
Sta. 708+65  
20' subbase  
as directed

ALL WORK BETWEEN STA. 708+15 AND STA. 721+15 IS INCLUDED IN THE TUNNEL PLANS SHEETS NO. 14 TO 57, EXCEPT DRAINAGE ITEMS AT EAST AND WEST PORTALS.

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WOODBIDGE AND NEW HAVEN		1947		10	73

WILBUR CROSS PARKWAY PROJECT NO. 185-90




PLAN	NOTE BOOK NO.
Surveyed	
Plotted	
Line plotted	
Traced	
Structures noted	

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.



JOSEPH J. SOKOL



B.M. 96 Spike in 18" Oak Elev 179.19

**CURVE DATA ALONG FACE OF CURBS**  
 $\Delta = 0^{\circ}-36'-28.58''$   
 $D = 0^{\circ}-06'-12.54''$   
 $H = 55367.33'$   
 $T = 293.75'$   
 $L = 587.475'$

**CENTER PARK TRANSITION**

STA.	E. TO CURBFACE	STA.	E. TO CURBFACE	STA.	E. TO CURBFACE
720+75	29.00	726	17.51	+50	12.84
721	19.99	+50	17.01	731	12.41
+50	19.95	+62.47	16.88	+50	12.02
722	19.86	727	16.48	732	11.69
+50	19.72	+50	15.95	+50	11.39
723	19.54	728	15.42	733	11.14
+50	19.32	+50	14.89	+50	10.94
724	19.05	729	14.36	734	10.78
+50	18.73	+50	13.83	+50	10.67
725	18.37	+62.47	13.70	735	10.60
+50	17.96	730	13.31	+49.85	10.58

**CURVE DATA ALONG FACE OF CURBS**  
 $\Delta = 0^{\circ}-36'-28.50''$   
 $D = 0^{\circ}-06'-12.54''$   
 $R = 55367.33'$   
 $T = 293.75'$   
 $L = 587.475'$


**R.I. Face of Curbs**  
Sta. 735+49.95

JOHN BADOLI

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE QUANTITIES OR ACCURATE QUANTITIES OF ANY KIND OF WORK WHICH WILL BE REQUIRED.

NOTE: B.C. Lines plotted on this sheet.

WILBUR CROSS PARKWAY  
PROJ. 185-90




DATE	
BY	
PROFILER	
NOTE BOOK NO.	
NO.	

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.




FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CON. N.	NEW HAVEN		1947		14	73

PROJECT NO. 185-90  
NO REVISIONS SUBMITTED FOR THIS SHEET



PLAN  
~Scale 1"=100'~



ELEVATION ALONG & PARKWAY  
Scale { HOR. 1"=100' / VERT. 1"=100' }

NOTE:  
For stationing and details of Borings "B", "C", "D" etc. and 1, 2, 3, 4 & 5, see Sheet No. 3  
For Section "A-A" see Sheet No. 31

~GENERAL NOTES~

This Project to be constructed under the Standard Specifications of the State of Connecticut, Form #801 dated March 1947, and special provisions. Dimensions of reinforcement are to center line of reinforcement bars unless otherwise noted. All bars are deformed bars with splices lapped 45 diameters end placed in contact and wired together, unless otherwise noted. Where Bagged Screened Gravel is specified the contractor has the option of furnishing Screened Gravel or Crushed Stone. The gradation shall be nominal 3/4" in either case.

Adequate keys shall be provided at all construction joints. Construction joints other than those shown will not be permitted without written approval of the Engineer. For definition of "A" Line and "B" Line see Supplementary Specifications, "Special Provisions." Item of Joint Filler For Bridges shall include that required for outside edges of pavement. All Joint Filler shall be premoistened bituminous type of the sizes specified.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE QUANTITIES OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL GENERAL PLAN	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE <u>As Noted</u>	PROJECT NO. _____
MADE BY <u>A.H.R.</u>	TUNNEL SHEET NO. _____
CHECKED BY <u>G.V.</u>	DATE _____
APPROVED _____	1 of 44

# LIST OF DRAWINGS

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		15	73

PROJECT NO. 185-90

SHEET NO.	TITLE
<b>GENERAL</b>	
1 -	GENERAL PLAN
2 -	LIST OF DRAWINGS AND SUMMARY OF QUANTITIES
3 -	BORINGS
<b>ARCHITECTURAL</b>	
4 -	WEST PORTAL - PLAN AND ELEVATIONS
5 -	EAST PORTAL - PLAN AND ELEVATIONS
6 -	ARCHITECTURAL DETAILS - WEST PORTAL ARCH
7 -	ARCHITECTURAL DETAILS - EAST PORTAL ARCH
8 -	ARCHITECTURAL DETAILS - TURRETS
9 -	ARCHITECTURAL DETAILS - TURRETS
10 -	MISCELLANEOUS STONE DETAILS
11 -	TILE AND GRILLE DETAILS - TUNNEL WALLS
12 -	CONTROL ROOM DETAILS
13 -	VENTILATING HOUSE
<b>GRADING</b>	
14 -	WEST PORTAL GRADING PLAN I
15 -	WEST PORTAL GRADING PLAN II
16 -	EAST PORTAL GRADING PLAN I
17 -	EAST PORTAL GRADING PLAN II
18 -	GRADING CROSS SECTIONS
<b>STRUCTURAL</b>	
19 -	WEST AND EAST PORTALS - PROFILES
20 -	WEST PORTAL
21 -	WEST PORTAL - SECTIONS

SHEET NO.	TITLE
<b>STRUCTURAL - CONTINUED</b>	
22 -	WEST PORTAL - SECTIONS
23 -	WEST PORTAL - SECTIONS AND PORTAL DRAINAGE
24 -	EAST PORTAL
25 -	EAST PORTAL - SECTIONS
26 -	EAST PORTAL - SECTIONS
27 -	EAST PORTAL - SECTIONS, DETAILS AND PORTAL DRAINAGE
28 -	CONCRETE DETAILS AT TURRETS
29 -	TYPICAL TUNNEL SECTION TYPE I
30 -	SPECIAL TUNNEL SECTIONS TYPE II & TYPE III
31 -	VENTILATING SHAFT AND CONTROL ROOM
32 -	VENTILATING HOUSE - FRAMING PLAN
<b>MECHANICAL</b>	
33 -	CONTROL ROOM
34 -	DRAINAGE
35 -	VENTILATION
36 -	DETAILS OF FAN
<b>ELECTRICAL</b>	
37 -	WIRING DIAGRAM
38 -	PULL BOX DETAILS
39 -	CONDUIT PLAN - TUNNEL
40 -	CONDUIT DETAILS
41 -	LIGHTING
42 -	FEEDER CABLE PLAN
43 -	CONTROL ROOM CONDUIT PLAN
44 -	GENERAL ARRANGEMENT PLAN - CONTROL ROOM

## SUMMARY OF QUANTITIES

ITEM NO	DESCRIPTION	UNIT	QUANTITY
130	PORTLAND CEMENT	bbl.	21,750
141	JOINT FILLER FOR BRIDGES	s.f.	700
153	DEFORMED STEEL BARS	lb.	673,000
163	MEMBRANE WATERPROOFING	s.y.	1,500
164	METAL FLASHING	lb.	1,000
179	BROKEN STONE FOR BASE	ton	2,860
188	TRANSVERSE EXPANSION JOINT	l.f.	260
191	MAT REINFORCEMENT FOR CONCRETE PAVEMENT	s.y.	6,200
192	STEEL TIE BARS	lb.	1,600
195	CONCRETE FOR PAVEMENT	c.y.	1,380
245	CONCRETE GUTTER	s.y.	350
300 A	PORTAL EXCAVATION	c.y.	29,150
300 B	BAGGED SCREENED GRAVEL	c.y.	530
301	TUNNEL EXCAVATION	c.y.	51,300
302	SHAFT EXCAVATION	c.y.	1,560
303	ROCK EXCAVATION FOR ENLARGEMENTS OF TUNNEL AND VENTILATING SHAFT	c.y.	150
304	PROTECTIVE COATINGS OF CEMENT MORTAR	c.y.	50
305	STEEL ARCH RIBS, SILLS AND COLUMNS	lbs.	365,000
306	PERMANENT TIMBER LAGGING	m.f.b.m.	20
307	STONE PACKING	c.y.	300
308	DRILLING HOLES IN ROCK	l.f.	1,500







ITEM NO	DESCRIPTION	UNIT	QUANTITY
309	GROUT	c.y.	100
310	SAND FOR GROUT	c.y.	100
311	STEEL PIPES FOR GROUTING AND PANNING	l.f.	1,000
312	SHEET STEEL FOR PANNING	lbs.	1,000
313	DOWEL RODS	l.f.	500
314	CONCRETE LINING OF TUNNEL	c.y.	8,820
315	CONCRETE IN PORTALS	c.y.	2,950
316	CONCRETE LINING OF VENTILATING SHAFT	c.y.	820
317	WIRE MESH	lbs.	7,500
318	TUNNEL DRAINAGE SYSTEM	l.s.	
319 A	PORTAL DRAINAGE SYSTEM, 6" V.C. PIPE	l.f.	430
319 B	PORTAL DRAINAGE SYSTEM, 6" C.I. PIPE	l.f.	120
320	GLAZED TILE FACING	s.y.	4,500
321	INTERCEPTING DITCH, STONE MASONRY PAVED (ON HILLSIDE)	s.y.	510
322	BALDWIN PARKWAY DRAINAGE SYSTEM	l.s.	
323	RANDOM ASHLAR STONE MASONRY	c.y.	280
324	DIMENSION STONE MASONRY	c.y.	250
325	CONCRETE SAFETY CURB	c.y.	1,600
326	VENTILATING HOUSE	l.s.	
327	MISCELLANEOUS TUNNEL WORK	l.s.	
328	VENTILATING SYSTEM	l.s.	
329	TUNNEL ELECTRICAL SYSTEM	l.s.	

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL LIST OF DRAWINGS AND SUMMARY OF QUANTITIES	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE _____	PROJECT NO. _____
MADE BY <u>A.H.P.</u>	TUNNEL SHEET NO. _____
CHECKED BY <u>G.V.</u>	2 of 44
APPROVED _____ DATE _____	

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CON N.	NEW HAVEN		1947		16	73

PROJECT NO. 185-90



Note: For Location see General Plan - Sheet N&I

-LEGEND-  
W.L. = Water Level  
G.S. = Ground Surface

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL BORINGS	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS	NEW YORK, N.Y.
SCALE 1" = 10' Vert.	PROJECT NO.
MADE BY R.C.	TUNNEL SHEET NO.
CHECKED BY A.T.W.	3 OF 44
APPROVED _____	DATE _____

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.







FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		19	73

PROJECT NO. 185-90


NO. 185-90-19-73




1/2 ELEVATION AT CENTER MALL



PART ELEVATION AT SIDES




SECTION A-A



PLAN OF JAMBS AT SPRING LINE

NOTE: ELEVATIONS GIVEN ARE TO BED OF STONE



SECTION B B

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

**CONNECTICUT STATE HIGHWAY DEPARTMENT**











**WILBUR CROSS PARKWAY WEST ROCK TUNNEL ARCHITECTURAL DETAILS WEST PORTAL ARCH**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.

SCALE 1/2" = 1'-0"  
MADE BY G.C.C. - H.G.  
CHECKED BY L.J.H. - C.C.C.  
APPROVED \_\_\_\_\_ DATE 11/7/47

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 6 OF 44








THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

NOTE: FOR DETAILS OF TYPE A AND TYPE B QUINS SEE DWG NO. 10


<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
<b>WILBUR CROSS PARKWAY WEST ROCK TUNNEL ARCHITECTURAL DETAILS TURRETS</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD	
ENGINEERS	NEW YORK, N.Y.
SCALE 1/2" = 1'-0"	PROJECT NO.
MADE BY C.G.C.-S.J.I.	TUNNEL SHEET NO.
CHECKED BY C.G.C.-L.J.H.	DATE 11/7/47
APPROVED	8 OF 44






NOTE-GROUT WITH BROKEN STONE AND CEMENT ON ALL TURRETS.


PLAN.




FRONT ELEVATION TURRET D




FRONT ELEVATION TURRET E




FRONT ELEVATION TURRET Y




FRONT ELEVATION TURRET F




SECTION C-C. TURRETS B, E, F.




SECTION D-D. TURRETS Y, F.




STONE-W.




STONE-X.




STONE-Y.




STONE-Z.




CAPSTONE. (1 PIECE)



TYPICAL COPING



COPING AT EXPANSION JOINTS.



PLAN STONE-T.

NOTE-

1-VOLUME OF STONE FOR COPING SHALL BE DETERMINED BY CROSS SECTION AREA TIMES LINEAL LENGTH MEASURED ALONG CENTER LINE.







2-FOR DETAILS OF TYPE A & TYPE B QUINS SEE SHEET NO 10.

NOTE- BATTERED FACES ON ALL TURRETS ARE 3/8" IN 1'-0".

PAYMENT LINES FOR DIMENSION MASONRY COPING STONES & TURRETS.


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL	
<b>ARCHITECTURAL DETAILS TURRETS</b>	
PARSONS, BRINCKERHOFF, HOGAN & MAGDONALD	
ENGINEERS	NEW YORK, N.Y.
SCALE 1/2" = 1'-0"	PROJECT NO.
MADE BY C.C.C.-L.J.H.	TUNNEL SHEET NO.
CHECKED BY C.C.C.-L.J.H.	9 of 44
APPROVED	DATE 11/7/47



LEGEND	
	INDICATES CONCRETE IN SECTION
	INDICATES DIMENSION STONE MASONRY IN PLAN & SECTION
	INDICATES DIMENSION STONE MASONRY IN ELEVATION.
	INDICATES RANDOM ASHLAR STONE MASONRY IN PLAN & SECTION
	INDICATES RANDOM ASHLAR STONE MASONRY IN ELEVATION
	INDICATES METAL IN SECTION
F.P.	INDICATES FINE POINT FINISH
C.P.	INDICATES COARSE POINT FINISH.
S	INDICATES SEAM FACE
S-R	INDICATES SPLIT OR ROCK FACE

- GENERAL NOTES**
- FOR METHODS OF ANCHORING MASONRY SEE STRUCTURAL DRAWINGS.
  - ALL DIMENSION STONE MASONRY & RANDOM ASHLAR STONE MASONRY SHALL BE CARRIED DOWN TO TOP OF CONCRETE ELEVATIONS SHOWN OR NOTED (SEE STRUCTURAL DWGS).
  - ALL COPING AND CAPSTONES SHALL BE DOWELED TO WALLS AND TURRETS WITH 1/2" x 4" LONG BRONZE DOWELS - NOT LESS THAN TWO TO EACH STONE
  - DIMENSION MASONRY JOINTS SHALL BE 1/2" RANDOM ASHLAR STONE MASONRY JOINTS SHALL BE 3/4"
  - RANDOM ASHLAR STONE MASONRY JOINTS SHALL BE RAKED TO A DEPTH OF 1/2" TO 3/4"
  - ALL STONE SURFACES IN CONTACT WITH SLIDING OR EXPANSION JOINTS SHALL BE FINE POINTED
  - POINTING OF DIMENSION STONE MASONRY SHALL BE AS SHOWN ON DETAILS AND UNLESS OTHERWISE NOTED ALL WASHES ON COPINGS AND CAPSTONES AND THE SOFFITS OF ALL ARCH RING STONES SHALL BE FINE POINT. ALL OTHER EXPOSED SURFACES SHALL BE COARSE POINT.
  - TYPE 'A' AND TYPE 'B' QUOINS WILL BE PAID FOR AS DIMENSION STONE MASONRY BUT SHALL BE OF THE SAME SOURCES AND IN THE SAME PROPORTION AS THE RANDOM ASHLAR STONE MASONRY. RETURN FACES SHALL BE POINTED AS DETAILED OR CALLED FOR.
- THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.



PAYMENT LINES  
DIMENSION MASONRY  
QUOINS AT END PIERS.  
(NO SCALE.)

CONNECTICUT  
STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
MISCELLANEOUS STONE  
DETAILS


PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE 1/4" = 1'-0"  
MADE BY C.C.C.-L.J.H.  
CHECKED BY L.J.H.-C.C.C.  
APPROVED \_\_\_\_\_ DATE 11/7/47


PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 10 OF 44

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		24	73


PROJECT NO. 185-90



NICHE & FACING TILE ELEVATIONS TUNNEL WALLS.  
SCALE 1" = 20'-0"



WALL NICHE DETAILS  
SCALE 3/4" = 1'-0"



DETAIL A  
SCALE 2" = FULL SIZE











THE INFORMATION INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT  
WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
TILE & GRILLE DETAILS  
TUNNEL WALLS

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE AS NOTED  
MADE BY C.C.C. - P.S.H.  
CHECKED BY C.C.C. - L.J.H.  
APPROVED \_\_\_\_\_ DATE 11/7/47

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 11 OF 44




THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL	
<b>CONTROL ROOM DETAILS</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE AS NOTED	PROJECT NO.
MADE BY C.C.C.-P.S.H.	TUNNEL SHEET NO.
CHECKED BY C.C.C.-L.J.H.	12 OF 44
APPROVED _____	DATE 11/17/47




Note: Extend Intercepting Ditch to Station 0+00 with gradient not less than 2%



TYPICAL SECTION IN FULL CUT




TYPICAL SECTION STONE MASONRY PAVED INTERCEPTING DITCH Scale - 1/2" = 1'-0"



TYPICAL EXPANSION JT. Spaced 70'± on centers. TYPICAL SECTION CONCRETE PAVED GUTTER TOP OF EAST & WEST PORTALS Scale - 1/2" = 1'-0"

Note: Parkway gutters approaching Portal see Gutter Detail Sheet No. 15  
 Rock Gutters are shown in section, Sheet No. 18  
 For construction of Parkway approach paving see Sheet No. 18  
 See General Notes Sheet No. 16




<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
<b>WILBUR CROSS PARKWAY WEST ROCK TUNNEL WEST PORTAL GRADING PLAN I</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE 1/8" = 1'-0"	PROJECT NO.
MADE BY R.T.	TUNNEL SHEET NO.
CHECKED BY J.W.T.	DATE
APPROVED	14 OF 44


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		28	73

PROJECT NO. 185-90



GUTTER DETAIL  
Scale 1/2"=1'-0"



VENTILATING HOUSE  
Scale 1/8"=1'-0"

See Sheet Nos. 14, 16 for all notes.


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
WEST PORTAL  
GRADING PLAN II**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE 3/8"=1'-0"	PROJECT NO.
MADE BY R.T.	TUNNEL SHEET NO.
CHECKED BY J.W.T.	15 of 44
APPROVED _____	DATE _____



FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		29	73

PROJECT NO. 185-90

NOTE  
 For Typical Section of Concrete Paved Gutter see Sheet No. 14  
 Parkway Gutter approaching Portal see Gutter Detail Sheet No. 15  
 Rock Gutters are shown in section, Sheet No. 18  
 For construction of Parkway approach paving see Sheet No. 18

GENERAL NOTES FOR GRADING

Existing Contours	
Finished Contours	
Reinforced Concrete Pipe	
Excavation Spot Grades - Mall	186.95
Finished Spot Grades	186.95

The subgrade in all unpaved areas shall be 4" below finished contours and spot grades except for rock gutters, rock ledges, exposed rock slopes as shown, cut and fill areas for intercepting ditch, and center mall.

In center mall the subgrade shall be 6" below finished grade.

For rock gutters and ledges, and rock slopes, excavation shall be to finished grade.

Cut and fill areas for intercepting ditch, the work shall be carried to finished grade.

Subgrade for paved intercepting ditch and gutters as shown on Sheet No. 14

See Sheet No. 18 for Excavation, Pay Line under approach paving

In unpaved areas the top 3' of fill up to subgrade to be selected and approved material.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
 WEST ROCK TUNNEL  
 EAST PORTAL  
 GRADING PLAN I

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD

ENGINEERS NEW YORK, N.Y.

SCALE 1/8" = 1'-0"

MADE BY J.W.T.


CHECKED BY J.W.T.

APPROVED DATE

PROJECT NO.

TUNNEL SHEET NO.

16 of 44




185 90

147 03



FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		30	73

PROJECT NO. 185-90  
Sta. 721-15



-NOTE-  
See Sheet No. 16  
for all notes.

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
EAST PORTAL  
GRADING PLAN II**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE 1/8" = 1'-0"  
MADE BY J.W.T.  
CHECKED BY J.W.T.  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 17 OF 44


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

PROJECT NO. 185-90

NO PORTALS SUBMITTED FOR THIS SHEET

NOTE

For additional spot grades and finished contours in front and behind Portals, and General Notes See Sheet No's 14, 15, 16, 17 Excavation Pay Line



**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL**

**GRADING  
CROSS SECTIONS**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.


SCALE VER. & HOR. 1" = 10'-0"  
MADE BY J.W.T.  
CHECKED BY J.W.T.  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. \_\_\_\_\_  
18 OF 44


NO REVISIONS SUBMITTED FOR THIS SHEET

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		32	73

PROJECT NO. 185-90




PROFILE 40' FT NORTH OF P'KWAY.




PROFILE 40' FT NORTH OF P'KWAY.

WEST PORTAL




PROFILE ALONG PARKWAY




PROFILE ALONG PARKWAY

EAST PORTAL



PROFILE 40' FT. SOUTH OF P'KWAY



PROFILE 40' FT. SOUTH OF P'KWAY.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
<b>WILBUR CROSS PARKWAY WEST ROCK TUNNEL WEST AND EAST PORTALS PROFILES</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE 1"=10' Hor. & Vert.	PROJECT NO.
MADE BY P.C.	TUNNEL SHEET NO.
CHECKED BY A.T.W.	19 OF 44
APPROVED _____	DATE _____

185 901


147 03

PROJECT NO. 185-90

REVISIONS SUBMITTED FOR THIS SHEET



PLAN



ELEVATION


- NOTES**
1. For General Notes see Sheet No. 1
  2. For Sections A-A, B-B, C-C, D-D, H-H, X-X, & Y-Y see Sheet No. 21
  3. For Sections E-E, P-P, R-R, S-S, T-T & Z-Z see Sheet No. 23
  4. For Sections J-J, K-K, L-L, M-M, N-N, Q-Q, U-U, V-V, & W-W see Sheet No. 22
  5. Section F-F similar to Section F-F East Portal shown on Sheet No. 25
  6. Section G-G similar to Section G-G East Portal shown on Sheet No. 25
  7. Sections A-A, B-B & C-C similar to Section X-X East Portal shown on Sheet No. 25
  8. For Portal Drainage see Sheet No. 23
  9. For Tunnel Drainage see Sheet No. 34
  10. For Details and location of Electrical Conduits see Sheets No. 39 & 40
  11. For Elevations and dimensions of stone steps see Sheet No. 4

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL WEST PORTAL	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD	
ENGINEERS	NEW YORK, N.Y.
SCALE 1/8" = 1'-0"	PROJECT NO.
MADE BY G.V.	TUNNEL SHEET NO.
CHECKED BY A.B.J.	DATE
APPROVED	20 of 44


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		34	73


PROJECT NO. 185-90




SECTION A-A




SECTION B-B




SECTION X-X




SECTION C-C




SECTION Y-Y




SECTION D-D




SECTION V-V




SECTION H-H



SECTION U-U



SECTION S-S



SECTION T-T

NOTE "A":  
Square off rock face in front of Portals and pour concrete to rock face.

- NOTES:
- 1- For General Notes See Sheet #1
  - 2- For Wall and slab reinforcing not shown see Sheet #20
  - 3- Terminate waterproofing in reglet as shown in Detail "C" Sheet #27
  - 4- For location of Sections: A-A, B-B, C-C, D-D, H-H, X-X & Y-Y See Sheet #20


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL WEST PORTAL SECTIONS	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD	
ENGINEERS	NEW YORK, N.Y.
SCALE: 1/4" = 1'-0"	PROJECT NO.
MADE BY: G.V.	TUNNEL SHEET NO.
CHECKED BY: A.B.J.	21 OF 44
APPROVED _____	DATE _____

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		35	73

PROJECT NO. 185-90

NOTE "A"  
Square off rock in front of Portals and pour concrete to rock face.  
NOTE: SEE REVISED SHEET NO. 20A.



- SECTION M-M
- NOTES
1. For Wall and Slab reinforcing not shown see Sheet No. 20
  2. Terminate waterproofing in register as shown in DETAIL "C" Sheet No. 27
  3. For location of Sections J-J, K-K, L-L, M-M, N-N, Q-Q, U-U, V-V, & W-W see Sheet No. 20
  4. Section S-S similar to Section S-S East Portal see Sheet No. 27
  5. For General Notes see Sheet No. 1

CONNECTICUT  
STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
WEST PORTAL  
SECTIONS

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD

ENGINEERS NEW YORK, N.Y.

SCALE 1/8" = 1'-0" Unless noted

MADE BY G.V.

CHECKED BY A.B.J.

APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. \_\_\_\_\_

TUNNEL SHEET NO. 22 OF 44


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

NO REVISIONS SUBMITTED FOR THIS SHEET


FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		35	73

PROJECT NO 185-90


RECEIVED  
 29th Highway Dept.  
 NOV 11 1948



SECTION MM




SECTION NN



PLAN


E EAST SOUND TUNNEL

See Sheet 20 for portion of West Portal not shown.




ELEVATION  
SCALE 1/8"=1'-0"

- NOTES:
1. These revisions supersede Sections C-C, D-D, M-M, N-N, and Q-Q shown on Sheet No 22.
  2. For Section L-L see Sheet No 22.
  3. For General Notes see Sheet No 1.



VIEW AA

SECTION BB



SECTION UU  
PARTS NOT SHOWN SAME AS SHOWN FOR SECTION UU SHEET NO. 22


CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL WEST PORTAL REVISIONS AT SOUTH END OF PORTAL	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS	NEW YORK, N.Y.
SCALE 1/8"=1'-0" UNLESS NOTED. MADE BY - G.V. CHECKED BY - ABJ APPROVED _____ DATE _____	PROJECT NO. _____ TUNNEL SHEET NO. 22A






FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		37	73

PROJECT NO. 185-90



PLAN

NOTE: Dimensions given along face of wall.



ELEVATION

- NOTES
1. For General Notes see Sheet No. 1
  2. For Sections A-A, B-B, C-C, L-L, M-M, N-N, O-O, P-P, Q-Q, R-R, T-T, & U-U see Sheet No. 26
  3. For Sections E-E, F-F, G-G, & X-X see Sheet No. 25
  4. For Sections D-D, J-J, K-K, S-S, V-V & W-W see Sheet No. 27
  5. Section H-H similar to Section G-G Sheet No. 25
  6. Sections A'-A', B'-B' & C'-C' similar to Section X-X shown on Sheet No. 25
  7. For Portal Drainage see Sheet No. 27
  8. For Tunnel Drainage see Sheet No. 34
  9. For Details and location of Electrical Conduits see Sheets No. 39 & 40
  10. For Elevations and dimensions of stone steps see Sheet No. 5

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
EAST PORTAL**


PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE 1/8" = 1'-0"


MADE BY G.V.  
CHECKED BY A.B.J.  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 24 OF 44


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.




SECTION J-J




SECTION K-K




SECTION L-L




PLAN - NO. WINGWALL EAST PORTAL




SECTION M-M




CROSS SECT. A-A



SECTION Q-Q



SECTION R-R



ELEV. - NO. WINGWALL


**NOTES**  
 These revisions supersede Sections J-J, K-K, L-L, M-M, Q-Q & R-R shown on Sh.#24. For Sections H-H, V-V & W-W see Sh.#25 & 27. For General Notes see Sh.#1. Terminate Waterproofing in right as shown in DETAIL C sheet # 27. Install 6" V.C. Tile Drain similar to North Wingwall of West Portal as shown on Sh.#23.

Steps for stone masonry to be maintained at original Elevations as shown on Sheet #5, in order to retain the architectural design.


CONNECTICUT STATE HIGHWAY DEPARTMENT  
 WILBUR CROSS PARKWAY  
 WEST ROCK TUNNEL  
**EAST PORTAL**  
 REVISED NORTH WINGWALL

Scale 1/4" = 1'-0"  
 Made by J.H.A.M.  
 Checked by  
 Approved by  
 Project No. 185-90  
 Tunnel Sh. No. 24A


PROJECT NO. 185-90



SECTION E-E




SECTION F-F




SECTION G-G



SECTION K-K



SECTION A-A



SECTION X-X

**NOTE "A":**

Square off rock in front of Portals and pour concrete to rock face.

**NOTES:**











- 1 - For General Notes see Sheet No. 1
- 2 - For Wall and slab steel not shown see Sheet No. 24
- 3 - Terminate waterproofing in reglet as shown in Detail "C" Sheet No. 27
- 4 - For location of Sections: E-E, F-F, G-G, & X-X. see Sheet No. 24

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL EAST PORTAL SECTIONS	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE: 1/4" = 1'-0"	PROJECT NO.
MADE BY: G.V.	TUNNEL SHEET NO.
CHECKED BY: A.B.J.	DATE: 25 OF 44
APPROVED: _____	

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		39	73

PROJECT NO. 185-90




NOTE 'A'  
Square off rock in front of Portals and pour concrete to rock face.

- NOTES
1. For General Notes see Sheet No. 1
  2. For wall and slab reinforcing see Sheet No. 24
  3. Terminate waterproofing in register as shown in DETAIL "C" Sheet No. 27
  4. For location of Sections A-A, B-B, C-C, L-L, M-M, N-N, O-O, P-P, Q-Q, R-R, T-T & U-U, see Sheet No. 24

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
<b>WILBUR CROSS PARKWAY WEST ROCK TUNNEL EAST PORTAL SECTIONS</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD	
ENGINEERS	NEW YORK, N.Y.
SCALE: 1/4" = 1'-0" Unless Noted	PROJECT NO.
MADE BY: G.V.	TUNNEL SHEET NO.
CHECKED BY: A.G.V.	26 OF 44
APPROVED: _____	DATE: _____



**CONNECTICUT STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY WEST ROCK TUNNEL**


**EAST PORTAL SECTIONS, DETAILS & PORTAL DRAINAGE**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD


ENGINEERS	NEW YORK, N.Y.
SCALE 1/4"=1'-0" unless noted	PROJECT NO.
MADE BY G.V.	TUNNEL SHEET NO.
CHECKED BY A.B.V.	27 of 44
APPROVED	DATE

- NOTE "A"**  
Square off rock in front of Portals and pour concrete to rock face.
- NOTES:**
- For General Notes see Sheet No. 1
  - For Wall and Slab Reinforcing not shown see Sheet No. 24
  - Terminate Waterproofing in reglet as shown in Detail "C"
  - For location of Sections D-D, J-J, K-K, S-S, V-V, & W-W see Sheet No. 24


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.




TURRET - A




TURRET - F




TURRETS - B & C



TURRET - E



TURRET - X



TURRET - Y

NOTE:-  
For location see East & West Portals  
Sheets N<sup>o</sup> 20 & N<sup>o</sup> 24

CONNECTICUT  
STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
CONCRETE DETAILS AT TURRETS



PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE: 1/2" = 1'-0"  
MADE BY: C.C.C.  
CHECKED BY: A.B.J.  
APPROVED: \_\_\_\_\_ DATE: \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 28 OF 44

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


PROJECT NO. 185-90



COORDINATES OF TUNNEL ARCH

Y	X	0	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	12.5
INTRADOS---Y <sub>1</sub>		10.50	10.49	10.47	10.37	10.20	17.97	17.68	17.31	16.88	16.39	15.83	15.21	14.52	13.76	13.36
EXTRADOS---Y <sub>2</sub>		19.50	19.49	19.47	19.38	19.22	19.00	18.73	18.38	17.98	17.51	16.99	16.39	15.74	15.02	14.64
PAYLINE---Y <sub>3</sub>		20.00	19.99	19.97	19.88	19.73	19.52	19.25	18.92	18.53	18.08	17.56	16.99	16.35	15.65	15.28

TYPICAL CROSS SECTION--TYPE I  
WHERE STEEL SUPPORTS ARE NOT REQUIRED



SECTION A-A

~~TYPICAL TUNNEL SECTION~~  
~~NOT USED~~

- NOTES:
1. For General Notes see Sheet No. 1
  2. For location of electrical conduits see Sheet No. 38, 39 & 41
  3. For location of tunnel drainage see Sheet No. 34
  4. For definition of "A" Line and "B" Line see Supplementary Specifications, "Special Provisions."
  5. For Details and locations of Niches in Walls See Sheet No. 11
  6. For Details and locations of Niches for Lights See Sheet No. 41
  7. For Details of Control Room See Sheet No. 31
  8. For Details of Expansion and Construction Joints in Pavement See: "Standard Paving Details"

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**


**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
TYPICAL TUNNEL SECTION  
TYPE I**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS NEW YORK, N.Y.


SCALE 1/2"=1'-0"  
MADE BY P.C.  
CHECKED BY G.V.  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 29 of 44

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.



**TYPICAL CROSS SECTION TYPE II**  
WHERE STEEL SUPPORTS ARE REQUIRED  
~Scale 1/2"=1'-0"



**TYPICAL CROSS SECTION TYPE III**  
WHERE TOP OF ROCK IS BELOW SPRING LINE OF ARCH AND FOR CUT AND COVER SECTION.  
~Scale 4"=1'-0"

- NOTES:
1. For General Notes see Sheet No. 1
  2. For location of electrical conduits see Sheet Nos. 38, 39 & 41
  3. For location of tunnel drainage see Sheet No. 34
  4. For definition of "A" Line and "B" Line see Supplementary Specifications "Special Provisions."
  5. For Details of Curbs and Roadway see Sheet No. 29
  6. For Coordinates of Intrados see Sheet No. 29
  7. For Details of Expansion and Construction Joints in pavement see "Standard Paving Details"
  8. For Details and locations of Niches in Walls see Sheet No. 11
  9. For Details and locations of Niches for Lights see Sheet No. 41









THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
<b>WILBUR CROSS PARKWAY WEST ROCK TUNNEL SPECIAL TUNNEL SECTIONS TYPE II &amp; TYPE III</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD	
ENGINEERS NEW YORK, N.Y.	
SCALE <i>As Noted</i>	PROJECT NO.
MADE BY <i>R.C.</i>	TUNNEL SHEET NO.
CHECKED BY <i>G.V.</i>	30 OF 44
APPROVED _____	DATE _____



FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		44	73

PROJECT NO. 185-90



**NOTES:-**  
 For Location of Section A-A See Sheet #1  
 For Sections C-C & D-D See Sheet #32  
 For Section B-B See Section B-B Sheet #33  
 For General Notes See Sheet #1  
 For Details Not Shown See Architectural Dwg.  
 For Drainage see Sheet #34  
 For Electrical Conduits see Sheet #43

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


**CONNECTICUT STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY WEST ROCK TUNNEL VENTILATING SHAFT AND CONTROL ROOM**


PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS  
NEW YORK, N.Y.

SCALE: 1/4" = 1'-0" Unless noted.  
 MADE BY: P.C.  
 CHECKED BY: G.V.  
 APPROVED: \_\_\_\_\_ DATE: \_\_\_\_\_


PROJECT NO. \_\_\_\_\_  
 TUNNEL SHEET NO. 31 OF 44




**ROOF FRAMING PLAN**  
SCALE: 1/4" = 1'-0"




**SECTION A-A**  
SCALE: 3/4" = 1'-0"




**SECTION B-B**  
SCALE: 3/4" = 1'-0"




**SECTION M-M**  
SCALE: 3/4" = 1'-0"





**SECTION D-D**  
SCALE: 1" = 1'-0"




**SECTION E-E**  
SCALE: 1" = 1'-0"




**SECTION F-F**  
SCALE: 3/4" = 1'-0"




**SECTION C-C**  
SCALE: 1/4" = 1'-0"




**PLAN D-D**  
SCALE: 1/4" = 1'-0"



**DETAIL "K"**  
SCALE: 1" = 1'-0"



**SECTION G-G**  
SCALE: 3/4" = 1'-0"



**DETAIL "L"**  
SCALE: 1" = 1'-0"

**NOTES:**  
Rivets 3/4"  
Open Holes 1 1/2" Unless Noted  
For Location of Section C-C and Plan D-D See Sheet # 31  
For Details Not Shown See Architectural Dwg.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

**CONNECTICUT STATE HIGHWAY DEPARTMENT**






**WILBUR CROSS PARKWAY WEST ROCK TUNNEL VENTILATING HOUSE FRAMING PLAN**

PARSONS, BRINGERHOFF HOGAN & MACDONALD

ENGINEERS	NEW YORK, N.Y.
SCALE As Shown	PROJECT NO.
MADE BY P.C.	TUNNEL SHEET NO.
CHECKED BY G.Y.	32 OF 44
APPROVED	DATE

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		46	73

PROJECT NO. 185-90



SECTION B-B

SECTION A-A

SECTION D-D

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL CONTROL ROOM	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE 1/4" = 1'-0"	PROJECT NO.
MADE BY J.P.	TUNNEL SHEET NO.
CHECKED BY S.R.A.P.	33 OF 44
APPROVED _____	DATE _____

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		47	73

PROJECT NO. 185 - 90


See Revised Drawing Sheet No 47A for Sump For Ramp Drain

See Revised Drawing Sheet No 47A for Catch Basin with Sump

See Revised Drawing Sheet 47A For Catch Basin without Sump




**GENERAL PLAN**  
Scale in Feet




**SECTION D D**


17'x24' C.I. Gutter Box - 200' Ctrs.  
8' 45' C.I. Inlet Bend  
Clow - National Pipe Products  
F-3720 & F-3722  
or Equal




**SECTION C C**



**PLAN**  
**SECTION B B**  
**CONTROL ROOM**  
Scale: 1/4" = 1'-0"




**INNER CURB**




**CURB DETAILS**  
Scale: 1" = 1'-0"

**OUTER CURB**




**SECTION A A**  
Scale: 1" = 1'-0"



**DETAIL OF RAMP DRAIN**  
Scale: 1/2" = 1'-0"


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL DRAINAGE	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE: AS NOTED	PROJECT NO.
MADE BY: J.P.	TUNNEL SHEET NO.
CHECKED BY: S.R. Apt	34 of 44
APPROVED: _____	DATE: _____




NOTE: DIMENSIONS NOT SHOWN ARE THE SAME AS IN DRAWING FOR "OUTER CURB."


DETAIL OF CATCH BASIN WITHOUT SUMP  
Scale 1" = 1'-0"



SECTION G-G




SECTION F-F  
Scale 1" = 1'-0"




NOTE: DIMENSIONS NOT SHOWN ARE THE SAME AS IN DRAWING FOR "OUTER CURB."

DETAIL OF CATCH BASIN WITH SUMP  
Scale 1" = 1'-0"



SECTION E-E



DETAIL OF SUMP FOR RAMP DRAIN  
Scale 1/2" = 1'-0"

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


CONNECTICUT  
STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
DRAINAGE REVISIONS

SCALES AS NOTED	NUMBER
MADE BY M. Kramer DATE 12-22-47	185-90
CHECKED BY _____ DATE _____	SHEET NO.
APPROVED _____ DATE _____	34A OF 44


FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		48	73

PROJECT NO. 185-90




GENERAL PLAN  
SCALE IN FEET  
0 40 80


Note: Niches inside Walls to be located at Tile Joints See Sh. No. II




PLAN CONTROL ROOM  
Scale: 4" = 1'-0"




DETAIL OF CO VENTILATION CONTROL NICHE  
Scale: 1" = 1'-0"



SECTION A-A



DETAIL OF CO<sub>2</sub> FIRE EXTINGUISHER NICHE  
Scale: 1" = 1'-0"



SECTION B-B

For Detail of Doors for Niches See Sheet No. II


CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL VENTILATION	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD	
ENGINEERS	NEW YORK, N.Y.
SCALE: AS NOTED	PROJECT NO.
MADE BY: S.S.	TUNNEL SHEET NO.
CHECKED BY: S.R. Apt	35 OF 44
APPROVED: _____	DATE: _____

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		49	73

PROJECT NO. 185-90


*No Revision Furnished For This Sheet*



PLAN



SECTION A-A



SECTION B-B

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**


**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
DETAILS OF FAN**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE: 1" = 1'-0"  
MADE BY: S.S.  
CHECKED BY: S.R. Act  
APPROVED: \_\_\_\_\_ DATE: \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. **36** OF 44

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.



THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
WIRING DIAGRAM**


PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE \_\_\_\_\_ PROJECT NO. \_\_\_\_\_  
MADE BY *R.J.J.* TUNNEL SHEET NO. \_\_\_\_\_  
CHECKED BY *H.K.A.* DATE \_\_\_\_\_ 37 of 44  
APPROVED \_\_\_\_\_




FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		51	73


PROJECT NO. 185-90




TYPICAL DETAILS OF TYPE "A" PULL BOX  
Scale: 1/2" = 1'-0"





TYPICAL DETAILS OF TYPE "B" PULL BOX  
Scale: 1/2" = 1'-0"





TYPICAL DETAILS OF FRAME & COVER OF PULL BOXES  
Scale: 1/2" = 1'-0"




1" x 1/2" Steel Stop Bar to be Welded to 2" x 1/2" x 1/4" Angle Iron as shown.  
Full Size



DETAILS OF CONDUIT UNDER ROAD & TYPES "C" & "D" PULL BOXES  
Scale: 1/2" = 1'-0"








TYPICAL DETAILS OF ISOLATING TELEPHONE LINE IN PULL BOX  
Scale: 1/2" = 1'-0"



- NOTES:**
- 1 - See Conduit Plan before pouring Concrete.
  - 2 - Transite Board Shall be fastened by 1 1/2" No. 8 Parker-Kalon Screws.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL PULL BOX DETAILS	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE <i>As Shown</i>	PROJECT NO.
MADE BY <i>M.W.S.</i>	TUNNEL SHEET NO.
CHECKED BY <i>H.A.B.</i>	38 OF 44
APPROVED _____	DATE _____

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.



THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

- SYMBOLS**
- Portal Lights Outlets
  - Tunnel Lights Outlets
  - ⊕ Telephone
  - ⊙ Elec. Eye
  - ⊙ Traffic Lights
  - ⊕ Traffic Light Control
  - ⊕ Fire Extinguisher
  - ⊕ C.O. Vent. Control
  - ⊕ Manhole
  - ⊕ Pull Box Type "A"
  - ⊕ " " "B"
  - ⊕ " " "C"
  - ⊕ " " "D"

- NOTES**
- ① For Details of Fixture Outlets See General Lighting Plan.
  - ② For Details of Conduit Pull Boxes See Pull Box Details.
  - ③ For Control Conduit Plan See Control Room Conduit Plan.
  - ④ Dimensions shown in Plan locating Telephones, Traffic Light Controls, Fire Extinguishers and C.O. Controls are plus and minus dimensions. Niches in side walls for these items to be located at tile joints. See Sheet #11.

**CONNECTICUT STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY WEST ROCK TUNNEL CONDUIT PLAN-TUNNEL**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD


ENGINEERS NEW YORK, N.Y.

SCALE As Shown PROJECT NO. \_\_\_\_\_


MADE BY M.W.S. TUNNEL SHEET NO. 39 OF 44

CHECKED BY DATE \_\_\_\_\_



APPROVED DATE \_\_\_\_\_




ELEVATION OF WEST PORTAL OF EAST BOUND TUNNEL  
Scale: 4"=1'-0"




SECTION "A-A"




TYPICAL DETAIL OF MANHOLE & COVER  
Scale: 1/4"=1'-0"




TYPICAL DETAIL OF TRAFFIC LIGHTS & TRAFFIC CONTROL INSTALLATION  
Scale: 4"=1'-0"




CROSS SECTION VIEW OF INSTALLATION OF OVERHEAD CONDUIT FOR FIRE EXTINGUISHER  
Scale: 4"=1'-0"




TYPICAL DETAIL OF C.O. DETECTOR INSTALLATION  
Scale: 4"=1'-0"



TYPICAL DETAIL OF TELEPHONE CONDUIT INSTALLATION  
Scale: 4"=1'-0"



TYPICAL DETAIL OF FIRE EXTINGUISHER INSTALLATION  
Scale: 4"=1'-0"




DETAILS OF TRAFFIC LIGHTS WITH FLASHER

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


<b>CONNECTICUT STATE HIGHWAY DEPARTMENT</b>	
<b>WILBUR CROSS PARKWAY WEST ROCK TUNNEL CONDUIT DETAILS</b>	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE <i>As Shown</i>	PROJECT NO.
MADE BY <i>M.W.S.</i>	TUNNEL SHEET NO.
CHECKED BY <i>J.H.B.</i>	40 OF 44
APPROVED _____	DATE _____

PROJECT NO. 185-90




NOTE: Niches in Side Walls to be located at Tile Joints See Sheet #11

GENERAL PLAN  
Scale: 1" = 40'




TUNNEL LIGHTING FIXTURE  
FORM 79 - 300 W  
Scale: 1 1/2" = 1'-0"




PORTAL LIGHTING FIXTURE  
TYPE L-43 - 750 W  
Scale: 1 1/2" = 1'-0"


- SYMBOLS**
- ☒ Tunnel Lights 300 W.
  - + Portal Lights 750 W.
  - ☎ Telephone
  - ⊙ Electric Eye
  - Traffic Lights
  - ⊠ Traffic Light Control
  - Fire Alarm & CO<sub>2</sub> Fire Extinguisher
  - Power Supply
  - CO Ventilation Control



PLAN OF CONTROL ROOM  
Scale: 1/4" = 1'-0"



SECTION "A-A"  
Scale: 1/4" = 1'-0"




SECTION "B-B"  
Scale: 1/4" = 1'-0"

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CONNECTICUT STATE HIGHWAY DEPARTMENT	
WILBUR CROSS PARKWAY WEST ROCK TUNNEL LIGHTING	
PARSONS, BRINCKERHOFF, HOGAN & MACDONALD ENGINEERS NEW YORK, N.Y.	
SCALE <i>As Shown</i>	PROJECT NO.
MADE BY <i>M.W.S.</i>	TUNNEL SHEET NO.
CHECKED BY <i>H.K.B.</i>	41 of 44
APPROVED _____	DATE _____

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		55	73

PROJECT NO. 185-90



CONNECTICUT  
STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
FEEDER CABLE PLAN

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD

ENGINEERS NEW YORK, N.Y.

SCALE 1"=100'  
MADE BY M.W.S.  
CHECKED BY H.R.P.  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO.  
TUNNEL SHEET NO.  
42 OF 44


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

Traced by A.L.M.

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		56	73

PROJECT NO. 185-90

NO DIMENSIONS SHOWN FOR THIS SHEET



CONTROL ROOM CONDUIT PLAN  
Scale: 1/2"=1'-0"

CONNECTICUT  
STATE HIGHWAY DEPARTMENT

WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
CONTROL ROOM CONDUIT PLAN

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE 1/2"=1'-0"  
MADE BY M.W.S.  
CHECKED BY H.A.B.  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_


PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. 43 OF 44

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		57	73

PROJECT NO. 185-90


NO PROVISIONS SUBMITTED FOR THIS SHEET





PLAN



SECTION A-A



SECTION C-C



ELEVATION OF SWITCHBOARD  
(DOORS REMOVED)

**CONNECTICUT  
STATE HIGHWAY DEPARTMENT**

**WILBUR CROSS PARKWAY  
WEST ROCK TUNNEL  
GENERAL ARRANGEMENT PLAN  
CONTROL ROOM**

PARSONS, BRINCKERHOFF, HOGAN & MACDONALD  
ENGINEERS  
NEW YORK, N.Y.

SCALE  $\frac{1}{2}'' = 1'-0''$

MADE BY *M.W.S.*

CHECKED BY *J.E.B.*

APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

PROJECT NO. \_\_\_\_\_  
TUNNEL SHEET NO. **44 OF 44**


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

# CROSS SECTIONS

SCALE 1 INCH = 10 FEET

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947	120	58	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



NOTE BOOK NO. A-185-05-02

Ground Surface Platted by	S.B.
" " Checked by	H.A.M.
Template Sections Platted by	H.T.P.
" " Checked by	L.B.W.
Areas by	H.U.T.
" " Checked by	L.B.W.
Template Sections Revised by	
" " Checked by	
Final Areas by	
" " Checked by	
Quantity Transferred and Inked by	

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

147 03

185-90




CROSS SECTIONS

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		59	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



NOTE BOOK NO. A-185-05-02

Ground Surface Platted by S.B.  
 " " Checked by H.A.M.  
 Template Sections Platted by L.B.W.  
 " " Checked by C.H.W.  
 Areas by L.B.W.  
 " " Checked by C.H.W.  
 Template Sections Revised by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_

185

147 03


# CROSS SECTIONS

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		60	73

## WILBUR CROSS PARKWAY PROJECT 185-90

For Pond Lily Ave. Ramp  
See Pond Lily Ave. Ramp  
Cross Sections.



NOTE BOOK NO. A-185-05-02

Ground Surface Platted by H.A.M.  
 " " Checked by S.B.  
 Template Sections Platted by L.B.W.  
 " " Checked by H.V.S.  
 Areas by L.B.W.  
 " " Checked by H.V.S.  
 Template Sections Revised by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED.

**CROSS SECTIONS**

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WOODBIDGE		1947		61	73

**WILBUR CROSS PARKWAY**  
PROJECT 185-90



**NOTE BOOK NO. 185-23 A**  
 Ground Surface Plotted by H.V.T.  
 " " Checked by L.Z.  
 Template Sections Plotted by L.B.M.  
 " " Checked by M.J.S.  
 Drawn by D.A.P.  
 " " Checked by M.V.S.  
 Template Sections Revised by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CROSS SECTIONS

Scale 1 inch=10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WOODBIDGE		1947		62	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



NOTE BOOK NO. 185-23-A  
 Ground Surface Plotted by S.S.W.  
 Checked by L.Z.  
 Template Sections Plotted by T.H.S.  
 Checked by M.V.S.  
 Areas by D.A.P.  
 Checked by M.V.S.  
 Template Sections Revised by  
 Checked by  
 Final Areas by  
 Checked by  
 Quantity Transferred and Inked by

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES. DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


147 03

CROSS SECTIONS

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WOODBIDGE		1947		63	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



NOTE BOOK NO. 185-23-A  
 Ground Surface Platted by S.J.W.  
 " " Checked by L.Z.  
 Template Sections Platted by L.B.W.  
 " " Checked by H.W.G.  
 Areas by H.W.G.  
 " " Checked by M.V.S.  
 Template Sections Revised by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

# CROSS SECTIONS

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WOODBIDGE		1947		64	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



NOTE BOOK NO. 185-23-A

Ground Surface Platted by	S.S.W.
" " Checked by	L.Z.
Template Sections Platted by	L.B.W.
" " Checked by	H.W.G.
Areas by	D.A.P.
" " Checked by	H.W.G.
Template Sections Revised by	
" " Checked by	
Final Areas by	
" " Checked by	
Quantity Transferred and Inked by	


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

# CROSS SECTIONS

SCALE 1 INCH = 10 FEET

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	WOODBIDGE		1947	140	65	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



**NOTE BOOK NO. 185-23-A**

Ground Surface Platted by	S.S.W.
" Checked by	L.Z.
Template Sections Platted by	T.S.
" Checked by	
Areas by	D.A.P.
" Checked by	M.J.S.
Template Sections Revised by	
" Checked by	
Final Areas by	
" Checked by	
Quantity Transferred and Inked by	


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CROSS SECTIONS

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947		66	73

WILBUR CROSS PARKWAY  
Project 185-90



NOTE BOOK NO. 185-23-A

Ground Surface Platted by S.S.W.  
 Checked by L.Z.  
 Template Sections Platted by T.H.S.  
 Checked by L.B.W.  
 Areas by H.W.G.  
 Checked by L.B.W.  
 Template Sections Revised by \_\_\_\_\_  
 Checked by \_\_\_\_\_  
 Final Areas by H.T.T.  
 Checked by T.R.  
 Quantity Transferred and Inked by \_\_\_\_\_

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.




CROSS SECTIONS

Scale 1 inch=10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	NEW HAVEN		1947	120	67	73

WILBUR CROSS PARKWAY  
PROJECT 185-90



NOTE BOOK NO. 185-23-A  
 Ground Surface Plotted by S.S.W.  
 Checked by L.Z.  
 Template Sections Plotted by T.H.S.  
 Checked by H.B.W.  
 Area by H.W.G.  
 Checked by L.B.W.  
 Template Sections Revised by \_\_\_\_\_  
 Checked by \_\_\_\_\_  
 Final Area by \_\_\_\_\_  
 Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CROSS SECTIONS

Scale 1 inch = 10 feet

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	HAMDEN		1947	120	68	73

WILBUR CROSS PARKWAY  
Project 185-90



1/8  
3/4  
7/8

20' to 1/2" = 10' SECTION

Top Bank


NOTE BOOK NO. 185-23-A  
Ground Surface Plotted by S.S.W.  
Checked by L.Z.  
Plate Sections Plotted by T.H.J.  
Checked by L.B.W.  
Checked by T.R.  
Checked by L.W.B.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CROSS SECTIONS  
SCALE 1 INCH = 10 FEET

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	FISCAL YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	HAMDEN		1947		69	73

WILBUR CROSS PARKWAY  
PROJECT 185-90




NOTE BOOK NO. 185-23 A  
Ground Surface Platted by S.S.W.  
" " Checked by L.Z.  
Template Sections Platted by T.H.S.  
" " Checked by L.B.W.  
Areas by T.R.  
" " Checked by L.B.W.  
Template Sections Revised by \_\_\_\_\_  
" " Checked by \_\_\_\_\_  
Final Areas by \_\_\_\_\_  
" " Checked by \_\_\_\_\_  
Quantity Transferred and Inked by \_\_\_\_\_

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

CROSS SECTIONS  
SCALE 1 INCH=5 FEET  
FORM No. Eng. 13 Ed. 6-45

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	STATE PROJ. NO.	YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	New Haven and Westbridge			1947		70	73

WILBUR CROSS PARKWAY  
PROJECT NO. 185-90  
POND LILY AVE. RAMP



NOTE BOOK NO. 185-66-A  
Ground Surface Plotted by G.S. Koch  
" " Checked by L.E. Fitts  
Template Sections Plotted by L. Osterling  
" " Checked by J.J. O'Brien  
Areas by H. Cahoon  
" " Checked by J.J. O'Brien  
Final Sections Plotted by \_\_\_\_\_  
" " Checked by \_\_\_\_\_  
Final Areas by \_\_\_\_\_  
" " Checked by \_\_\_\_\_  
Quantity Transferred and Inked by \_\_\_\_\_

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.


# CROSS SECTIONS

SCALE 1 INCH=5 FEET

FORM NO. ENG. 13 ED. 6-45

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	STATE PROJ. NO.	YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	New Haven and Woodbridge		185-90	1947		71	73

WILBUR CROSS PARKWAY  
PROJECT NO. 185-90  
POND LILY AVE. RAMP



**NOTE BOOK NO. 185-66A**

Ground Surface Plotted by G.S. Koch  
 " " Checked by L.E. Flitz  
 Template Sections Plotted by L. Osterling  
 " " Checked by J.J. O'Brien  
 Areas by J.J. O'Brien  
 " Checked by H. Caboon


Final Sections Plotted by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by Conerly  
 " " Checked by Raymond  
 Quantity Transferred and Inked by \_\_\_\_\_

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

**CROSS SECTIONS**  
 SCALE 1 INCH=5 FEET  
 Form No. Eng. 13 Ed. 6-45

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	STATE PROJ. NO.	YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
7	CONN.	New Haven and Woodbridge			1947		72	73

WILBUR CROSS PARKWAY  
 PROJECT NO. 185-90  
 POND LILY AVE. RAMP



**NOTE BOOK NO. 185-66 A**  
 Ground Surface Plotted by G.S. Koch  
 " " Checked by L.E. Fitts  
 Template Sections Plotted by L. Osterling  
 " " Checked by J.J. O'Brien  
 Areas by J.J. O'Brien  
 " " Checked by H. Cahoon  
 Final Sections Plotted by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OF DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

# CROSS SECTIONS

SCALE 1 INCH=5 FEET  
FORM NO. ENG. 13 E-6-45

FED. ROAD DIST. NO.	STATE	TOWN	FED. AID PROJ. NO.	STATE PROJ. NO.	YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
9	CONN.	New Haven and Woodbridge		185-90	1947		73	73

WILBUR CROSS PARKWAY  
PROJECT NO. 185-90  
POND LILY AVE. RAMP



**NOTE BOOK NO. 185-66A**

Ground Surface Plotted by G. S. Koch  
 " " Checked by L. E. Fitta  
 Template Sections Plotted by L. Osterling  
 " " Checked by J. J. O'Brien  
 Areas by J. J. O'Brien  
 " " Checked by H. Cahoon  
 Final Sections Plotted by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Final Areas by \_\_\_\_\_  
 " " Checked by \_\_\_\_\_  
 Quantity Transferred and Inked by \_\_\_\_\_

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OR ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

147 03

185 90

E1.90

WEST ROCK TUNNELS  
CONSTRUCTED UNDER THE SUPERVISION  
OF THE  
CONNECTICUT STATE HIGHWAY DEPARTMENT  
COMPLETED NOVEMBER 1949

GOVERNORS

RAYMOND E. BALDWIN

JAMES L. McCONAUGHY

WILBERT SNOW

JAMES J. SHANNON

CHESTER BOWLES

HIGHWAY COMMISSIONERS

WILLIAM J. COX

G. ALBERT HILL

DEPUTY HIGHWAY COMMISSIONERS

ARTHUR W. BUSHELL

ROY E. JORGENSEN

CONSULTING ENGINEERS

PARSONS BRINCKERHOFF HALL AND MACDONALD

CONTRACTORS

GULL CONTRACTING CO. INC AND L. G. DEFELICE & SON INC. NEW YORK N.Y.

4-8

3-6

Scale - 4" = 1'-0"



PROPOSED COMMEMORATIVE TABLET  
WEST ROCK TUNNEL - NEW HAVEN CONN  
CONNECTICUT STATE HIGHWAY DEPARTMENT  
165 Capital Avenue Hartford Conn.



Sept 2-1949 Drawn by G.L.D.

Material - BRONZE - SHOT BLASTED  
LETTERS - Roman - Static - Polished Faces  
Fastenings - 4- Exp. Bolts of Bronze

One Required - Mounted on one Face.  
Completely erected - by - Oct 15-1949.

147 03





NORTH HALF

Frame No.	Date Taken	Cond. of Frame	Avg. Rdg.	Avg. Diff.	Stress
132	10-4	Unloaded	.0636	-	-
	10-11	Loaded	.0655	+.0019	+5700
	10-25	"	.06445	+.00085	+2350
	10-29	"	.06587	+.00227	+6810
	11-2	"	.0623	-.0013	-3900
167	10-25	Unloaded	.07115	-	-
	10-29	Loaded	.0721	+.00095	+2805
	11-2	"	.06863	-.00252	-7560
	11-18	"	.0661	-.00505	-15150
175	10-29	Unloaded	.06505	-	-
	11-2	Loaded	.0609	-.00415	-12450
	11-18	"	.06418	-.00095	-2850

SOUTH HALF

Frame No.	Date Taken	Cond. of Frame	Avg. Rdg.	Avg. Diff.	Stress
132	10-4	Unloaded	.07125	-	-
	10-11	Loaded	.07385	+.0026	+7800
	10-25	"	.0729	+.00165	+4950
	10-29	"	.07333	+.00208	+6240
	11-2	"	.0705	-.00075	-2250
167	10-25	Unloaded	.06653	-	-
	10-29	Loaded	.05733	-.0092	-27600
	11-2	"	.0644	-.00213	-6390
	11-18	"	.06783H	+.0013	+3900
175	10-29	Unloaded	.06967	-	-
	11-2	Loaded	.06827	-.0014	-4200
	11-18	"	.06993B	+.00026	+780

NORTH HALF

Frame No.	Date Taken	Cond. of Frame	Avg. Rdg.	Avg. Diff.	Stress
163	10-26	Unloaded	.06567	-	-
	10-29	Loaded	.06473	-.00094	-2820
	11-1	"	.06083	-.00484	-14520
	11-18	"	.05892	-.00675	-20250
169	10-29	Unloaded	.06263	-	-
	11-1	Loaded	.0567	-.00593	-17790
	11-18	"	.05966	-.00297	-8910
172	11-1	Unloaded	.06473	-	-
	11-18	Loaded	.06903	+.0043	+12900

SOUTH HALF

Frame No.	Date Taken	Cond. of Frame	Avg. Rdg.	Avg. Diff.	Stress
163	10-26	Unloaded	.06777	-	-
	10-29	Loaded	.06787	+.00017	+510
	11-1	"	.06595	-.00175	-3250
	11-18	"	.0657	-.0020	-6000
169	10-29	Unloaded	.0699	-	-
	11-1	Loaded	.0693	-.0006	-1800
	11-18	"	.07047	+.00057	+1710
172	11-1	Unloaded	.07385	-	-
	11-18	Loaded	.0755	+.00165	+4950

\*-Roof of Frame Shifted South

H-Blocked and Hid by Rock  
B-Blocked

CONNECTICUT  
STATE HIGHWAY DEPT.

## WEST ROCK TUNNEL

Stress Readings on Steel Frames

Scale 1/2" = 1'-0"	Project No.
Made By H.S.F.	Sheet No.
Checked By J.M.	1 of 1
App. By	Date 11-23-48

Deformation Readings taken by C.L. Nord  
Check " " " W. Brandt  
Avg. Ehrenfels  
Recording made by Aug. Ehrenfels

# Appendix B

## Reference Documents – NCHRP 216

This page intentionally left blank.

NATIONAL  
COOPERATIVE  
HIGHWAY  
RESEARCH  
PROGRAM

# NCHRP

Web-Only Document 216:

## Emergency Exit Signs and Marking Systems for Highway Tunnels

Laura Higgins  
Paul Carlson  
Jeff Miles  
Texas A&M Transportation Institute  
The Texas A&M University System  
College Station, TX

Stephen Rozyckie  
Martha Averso  
David Graham  
Brian Seip  
Gannett Fleming, Inc.  
Harrisburg, PA

Gunnar Jenssen  
SINTEF Technology and Society  
Trondheim, Norway

Contractor's Final Report for NCHRP Project 20-59(47)  
Submitted August 2015



TRANSPORTATION RESEARCH BOARD

*The National Academies of*

SCIENCES • ENGINEERING • MEDICINE

### **ACKNOWLEDGMENT**

This work was sponsored by the American Association of State Highway and Transportation Officials (AASHTO), in cooperation with the Federal Highway Administration, and was conducted in the National Cooperative Highway Research Program (NCHRP), which is administered by the Transportation Research Board (TRB) of the National Academies of Sciences, Engineering, and Medicine.

### **COPYRIGHT INFORMATION**

Authors herein are responsible for the authenticity of their materials and for obtaining written permissions from publishers or persons who own the copyright to any previously published or copyrighted material used herein.

Cooperative Research Programs (CRP) grants permission to reproduce material in this publication for classroom and not-for-profit purposes. Permission is given with the understanding that none of the material will be used to imply TRB, AASHTO, FAA, FHWA, FMCSA, FRA, FTA, Office of the Assistant Secretary for Research and Technology, PHMSA, or TDC endorsement of a particular product, method, or practice. It is expected that those reproducing the material in this document for educational and not-for-profit uses will give appropriate acknowledgment of the source of any reprinted or reproduced material. For other uses of the material, request permission from CRP.

### **DISCLAIMER**

The opinions and conclusions expressed or implied in this report are those of the researchers who performed the research. They are not necessarily those of the Transportation Research Board; the National Academies of Sciences, Engineering, and Medicine; or the program sponsors.

The information contained in this document was taken directly from the submission of the author(s). This material has not been edited by TRB.

*The National Academies of*  
SCIENCES • ENGINEERING • MEDICINE

The **National Academy of Sciences** was established in 1863 by an Act of Congress, signed by President Lincoln, as a private, non-governmental institution to advise the nation on issues related to science and technology. Members are elected by their peers for outstanding contributions to research. Dr. Ralph J. Cicerone is president.

The **National Academy of Engineering** was established in 1964 under the charter of the National Academy of Sciences to bring the practices of engineering to advising the nation. Members are elected by their peers for extraordinary contributions to engineering. Dr. C. D. Mote, Jr., is president.

The **National Academy of Medicine** (formerly the Institute of Medicine) was established in 1970 under the charter of the National Academy of Sciences to advise the nation on medical and health issues. Members are elected by their peers for distinguished contributions to medicine and health. Dr. Victor J. Dzau is president.

The three Academies work together as the **National Academies of Sciences, Engineering, and Medicine** to provide independent, objective analysis and advice to the nation and conduct other activities to solve complex problems and inform public policy decisions. The Academies also encourage education and research, recognize outstanding contributions to knowledge, and increase public understanding in matters of science, engineering, and medicine.

Learn more about the National Academies of Sciences, Engineering, and Medicine at [www.national-academies.org](http://www.national-academies.org).

---

The **Transportation Research Board** is one of seven major programs of the National Academies of Sciences, Engineering, and Medicine. The mission of the Transportation Research Board is to increase the benefits that transportation contributes to society by providing leadership in transportation innovation and progress through research and information exchange, conducted within a setting that is objective, interdisciplinary, and multimodal. The Board's varied activities annually engage about 7,000 engineers, scientists, and other transportation researchers and practitioners from the public and private sectors and academia, all of whom contribute their expertise in the public interest. The program is supported by state transportation departments, federal agencies including the component administrations of the U.S. Department of Transportation, and other organizations and individuals interested in the development of transportation.

Learn more about the Transportation Research Board at [www.TRB.org](http://www.TRB.org).

# CONTENTS

<b>List of Figures</b> .....	<b>vii</b>
<b>List of Tables</b> .....	<b>viii</b>
<b>Acknowledgments</b> .....	<b>ix</b>
<b>Abstract</b> .....	<b>x</b>
<b>Executive Summary</b> .....	<b>1</b>
Background.....	1
Research Approach and Results .....	2
Focus Group Discussions.....	2
Tunnel Simulation.....	2
Sign Visibility .....	4
Proposed Guidelines .....	5
<b>Chapter 1. Introduction</b> .....	<b>8</b>
<b>Chapter 2. Background</b> .....	<b>9</b>
Human Responses in Tunnel-Related Emergencies .....	9
Lessons Learned from Past Tunnel Disasters .....	9
Laboratory Studies and Simulations .....	10
Sign and Marking Comprehension .....	11
Visibility of Sign and Marking Technologies.....	12
Audio Beacons and Messages.....	13
Existing Standards for Tunnel Emergency Exit Signs and Markings .....	14
Exit Sign Formats and Graphics .....	15
Sign Size .....	15
Sign Placement.....	16
Sign Luminance and Visibility .....	16
Emergency Exit Path and Door Lighting.....	16
Audio Signals.....	17
Expert Input .....	17
Driver Responses to Tunnel Incidents .....	18
Emergency Procedures.....	19
Emergency Announcements and Exit Guidance.....	19
Exit Sign and Marking Considerations .....	20
<b>Chapter 3. Focus Groups—Research Approach and Results</b> .....	<b>21</b>

Procedure and Results.....	21
Slowing/Stopping Traffic in a Tunnel .....	21
Stopped Traffic, Drivers Exiting Vehicles.....	22
Stopped Traffic, Smoke .....	23
DMS Messages .....	23
Audio Announcement .....	26
Leaving Vehicle and Subsequent Actions .....	27
Follow-Up Questions and Other Comments.....	28
Focus Group Conclusions.....	29
<b>Chapter 4. Tunnel Simulation Procedure and Results.....</b>	<b>31</b>
Participant Demographics.....	31
Study Procedures .....	31
Stage 1: Response to Emergency Situation and Messages .....	32
Stage 2: Sign/Marking Comprehension and Visibility .....	34
Exit Survey.....	40
Results.....	40
Stage 1: Response to Emergency Situation and Messages .....	40
Stage 2: Sign Comprehension.....	43
Stage 2: Sign Visibility .....	46
Stage 2: Path Marking Preferences .....	46
Exit Survey Responses.....	49
Tunnel Simulation Conclusions.....	53
Exit Sign Comprehension .....	54
Path Markings and Audio Beacons.....	54
<b>Chapter 5. Photometric Measurement Procedure and Results .....</b>	<b>55</b>
Luminance Measurement Results .....	55
Luminance and Contrast in Smoke.....	57
Detection and Legibility Distances.....	62
Running Man EXIT Signs .....	64
Running Man Directional/Distance Signs .....	66
Text EXIT Signs .....	67
Running Man Symbol (LED).....	68
Emergency Phone and Refuge Point Signs.....	69
PL Path Marker .....	70



Photometric Measurement and Visibility Conclusions .....	71
<b>Chapter 6. Conclusions, Recommendations, and Suggested Research.....</b>	<b>72</b>
Research Conclusions .....	72
Emergency Evacuation Messages.....	72
Emergency Exit Sign and Marking Formats.....	72
Sign Technologies.....	73
Recommendations.....	73
Emergency Evacuation Messages.....	73
Emergency Exit Sign and Marking Formats.....	74
Sign Technologies and Visibility.....	74
Suggested Research .....	75
Emergency Announcements/Messages.....	75
Sign and Marking Formats and Placement .....	75
Implementation of Research Findings and Products .....	76
Initial Implementation—Presentations and Papers on Study Recommendations.....	76
Suggested Future Implementation Projects .....	77
<b>References.....</b>	<b>80</b>

**The proposed set of guidelines, published as a brochure, can be found at <http://www.trb.org/Main/Blurbs/173414.aspx>.**

## LIST OF FIGURES

Figure 1. Exit door sign format.....	6
Figure 2. Sample exit directional sign formats.....	6
Figure 3. Running man exit symbol, from ISO 7010.....	15
Figure 4. Layout for tunnel simulation.....	32
Figure 5. Tunnel simulation, Stage 1: video clip viewed from vehicle.....	33
Figure 6. View of simulated tunnel, with partially dissipated smoke.....	37
Figure 7. Viewing distance/angle for test signs.....	38
Figure 8. Mounting brackets for test signs (shown without ambient smoke).....	38
Figure 9. LED path lights in simulated tunnel.....	39
Figure 10. Exit survey, question 1.....	49
Figure 11. Exit survey, question 2.....	50
Figure 12. Exit survey, question 3.....	50
Figure 13. Exit survey, question 4.....	51
Figure 14. Exit survey, question 5.....	51
Figure 15. Exit survey, questions 6 and 7.....	52
Figure 16. Exit survey, questions 8 and 9.....	52
Figure 17. Exit survey, question 10.....	53
Figure 18. Exit survey, question 11.....	53
Figure 19. Equipment used to measure smoke opacity, sign luminance and contrast.....	55
Figure 20. Luminance measurements of selected LED and PL negative contrast signs.....	58
Figure 21. Contrast ratios: running man signs vs. tunnel wall, with ambient light.....	59
Figure 22. Contrast ratios: running man signs vs. tunnel wall, no ambient light.....	59
Figure 23. Contrast ratios: sign positive/negative luminance areas, with ambient light.....	60
Figure 24. Contrast ratios: sign positive/negative luminance areas, with no ambient light.....	61
Figure 25. Luminance measurements of selected LED and PL positive contrast signs.....	61
Figure 26. Contrast ratios: sign positive/negative luminance areas of EXIT text-only signs, with ambient light.....	62
Figure 27. Estimated detection and legibility distances at varying smoke opacity percentages.....	64
Figure 28. Detection distances for running man EXIT signs, LED and PL.....	65
Figure 29. Legibility distances for running man EXIT Signs, LED and PL.....	65
Figure 30. Detection distances for running man direction/distance signs, LED and PL.....	66
Figure 31. Legibility distances for running man direction/distance signs, LED and PL.....	67
Figure 32. Detection distances for text EXIT signs, LED and PL.....	68
Figure 33. Legibility distances for text EXIT signs, LED and PL.....	68
Figure 34. Detection and legibility distances for running man symbol-only sign (LED).....	69
Figure 35. Detection distances for emergency phone and refuge point signs.....	70
Figure 36. Legibility distances for emergency phone and refuge point signs.....	70
Figure 37. Detection distances for PL path marker.....	71

## LIST OF TABLES

Table 1. Participating Subject Matter Experts. ....	18
Table 2. Focus Group Participant Demographics. ....	21
Table 3. Tunnel Simulation Participant Demographics. ....	31
Table 4. Experimental Groups for Tunnel Simulation. ....	32
Table 5. Signs, Markings, and Beacons Tested in Tunnel Simulation, Stage 2. ....	35
Table 6. Viewing Orders of the Test Signs during Stage 2 of the Tunnel Simulation. ....	36
Table 7. Summary of Participant Responses to Tunnel Simulation, Stage 1. ....	40
Table 8. Tunnel Simulation, Stage 1: Additional Information Wanted. ....	43
Table 9. Comprehension Scores for Symbol-Only Signs. ....	44
Table 10. Comprehension Scores for Signs with Text. ....	45
Table 11. Path/Door Marking Comparisons. ....	47
Table 12. Signs Measured with Photometric Equipment. ....	56
Table 13. Luminance Measurements and Conditions. ....	57
Table 14. Detection and Legibility Distances Predicted at Varying Smoke Opacity Levels. ....	63
Table 15. Implementation Activities by Research Team. ....	77
Table 16. Suggested Future Implementation Projects. ....	78

## **ACKNOWLEDGMENTS**

The research reported herein was performed under NCHRP Project 20-59(47) by the Texas A&M Transportation Institute (TTI), a member of The Texas A&M University System. The research team gratefully acknowledges the input of the Regulatory and Warning Signs Technical Committee of the National Committee on Uniform Traffic Control Devices, as well as that provided by the 20-59(47) project panel. Thanks also go to Jeremy Johnson, Dan Walker, Ivan Lorenz, Kai Johnson, Sarah Hammond, Christine Yager, Sarah Badillo, Paige Ericson, David Dobrovolsky, Neal Johnson, and Rod Cavness, all of TTI, for their valuable help with preparing for and conducting data collection for the human factors studies, and to Dr. Srinivas Geedipally of TTI for his input on data analysis.

## ABSTRACT

This research project focused on determining effective messages for encouraging drivers to leave their vehicles and evacuate a tunnel on foot; determining sign and marking formats that most effectively lead people to emergency tunnel exits; and determining the most visible sign and marking materials and technologies for use in highway tunnel environments.

Focus groups were conducted to explore potential evacuation messages and delivery methods. Next, a simulated tunnel environment was used to test driver responses to emergency messages, and to test visibility and comprehension of selected emergency exit signs and markings, including the running man pictogram prescribed in the International Organization for Standardization's 7010 guidelines. Results indicate that the running man pictogram was correctly or partially understood as indicating an exit by a majority of participants, and that a directional sign with the pictogram, "EXIT" text, a directional arrow, and distance in feet was correctly understood by virtually all participants. Visibility distances of tested internally illuminated signs were somewhat longer than those of tested photoluminescent signs; visibility for all sign technologies dropped sharply when viewed through smoke. The final product is a proposed set of guidelines for emergency exit signs, markings, and messages for use in tunnels in the United States, published as a brochure, which can be found at <http://www.trb.org/Main/Blurbs/173414.aspx>.

## **EXECUTIVE SUMMARY**

Emergencies such as vehicle crashes, fires, hazardous waste spills, or terrorist activities can be particularly hazardous when they occur inside long underground tunnels. The enclosed environment of a highway tunnel can concentrate heat, smoke, or other toxic gases resulting from the incident; limited right-of-way means that even a partially blocked lane can potentially trap vehicles and hinder access for emergency responders. As a result, tunnel users may need to evacuate themselves on foot via emergency exits. This research study examined emergency exit signs, markings, and messages intended for use in highway tunnels. The study's three primary objectives were as follows:

- To evaluate the effectiveness of emergency messages and their delivery methods (i.e., visual, audible, or both) to encourage drivers to leave their vehicles and evacuate a tunnel on foot.
- To evaluate the effectiveness of sign messages, as well as signing and marking formats, to lead people to emergency tunnel exits.
- To evaluate the visibility of different sign and marking materials and technologies for use in highway tunnel environments, in particular when a tunnel is filled with smoke.

## **BACKGROUND**

Studies of past tunnel emergencies have found that tunnel users often do not act independently to evacuate themselves on foot, instead choosing to remain in or near their vehicles. Some reasons for making the potentially fatal decision not to evacuate are the lack of awareness of an unfolding hazard, uncertainty about the appropriate course of action, reluctance to leave the perceived safety of the vehicle, and reluctance to abandon property. During an emergency, people have a tendency to wait for information or instruction rather than seeking it out. If and when people do decide to exit a tunnel in the face of a recognized danger, a common tendency is to try to reach the main tunnel portal entrance through which they drove into the tunnel, rather than emergency exits for pedestrians, which may be nearer. In fact, drivers may not be aware of the existence of emergency exits or cross passageways and therefore may not recognize the purpose of exit doors along the tunnel wall. Additionally, people tend to overestimate the amount of time they have to evacuate during a fire, a potentially fatal mistake since fire and smoke can spread more quickly in a tunnel fire than in a building.

In the absence of emergency responders to give directions, in-tunnel signs, marking systems, lighting, and/or audible signals must provide direction to tunnel users. Both the need to evacuate and the location of the nearest emergency exits must be clearly communicated. Additionally, the signs and markings must be visible to pedestrians under potentially adverse viewing conditions, including darkness and smoke. Existing guidelines that address aspects of emergency exit signs and markings for highway tunnels include the following:

- Directive 2004/54/EG of the European Parliament establishes minimum safety requirements for all roadway tunnels on the Trans European Roadway Network that are longer than 500 meters. One of the objectives of the guidelines is to improve conditions for self-rescue from a tunnel in an emergency, including guidelines for evacuation lighting and signing.

- The National Fire Protection Association (NFPA) is a nonprofit organization with members from nearly 100 nations. As part of its mission, NFPA has developed approximately 300 codes and standards for mitigating the risk and effects of fires. Three NFPA codes that directly address emergency exit signs and markings for highway tunnels are NFPA 502, *Standard for Road Tunnels, Bridges, and Other Limited Access Highways*; NFPA 170, *Standard for Fire Safety and Emergency Symbols*; and NFPA 101, *Life Safety Code*.
- The International Building Code's (IBC's) guidelines do not directly apply to exit door and exit pathway signs and markings in tunnels; however, they represent a standard for exit signing in buildings that is consistent and recognized throughout the United States.
- The International Commission on Illumination's (CIE's) 193-2010 Emergency Lighting in Road Tunnels provides guidelines for emergency lights and markings for pedestrians in highway tunnels, including marking recommendations for emergency exit doors.

## **RESEARCH APPROACH AND RESULTS**

Building on prior research and existing U.S., European, and international standards for emergency exit signs and markings, researchers tested selected messages, sign and marking formats, and sign and marking technologies with volunteer participants. Research activities included focus group discussions and a simulation of a tunnel emergency situation involving smoke. The expert panel discussion included tunnel operators and emergency responders, and their responses were used to revise the focus group discussion and tunnel fire simulation, as well as to identify potential maintenance or other technical issues associated with signs and markings.

### **Focus Group Discussions**

Two focus group discussions were conducted to gain a better understanding of how tunnel users might respond to various tunnel incident scenarios and warnings. Participants were presented with pictures, videos, and audio clips pertaining to a hypothetical emergency involving fire inside a highway tunnel. Participants discussed how they might react to a similar situation, what types of information and messages would be most effective, and what might influence their decisions to either stay in their vehicle or evacuate the tunnel on foot. The results of the focus group discussions included the following:

- Participants indicated that uncertainty about what is happening might lead to a delayed or incorrect response, so it would be important to relay to tunnel occupants details about the emergency or at least instruct the drivers to evacuate the tunnel.
- The messages that participants found most useful included a brief statement about the emergency, followed by a direct action statement. Examples of this type of message, displayed on an electronic message sign, included “Emergency—walk to exits” and “Fire in tunnel—walk to exits.” Audio messages including the same information elements were also considered effective.

### **Tunnel Simulation**

The tunnel simulation tested individual responses to a tunnel emergency scenario similar to those discussed by the focus groups and tested several sign and marking formats and

technologies within the simulated tunnel environment, both for participants' comprehension of and confidence in various formats and for detection and legibility distances through smoke.

### *Response to Emergency Situation and Messages*

Stage 1 of the tunnel exercise simulated a vehicle trip through a highway tunnel that was stopped by a traffic jam, followed by the appearance of smoke in the tunnel and sounds of stopped traffic and tunnel ventilation. One-third of participants received only these visual and auditory cues to the situation, another one-third also saw a dynamic message sign (DMS) with the message "Fire in tunnel—walk to exits," and a final one-third heard a longer audio message: "Attention—there is a vehicle fire in the tunnel. Turn off your engine and leave your keys in the vehicle so that it can be moved by emergency personnel. Leave your vehicle and walk quickly to emergency exits." Results of Stage 1 included the following:

- While all three groups included participants who indicated that they would stay in their vehicle as well as participants who indicated they would leave the vehicle, the two groups of participants who received a message about the incident (either visually or audibly) were much more likely to say they would leave the vehicle and exit on foot (81 percent of those who saw the DMS and 73 percent of those who heard the audio announcement) versus the group who received no message (20 percent).
- When asked what additional information they would want or need regarding the situation, participants who had not received a message were most likely to request information about the nature and seriousness of the situation, as well as instructions about what they should do. Participants who had received either of the two messages were most likely to ask about the locations of the exits and how to identify them.

### *Sign Comprehension*

Participants viewed nine signs. Three of the signs were symbol-only signs: a "running man" symbol-only sign, a "refuge point" sign, and an emergency telephone sign. Researchers asked participants what they thought each of these signs meant. The other six signs all incorporated the word "EXIT," and participants were asked where they would expect to find an exit door based on each sign. Some of the principal results from the comprehension testing included the following:

- The stand-alone running man symbol was identified correctly by 48 percent of participants as an exit sign, while another 38 percent assumed that the sign indicated a direction or path for them to follow.
- All signs that included the word "EXIT" were correctly identified by all participants as indicating a tunnel exit. Comprehension scores for signs with "EXIT" text, therefore, measured participants' understanding of an exit's location relative to the location of the sign.
- Once the running man symbol was paired with the word "EXIT," most participants thought that the running man sign (with or without the word "EXIT") indicated a direction, even without a supplemental arrow. Therefore, participants most frequently assumed that the running man symbol indicated an exit to the side of the sign or farther away in the direction that the running figure was facing. However, participants saw the



test signs in the context of a wall-mounted frame and so did not have the added context of a visible doorway.

- A small number of participants did not recognize the chevron arrows on a text-only EXIT sign as directional arrows. All participants recognized tailed arrows as indicating a direction.
- When the running man sign was paired with a (tailed) directional arrow and a distance, comprehension of the exit's location relative to the sign was perfect among nearly all participants.
- When a running man exit sign included an arrow but no specified distance, many participants assumed that an exit was nearby in the direction of the arrow; if no distance was provided, they assumed the distance to the exit was very short.

### *Path Marking Preferences*

Participants were presented with four pairs of exit path/door marking formats and asked to select the option from each pair that they would feel most confident about following to an exit:

- Steady-state light-emitting diode (LED) lights vs. LED lights flashing in unison.
- Unison-flash LED lights alone vs. unison-flash LED lights plus an audio beacon saying, "Exit here."
- Unison-flash LED lights vs. traveling LED lights that illuminated in a left-to-right sequence.
- Unison-flash LED lights plus an "exit here" audio beacon vs. traveling LED lights.

In general, participants preferred flashing lights over steady-state lights, and traveling lights that indicated a direction over unison-flash lights. An audio beacon was a favored option to indicate the location of doorway; however, when the audio beacon was compared against traveling/directional pathway lights, many participants indicated that the traveling lights would be more useful farther away from an exit door, and the audio beacon would be helpful close to the door.

### **Sign Visibility**

To assess the visibility of the signs tested, researchers measured the luminance of each sign's positive (brighter) and negative (darker) areas, as well as of the gray walls and frames surrounding the signs. Measurements were conducted in clear conditions and in smoky conditions with smoke opacity levels of 4, 5, 10, 12 and 23 percent, and in both low ambient light and darkness. The measurements were used to calculate the contrast ratio of each sign compared to the tunnel wall, and also the contrast ratio of each sign's positive and negative elements, i.e., sign legend versus sign background. Sign visibility was also measured during participant testing in the tunnel simulation by recording the distances at which participants could detect and read each sign. Some of the signs were internally illuminated by LEDs, while others were photoluminescent (PL).

### *Luminance and Contrast in Smoke*

The luminance measurements showed that the overall luminance levels and the contrast ratios between signs and the tunnel wall, and between the sign legends and background, all

diminished sharply when the signs were viewed through smoke. This significantly affected how far away signs could be seen and also reduced the contrast between their light and dark areas, which made text and symbols more difficult to read. The principal findings from the luminance measurements included the following:

- In general, LED signs in clear conditions had much higher luminance levels than PL signs, and this difference continued when signs were measured in smoky conditions. However, these differences in luminance diminished as smoke opacity increased.
- Under low levels of ambient light, the contrast of sign luminance with the tunnel wall diminished rapidly as smoke opacity increased. In general, LED signs slightly outperformed PL signs. When there was no ambient light, contrast between the tested signs and the tunnel walls was much higher, and PL signs displayed higher contrast ratios than LED signs.
- Contrast ratios between sign legends and backgrounds were consistently higher for PL signs than for LED signs. This was the case with low levels of ambient light and was even more pronounced without ambient light.

### *Detection and Legibility Distances*

During the tunnel simulation, detection and legibility distances were recorded for each sign that participants viewed, as well as for a photoluminescent path marking square. Some of the findings from visibility testing of the signs with study participants included the following:

- For all of the signs, smoke density/opacity was a significant factor in detection and visibility distances, as would be expected from the sharp drop in sign/markings luminance and contrast that was seen in the photometric measurements.
- The LED signs that were tested could be seen from farther away than the tested PL signs, as would be expected from the LED signs' higher luminance values.

## **PROPOSED GUIDELINES**

The findings from the study are summarized in a set of proposed guidelines for the format and placement of emergency exit signs and markings for highway tunnels. The guidelines also address considerations for selecting sign and marking materials and technologies, as well as some preliminary recommendations for public outreach and education pertaining to tunnel emergencies and exit plans. Highlights from the proposed guidelines include the following:

- **Emergency Exit Sign Formats.** Emergency exit door and directional signs should include the running man symbol in combination with the word "EXIT," as shown in Figure 1. Sign colors should be green and white. This sign should be placed on the exit door if possible, or on the tunnel wall immediately to the right or left of the door, preferably with the midpoint of the sign no higher than 1.5 meters (4.9 feet) above the floor.



**Figure 1. Exit door sign format.**

- **Emergency Exit Directional Sign Formats.** Signs indicating directions to emergency exits should be placed at least every 25 meters (82 feet) along the tunnel wall. These signs should include the running symbol and “EXIT” text, with the addition of a tailed directional arrow and the distance to the nearest exit in feet (see Figure 2). If exits are located in two directions relative to the location of the sign, two signs should be placed side by side to indicate the directions and respective distances to the two exits.



**Figure 2. Sample exit directional sign formats.**

- **Exit Door Markings.** The area around each exit door should be illuminated at a level that is three to five times brighter than the illumination of the adjacent walls. In addition, exit doors should be marked with strobe lights that activate only during an emergency. The lights should strobe at a frequency of between 1 Hertz and 2 Hertz; white strobe lights are specified under current NFPA guidelines, though further research may be warranted to compare white versus green strobe lights (recommended by some international guidelines) for this purpose.
- **Exit Door Audio Beacons.** Auditory beacons may be used to supplement (not replace) illuminated exit door lighting. When used, auditory beacons should only contain a single message, such as “exit here” or “refuge shelter,” and may be in more than one language in addition to English. The primary benefit of an audible exit door beacon will be realized in the area close to the door. The decibel level used for the beacon should be calibrated to be audible to listeners within a relatively short radius of the door itself, and the use and type of auditory beacons should take into account the specific acoustic characteristics of the location in which it is used.
- **Exit Path Markings.** Exit path markings can be static or dynamic. If feasible, path markers should indicate a direction to an exit door. This may be accomplished with a dynamic light array, controlled automatically or manually by tunnel operations staff, that lights sequentially to indicate a direction. If directional/sequential LED arrays are not a feasible option, LED lights that can be activated to flash in unison during emergency situations seem to be slightly more effective than steady-state lights for indicating an emergency exit path. Path direction to exit doors can also be accomplished with static

markers that include a directional arrow. Pathway markings should be placed no more than 1 meter (3 feet) above the pathway floor.

- **Emergency Messages.** In the event of an in-tunnel emergency or disruptive incident, it is beneficial to broadcast a message to drivers if possible, visually and/or audibly. In the case of an emergency that requires drivers to evacuate the tunnel on foot, an emergency message can be especially important for encouraging the evacuation. The message should contain, at minimum, the following pieces of information:
  - A brief statement about the nature of the emergency, e.g., “fire in tunnel” or “vehicle fire ahead.”
  - Direct instructions about the action to take, e.g., “walk to exits” or “leave vehicles, walk to exits,” if evacuation on foot is warranted. An evacuation direction (e.g., upstream of the fire) should be specified, if applicable.

An emergency message broadcast via a dynamic message sign should be no more than two phases long, with a maximum of three lines/three bits of information per phase. Auditory messages may permit slightly longer messages than dynamic message signs; however, both loudspeakers and radio override systems can be problematic in a tunnel environment. Wireless emergency alerts may have potential for delivering emergency messages via driver cell phones.

- **Sign Material and Technology Considerations.** Internally lit, externally lit, or photoluminescent signs are all options for tunnel environments. Sign spacing should take sign luminance and associated visibility distance into consideration. Any sign or marking must be capable of withstanding environmental and traffic conditions in a highway tunnel, as well as tunnel cleaning procedures (or should be capable of being removed prior to tunnel cleaning). This can mean waterproofing the housings around electrical components for internally illuminated signs and selecting water-resistant and corrosion-resistant materials and coatings. Photoluminescent signs should be selected according to the availability of ambient light to charge them.
- **Public Education and Outreach.** Public service announcements and/or other public outreach materials may be useful for educating drivers about safe behaviors associated with driving in highway tunnels, including information about tunnel incident procedures and tunnel emergency exits, such as cross passageways and refuge areas as applicable. This type of advance education may improve the responses of drivers in the event of a tunnel-related emergency and may also predispose them to look or listen for emergency announcements during an incident.

## CHAPTER 1. INTRODUCTION

Emergencies such as vehicle crashes, fires, hazardous waste spills, or terrorist activities can be particularly hazardous when they occur inside underground tunnels. Because stopped or trapped vehicles can make it difficult or impossible for emergency responders to quickly reach or respond to an emergency situation in a tunnel, tunnel users must often evacuate themselves. A 2006 scan tour of underground tunnels in Europe found consistent signing in use from country to country for the purpose of directing tunnel users to emergency exits (Ernst et al. 2006). This research project sought to evaluate signs, markings, and auditory messages in order to develop guidelines for use in tunnels in the United States.

The work plan for this project focused on researching three critical issues in order to develop an objective set of guidelines for tunnel emergency exit signs and markings:

1. Determine the messages and delivery methods (visual, audible, or both) that will encourage drivers to leave their cars and exit a tunnel on foot when conditions warrant such an evacuation.
2. Determine the sign graphics and colors, sign messages, marking types and colors, and auditory messages that most effectively lead people to emergency tunnel exits.
3. Determine the most visible sign and marking materials and technologies for dark and smoky conditions.

The project was conducted in four phases. In Phase I, the research team conducted a review of published studies and existing standards pertaining to emergency exit signs and markings, and developed a final research plan for conducting human factors studies. In Phase II, focus group discussions and a simulation of a tunnel environment under emergency conditions were used to measure human response to various signs and markings intended to lead pedestrians safely out of tunnels during emergency situations. A proposed guide for emergency exit signs and marking systems was developed in Phase III. This research report, including the proposed guidelines and an implementation plan for the guidelines, were developed during Phase IV.

## **CHAPTER 2. BACKGROUND**

Vehicle crashes, fires, and other emergency situations pose particular dangers when they occur in long roadway tunnels; the limited space available for vehicle mobility means that a fully or partially blocked travel lane can quickly trap vehicles, and the confined space within a tunnel can also concentrate heat, smoke, or other toxic gases resulting from the incident. An added danger is that emergency responders will be delayed in responding due to the time needed to reach the tunnel and to access the incident scene inside the tunnel, making it necessary for travelers inside the tunnel to evacuate themselves, often on foot. In the absence of emergency responders to provide direction, in-tunnel signs, marking systems, lighting, and/or audible signals must communicate to tunnel users both the need to evacuate and the location of the nearest emergency exits.

### **HUMAN RESPONSES IN TUNNEL-RELATED EMERGENCIES**

Studies of past tunnel emergencies have found that tunnel users often do not act independently to evacuate themselves on foot, instead choosing to remain in or near their vehicles. If and when people do decide to exit a tunnel in the face of a recognized danger, a common tendency is to try to reach the main (vehicular) tunnel portal, rather than emergency exits for pedestrians, which may be nearer. The reasons for these potentially fatal courses of action can include lack of awareness of an unfolding hazard, uncertainty about the appropriate course of action, reluctance to leave the perceived safety of the vehicle, reluctance to abandon property, and (in the case of fire) incorrect assumptions or estimations regarding how quickly the fire and smoke will spread (van Waterschoot et al. 2008, Nilsson et al. 2009).

### **Lessons Learned from Past Tunnel Disasters**

A review of 26 tunnel fires that occurred between 1970 and 2003 found some commonalities in the behaviors and responses of the public. Observations of frequent driver responses to those incidents included the following:

- During an emergency, people have a tendency to wait for information or instruction rather than seeking it out.
- Motorists often do not recognize they are in danger. On an open roadway, stopped traffic or even a vehicle fire is not usually an emergency situation for other vehicles on the road; therefore, motorists without prior education about tunnel fires/hazards may not recognize an unfolding emergency until it is communicated by announcements, message signs, or other signals.
- Drivers are reluctant to abandon their vehicles and personal items.
- The exit that people are most likely to try to reach is the main tunnel portal—that is, the roadway entrance through which they drove into the tunnel. Emergency exits may be missed or disregarded in favor of the more familiar main portal.
- People tend to overestimate the amount of time they have to evacuate during a fire (van Waterschoot et al. 2008).

Several of these observations were tragically illustrated in the Mont Blanc (France-Italy) and Tauern (Austria) tunnel fires in 1999 and the St. Gotthard (Switzerland) tunnel fire of 2001.

The Mont Blanc fire, which began when a truck carrying flour and margarine caught fire inside the 7-mile-long tunnel, resulted in a 53-hour blaze that destroyed 36 vehicles. Of the 39 people who died in the fire, 29 were found still inside their vehicles; others tried to leave but were too late to escape the spread of fire and smoke, or fled to refuge chambers within the tunnel that ultimately failed due to the heat and duration of the fire. The Tauern tunnel fire, the result of a vehicle collision that in turn exploded a truck's cargo of spray paint cans, killed eight people in the initial crash and another four in the fire that followed. The St. Gotthard tunnel fire, which also resulted from a vehicle collision inside the tunnel, resulted in 11 deaths, again including some people who might have been able to escape before the fire spread. In all three cases, the seriousness of the developing fire was not immediately realized by other drivers in the tunnel, particularly those who were farther from the initial accident and could not see what had happened, and so crucial escape time was lost (Jenssen 2007, Eder et al. 2013, OECD 2006).

### **Laboratory Studies and Simulations**

A driving simulation conducted by Netherlands Organization for Applied Scientific Research (TNO) observed the reactions of drivers when they were confronted by an in-tunnel traffic jam followed by approaching smoke. Drivers in the study were provided with one of three different information conditions:

- Drivers in Condition 1 were provided no information on how to respond to the situation shown.
- Drivers in Condition 2 were given an information leaflet containing information on safe behavior in tunnels prior to beginning the simulation.
- Drivers in Condition 3 were provided the same information leaflet prior to the simulation and also heard two messages from a virtual tunnel operator during the simulation. The first of these messages ("Please turn off the engine") was played 2.5 minutes after the simulated traffic accident, which was also 1 minute before smoke appeared in the tunnel. The second message ("Please go to the escape exits") played 1.5 minutes after the first message, which was 30 seconds after the appearance of smoke.

The study's results showed that increasing the information provided to drivers markedly affected their decisions to leave (or to state their intention to leave) the simulated vehicle in response to the unfolding tunnel fire. With no information other than the visual cues shown during the simulation, 65 percent of drivers in Condition 1 ultimately indicated their intention to leave the vehicle, compared to 75 percent of drivers in Condition 2 and 94 percent of drivers in Condition 3. Additionally, the three information conditions influenced the time that drivers took to decide to leave the vehicle. Measured from the time that traffic came to a stop in the simulated tunnel, Condition 1 drivers took an average of 3.16 minutes to leave the vehicle (if they left at all), the average time for Condition 2 drivers was 2.54 minutes, and the average time for Condition 3 drivers was 2.23 minutes. For Condition 3 drivers, this evacuation time equated to approximately 0.23 minutes following the voice announcement (Jenssen 2008).

A similar study in Sweden in 2007 used a simulated emergency scenario in an actual roadway tunnel to examine motorist behaviors when confronted with a tunnel fire, and to assess the influence of various types of evacuation information on those behaviors. The 29 participants in the experiment all drove (as a queue of 29 vehicles) into a dual-bore tunnel in which a simulated accident scene blocked their path. Two and a half minutes after the first vehicle in the

queue stopped, information signs began displaying a message instructing drivers to turn off their engines and evacuate the tunnel, and a prerecorded alarm began providing a similar message in three languages. At the same time, green flashing lights were activated at emergency exits close to the simulated accident site. In this experiment, the 19 participants at the head of the queue (i.e., within view of the accident site) left their vehicles and had reached or were en route to emergency exits before the alarms and flashing lights activated; for this group, seeing others begin to evacuate was a common factor in their decision to do the same. The remaining participants, who were farther back and therefore could not see the accident site, opened their vehicle doors within a few seconds of alarm activation; while these participants found the audio message difficult to understand, nine out of 10 of them cited it as a factor in their decision to leave their vehicle. Some also mentioned the signs as a factor, while others indicated that they did not notice them. The flashing lights at exit doors were seen only by members of this latter group (Participants 20–29); three recalled the flashing lights as being important to their identification of the door, while the others did not (Nilsson, Johansson, and Frantzich 2009).

## **SIGN AND MARKING COMPREHENSION**

Studies of emergency exit way-finding guidance in the literature include evaluations of signs and visible markings and beacons, as well as of audible signals and messages.

In a high-anxiety situation, a person's focus narrows and cognitive ability is reduced. For this reason, it is important to provide simple, straightforward instructions about what to do and where to go in the event of an emergency. Alarms that include specific messages to leave vehicles and exit the tunnel may help to reduce delayed responses; signs and markings that are easy to see and understand can help to direct people to the closest exit (Nilsson et al. 2009, Morley and Corbett 1997). Since most tunnel users cannot be expected to have specific knowledge or training for evacuating themselves from their vehicles and from the tunnel, the guidance offered by signs, markings, and auditory messages must be straightforward and intuitive.

Running man graphical exit signs were tested with airline passengers at Schipol Airport in Amsterdam to evaluate the comprehensibility of graphical sign messages including the identification of the exit door and an indication that an exit door is located to the left or right of the sign. The signs were tested with people traveling to and from all regions of the world to compare comprehension across different nationalities and languages. Comprehension of these graphical signs was above 66 percent for survey participants who were from Western Europe, North America, and Australia/New Zealand; it was lower for participants from Eastern Europe, Asia, Africa, Latin America, and the Middle East (Morley and Corbett 1997).

In a similar comprehension study conducted by the Federal Aviation Administration, approximately 50 percent of study participants correctly identified the meaning of the running man symbolic exit sign when the sign was viewed in isolation, compared to 97 percent who correctly identified the meaning of a text EXIT sign; symbolic signs indicating the direction to an exit were correctly identified by about 43 percent of participants. When the signs were viewed in context (pictures showing exit doors from the interior of an airplane), comprehension of signs using the running man symbol rose to an average of 70 percent. The study concluded that the symbolic exit signs were not equivalent to the traditional (in the United States) EXIT text sign and would need "additional compensating factors" to provide an equivalent level of safety for people needing an emergency exit (McLean and Corbett 2007).



A series of experiments in Sweden testing exit markings for tunnels found that green flashing lights at exit doors, particularly lights that activate at the onset of a fire alarm, were the most successful for catching the attention of study participants and communicating the intended “exit here” message. Orange flashing lights were also attention getting, but were more likely to be interpreted by participants as signaling danger rather than a safe exit (Nilsson 2009, Ronchi et al. 2012).

A 2013 tunnel evacuation study compared the effects of five different combinations of emergency exit markings on participants’ evacuation speed and exit choice within a smoke-filled tunnel. The test exit door treatments included the following combinations:

1. A backlit emergency exit sign.
2. The exit sign plus green flashing lights on either side of the door.
3. The exit sign, a non-flashing white halogen light above the door, and non-flashing green and white lights on either side of the door.
4. The exit sign plus a loudspeaker that broadcast an audible signal/message instructing participants to exit at that location.
5. The exit sign, plus all of the light options from Scenarios 2 and 3 (white halogen light above the door, green flashing lights on either side of the door, green and white non-flashing lights on either side of the door).

The five different exit treatments did not, in general, change the frequency of correct exit selection when participants were on the same side of the tunnel as the exit door. Under Treatment Conditions 1, 2, 4, and 5, the designated emergency exit was successfully found by 100 percent of the study participants whose starting point in the tunnel was on the same side of the tunnel as the exit door. However, for participants who started on the opposite wall of the tunnel (meaning that they would have to cross the width of the tunnel to reach the exit door), exit door treatments became more significant, with the green flashing lights and the audible signal producing more consistent results than the exit sign alone or the exit sign with any of the steady-state lights. In Treatment Condition 3, the steady-state white and green lights actually deterred a few participants from approaching the exit door from either the same or the opposite wall. Statements made by participants indicate that some thought the arrangement of green and white lights represented the outline of a train rather than an exit door (Fridolph et al. 2013).

## **VISIBILITY OF SIGN AND MARKING TECHNOLOGIES**

Signs and markings intended to guide tunnel users on foot to exits in the event of an emergency must be visible to pedestrians under potentially adverse viewing conditions, including darkness and smoke. Because some types of tunnel-related emergencies may affect electrical systems, emergency signs and markings should be able to operate at least temporarily on independent power sources, or operate without the need for electrical power (e.g., photoluminescent materials).

A series of studies on visibility of signs through various types of smoke found that the smoke density, light scatter off smoke particles, and brightness and contrast threshold of the sign were the most significant factors determining how far away the sign could be seen. However, smoke’s irritant effects, especially at higher densities, also affected visibility. Tests found that visibility distance of a given object in non-irritant smoke was a linear function of smoke density, and visibility dropped off sharply and non-linearly in irritant smoke (Jin 1997). An earlier study

also examined the effects of sign luminance on visibility through smoke, finding that smoke had to reach an optical density of between 0.07 and 0.16  $\text{od/m}$  to obscure signs with average luminances over  $70 \text{ cd/m}^2$ ; signs with lower average luminances were obscured at lower smoke densities (Collins et al. 1992).

A study comparing laser diodes, xenon discharge tubes, and high-intensity LEDs as visual beacons for tunnel evacuations found that high-intensity LEDs provided the best visibility through smoke. A subsequent emergency evacuation guidance system was developed that used high-intensity LEDs configured as a flashing arrow to indicate the direction of an exit (Ellis et al. 2008). Similar systems have been implemented in Austria, coupled with LEDs to highlight the exit doors themselves. LED beacons, markings, and illuminated signs require relatively low levels of electrical power and can be operated using backup battery power if the main power in a tunnel is lost (Eigentler 2006).

A study by the University of Reading in the United Kingdom examined the visibility and legibility of exit route signs for people with visual impairments such as macular degeneration and cataracts. Participants viewed signs under normal lighting and emergency lighting conditions. In the initial data analysis (comparing four out of the total 24 signs evaluated), legibility distances were greater for two LED signs compared to two externally illuminated signs (Cook et al. 2005).

Photoluminescent signs and markings charge via exposure to a light source, and once charged, will glow in the dark. Because they do not need electrical power to operate, they offer a fail-safe in case of a widespread power loss. Another advantage of photoluminescent signs and markings is the ability to mount them completely flush to a wall, unlike powered signs or lights. Photoluminescent signs have been adopted in Canada for building exits and are required by city ordinance in New York for buildings over 75 feet tall (Carss 2010, Windle 2005). Photoluminescent materials can fail to fully illuminate, however, if they are inadequately charged by ambient light; some types may also degrade with exposure to ultraviolet radiation or moisture (Amy 2008).

## **AUDIO BEACONS AND MESSAGES**

Auditory beacons can provide guidance in poor visibility conditions and for visually disabled pedestrians; they can also help to attract attention to emergency exits even when visibility is good. A study of an emergency evacuation system for mine workers, however, found that auditory beacons used alone as a way-finding system resulted in slower walking speeds and longer evacuation times than auditory beacons coupled with visual beacons (14). In two studies conducted by Boer and Wijngaarden, auditory beacons that included a chiming sound followed by the words “exit here” resulted in significantly more test participants following the correct route to a designated exit, compared to auditory beacons that used a nonverbal sound only. Participants also walked more rapidly toward the self-explaining auditory beacon than they did toward a nonverbal sound (Boer and van Wijngaarden 2004, Boer and van Wijngaarden 2008).

A series of studies by Lund University in Sweden examined how emergency exit messages should be formulated and conveyed in order to facilitate efficient egress. In the first study, customers at IKEA in Gothenburg were presented with spoken emergency exit messages and then questioned about the messages they had heard. Next, an experiment was conducted at the University of Lund with three selected types of verbal messages. The study was conducted with uninformed university students. All trials were video filmed to determine decision and

reaction time to the messages. Both artificial and natural speech were used, with no notable difference in comprehension. The study noted that the artificial voice was very close to a natural voice in sound (Nilsson 2006).

Results of these two studies indicated that people remember less of the important information from a message if the message is too long. Based on the results, it is recommended that messages should not contain more than five information bits. One information bit is in this case a series of words that together build a single concept. Another finding is that people want to know the reason for the alarm. Since the initial phase of the emergency egress is characterized by indecision and information search, it is recommended to include a reason for the alarm in the speech message. Further, hearing that there is a fire leads to less misunderstanding. Hence, it is recommended that “fire” be included in the verbal message.

Comprehensible loudspeaker announcements contribute to proper motorist behavior in the event of fire and other road tunnel incidents. This is especially important for enabling self-rescue but also to ensure smooth traffic flow in case of traffic accidents, vehicle breakdowns, or other closed or blocked lanes. A research study in 2011 found that audible beacons using synchronized longitudinal sound resulted in considerably better speech comprehension inside tunnels compared to previous sound beacon technologies. This technology has been selected for use in highway tunnels in Germany; acoustic beacons using synchronized longitudinal sound are already installed in 10 German road tunnels. Further research is needed in order to develop and improve electro-acoustic sound beacons in tunnels even further. Topics that the 2011 study identified to be explored further included the following:

- Efficient adaptation of sound volumes to changing noise levels.
- Inclusion of escape ways and portal zones.
- Delivery of speech announcement text.
- Standardized ergonomic operation of speech announcements (Mayer et al. 2011).

## **EXISTING STANDARDS FOR TUNNEL EMERGENCY EXIT SIGNS AND MARKINGS**

A number of existing standards in the United States and elsewhere in the world address requirements for emergency exits and associated signage, markings, and audio signals. Some of these are specific to highway tunnels, while others were developed for building exits but may have application, with or without modification, to the highway tunnel environment. Directive 2004/54/EG of the European Parliament establishes minimum safety requirements for all roadway tunnels on the Trans European Roadway Network that are longer than 500 meters. One of the objectives of the guidelines is to improve conditions for self-rescue from a tunnel in an emergency, including guidelines for evacuation lighting and signing.

The National Fire Protection Association is a nonprofit organization with members from nearly 100 nations. As part of its mission, NFPA has developed approximately 300 codes and standards for mitigating the risk and effects of fires. Two NFPA codes that directly address emergency exit signs and markings for highway tunnels are NFPA 502, *Standard for Road Tunnels, Bridges, and Other Limited Access Highways*, and NFPA 170, *Standard for Fire Safety and Emergency Symbols*.

The International Building Code’s guidelines do not directly apply to exit door and exit pathway signs and markings in tunnels; however, they represent a standard for exit signing in buildings that is consistent and recognized throughout the United States.

The following sections summarize guidelines from these and other U.S. and European standards for emergency exit signs, markings, lighting, and audio signals.

### Exit Sign Formats and Graphics

Symbolic signs showing a running man exiting through a door were adopted for use in Europe in 1985 (Ernst et al. 2006, Turner 2010). The use of pictograms to replace text for emergency exit and other signs began to gain momentum across Europe in the early 1990s. Since that time, more than one version of a running man pictogram has been in use for exit signs across Europe. The International Organization for Standardization (ISO) 3864 (27) established one version of the pictogram as the standard for fire exit/escape signs, and this pictogram has also been adopted in ISO 7010, which provides guidelines for graphical symbols and colors for safety signs in general. The ISO 7010 exit sign, established in 2013, is a green sign with “EXIT” in white lettering in front of a man running into a door (see Figure 3).

A version of the running man symbol is the recommended exit sign format in Directive 2004/54/EG, Annex III. NFPA 170, Chapter 4, “Symbols for General Use,” provides guidance concerning the shape, colors, and use of symbols for general fire safety information. Table 4.2, “Symbols for General Use”, includes exit door signs and directional signs that incorporate the ISO 7010 running man symbol. Annex A, Section A.12.6.8 of NFPA 502 references this recommendation of NFPA 170.



**Figure 3. Running man exit symbol, from ISO 7010.**

### Sign Size

Several national and international standards provide guidelines for the sizes of exit signs and/or sign elements. NFPA 101 recommends a minimum character height of 6 inches for text EXIT signs. The Norwegian Public Roads Association Standard for Road Tunnels recommends a 400 mm by 400 mm (15.75 inches square) running man symbol sign for tunnel exit doors. IBC requires “EXIT” letters that are at least 6 inches tall and 2 inches wide (with the exception of the letter “I”), with a stroke width of at least 0.75 inches. Finally, British Standard 5499-4:2000 provides the equation  $D = hZ$  for calculating minimum sign height and minimum letter height for running man exit path signs, where:

- D = maximum viewing distance in meters.
- h = overall height of the sign’s printed area in millimeters.
- Z = a distance factor based on the illumination of the sign and the level of detail included in the sign’s legend. For exit path signs with the running man symbol, Z is generally assumed to be 170.

## Sign Placement

Annex III of Directive 2004/54/EG requires directional signs (running man exit symbol, directional arrows, distances in meters) to be placed every 25 meters (82 feet) along the tunnel wall, pointing to the two nearest emergency exits; the prescribed height of the signs is between 1 and 1.5 meters (between 3.3 and 4.9 feet) from the walking surface.

NFPA 502, Section 7.15 similarly prescribes that directional signs be placed every 25 meters (82 feet) or less on the side walls of a tunnel to indicate the distances to the two nearest exits. While the height of these signs from the ground or path is not specified, the guidelines state that the mounting height should take into account the signs' visibility during a fire.

## Sign Luminance and Visibility

Section 12.6.8 of NFPA 502 prescribes minimum illuminance levels for externally illuminated exit signs (5 foot-candles) and minimum luminance levels for internally illuminated exit signs (2.5 foot-lamberts). IBC requires that exit signs must be illuminated at all times, and that they have their own power source that is not dependent on the main power for the building or structure and that will keep the signs illuminated for at least 90 minutes in the event of a main power failure. Like NFPA 502, IBC requires that externally illuminated exit signs must be illuminated at an intensity of at least 5 foot-candles or 54 lux.

While NFPA 502 does not mention photoluminescent signs, NFPA 101 requires radioluminescent or electroluminescent signs to have a minimum luminance of 0.06 fL or 0.21 c/m<sup>2</sup> (37). ASTM Standard E 2072 similarly provides minimum luminance requirements for photoluminescent safety markings:

- In laboratory testing conditions:
  - 20 mcd/m<sup>2</sup> after 10 minutes in the dark.
  - 2.8 mcd/m<sup>2</sup> after 60 minutes in the dark.
- On site (4-inch-wide safety marking):
  - 15 mcd/m<sup>2</sup> after 10 minutes in the dark.
  - 2.2 mcd/m<sup>2</sup> after 60 minutes in the dark.

## Emergency Exit Path and Door Lighting

Directive 2004/54/EG requires general safety lighting to provide a minimum level of visibility in case of a power outage, as well as evacuation marker lights placed at a maximum height of 1.5 meters (4.9 feet) above the floor to help guide pedestrians who are evacuating the tunnel.

CIE 193-2010, *Emergency Lighting in Road Tunnels*, also provides guidelines for emergency lights and markings for pedestrians in highway tunnels. Section 2.3 of this standard sets the maximum height of evacuation-route pathway markers at 1 meter (3.3 feet) above the carriageway, with a maximum spacing of 10 meters (33 feet). Pathway markers may be permanently illuminated or activated only in the event of an emergency. CIE 193-2010 also provides detailed guidance regarding the illumination and marking of emergency exit doors, intended to encourage vehicle drivers and passengers to leave vehicles and exit on foot if needed. Exit door illumination is intended to make the doors visible and conspicuous to tunnel users at all times (not just during an emergency); CIE guidelines prescribe a doorway illuminance level

three to five times higher than the average illuminance of the surrounding walls, extending out from the door frame for 2 meters (approximately 6 feet) in all directions. Exit door markers are lights intended to act as signals to tunnel users during an emergency; the guidelines recommend flashing green marker lights arranged around the exit door that are activated only in emergency situations. Recommended minimum intensity of the green marker lights is 150 cd, and recommended flash rate is from 1 Hz to 2 Hz.

NFPA 72, *National Fire Alarm and Signaling Code*, Section 18.5.3, recommends the same flash rate (1 Hz to 2 Hz) for emergency strobe lights but recommends white or clear lights rather than green.

## **Audio Signals**

NFPA 72 provides guidance for audible alarms and evacuation messages for buildings, some of which may have some application for audible alarms and verbal messages in tunnels. Section 18.4 establishes auditory requirements for evacuation signals, including sound levels and signal characteristics. Some of NFPA 72's recommendations that may inform audio signal recommendations for highway tunnels include the following:

- Section 18.4.1 establishes maximum sound pressure levels from the combination of ambient noise with the sounds created by audio signals. Maximum peak sound pressure is limited to 110 A-weighted decibels (dBA) and maximum average sound pressure to 92 dBA.
- Section 18.4.2 describes a three-tone temporal alarm used to notify building occupants to evacuate.
- Section 18.4.3 establishes minimum sound level requirements for public-mode audible signals as 15 dB above the average ambient sound level.
- Section 18.4.6 outlines procedures for calculating minimum sound pressure levels needed to overcome a particular masking noise and may be applicable to certain emergency situations in tunnels, such as when jet fans are activated for ventilation.
- Section 18.4.7 provides recommendations for audible signals at exit doors.
- Section 18.4.10 describes voice intelligibility requirements for voice messages.

NFPA 502 Annex B, Section B.2.5 specifies maximum peak noise levels along highway tunnel evacuation paths of 115 dBA and maximum average levels of 92 dBA. This represents a 5 dBA increase in the maximum peak-level sound pressure specified in NFPA 72 for buildings, while the maximum average sound pressure is the same for both standards.

## **EXPERT INPUT**

Input was sought from experts in roadway signage, tunnel operations, and emergency response at various points throughout the project. First, members of the Regulatory and Warning Signs Technical Committee (RWSTC) of the NCUTCD were asked for their input regarding emergency exit signs and markings. Next, a subject matter expert (SME) panel of experienced tunnel facility responders in the law enforcement, fire/EMS, department of transportation (DOT), towing and recovery, and traffic incident management communities was assembled via WebEx on June 26, 2014, to discuss practices and experiences pertaining to tunnel incidents and emergencies. Finally, some additional tunnel operators were interviewed via telephone in

February 2015 regarding their emergency procedures, including communication to tunnel users. Table 1 lists the tunnel facility experts who provided input to this study.

**Table 1. Participating Subject Matter Experts.**

Participant		Agency/Committee	Title
NCUTCD	Bruce Ibarguen	Maine DOT	State Traffic Engineer
	Tom Heydel	Wisconsin DOT	Regional Traffic Engineer
	James Pline	Institute of Transportation Engineers (ITE)	Past ITE President
SME Panel	Michael Fitzpatrick	Massachusetts DOT	Highway Operations Center Manager
	Lorenzo Parra	Massachusetts DOT	Director of Highway Operations Center
	Lt. Dave Cain	Pennsylvania State Police	Commander, Central Patrol Section/Troop T, Everett
	Allen Baldwin	Winchester, VA Fire Department	Fire Chief
	Rusty Fitzhugh	Virginia DOT	Hampton Roads Bridges and Tunnels (HRBT) Operations Manager
	Tina Eley	Virginia DOT	HRBT Operations Supervisor
	Lisa Williams	Virginia DOT	Field Supervisor
	Eric Roberts	Virginia DOT	Field Supervisor
	Lynn Manges	Interstate Emergency Services, Towing and Recovery, Bedford, PA	Director of Towing Operations
Interviews	Todd Anselman	Colorado DOT, Hanging Lake Tunnels	Electronics Specialist
	Spencer Dickey	Colorado DOT, Hanging Lake Tunnels	Tunnel Operations Manager
	Douglas Haight	Washington DOT (WSDOT), Seattle Tunnel	WSDOT Project Engineer, Sound Transit Projects
	Chris Thomas	Washington DOT, Seattle Tunnel	Supervisor of Tunnel Operators

The following sections summarize the input received from the interviews and panel discussion.

### **Driver Responses to Tunnel Incidents**

Many drivers view car fires and other potentially hazardous incidents in tunnels as just another traffic slowdown. Because sightlines in tunnels can be shorter than on open roadways,

motorists may not even know what the incident is until or unless they are close to it. Frustration and anger are prevalent behaviors; drivers do not want to get stuck in an incident inside of a tunnel. A risky behavior that has been frequently observed is drivers speeding past the incident on their way out of the tunnel, risking everyone on the scene as well as themselves. Sometimes the opposite occurs, with drivers slowing down close to an incident to rubberneck, particularly drivers who are not accustomed to traveling in tunnel facilities.

When all lanes are blocked, motorists will sometimes exit their vehicles and linger around either in the tunnel tubes or on the surface prior to the incident. This causes the potential for further injury. The likelihood of additional incidents increases if traffic is diverted to other tunnel bores at crossings.

## **Emergency Procedures**

Many tunnels have ventilation systems that are activated in response to events involving smoke or other hazardous materials. When this occurs, all tunnel areas upstream of the incident (where the stopped traffic sits) are put into positive pressure. Exhaust fans activate downstream of the event, removing smoke and gases through the end of the tunnel and up vent building stacks. Motorists downstream of an incident do not tend to linger; they continue out of the tunnel.

Advanced monitoring and incident management systems are becoming more common in newly constructed or refurbished tunnels. These systems can include video and thermal cameras to enable operators to see the exact location and nature of an incident, including the presence and extent of smoke, and can automate response sequences including the activation of emergency signs and markings.

## **Emergency Announcements and Exit Guidance**

Planned and rehearsed strategies are important for clearing in-tunnel incidents quickly. Communication with the motorists approaching the incident is very important in allowing the opportunity to divert, if possible. On-scene temporary traffic control for intermediate and major incidents is one approach to this problem, and several of the agencies represented by the expert participants have developed and practiced procedures for getting first responders on scene as quickly as possible.

The represented agencies also use a variety of other techniques for communicating with drivers during an incident, including dynamic message signs, strobe lights at exit doors, and static signs; one agency also sends alerts out via Web feed and Twitter. A radio override system is in use at the Seattle Tunnel. Issues and limitations that the expert participants have experienced with various communication methods include the following:

- Dynamic/variable message signs, some with canned messages and some that can be manually programmed with a customized message, are in use in several of the tunnels represented by the participants. The Seattle Tunnel, as one example, contains some fixed variable message signs (VMSs) for lane control, alternating with VMSs that can display one of 110 preprogrammed messages as needed. The signs can be activated with appropriate messages as part of an automated incident management system that allows a tunnel operator to specify whether an evacuation is advised. The primary limitation of DMSs/VMSs is the short message length.



- Highway advisory radio and radio override systems are older technologies, and many tunnel operations are moving to or considering other options. Many override systems were designed for AM/FM radio frequencies, and with the rising prevalence of satellite radio and smartphone-based entertainment, the number of drivers that are likely to hear messages broadcast via radio override is diminishing. Radio override systems can also bleed into tunnel bores beyond the one affected, potentially causing confusion.
- Loudspeakers are not currently in use in the tunnels represented by the expert participants, due to problems with reverberation and resultant low intelligibility.

## **Exit Sign and Marking Considerations**

Each sign must convey a very specific message. The message must be brief, as the user will be in a stressful situation and will need to interpret the message immediately. Easily recognizable sign legends are important for exit door signs and for signs and markings that will direct the evacuee to the exit doors. Consideration must be given to which exit is nearest to the evacuee at any point along the tunnel. Static running man symbols are widely recognized, but a static sign could be pointing toward the hazard.

Assuming that the evacuee is unable to stay in his or her vehicle, emergency exit signs only need to be legible for a walking (or perhaps running) speed. Tunnel lighting is present in most highway tunnels. Therefore, the sign will have some ambient light on it already. However, if the emergency has knocked out power to the lighting, then the signs may need battery backup to allow the evacuee to see them. This would be true if the light were external or internal to the sign.

It will be important to convince people to get out of their vehicles and walk. LED edge markings, similar to those in the aisles of airplanes, could help provide guidance to the nearest exit. It will probably be necessary to have segmented sections of the tunnel with various controls for emergency path markings dependent on where the emergency occurs. An advantage of lighting in or near the pavement is that usually smoke is not as thick near the ground.

Strobe lighting is being used in some tunnels to identify exit doors, but more research may be needed to determine whether people interpret strobe lighting to mean “come this way” or “do not come this way.”

Signs and markings need to be able to withstand environmental and traffic conditions within a highway tunnel, as well as tunnel cleaning procedures (or should be removable during tunnel cleaning). Tunnel cleaning can involve pressure washing with water and/or rotating brushes.

Current U.S. tunnel designs and types of exits should be considered when recommending sign placement. To know what to develop for a sign layout, it is necessary to know where and to what the evacuee is being sent.

## CHAPTER 3. FOCUS GROUPS—RESEARCH APPROACH AND RESULTS

Two focus groups were conducted with drivers to gain a better understanding of how tunnel users might respond to various tunnel incident scenarios and warnings.

Focus group discussions were held on June 12, 2014, in a conference room at the Texas A&M Transportation Institute (TTI) office in Houston, Texas. The first group met at 1:00 p.m., and the second group met at 5:30 p.m. Each session lasted approximately 70 minutes. The demographics of the focus group participants are shown in Table 2.

**Table 2. Focus Group Participant Demographics.**

Group 1		Group 2	
<i>Gender</i>	<i>Age</i>	<i>Gender</i>	<i>Age</i>
M	23	M	20
M	54	M	41
M	61	M	56
M	64	M	58
F	18	M	68
F	22	F	20
F	24	F	25
F	27	F	39
F	43	F	56
F	53		
F	62		

### PROCEDURE AND RESULTS

A PowerPoint presentation was used to present the groups with pictures, video, and audio as stimuli for the discussion questions. Each of the moderated discussions began with an introduction by the moderator about focus group protocol and etiquette, followed by some icebreaker questions to give participants a chance to introduce themselves and to become comfortable participating in the discussion. Participants were asked to tell the group their first name, whether or not they had experience driving in tunnels, and (if applicable) what they liked best or least about driving in tunnels.

Of the 11 participants in Group 1, seven reported having driven through highway tunnels. In Group 2, six out of the nine participants have driven through tunnels. The results are presented in the rest of this section with respect to how the conditions were presented to the focus group participants.

#### Slowing/Stopping Traffic in a Tunnel

Participants viewed a brief video clip of a vehicle entering a highway tunnel, proceeding a distance into the tunnel, and then slowing as other traffic in the tunnel began braking. Following this video, participants were asked, “If you were driving through a tunnel and traffic slowed or stopped, what would you guess might be the reason?”

Participants in both groups identified possible reasons including ordinary rush-hour traffic congestion, road construction, a stalled vehicle, a traffic accident ahead, and a structural failure within the tunnel.

When asked what their initial reaction would be to this scenario, most participants indicated that they would wait for traffic to start moving again. One participant said that he would turn on his hazard lights to alert traffic behind him that he was stopped, and another said that she would try to maneuver her vehicle to an open space in the adjacent lane and try to keep moving toward the tunnel exit. A few participants indicated that they would feel frustrated or anxious about being stopped inside a tunnel. One or two participants in each group said that they would turn on the vehicle's radio to listen for messages about what was happening in the tunnel, and one participant in Group 1 commented that there should be signs throughout the tunnel to provide real-time messages.

### **Stopped Traffic, Drivers Exiting Vehicles**

Participants next viewed a still photo of traffic stopped inside a tunnel, with some of the drivers outside their vehicles standing or walking. When asked what might be happening in a scenario that looked like this, some participants speculated that there might be something more dangerous or unusual than an ordinary traffic jam farther ahead in the tunnel. Participants in both groups had mixed opinions about appropriate actions to take, with some saying they would want to exit their vehicle to find out what was happening and others believing that leaving their vehicles would place them at additional risk. Some sample comments were as follows:

- *Whatever it is, it's not good. If people are getting out of their cars, it's not good.*
- *But also those people getting out of their cars causes a problem, because once the traffic starts moving, someone might get hit. It's a hazard.*
- *I think it might be dangerous to stay in the car. If something's coming, you might not see it, and then you can't run.*
- *I think I'd get out of my car for a few seconds and stand up, to see if I could see any farther ahead, and get some sort of clue as to what's happening, as to why traffic isn't moving.*
- *I think in this situation, where people are out of their vehicles and talking, at least you're informed as to what is taking place, to put your mind at ease and not panic or get anxious about what's happening.*

While the specific action that participants said they might take varied, most participants agreed that they would be seeking additional information about the situation, such as the following:

- *Signs on the top and sides of the tunnel.*
- *Something similar to the signs you see on freeways, telling you about accidents or delays ahead.*
- *Ideally, the sign would be before you ever entered the tunnel. That way, it can divert traffic, or you can make the decision about whether to wait outside the tunnel or take a different route.*
- *If traffic is backed up, emergency personnel might not be able to get there. [They need] a way to communicate without needing someone to get in to the spot where the trouble is.*
- *[Message via] the radio.*

- *I would get out and try to find out from others who are walking around. Someone's bound to know what's going on.*

## **Stopped Traffic, Smoke**

Participants viewed a still picture showing vehicles in a tunnel surrounded by smoke. Most of the participants identified the haze in the photo as smoke, and some speculated it could be coming from a vehicle fire; one participant in each group thought it might be fog.

Reactions to a possible fire or similar emergency situation varied, with some participants saying that they would leave the tunnel as quickly as possible, on foot if necessary, and others commenting that they would be more likely to seek more information about the situation first. Two participants in Group 1 said that their first action, if they were close enough to see a burning vehicle or similar situation, would be to try to help whoever was in the vehicle or otherwise in immediate danger. Comments about this situation included the following:

- *Get out!*
- *I would ask cars behind me to back up.*
- *If I was close enough to see what was going on and I could possibly help, I think I would try to help.*
- *If I was behind the place in the tunnel where there was a fire going on, then my first reaction would be to get out of there.*
- *[My response] depends on how far it is to get out, and on what exactly is going on. Is there a fire? What kind of fire is it?*
- *[I might not leave] at this point, unless other people are leaving. If I see that others are exiting on foot or running, then I'm going too—I don't know if there are emergency exits or if I'm going all the way back [to the portal], but I'm getting out of there.*
- *The first thing would be to determine if it's smoke or if it's fog. If I smelled something burning, then I would try to exit.*
- *But on the other hand, if you and a lot of other people left their vehicles there, it could hinder emergency vehicles trying to get to the car that's on fire or to the person that's hurt.*
- *The key is signage...[that] could tell you to stay or exit.*

Finally, participants were asked where they would start looking for an exit if they did decide to leave their vehicle and walk. One participant said she would start heading “back the way I came,” indicating the tunnel’s main portal. Others speculated that there might be side doors, with ladders or staircases going up.

## **DMS Messages**

Participants viewed a series of three messages on a simulated dynamic message sign. Each message consisted of two phases, each consisting of a word or phrase that totaled 18 characters or fewer; the phases were animated on the slide so that they alternated on the screen every 2 seconds. This length of message was selected based on a typical DMS width for a two-lane tunnel (according to a tunnel operator and a DMS vendor who were consulted during the preparation of the focus group presentation). Two phases is the maximum recommended by the *Manual on Uniform Control Devices (MUTCD)* for DMS messages. This format was chosen

in part to assess the effectiveness of fairly short messages in conveying useful information and an appropriate sense of urgency.

### *“Emergency—Walk to Exits”*

The first message tested was “Emergency—Walk to Exits,” displayed in two phases (in the preceding text, the dash separated the two phases). Participants were asked, “What would be your reaction to seeing this message?”

Within Group 1, most participants indicated that they would follow the sign’s instructions. In Group 2, some participants said they would immediately follow the instructions, but others indicated that they might be slower to respond. Participant comments included the following:

- *That’s all the information I need.*
- *I would want to know why but would still exit because it says “emergency.”*
- *I’d think “okay, let’s go.”*
- *“Emergency” would slow me down if I was driving.*
- *If it’s at the beginning of the tunnel, I would still be trying to get my car out of there. But if it were in the middle of the tunnel, and traffic is stopped, and this came on, then I’m getting out of the car.*
- *I probably would panic. I would be nervous to walk in the tunnels I’ve been in; I’d be afraid to get hit.*

### *“Leave Vehicle—Walk to Exits”*

The second message tested was “Leave Vehicle—Walk to Exits.” Participants were again asked, “What would be your reaction to seeing this message?” Participants were also asked whether this message provided them with more or less useful information compared to the first message.

While some participants appreciated having the “leave vehicle” directive prior to “walk to exits,” most felt that receiving instructions without a reason being provided was less informative overall. Participants who preferred “leave vehicle” to “emergency” felt that the two-part directive provided extra guidance that might be useful in a stressful situation and also conveyed the message that leaving in a vehicle was not possible; participants who preferred “emergency” as the first part of the message felt that it was more important to provide context for the “walk to exits” command. Participant comments included the following:

- *I’d be suspicious [of “leave your vehicle”]. Why do I need to leave my vehicle? What are you trying to do?*
- *Not enough information.*
- *“Emergency, walk to exits” is better for me. The word “emergency” sticks out.*
- *I’d probably keep driving until I see more information rather than just leave my vehicle. Would like information that tells me the next step, like “get out and walk.”*
- *It gives specific commands. The other one just said “emergency,” so if I was driving I might slow down, but this one says, “Leave your vehicle, there’s a major problem.” Which means I’m going to leave my vehicle, I’m not going to question it.*

- *I would say that the “leave vehicle” is better for me; I see that word “emergency” and I’m scared. “Leave vehicle” doesn’t get me excited or upset, where “emergency” might make me anxious.*

### **“Fire in Tunnel—Walk to Exits”**

The third message tested was “Fire in Tunnel—Walk to Exits.” This was the least preferred message among both groups of participants. Participants expressed concern that seeing a “fire in tunnel” message might cause anxiety or panic that would impede safe evacuation. Comments on this message included the following:

- *Here’s my initial reaction to that: mayhem. I don’t think people would see that and walk to the exits. I think people would freak out and would run instead of walking. I would much prefer “leave vehicle” or “emergency” to “there’s a fire” because a bunch of people are going to freak out and run for the exits.*
- *As long as I’m being cautioned to get out of harm’s way, I can find out what happened after I’m safe.*
- *This is definitely my least favorite. It’s informative, which is awesome, but I would be more anxious, and nervous, and more inclined to run if this was the sign.*

In the following portions of the discussion, however, some participants expressed support for the specific hazard information provided by the phrase “fire in tunnel.”

### **Preferred Phrases**

Participants viewed a list of phrases that could be used in a DMS message and asked which phrases they felt would be the most useful to include in a message advising drivers to evacuate a tunnel on foot. Phrases shown included “Emergency,” “Fire in Tunnel,” “Turn off Vehicle,” “Leave Vehicle,” “Walk to Exits,” and “Exit on Foot.” Participants were also invited to modify these phrases or add different phrases to the list.

Nearly all participants agreed that “Walk to Exits” or “Exit on Foot” was an essential phrase. Participants were split on whether a description of the situation (e.g., “emergency”) or a supplemental command statement (e.g., “turn off vehicle” or “leave vehicle”) was more important to include; a slight majority preferred knowing something about the situation as a reason for the “walk to exits” or “exit on foot” directive. While most participants were still opposed to using “fire in tunnel” as the situation description, one participant supported its use. Participant comments included the following:

- *NOT “fire in tunnel.” The others are okay. I think “turn off vehicle” and “leave vehicle” are implied already by “walk to exits.” If there’s not an immediate need to leave (maybe an incident ahead but not an emergency), then “caution,” maybe even “stay in your vehicle” in that case. “Accident ahead, stay in vehicle.”*
- *Even though it would cause the most panic, I would like “fire in tunnel, walk to exits” if there really is a fire in there. I don’t want to be strolling through, not hurrying because I don’t know how dangerous it is. If there’s a fire, I would want to know right away before things start blowing up. If there is a fire, that information is essential, then after that “walk to exits.”*

- *“Turn off vehicle” because people in a panic would likely forget to do that and it could cause problems like a buildup of carbon monoxide, then “walk to exits.” That would get my attention.*
- *“Walk to exits” is most important. “Leave vehicle” is also good, because it means that the situation is urgent.*
- *I like “exit on foot” because it tells you that you can’t go in your car.*
- *They should go hand in hand. You need the situation plus the command so you don’t think you can stay in your vehicle if you shouldn’t. “This is what’s happening, now this is what you do.” That cuts down on the likelihood that you’ll panic, and you’ll know how to react. Is it giving me an option to leave, or telling me I need to leave now?*

### **Audio Announcement**

Participants listened to a recording of the following voice announcement: “Attention—there is a fire in the tunnel. Turn off your engine, leave the keys in your vehicle, and walk to emergency exits immediately.” Reactions to the announcement were slightly different between the two groups. In Group 1, most participants indicated that the announcement would encourage them to leave, though most said that they would not leave their vehicle keys behind and questioned the reason behind that request. As with the DMS announcements, some participants were opposed to specifying a tunnel fire as part of the announcement, rather than a more general “emergency,” but others supported the more specific description to convey the urgency of the situation. One Group 1 participant commented that the announcer’s voice was too emotional and could increase anxiety.

Comments from Group 1 participants about this message included the following:

- *Don’t say “fire in tunnel.”*
- *If you’re told to get out of your car and leave your keys, you want to know why.*
- *If there’s a fire, in most cases you won’t die from the fire, you’ll die from the carbon monoxide. If it says “fire” people know they could die so they will leave. Damn the car! The car and the keys aren’t going to do any good if you die.*
- *Need a calmer announcer’s voice. The announcer should not be sounding like he’s panicked. If he’s panicking, I’m going to panic.*
- *So maybe they should tell you, very calmly, that there’s a fire in the tunnel and you need to leave now. Take your keys, leave your keys, whatever, just leave.*

The reaction to the announcement among most Group 2 participants was more skeptical. They also questioned the request to leave vehicle keys behind, to the extent that some expressed their suspicions about the motivation of the entire announcement. The perception of the tone of the recorded announcement was also different than in Group 1; a Group 2 participant commented that the announcer’s voice was too monotone and needed more urgency to make the message believable. Overall, the participants in Group 2 indicated much more resistance to leaving their vehicles and exiting based on the information provided in the voice announcement. One older male in Group 2, however, commented that the mere fact that an emergency was important enough to warrant an announcement should be enough of a reason to pay attention to it.

Comments from Group 2 participants about the audio message included the following:

- *I would turn off my car and exit the tunnel, but I wouldn't leave my keys. I'm always skeptical; if it's coming over a loudspeaker it could have been hacked, they could be trying to steal my car. If I can't see smoke, I'm definitely not leaving my keys.*
- *Asking me to leave my keys now has me questioning the whole message. Had you just said "cut off engine, head to doors" I would pay attention. But because you're now asking me to leave my keys, I want to know what's going on.*
- *"Leave keys" is a red flag for me.*
- *Usually you don't hear an announcement or see something displayed unless there's an emergency... We may not know exactly what's going on, but the alarm says there's something happening. You don't know the degree of emergency, but something's happening or the alarm wouldn't be sounding, so beware.*

Other comments received in the two groups about emergency messages and delivery included the following:

- *Maybe use a scale for the urgency of the problem, like the hurricane rating system. "This is how much panic you should have, this is how much urgency."*
- *Provide the message in different languages, not just English.*
- *If I'm in a strange city and I don't know how long the tunnel is or where the exits are, other than the one behind me, I'd like something to tell me where the exit is.*
- *Say which exit to take.*
- *Hearing the announcement is better than seeing a flashing message.*
- *Should have a combination of signs and audio. If someone's playing music, they could miss an audio announcement.*

## **Leaving Vehicle and Subsequent Actions**

Participants were asked, "Would you take your car keys?" and "What other items would you try to take with you?" Nearly all participants indicated that they would take their car keys, most of them simply due to habit or because of the time delay involved in detaching a vehicle key from the rest of their keys. Two participants (both in Group 1) said they might leave the vehicle key so that emergency crews could move their vehicle if needed. Other items that participants indicated they would try to take included purses/wallets, phones, and personal/medical items. Two participants talked about taking children who were in the car, and one commented that if children were present, keeping calm and avoiding panic would become even more important.

The next question was, "If you saw other people who were staying in their vehicles, would that affect your decision to stay or leave? Would it change your actions in any other way?" Among the Group 1 participants, responses were very consistent: everyone in the group agreed that if there had been an announcement to leave, seeing other people still in their vehicles would not change their own decision to leave:

- *I would probably knock on their window and say, "It says to get out."*
- *If they didn't want to leave, I wouldn't waste my time and put myself in danger.*
- *I would encourage those people to leave, but I wouldn't stay there and argue with them.*



In Group 2, reactions were mixed, with some participants expressing more of a tendency to follow the lead of other drivers, and others opting to leave if prompted by warnings/announcements regardless of what others were doing:

- *If I saw that other people were staying in their vehicle, I would probably stay in mine. Worst-case scenario, I'd leave my car.*
- *I would go with the majority (if staying or leaving).*
- *I probably wouldn't walk as fast, if other people were staying. I would try to feel out the situation, question it more, but if everyone else is running towards exits I'd get out. I might walk toward the exit, but try to keep figuring out what's going on, maybe not go through the exit just yet.*
- *I would follow instructions given by sign or audio. They can't give you all the details about what's happening, but you need to follow directions or deal with the consequences.*
- *Here in Houston, we deal more with sudden flooding. There were people staying on the freeway during Hurricane Allison when the water was rushing toward them. If you hesitate for a few minutes, you could lose your life, so better safe than sorry. It's common sense.*
- *If there is a fire in a tunnel, you know it affects oxygen, so no matter what others are doing, if you know there's a fire, get out!*

### **Follow-Up Questions and Other Comments**

Participants were asked if they had other suggestions or questions regarding emergency signs or announcements in highway tunnels. Most of the suggestions received were for signs pointing the way to emergency exits, and for lighting strategies to indicate emergency situations. Participant comments included the following:

- *Post emergency signs at intervals (maybe every mile or mile and a half) throughout the tunnel.*
- *Put DMS signs every 200 feet letting you know where next exit is.*
- *Directional signs to exits would be helpful, spaced pretty closely so that you don't miss seeing a sign that could show you the way out. I think lighted signs would be best.*
- *I'd think you'd want phosphorescent signs, in case of loss of power.*
- *Maybe use lights to provide visual color coding as you get closer to the incident (green if there's no problem, yellow if there's a problem ahead, then red as you get close to where the danger is).*
- *Red and flashing lights are best [to indicate an emergency].*
- *More than anything, flashing lights get your attention, so maybe something that only flashes during an emergency situation would help me know that there's something wrong. If I'm driving and see something flashing, that's a sign to me to slow down, survey the surroundings. Words are good, but you can't always see them; you can always see something flashing.*
- *Use multiple languages; we have all languages here now.*

As follow-up questions, participants were shown examples of some symbols for emergency signs such as the running man exit sign, a text EXIT sign, emergency telephone, fire extinguisher, disabled-access refuge point, and the running man symbol with a directional arrow

and distance. Participants comprehended nearly all of these symbols without hesitation; there was some discussion about whether the refuge point sign indicated an exit, but most participants agreed that it probably indicated a safe place for people with disabilities to stay during an emergency until emergency responders could reach them.

When asked if the green running man exit sign and the red text EXIT sign conveyed the same or different meanings, most participants thought that the signs were more or less equivalent. A couple of participants felt that the running man symbol implied more urgency (because he appears to be running for the exit rather than walking), while two other participants felt that the red color of the text sign implied “emergency” more than the green color of the running man sign. However, all participants were confident that both indicated a way out of the tunnel.

## **FOCUS GROUP CONCLUSIONS**

Individual participants’ responses during the discussion were not consistently correlated to age, gender, or prior experience driving in tunnels, except that the participants who had traveled in tunnels frequently were more likely to mention concerns about the confined space in a tunnel if an emergency were to occur (e.g., concerns about vehicle exhaust building up during a traffic jam or about the limited space available for a person to walk alongside the traffic).

While many participants indicated that they would likely consider leaving a tunnel on foot if they saw smoke and/or saw other people exiting, several also indicated that uncertainty about what might be happening or about the safest course of action might cause them to wait for further information or instructions. Even before signs and audio announcements were introduced in the discussion, several participants suggested that information about in-tunnel incidents should be communicated to drivers if possible.

Participants were generally resistant to the idea of leaving their vehicle keys behind, with most of their comments indicating a lack of awareness of why that request would be made. This indicates that public education efforts on highway tunnel safety may need to include an explanation of why emergency responders might need to move vehicles, and/or that an explanation should be included if drivers are requested to leave their vehicle keys behind. There was a range of responses regarding the influence of other drivers’ behaviors on participants’ anticipated actions. In one focus group, there was a general tendency toward acting on provided information/announcements regardless of how others were perceived to be responding; in the other group, some participants weighed the crowd response as a significant factor in their own response. This indicates that public education efforts on highway tunnel safety in general may be warranted.

The emergency messages that the majority of participants found to be most helpful, as well as most likely to provoke the desired response, included an indication about the nature of the incident followed by a direct instruction. Of the instruction phrases presented, “walk to exits” was preferred by most participants, though “exit on foot” was also considered effective. “Turn off engine” and “leave vehicle” were considered to be useful supplemental instructions, but not as important as “walk to exits” for conveying the need to evacuate. The general term “emergency” was preferred over a more specific description such as “fire in tunnel,” due to participants’ concerns about possible anxiety or panic resulting from the term “fire;” however, some participants argued that a more specific description of the emergency would better communicate the urgency for an immediate evacuation.

The focus group results were used to finalize the emergency messages that were tested with participants in the tunnel simulation (described in the following chapter). Because “Fire in Tunnel—Walk to Exits” was parallel wording to the longer planned audio/text/Twitter message, and because earlier feedback from the project panel at the Phase I project meeting was in favor of specifying “fire” when fire is present, the DMS message subsequently tested in the tunnel simulation was “Fire in Tunnel—Walk to Exits.” Also, because of focus group feedback, the audio announcement used in the tunnel simulation included an explanation for the request to leave keys in vehicles.

## CHAPTER 4. TUNNEL SIMULATION PROCEDURE AND RESULTS

The tunnel simulation first tested individual responses to a tunnel emergency scenario similar to those discussed by the focus groups, and then tested several sign and marking formats and technologies within the simulated tunnel environment, both for participants' comprehension of and confidence in various formats and for detection and legibility distances through smoke.

The tunnel simulation took place in College Station, Texas, and involved 63 participants. Potential participants included licensed drivers aged 18 and older, both men and women; as with the focus groups, recruiting targeted a mixture of younger, middle-aged, and older adults.

### PARTICIPANT DEMOGRAPHICS

A total of 63 men and women from the Bryan-College Station area participated in the tunnel simulation. Participants ranged in age from 20 to 83. Table 3 summarizes the demographics of study participants.

**Table 3. Tunnel Simulation Participant Demographics.**

<b>Age Groups</b>	<b>Males</b>	<b>Females</b>
20–34	12	13
35–59	6	15
60+	9	8
<b>Total</b>	<b>27</b>	<b>36</b>

### STUDY PROCEDURES


The simulation occurred in two stages. Stage 1 was intended to test participant responses to an unfolding hazardous situation in a highway tunnel and to emergency announcements telling them to leave their vehicle and evacuate on foot. Participants were told that the study procedure was examining traffic control devices for highway tunnels but were not told in advance of the simulation exercise that the devices being tested pertained to emergency exits.

Stage 2 of the simulation tested sign and marking formats and technologies for participant comprehension and visibility. The researcher presented each participant with a series of signs, markings, LED beacons, and audio beacons within the smoke-filled chamber, testing the following:

- Detection distance for signs and markings.
- Identification/legibility distance for signs and markings.
- Comprehension/interpretation and preference for sign, marking, and beacon formats.

Figure 4 shows the final layout of the tunnel simulation room. In Stage 1, the participant was seated in the driver's seat of the parked vehicle with the researcher seated in the passenger seat. For Stage 2, the participant and researcher viewed each sign and treatment combination one at a time, using a 60-foot corridor. Ambient lighting was set at 10 lux (measured at floor level), and the chamber was then filled with artificial smoke; the density of the smoke was measured continually and recorded on each participant's data sheet for each sign and beacon option. Having the density of the smoke vary from the beginning to the end of each participant's

testing period allowed for the viewing distances of each sign and marking to be placed in the context of smoke density.



**Figure 4. Layout for tunnel simulation.**

Participants were divided into six groups, as shown in Table 4. This allowed for three different information conditions in Stage 1 and three different sign orders in Stage 2.

**Table 4. Experimental Groups for Tunnel Simulation.**

Group	Stage 1—Information Level	Stage 2—Sign Order
A	Ambient cues only	Sign order 1
B	Audio message	Sign order 2
C	DMS message	Sign order 3
D	Ambient cues only	Sign order 3
E	Audio message	Sign order 1
F	DMS message	Sign order 2


### Stage 1: Response to Emergency Situation and Messages

The first few minutes of the Stage 1 exercise simulated a trip through a highway tunnel that was stopped by a traffic jam, followed by the appearance of smoke. The purpose of the exercise was to determine what type of message is most effective for encouraging drivers to leave their vehicle and evacuate the tunnel on foot, if such an evacuation is warranted. Participants were divided into three experimental groups (20 to 22 participants in each group) for Stage 1.

The Stage 1 study procedure provided the same introduction to all participants as follows:

- In the intake/preparation room, the greeter told participants that they would be seated in a vehicle, would view a short video clip, and would be asked to execute or describe the actions they would take that they believed were the most appropriate based on what they saw and heard.
- The researcher escorted the participant to the driver’s seat of a parked car inside the tunnel simulation chamber. The researcher sat in the passenger seat of the same vehicle.
- Once the participant and the researcher were seated in the vehicle, the researcher repeated the instructions to the participant, began the video recording of the forward scene, and

played the simulation video. The video was projected on a wall in front of the vehicle to provide a near-full-size image of the simulated trip (see Figure 5). The clip showed a driver's view of a vehicle entering a highway tunnel and then encountering slowing and stopping traffic while inside the tunnel. The end of the clip was edited to show dark smoke streaming into the tunnel from ahead of the driver's vehicle and darkening the view of the tunnel. The soundtrack of the video was also edited to add the sounds of vehicle horns, engines, and a loud ventilation fan.



**Figure 5. Tunnel simulation, Stage 1: video clip viewed from vehicle.**

As the clip ended and the ambient sounds began, the experimental groups were provided information as follows:

- Group 1 participants were given no additional information beyond the ambient visual and audible cues from the video.
- Group 2 participants saw an overhead DMS displaying the message “FIRE IN TUNNEL—WALK TO EXITS.”
- Group 3 participants heard the following recorded audio message (via an MP3 player and portable speaker inside the vehicle): “Attention—there is a vehicle fire in the tunnel. Turn

off your engine and leave your keys in the vehicle so that it can be moved by emergency personnel. Leave your vehicle and walk quickly to emergency exits.”

Participant comments during the scenario were recorded. Following the video clip and any provided messages (DMS or audio), the researcher also prompted participants, as appropriate, with the following questions:

- “Given what you have observed so far, what would be your response at this point?”
- “What additional information would you look for?”

The researcher recorded all verbal responses to the questions, as well as any other participant actions in response to the simulated scenario. All participants, regardless of their experimental group and/or response to Stage 1, proceeded to Stage 2.







## **Stage 2: Sign/Marking Comprehension and Visibility**

In Stage 2, participants viewed a selection of exit signs, pathway markings, and exit door markings and beacons. A total of six sign formats were tested:

- A running man symbol with no text (ISO 7010 version of the symbol). This sign was the first viewed by every participant and was shown only as an internally illuminated sign.
- A running man symbol plus the word “EXIT.” Every participant saw this format twice, once as an internally illuminated sign and once as a photoluminescent sign.
- A running man symbol plus “EXIT” text, a directional arrow, and numerals identifying a distance in feet. Every participant saw this format twice. The internally illuminated version of the sign included a distance of 168 feet, and the photoluminescent version of the sign included a distance of 154 feet. These distance numbers were chosen deliberately to make participants less able to guess at a number before they could actually read it; in actual practice, it would be more typical to position signs at more predictable distances such as 150 feet or 175 feet.
- A text-only EXIT sign. Every participant saw two versions of this sign. The internally illuminated version of the sign also included chevron-type arrows on either side of the text, pointing right and left. The photoluminescent version of the sign did not include arrows.
- An emergency telephone symbol-only sign. Each participant saw this sign once; the sign was photoluminescent.
- A symbol-only sign designating an emergency refuge area for persons with disabilities. Each participant saw this sign once; the sign was photoluminescent.

Each participant also viewed a set of photoluminescent path markers. These included no text or graphics and were a non-electronic version of the LED path markers that were also tested during Stage 2. Table 5 summarizes the emergency exit signs and other devices that were tested during Stage 2.

**Table 5. Signs, Markings, and Beacons Tested in Tunnel Simulation, Stage 2.**

Comprehension Questions and Visibility Distances		a. LED Version	b. PL Version
 1. Running man (RM) symbol		X	
 2. Running man with EXIT text (exit door version)		X	X
 3. Refuge area sign			X
 4. Emergency telephone sign			X
 5. EXIT text-only signs		X	X
 6. Running man + EXIT text + arrow + distance		X	X
Visibility Distance Only		a. LED Version	b. PL Version
7. Pathway markers			X
Exit Door Markers—Forced-Choice Preference/Confidence Pairs			
8a. Flashing green	8b. Steady-state green	X	
9a. Flashing green	9b. Flashing green + verbal audio beacon	X	
10a. Flashing green	10b. Flashing green (traveling)	X	
11a. Flashing green (traveling)	11b. Flashing green + verbal beacon	X	

The signs were shown in three different sign orders, with approximately one-third of participants assigned to each of the three orders. Varying the orders in which the signs were



presented served two purposes—to minimize the impact of learning effects on comprehension results and to ensure that the same signs were not always seen in thicker smoke (present at the beginning of each participant’s test) or thinner smoke (present toward the end of each participant’s test). The exception was the symbol-only running man sign, which was the first sign that every participant saw; this was to better test comprehension of the running man symbol (before participants saw the symbol in combination with the “EXIT” text. The sign orders are shown in Table 6.

**Table 6. Viewing Orders of the Test Signs during Stage 2 of the Tunnel Simulation.**

<b>Sign Order 1</b>	<b>Sign Order 2</b>	<b>Sign Order 3</b>
RM symbol	RM symbol	RM symbol
EXIT + arrows	RM + EXIT (LED)	Emergency phone
Emergency refuge	Markers (PL)	RM + EXIT + arrow + 154 ft
RM + EXIT (PL)	RM + EXIT + arrow + 168 ft	EXIT
Emergency phone	EXIT + arrows	RM + EXIT (LED)
RM + EXIT + arrow + 154 ft	Emergency refuge	Markers (PL)
EXIT	RM + EXIT (PL)	RM + EXIT + arrow + 168 ft
RM + EXIT (LED)	Emergency phone	EXIT + arrows
Markers (PL)	RM + EXIT + arrow + 154 ft	Emergency refuge
RM + EXIT + arrow + 168 ft	EXIT	RM + EXIT (PL)

Ambient lighting within the artificial tunnel was adjusted to approximately 10 lux (measured in smoke-free conditions at floor level) to approximate typical nighttime tunnel lighting levels, and the tunnel was then filled with artificial smoke, as shown in Figure 6. The density of the smoke was measured throughout each participant’s testing session, recorded each time the participant viewed a sign.




**Figure 6. View of simulated tunnel, with partially dissipated smoke.**

*Procedure for Sign and Marking Comprehension/Visibility*

Each participant viewed each sign treatment one at a time, using the 60-foot corridor. Distances were pre-marked on the floor, and the researcher assisted the participant in finding and staying close to this marked path.

All signs were viewed at a height of 1.4 meters (4.5 feet) from the floor/walkway level. Signs were mounted at a 10-degree angle from the side walls of the corridor, to approximate a likely viewing angle of a pedestrian standing in the vehicle lane (i.e., standing next to his/her vehicle) and viewing a sign mounted flat on a tunnel wall from about 12 meters (40 feet) away. This slight angling of the test signs toward the participant helped to compensate for the much more constricted viewing angles possible in the 6-foot-wide artificial tunnel (see Figure 7 and Figure 8).

Pathway markings were viewed at a height of 1 meter (3 feet) from the floor/walkway level, in accordance with CIE 193-2010 (see Figure 9).



**Figure 7. Viewing distance/angle for test signs.**



**Figure 8. Mounting brackets for test signs (shown without ambient smoke).**



**Figure 9. LED path lights in simulated tunnel.**

This part of the simulation tested the following:

- **Detection distance:** For each of the sign and marking treatments, participants were asked to walk slowly forward from the start point marked in the corridor (a point at least 12 meters/40 feet away from the sign or marking) and to stop and tell the researcher when they could first see the sign or marking. The researcher recorded this distance, using distance markings on the floor of the corridor.
- **Legibility distance** (signs only): Participants were asked to continue walking slowly forward and to stop and tell the researcher when they could read the text and/or describe the symbol shown on the sign. The researcher recorded this distance.
- **Comprehension** (signs only): Participants were asked the meaning/message of the sign; in the case of exit signs that featured the word “exit,” participants were asked where they would expect to find the exit based on the sign. The researcher recorded the participants’ responses to these questions.

#### *Procedure for Pathway/Exit Door Treatments*

In place of actual exit doors, LED lights were used to mark pathways extending in both directions from the center of the corridor. The first four LED markers were placed at a height of 1 meter (3.2 feet) above the floor, spaced approximately 1.8 meters (6 feet) apart. The final LED marker in each direction was placed high on the wall close to each end of the corridor, in positions that would be at the top of standard-height doorways. In addition to the LEDs, an audio speaker was mounted at one end of the corridor close to the final LED doorway light. Participants viewed (and sometimes heard) each pair of pathway/door treatments from the center

point of the corridor; the researcher then asked, “Which direction would you be more confident about turning to find an exit?” and recorded the participants’ answers, along with the participants’ reasons for choosing as they did.

### Exit Survey

Besides the sign comprehension questions that were asked in the simulated tunnel environment, participants answered questions about some additional symbol and color combinations in a brief exit survey conducted after they finished Stage 2. Pictures of the signs and symbols were presented to each participant on a laptop computer, and the researcher recorded the participant’s verbal responses.

## RESULTS

### Stage 1: Response to Emergency Situation and Messages

Information was collected for 63 participants in Stage 1. Only one participant physically left the vehicle in response to the simulation in Stage 1 (after hearing the audio message instructing drivers to leave vehicles). The rest of the participants responded only verbally regarding their response to the situation and the information presented. The comments offered by participants during and immediately following the simulated drive, as well as their responses to the questions, were used to categorize their probable reactions to the emergency situation as “more likely to stay in the vehicle” or “more likely to leave the vehicle.” Table 7 summarizes these two categories of responses across the three information conditions (ambient cues only, DMS message, audio message).

**Table 7. Summary of Participant Responses to Tunnel Simulation, Stage 1.**

<b>Response</b>	<b>Ambient Cues Only</b>	<b>DMS Message</b>	<b>Audio Message</b>	<b>Total</b>
Stay in the vehicle	16 (80%)	4 (19%)	6 (27%)	28
Leave the vehicle	4 (20%)	17 (81%)	16 (73%)	35
<i>Total</i>	<i>20</i>	<i>21</i>	<i>22</i>	<i>63</i>

Chi-square analysis of responses indicated that participants who received the DMS message were significantly more likely to indicate an intention to leave the vehicle versus participants who received ambient cues only: Chi-square critical value = 15.1;  $p(X^2 > CV = 0.0001)$ . Similarly, participants who received the audio message were significantly more likely to indicate an intention to leave the vehicle versus those who received ambient cues only: Chi-square critical value = 11.6;  $p(X^2 > CV = 0.0007)$ .

There was no significant difference in expressed intentions between the participants who heard the audio message versus those who saw the DMS message: Chi-square critical value = 0.43;  $p(X^2 > CV = 0.51)$ .

#### *Staying or Leaving: Participant Comments*

Participants who indicated that they would be more likely to stay in their vehicle tended to talk about needing more information, waiting to see what others would do, waiting to see if smoke or fire got closer to them, or simply feeling that remaining in the vehicle would be the

safest course of action. Example comments from participants who indicated that they would be more likely to stay in the vehicle, at least until something else caused them to decide to leave, are listed below.

Comments from participants who received no warning message included:

- *I would stay in my car, maybe roll down my window to see if other people were getting out, but I definitely wouldn't get out first. Actually, I probably would just be wishing I had cell phone reception.*
- *I'd probably stay in my car, to be honest. I might eventually leave, would run in the opposite direction from the smoke.*
- *Can't get out because there are cars in front and back of me. If I left my vehicle it would be blocking the tunnel, or at least the lane. I would just sit and see if it was going to clear up and if the traffic would start moving again.*
- *I'd probably stay in the car unless things started getting hot. I might open the door to see if the smoke was all the way to the ground; if not, I might crawl out. If the whole tunnel is full of smoke, you're going to have to make a decision pretty fast.*
- *I'd stay in my car and see what might happen; if I had my phone I would call 911 and see if they could tell me what was happening. I might get out and talk to the person behind me to see if they know what's going on, but then might get back in my car—I feel like that might be safer.*
- *I would stop or slow down and see what is ahead and what options I have, either getting around it or getting out of it. Right now I think the only option I have is to stay with it, moving slowly or stopping as needed, and just work my way through it.*

Comments from participants who received a DMS or audio warning but still indicated they would be more likely to stay in the vehicle included the following:

- *I'm not going to get out without knowing what's out there. I'll wait for more information like what we heard on the radio. I would open it up to look, but I would stay in the car until I heard more about what to do. I'd want to wait until other cars were stopped, see what people in other cars were doing.*
- *Probably stay in my car and see what other people do.*
- *I'd be sitting in the car thinking "where the hell is an exit?" Because I hadn't seen any exit signs along the way that I'm aware of.*

Participants who indicated that they would be likely to leave their vehicle seemed either to recognize that smoke or fire in a tunnel presented an immediate hazard or to trust an official-sounding instruction to leave. Example comments are listed below.

Comments from participants who received no warning message but indicated they would leave their vehicle included:

- *I'd get out of my car and try to analyze by the available light how to exit and get out; the first place I would look is up, to see if there's any potential on those walls. I'm a brainstormer, so I would get with some other drivers and start strategizing a way out of there. Forget the car; I would take my purse, I'd be trying to call 911. I'd be extremely worried*

*for elderly and handicapped people, and would organize a search for anyone needing help inside the other vehicles. I'd be taking action.*

- *If it's smoke, I would think something is in danger of exploding and I would do my best to get away from it, if possible. If there was no way around in my car, I would probably get out to see, and run away if it looks dangerous. My life is more important than my car!*

Comments from participants who received a DMS or audio warning and indicated they would leave their vehicle were:

- *[DMS message] It says "walk to exit." I guess I'd walk to the exit. I'd head toward that sign. If I didn't have anything to carry with me, or any family to worry about, I'd probably make it.*
- *[DMS message] I remember passing the exit just several car lengths back, so I'm going to exit the car, go back and take that exit. It was kind of hard to see; I didn't see a lit exit sign. That would help, kind of like an exit sign in a building.*
- *[DMS message] I noticed when I was driving that there seems to be a railing to the left, so there's probably a walkway there. Assuming my cell phone was charged, I would turn it on and turn on the flashlight. Get out of the car, since that's what I'm being told to do, take my keys with me. If I knew the tunnel and had a good feeling for how long it was, I'd know which way to walk. If I didn't know the tunnel, I would probably walk back the way I came.*
- *[Audio message] If I hear someone telling me to get out of the car, I'm getting out of the car. I can guarantee you that's exactly what I'd do. I'd leave the key in the car. I'd probably try to grab my iPad, personal items, maybe grab some water if I had it in the car. And when I got out, I'd expect to see other people getting out too.*
- *[Audio message] I would probably listen to what he said and get out. Because that would be the emergency folks telling us what to do.*
- *[Audio message] I guess I'd get everyone out of the car and leave. I'm always attached to my keys, so leaving the keys in the car might be a challenge. I would assume that is what I'd do. If you see a fire in a tunnel, I'm not sure I would know what to do, so having a voice tell me what to do would be helpful, along with seeing other people getting out and leaving.*

### **Additional Information Needs**

Participant responses regarding additional information they would want to have most often fell into one of the following categories:

- Location of emergency exits.
- Pathway or other emergency lighting.
- Cause of the incident.
- Seriousness of the incident/situation.
- Instructions about what to do.

Table 8 summarizes the number of requests that were made by participants for each type of information under each of the three conditions. These total more than the number of participants since many participants listed several types of information that they would want.

**Table 8. Tunnel Simulation, Stage 1: Additional Information Wanted.**

Additional Information Wanted	Frequency of Request for Each Participant Group		
	Ambient Cues Only (20 participants)	Audio Message (21 participants)	DMS Message (22 participants)
Location of exits	4	15	17
Lights/path	7	8	12
Instructions about next actions	11	4	3
Cause of incident	12	2	3
Seriousness of incident	11	1	3
Other	0	7	1
None	0	2	1

As can be seen in the table, there was a difference in the information needs most frequently identified by participants who received only ambient cues about the emergency, versus those identified by participants who received one of the two messages. Participants who received only ambient cues were more likely to ask for instructions about what to do and about the cause of the incident and the seriousness of the incident—information that had already been provided to the other groups of participants. Participants who received either of the two messages were more likely to ask about exit locations and how to find them.

Other information needs that were mentioned by some participants included instructions to drivers to stop and/or watch for pedestrians, information about where drivers should stop (e.g., within their current lane or on a specified side of the tunnel), information about who/what entity was making the announcements (e.g., tunnel operator, emergency services), whether there would be additional announcements that people should be listening for, what would happen to abandoned vehicles, and where people should gather once they were out of the tunnel.

## **Stage 2: Sign Comprehension**




Each time a participant indicated that he or she could see/read the words and/or symbols on a sign, the researcher asked, “What is on the sign?” Once the participant had described the symbols and/or read the text on the sign, the researcher asked the participant about the meaning of the sign.

### *Symbol-Only Signs*

For signs that displayed symbols only (no text), the researcher then asked, “What do you think the sign is telling you?” Participants’ verbal responses to these questions were recorded and later scored according to how closely each participant’s interpretation of each sign matched the intended meaning of the sign. The scores for symbol-only signs are summarized in Table 9 as “correct,” “partially or near correct,” and “incorrect or don’t know.” Descriptions of these scores for each sign type are described in the subsections below.



**Table 9. Comprehension Scores for Symbol-Only Signs.**

Sign		Correct Definition	Partially or Near Correct	Incorrect or Don't Know
Running man symbol		29 (48%)	23 (38%)	9 (15%)
Refuge point		5 (8%)	46 (75%)	10 (16%)
Emergency phone		53 (87%)	7 (11%)	1 (2%)

**Running Man Symbol.** The running man symbol was the first sign each participant saw; this order was intended to gauge how well the symbol was comprehended as a stand-alone information element. Most participants identified the symbol as a “running person,” “running man,” “someone running,” or “pedestrian.” When asked what the sign meant, 29 participants (48 percent) said that it indicated an exit (scored as “correct” in Table 9); another 23 (38 percent) said that it indicated a walkway or path that they would follow (scored as “partially/near correct”).

The nine participants whose responses were scored as “incorrect” thought the sign was a pedestrian crossing sign, to warn drivers that someone may be crossing the roadway in front of them.

**Emergency Phone Symbol.** This sign was included in the comprehension testing primarily to reduce the expectation that every sign would have something to do with an exit from the tunnel. Sixty out of 61 participants (98 percent) identified the phone and flame symbols on the sign; 53 out of 61 (87 percent) specifically stated that the phone was an “emergency” phone or a “phone to report a fire.” Seven participants (11 percent) indicated that the sign indicated a phone, but not necessarily for emergencies; one of these stated that it might be a phone that is fire protected. One participant stated that he/she had “no idea” what the paired symbols might mean.






**Refuge Point.** This sign, which like the emergency telephone sign was included to indicate something other than an exit from the tunnel, was the least-recognized symbol among the participants. While all participants correctly identified the wheelchair symbol as indicating something pertaining to people with disabilities, only five (8 percent) stated that the sign identified a safe/refuge area. Ten participants guessed that the sign indicated something (but could not guess what) for a disabled person, or that it was warning drivers to watch for people with disabilities close to the road. The remaining 46 participants guessed that the sign marked an accessible exit door or ramp, or a stored wheelchair that could be used to transport a disabled person.

*Signs Including “EXIT” Text*

For signs that included the text “EXIT,” the researcher asked the participants, “Where would you expect to find the exit, based on this sign?” Participant responses were scored as “correct” if their expectation for the sign location matched the customary use of the sign (i.e., a text EXIT sign or a running man sign with no directional arrow would be used on or above an exit door; signs with directional arrows would be used to indicate that an exit would be in the direction of the arrow or arrows). Table 10 summarizes the comprehension scores for the signs that included EXIT text as part of the legend.

It should be emphasized that the comprehension scores in Table 10 should be not considered as having identical meanings to the comprehension scores for the symbol-only signs shown in Table 9; it can be assumed that all participants recognized the signs containing EXIT text as representing exits. The correctness of participant responses for the signs containing text refers only to where participants expected to find exits, based on a given sign.

**Table 10. Comprehension Scores for Signs with Text.**

Sign	Correct Exit Location	Partially or Near Correct Location	Incorrect or Don’t Know	
Running man + EXIT text (1 <sup>st</sup> viewing)		16 (26%)	45 (74%)	0 (0%)
Running man + EXIT text (2 <sup>nd</sup> viewing)		11 (18%)	50 (82%)	0 (0%)
Running man + EXIT + distance + arrow (1 <sup>st</sup> viewing)*		60 (98%)	1 (2%)	0 (0%)
Running man + EXIT + distance + arrow (2 <sup>nd</sup> viewing)*		59 (97%)	1 (2%)	1 (2%)
EXIT text + arrows		46 (75%)	2 (3%)	13 (21%)
EXIT text only		51 (84%)	7 (11%)	3 (5%)

\*Participants in Groups B and F saw the “154 ft” sign first; participants in Groups A, C, D, and E saw the “168 ft” sign first.

**Running Man with EXIT Text.** Participants saw this sign format twice, once as an LED-illuminated sign and once as a photoluminescent sign. All participants identified this as an exit sign; most (74 percent on first viewing, 82 percent on second viewing) thought that it indicated an exit nearby but past the sign in the direction that the running man was facing (scored as partially or near correct in Table 10). A smaller percentage (26 percent on first viewing, 18 percent on second viewing) identified the sign as being an exit door sign; this was scored as “correct” in Table 10.

**Running Man with EXIT Text, Arrow, and Distance.** Participants saw one LED-illuminated sign showing an exit 168 feet to the right, and one photoluminescent sign showing an exit 154 feet to the left; Participant Groups B and F saw the 154 feet sign first, while the other groups saw the 168 feet sign first. Nearly all participants comprehended both of these signs correctly, stating that the exit was in the direction that the arrow was pointing, at the stated distance away. Some participants commented that while they were uncertain of how far 168 feet or 154 feet would be, the sign nonetheless provided them with the information that the exit was some distance away, not in the immediate area. A small number of participants stated the distance and then translated that distance into an approximate number of paces that would get them to the exit.

One partially correct response for this sign was a misreading of the number as 15.4 feet instead of 154 feet; the other was a statement that the exit was “to the left of that sign” (the direction of the arrow) without specifying a distance. The only incorrect interpretation of this sign was from one participant who thought that it could mean “exit here, then go 168 feet in the direction of the arrow.”

**EXIT Text Signs with Chevron Arrows (Two Directions).** Participants saw two versions of an EXIT text-only sign: an LED internally illuminated sign that included two chevron arrows (indicating exits in either direction) and a photoluminescent EXIT sign without arrows. The EXIT sign with the bi-directional arrows was recognized by all participants as indicating one or more exits, but participants’ expected locations of those exits were not as consistent. The correct answer, that the two arrows indicated exits in both directions, was stated by 46 of the 61 participants (75 percent). Two participants (3 percent) stated that the exit was next to the sign, implying an exit in one direction rather than two. The remaining 13 participants (21 percent) assumed that the exit would be directly below the sign; some of these, from their comments, seemed not to recognize the chevron arrows as representing directions (one participant said specifically that they looked like brackets).

**EXIT Text Signs (No Arrows).** All participants recognized the sign as identifying an exit, and 51 out of 61 (84 percent) expected that the sign would be hanging on or directly above the exit door. Another seven (11 percent) expected to find the exit door in close proximity to the sign. Three participants (5 percent) stated that they were uncertain where an exit would be in relation to the sign’s location.

## **Stage 2: Sign Visibility**

Results for the sign detection and legibility distances are included in Chapter 5, along with the luminance measurements for each sign.

## **Stage 2: Path Marking Preferences**

Four formats of pathway/exit door beacons were tested. All of these formats included a series of green LED lights spaced approximately 1.2 meters (4 feet) apart along the wall at a height of 1 meter (3.2 feet). The final LED light at either end of the artificial tunnel structure was positioned high on the wall to simulate a light just above a doorway. The four formats included the following:

- Steady-state LEDs (no flashing).
- Unison flash, in which all of the LEDs along the path flashed on and off at the same time.

- Traveling flash, in which the LED lights flashed individually in a repeated sequence from left to right (from the perspective of the viewer) and thus appeared to travel to the right.
- Unison-flash LEDs plus an audio beacon at the door location.

As described in the procedures section, these four options were presented to participants in pairs, as shown in Table 11, with one option in each pair to the left of the participant and the other option to the right of the participant. The participant was then asked, “Which direction would you be more confident about going to find an exit (left or right)?” A follow-up question asked for the participant’s reason for his or her preference.

**Table 11. Path/Door Marking Comparisons.**

<b>Comparison</b>	<b>Most Frequently Preferred</b>	<b>Number Preferring (out of 61)</b>	<b>Percent Preferring</b>
Unison flash vs. steady state	Unison flash	37	61%
Unison flash vs. unison flash + audio	Unison flash + audio	56	92%
Unison flash vs. traveling flash	Traveling flash	49	80%
Unison flash + audio vs. traveling flash	Unison flash + audio	44	72%

### *Unison Flash versus Steady State*

Participants viewed a series of steady-state (continuously lit) LED path markers to the right and a series of LED path markers to the left that flashed in unison. Sixty-one percent of participants preferred the unison-flash markers to the steady state. Comments from participants who preferred the unison-flash markers included the following:

- *The blinking draws attention.*
- *It indicates “emergency” and “attention.”*
- *The flashing says, “Move!”*
- *It seems like it’s active, that it’s trying to point out something.*
- *Steady lights are just lighting; the flashing lights are telling me to do something.*
- *You can tell it’s not just normal lighting; since it draws your attention, it must matter more.*

Comments from participants who preferred the steady-state markers included the following:

- *Sometimes blinking means “hazardous”; the solid [steady-state] markers look like an airplane exit path.*
- *The flashing almost seems like something’s wrong, while the steady lights are reassuring.*
- *I don’t particularly like strobe lights because they’re a little disorienting. Maybe a slower flash rate would be better.*

- *The flashing almost looks like “watch out, there’s a problem.”*
- *The steady lights are not as disorienting and provide easier depth perception in a smoky environment.*

### *Unison Flash versus Unison Flash plus Audio*

In this comparison, both the left and the right series of LED path markers flashed in unison; in addition, an audio beacon to the left of the participant (approximately 8.5 meters or 28 feet away) repeated the phrase “exit here,” alternating between English and Spanish. Ninety-two percent of participants preferred the addition of the audio message to the path markers alone. Comments from participants who preferred the addition of the audio message included the following:

- *I’d follow the sound.*
- *The voice is telling me to go that way.*
- *That’s where the sound is coming from. In this case, the flashing lights call attention to the voice and the path.*

There were no participants who stated that they preferred the flashing lights without the audio beacon, but some had no preference between the two pathway directions. Comments from these participants included the following:

- *I wouldn’t trust the direction of the voice; it’s inadequate as a directional guide.*
- *I can’t tell where the voice is coming from.*
- *I’d change the message to “follow my voice and exit here.”*

### *Unison Flash versus Traveling Flash*

Participants viewed a series of LED path markers to the left that flashed in unison, and a series to the right that flashed individually in a repeating sequence that began with the marker closest to the participant and traveled down the wall to the right. Eighty percent of participants preferred the traveling flash to the unison flash. Comments from participants who preferred the traveling flash option included the following:

- *I like the progression of the lights telling me the direction to go.*
- *It looks like an arrow.*
- *I see which direction it wants me to follow.*
- *It’s a slower blink than the [unison flash]; it doesn’t mess with my eyes as much. Besides, the lights imply “that way,” like runway lights.*

Comments from participants who preferred the unison flash included the following:

- *The [unison flash] is more prominent.*
- *It seems to be blinking faster than the other direction.*
- *Both are good; [unison flash] is drawing me [toward it] more.*

### *Unison Flash plus Audio versus Traveling Flash*

The unison-flash LED lights plus the “exit here” audio beacon were presented to the participants’ left, while the traveling flash LED path (with no audio) was presented to the right. Seventy-two percent of participants preferred the unison flash plus audio to the traveling flash, but several of these commented that a combination of the two strategies would be ideal. Comments from participants who preferred the unison flash plus audio option included the following:


- *Easier to go toward the voice, especially if you’re disoriented.*
- *The voice outweighs the [traveling] lights.*
- *The voice gives me immediate confidence to go that way.*
- *The voice is more prominent, but I would recommend using both.*
- *The voice is good, but [traveling] lights would also be powerful; the voice could be echoing more in a tunnel.*

Comments from participants who preferred the traveling flash option included the following:

- *“Exit here” may not mean anything if I’m disoriented; also [the traveling light path] is a little calmer.*
- *The arrow effect is good.*
- *In a tunnel, it might be hard to tell where the voice is coming from.*


### **Exit Survey Responses**

The first question in the exit survey asked, “Does the direction the running figure is facing always indicate the direction of the exit?” (see Figure 10). Of the 63 participants, 58 (92 percent) answered “yes” to this question, which is consistent with how most participants interpreted the directionality of the running man signs during Stage 2.




**Figure 10. Exit survey, question 1.**

Question 2 asked whether a running man symbol on a sign meant the same thing to participants as the symbol accompanied by the word “EXIT” (see Figure 11). Fifty participants (79 percent) answered that the two signs meant the same; of these, 48 nevertheless preferred the version that included the “EXIT” text, feeling it provided more clarity.



**Figure 11. Exit survey, question 2.**


Question 3 asked whether the running man symbol meant the same to participants as the traditional EXIT text sign (see Figure 12). Responses were mixed, with 30 participants (48 percent) answering that the two signs had the same meaning and 33 participants (52 percent) answering that the signs had different meanings. Of the 30 participants who felt that the two signs had equivalent meanings, 22 preferred the text EXIT sign, most often because they felt it was clearer and more familiar. Participants who answered that the two signs had different meanings tended to interpret the running man symbol as indicating an upcoming exit in the direction that the running man was facing, versus assuming that the text EXIT sign would be used at the location of the exit itself.



**Figure 12. Exit survey, question 3.**


Question 4 asked whether a red EXIT text sign meant the same to participants as a green text sign (see Figure 13). Fifty-seven participants (90 percent) answered that the two sign colors had the same meaning; of these, 31 preferred red and 16 preferred green. Participant comments about sign colors included the following:

- *Green means that you can exit this direction at any time. Red would mean it's an emergency exit only.*
- *In the tunnel, I could see green easier than red.*
- *I'm more accustomed to a red exit sign.*



**Figure 13. Exit survey, question 4.**

Question 5 asked if a running man symbol alone meant the same thing to participants as a running man sign paired with a directional arrow (see Figure 14). Fifty participants (79 percent) answered that the addition of the arrow did not change the meaning of the sign (in actuality, the running man symbol by itself is generally used for an exit door, while the addition of an arrow indicates that the exit is in the direction of the arrow). This again underscores the prevailing view among the study participants that the running man symbol by itself indicated direction.




**Figure 14. Exit survey, question 5.**

Questions 6 and 7 paired a running man symbol with arrows pointing directly up and down, respectively, and asked what the symbol combinations would mean to participants (see Figure 15).

Twenty-two participants (35 percent) selected one of the two provided answers: that the down arrow likely meant “you are at the exit,” with some of these stipulating that they would expect this combination to be positioned above a doorway. Seven participants (11 percent) selected the answer “you need to keep going in your current direction for the exit.” The other 33 participants (52 percent) provided other definitions for this symbol combination, with most answering that the arrow would indicate a staircase, elevator, or downward slope.


The up arrow was also identified by the largest number of participants (26, or 41 percent) as indicating an upward staircase, ramp, or elevator. Twenty participants (32 percent) selected the provided answer “you need to keep going for the exit,” and eight selected the answer “you are at the exit.”





**Figure 15. Exit survey, questions 6 and 7.**


Questions 8 and 9 similarly paired a running man symbol with different directional arrows (an arrow pointing directly right versus an arrow pointing right but angled either up or down, as shown in Figure 16.) Most participants (57, or 90 percent, for the downward-angled arrow; 59, or 94 percent for the upward-angled arrow) believed that the arrow pointing directly right indicated that an exit would be on the same level as the pedestrian, while an angled arrow indicated that the pedestrian would have to go up or down, most likely via a staircase. A couple of participants thought the angled arrows could indicate an exit at the same vertical level, but in a diagonal direction or around a corner from the location of the sign.



**Figure 16. Exit survey, questions 8 and 9.**


Question 10 asked participants if small chevron arrows and tailed arrows meant the same thing when used with exit signs (see Figure 17). Fifty-seven participants (90 percent) answered that the two arrows had the same meaning, though 47 of these preferred the tailed arrow to the chevron arrow for visibility and/or clarity. Comments from the small number of participants who indicated that the two arrows had two different meanings included the following:

- *The chevron arrow means that the exit is underneath the sign and to the right. The tailed arrow means that exit is coming up to the right, but you need to keep walking.*
- *The chevron doesn't look like an arrow, especially if it's on both sides. Maybe three chevrons in a row would look more like a direction.*



**Figure 17. Exit survey, question 10.**

Question 11 asked participants if a running man exit sign that included a distance along with a directional arrow meant the same as the directional sign without a distance (see Figure 18). Responses were mixed, with 37 participants (59 percent) answering that the two formats meant the same thing and 26 participants (41 percent) answering that the two signs provided different messages. Participants who indicated that the two signs provided different messages most frequently assumed that the sign without a specific distance included should indicate an exit that is only a short distance away. Participant comments, regardless of the answer selected, were very similar—most preferred the sign that included the distance, feeling that it provided clearer and more complete information to pedestrians.



**Figure 18. Exit survey, question 11.**

## **TUNNEL SIMULATION CONCLUSIONS**

Stage 1 of the tunnel simulation indicated that providing an evacuation message to drivers during an emergency situation increases the likelihood that they will leave their vehicle. The message mode (sign or audio) did not seem to greatly influence this result, as long as drivers received the information in one form or another. As seen in the focus group results, the most important message elements seemed to be an explanation of the situation and direct instruction; the drivers who did not receive a message in Stage 1 were most likely to ask for these pieces of information. Once drivers indicated their decision to leave the vehicle, their most frequent questions were about how to find and identify exits. One caveat that should be noted regarding the audio message is that participants heard this message via a small speaker inside the vehicle, not from a loudspeaker outside the vehicle. The sound quality and therefore the intelligibility of

the audio message would be greatly reduced if it were broadcast over a loudspeaker inside a tunnel.

## **Exit Sign Comprehension**

In Stage 2, participants had little or no trouble comprehending most of the exit signs. The stand-alone running man symbol that was presented first was identified correctly by 48 percent of participants as an exit sign, while another 38 percent assumed that the sign indicated a direction or path for them to follow. Once the running man symbol was paired with the word EXIT, the most common misconception by participants had to do with where they would expect to find the exit door in relation to the sign.

Most participants thought that the running man sign (with or without the word EXIT) indicated a direction, even without a supplemental arrow. Because of this inferred directionality, the most frequent assumption among participants was that the running man symbol indicated an exit that was to the side of the sign or farther away in the direction that the running figure was facing. It should be noted, however, that participants saw all signs in the context of a wall-mounted frame and so did not have the added context of a visible doorway.

Conversely, the only notable misconception about the text-only EXIT sign was related to the version of the sign that included chevron arrows in two directions; a small number of participants did not recognize the directionality of this sign and assumed that it must be above the exit door itself. The confusion among those participants seemed to lie with recognition of the chevrons as directional arrows, and the familiarity of seeing text EXIT signs above exit doors.

When the running man sign was paired with a (tailed) directional arrow and a distance, comprehension was perfect among nearly all participants. A directional arrow without a distance included (tested with a text EXIT sign in Stage 2 and with a running man sign in the exit survey) was generally understood to indicate that an exit would be found in the direction of the arrow, but most participants felt that specifying the distance to the exit provided clearer information. The assumption among many participants was that an arrow without a specified distance implied that the exit was nearby.

Tailed arrows were preferred by participants over chevron arrows for indicating a direction to an exit. Tailed arrows pointing directly left or right were clearly understood; arrows pointing or angled up or down required explanation.

## **Path Markings and Audio Beacons**


Directional/traveling path markers leading to an exit door and an audio beacon at the door location were the most preferred options among those presented to participants; when these two measures were placed opposite each other, more participants ultimately preferred the audio beacon as a directional aid. However, it should be noted that the audio beacon was less than 30 feet away, and acoustics in the artificial tunnel are not the same as in an actual tunnel (and a few participants still had trouble determining the direction the sound was coming from). Audio beacons would therefore be effective only at short distances (and in locations where ambient noise levels would not be likely to mask the sound), while the effectiveness of directional path lighting would extend over longer distances.

Non-directional path markings were also considered valuable; participant preferences were mixed about flashing versus steady-state markers, with a slight majority preferring flashing markers.

## CHAPTER 5. PHOTOMETRIC MEASUREMENT PROCEDURE AND RESULTS

The researchers took photometric measurements to quantify the visibility for each of the study treatments using two different methods. First, they monitored the opacity of the smoke throughout the study to quantify the available visibility during testing. A Wager 6500 smoke meter (Figure 19a) provided a continuous output of smoke opacity in the vicinity of the signs in the artificial tunnel. The percent opacity was recorded each time a participant viewed a sign. Zero percent opacity would equate to a clear tunnel with no smoke; 100 percent opacity would prevent any transmission of light.

Separately from participant testing, luminance measurements of test signs were conducted using a calibrated Remax/Radiant Imaging PM-1600 charge-coupled device (CCD) photometer (Figure 19b).








**Figure 19. Equipment used to measure smoke opacity, sign luminance and contrast.**

### LUMINANCE MEASUREMENT RESULTS

Table 12 describes the signs that were measured with the photometer. These signs represented two different types of sign technologies (internally LED-illuminated and photoluminescent) as well as positive versus negative contrast. Positive contrast signs typically consist of a light-colored legend against a darker background. The positive contrast signs tested in this study were the two text-only EXIT signs, one with text that was internally illuminated by LEDs and the other with photoluminescent text, both against non-illuminated backgrounds. (The LED and PL versions of the directional arrows, seen as part of the running man exit distance signs, were also positive contrast.) Negative contrast signs have a darker legend against a light (or illuminated/photoluminescent) background. The running man symbols and accompanying EXIT and distance text are all positive contrast sign elements. All of the signs that participants viewed in the tunnel simulation represented variations of the two technologies and the two contrast types shown in Table 12.

**Table 12. Signs Measured with Photometric Equipment.**

Sign	Sign	Comments
Running Man Exit Distance (LED)		Portions of the sign are covered by gray tunnel wall panels to provide background contrast
Sections of Running Man Exit Distance (PL)		Individual panels (EXIT, arrow, distance) are measured individually against a gray background
Text EXIT with Illuminated Letters (LED)		Sign background/casing is white but appears dark in low light levels when text is illuminated
Text EXIT with Glow Letters (PL)		Sign background is red but appears darker in low light
PL Marker		Photo shows PL marker (top) against gray background (bottom)


Each of these signs was measured under non-smoke and smoke conditions and under two ambient lighting conditions: with the emergency-level ambient lighting conditions used during the participant testing (set at approximately 10 lux) and with no ambient light. While luminance should not change with distance for most treatments under non-smoke conditions, it will under smoke conditions, so measurements were completed at multiple viewing distances and smoke opacity levels, as shown in Table 13. Measurements included the luminance levels of each treatment’s positive (brighter) and negative (darker) elements, as well as the luminance of the gray painted background around each sign (representing the tunnel wall). This allowed researchers to calculate the luminance contrast of the positive and negative elements within each sign, as well as the contrast between each sign and the tunnel wall.

**Table 13. Luminance Measurements and Conditions.**

Luminance Measurements	Overhead Lighting	Viewing Distance	Opacity
<ul style="list-style-type: none"> <li>• Positive (brighter) element of sign</li> <li>• Negative (darker) element of sign</li> <li>• Gray background behind sign</li> </ul>	Yes	5 feet (1.5 meters)	0%
			12%
			23%
		10 feet (3 meters)	5%
			10%
		25 feet (7.6 meters)	4%
	No	5 feet (1.5 meters)	0%
			12%
			23%
		10 feet (3 meters)	5%
			10%
		25 feet (7.6 meters)	4%

**Luminance and Contrast in Smoke**


The photometric measurements quantified the effects of the artificial smoke on luminance and contrast levels of the test signs. As shown in Figure 20, the effective luminance of both LED and PL signs viewed from 10 feet (3 meters) away declined sharply at low levels of smoke opacity. The “EXIT” segment from the LED running man exit distance sign’s measured luminance of 335 cd/m<sup>2</sup> (97.8 fL) in clear conditions dropped to 74.1 cd/m<sup>2</sup> (21.6 fL) with a smoke opacity of only 5 percent; at 10 percent smoke opacity, the effective luminance of the sign was 29.8 cd/m<sup>2</sup> (8.7 fL). A viewing distance of 5 feet (1.5 meters) reduced the effects of smoke opacity somewhat (93.6 cd/m<sup>2</sup> or 27.3 fL at 12 percent smoke opacity, 34.2 cd/m<sup>2</sup> or 10 fL at 23 percent opacity), but the effects were still dramatic. The PL sign began at a much lower luminance level (12 cd/m<sup>2</sup> or 3.5 fL with no smoke) and declined to 5.9 cd/m<sup>2</sup> (1.7 fL) at 5 percent smoke opacity and 4.7 cd/m<sup>2</sup> (1.4 fL) at 10 percent smoke opacity (both at a 10-foot/3 meter viewing distance).




**Figure 20. Luminance measurements of selected LED and PL negative contrast signs.**

Besides the sharp drop in visible luminance from the test signs as smoke opacities increased, significant declines were seen in the contrasts between the signs and the tunnel wall and between the signs' positive and negative luminance areas. Figure 21 shows the contrast ratios of the LED and PL running man signs—specifically the contrast between the illuminated/glowing backgrounds of these signs with the gray tunnel wall panels under an ambient light level of approximately 10 lux. The luminance ratio of the LED sign backgrounds to the tunnel wall was approximately 72:1 in clear conditions; at a 10-foot viewing distance, this ratio dropped to 5:1 at 5 percent smoke opacity and less than 3:1 at 10 percent smoke opacity. The PL signs also declined in contrast with the wall background, from 9:1 with no smoke to 1.5:1 and then 1.1:1 at 5 percent and 10 percent smoke opacities, respectively.

When there was no ambient light, and therefore much less veiling luminance from light reflecting off smoke particles, contrast ratios between the signs and the tunnel walls improved. Figure 22 illustrates the contrast ratios at the same viewing distances and smoke opacity levels when no ambient light was present. The luminance contrast of the LED signs with the wall from 10 feet away was approximately 97:1 with no smoke, 7.6:1 at 5 percent smoke opacity, and 4.2:1 at 10 percent smoke opacity. The PL signs actually fared better than the LED signs in darkness, with contrast ratios of 137:1 in clear conditions, 9.6:1 at 5 percent smoke opacity, and 5.2:1 at 10 percent smoke opacity.



**Figure 21. Contrast ratios: running man signs vs. tunnel wall, with ambient light.**




**Figure 22. Contrast ratios: running man signs vs. tunnel wall, no ambient light.**

Finally, the contrast ratios between the positive (brighter) and negative (darker) areas within each sign also declined with increasing smoke opacity, as shown in Figure 23. This is one metric in which PL signs surpassed LED signs in clear (no smoke) conditions when ambient light was present: the positive/negative contrast of the green “EXIT” text against the




photoluminescent background was approximately 16:1. The corresponding contrast for the LED sign was approximately 4:1. At 5 percent smoke opacity, the contrast ratio for the PL sign dropped to 1.6:1; the corresponding contrast for the LED sign was 2.3:1.

The positive/negative ratios improved in the absence of ambient light, similar to the improvement seen in the sign/wall contrasts (see Figure 24). Again, the PL version of this sign had higher positive/negative element contrasts than the LED version (likely because even the dark portions of the LED signs were somewhat illuminated by the internal LEDs, while the dark portions of the PL signs had no such illumination).




**Figure 23. Contrast ratios: sign positive/negative luminance areas, with ambient light.**




**Figure 24. Contrast ratios: sign positive/negative luminance areas, with no ambient light.**

All of the above descriptions focused on the negative contrast portions of the running man signs. Figure 25 compares the luminance of the LED and PL versions of the text-only EXIT signs with illuminated or photoluminescent text against a non-illuminated background. Figure 26 compares the contrast ratios of the positive and negative elements of these two signs.



**Figure 25. Luminance measurements of selected LED and PL positive contrast signs.**



**Figure 26. Contrast ratios: sign positive/negative luminance areas of EXIT text-only signs, with ambient light.**

The luminance measurements all displayed some general trends that were echoed in the detection and legibility distance results in the tunnel simulation.

- All of the signs lost much of their effective luminance even with very low levels of smoke in the atmosphere. This affected how far away they could be seen and reduced the contrast between their light and dark areas, which made text and symbols more difficult to read.
- In general, PL signs began at much lower luminance levels than LED signs and remained at lower luminance levels compared to LED signs in smoky conditions. However, the differences in luminance between the PL and LED signs diminished as smoke opacity increased.
- Under low levels of ambient light, the contrast of sign luminance with the tunnel wall diminished rapidly as smoke opacity increased. In general, LED signs slightly outperformed PL signs. When there was no ambient light, contrast between the tested signs and the tunnel walls was much higher, and PL signs displayed higher contrast ratios than LED signs.
- Contrast ratios between lighter and darker regions of a sign (e.g., the contrast between a sign’s legend and its background) were consistently higher for PL signs than for LED signs. This was the case with low levels of ambient light and was even more pronounced without ambient light.

## DETECTION AND LEGIBILITY DISTANCES

Detection and legibility distances were recorded for each sign that participants viewed, as well as for a photoluminescent path marking square. In some cases, detection and legibility distances for a single sign were nearly identical; this happened most frequently with single-panel signs such as the text-only EXIT signs and the symbol-only running man sign.


Participants saw treatments at varying smoke opacities, despite efforts to maintain some consistency in smoke volume and density during participant testing. The output of the smoke machine could not be precisely regulated; in addition, smoke opacity gradually diminished

within each participant’s testing period due to the movement of the participant and researcher through the simulated tunnel. With the exception of the initial running man symbol sign, which was always presented first to participants, the test signs were presented in three different orders to help balance the effects of smoke opacity across the testing sessions; however, the exact opacity percentage at the moment each sign was viewed varied from participant to participant. Because of this variance in smoke opacity, a paired t-test of the detection distances and legibility distances could not be conducted between pairs of signs. Instead, a comparison of the scatter plots and trend lines of the detection and visibility distances for each sign was conducted.

A power regression was the best fit for most of the sign detection and visibility distances through the range of smoke opacity conditions. While smoke opacities ranged from 5.6 percent to 28.7 percent (a handful of measurements with smoke opacities less than 5 percent were removed from the data set as outliers), about two-thirds of the measured opacity levels during participant testing fell between 8 and 14 percent, with a mean opacity of 10.9 percent and a median of 10.4 percent. Table 14 summarizes the detection and legibility distances predicted by the regression equations for each of the tested signs at smoke opacities of 5, 10, 12, and 23 percent. Figure 27 extrapolates the predicted detection and legibility distances for the LED and PL versions of the running man exit distance signs at smoke opacities up to 40 percent.

**Table 14. Detection and Legibility Distances Predicted at Varying Smoke Opacity Levels.**

Sign		Opacity				<i>R<sup>2</sup> of Trend Line</i>
		5%	10%	12%	23%	
Predicted Detection Distance (in feet)	Running Man Exit (LED)	40.4	22.4	19.2	11.0	0.84
	Running Man Exit (PL)	21.6	11.1	9.4	5.0	0.78
	Running Man Exit Distance (LED)	44.9	24.6	21.0	11.9	0.85
	Running Man Exit Distance (PL)	23.6	11.9	10.0	5.3	0.78
	Text EXIT (LED)	28.8	15.7	13.3	7.5	0.83
	Text EXIT (PL)	22.0	10.6	8.7	4.4	0.79
	Running Man Symbol (LED)	39.1	19.2	15.9	8.2	0.64
	Phone (PL)	10.1	5.6	4.8	2.8	0.36
	Refuge (PL)	12.4	6.5	5.5	3.0	0.34
	Marker (PL)	22.2	12.1	10.3	5.8	0.66
Predicted Legibility Distance (in feet)	Running Man Exit (LED)	28.9	17.7	15.5	9.8	0.57
	Running Man Exit (PL)	12.8	8.0	7.0	4.5	0.40
	Running Man Exit Distance (LED)	34.1	18.7	16.0	9.1	0.73
	Running Man Exit Distance (PL)	15.2	9.0	7.8	4.8	0.53
	Text EXIT (LED)	21.8	14.1	12.5	8.3	0.61
	Text EXIT (PL)	17.2	9.7	8.3	4.9	0.50
	Running Man Symbol (LED)	25.3	15.0	13.1	8.0	0.48
	Phone (PL)	7.6	4.8	4.2	2.7	0.35
	Refuge (PL)	8.5	5.3	4.7	3.0	0.25



**Figure 27. Estimated detection and legibility distances at varying smoke opacity percentages.**

Details of the observed detection and legibility distances of tested signs are provided in the following sections.

### Running Man EXIT Signs

The running man EXIT signs consisted of a running man symbol accompanied by the word “EXIT.” These signs had an illuminated (LED) or glow (PL) white background, with dark green symbols and text. Figure 28 shows the scatter plots and trend lines for the detection distances of the internally illuminated and photoluminescent versions of the signs. Figure 29 shows the scatter plots and trend lines for the legibility distances of these signs.

The regression equation for detection of the LED-illuminated running man EXIT sign ( $R^2 = 0.84$ ) predicted a detection distance of 22.4 feet when smoke opacity was 10 percent and 19.2 feet when smoke opacity was 12 percent. Predicted detection distance for the PL version of this sign ( $R^2 = 0.78$ ) was 11.1 feet at 10 percent smoke opacity and 9.4 feet at 12 percent opacity, approximately half the respective distances for the LED version of the sign. Greater variances in the observed legibility distances for these two signs resulted in weaker trends than those for the detection distances, but predicted legibility distances for the PL sign were also about half the distances for the LED sign at 10 percent and 12 percent smoke opacity.




Figure 28. Detection distances for running man EXIT signs, LED and PL.




Figure 29. Legibility distances for running man EXIT Signs, LED and PL.

## Running Man Directional/Distance Signs

The running man directional/distance test signs included the running man symbol and “EXIT” text, plus a distance shown in numerals and a tailed arrow pointing either left or right. Figure 30 shows the scatter plots and trend lines for the observed detection distances of the internally illuminated and photoluminescent versions of the running man directional signs. Figure 31 shows the scatter plots and trend lines for the observed legibility distances of the internally illuminated and photoluminescent versions of these signs.

The regression equation for detection of the LED-illuminated running man direction/distance sign ( $R^2 = 0.85$ ) predicted detection distances of 24.6 feet at smoke opacity of 10.0 percent and 21 feet at 12 percent opacity. Detection distances predicted for the PL version of this sign ( $R^2 = 0.77$ ) were 11.9 feet at 10 percent smoke opacity and 10 feet at 12 percent opacity. Legibility distances predicted for the LED version of the sign ( $R^2 = 0.73$ ) were 18.7 feet at 10 percent smoke opacity and 16.0 feet at 12 percent opacity; the legibility distances predicted for the PL version of the sign ( $R^2 = 0.53$ ) were 9 feet at 10 percent opacity and 7.8 feet at 12 percent opacity.




Figure 30. Detection distances for running man direction/distance signs, LED and PL.




Figure 31. Legibility distances for running man direction/distance signs, LED and PL.

### Text EXIT Signs

Two text-only EXIT signs with illuminated (LED) or glow (PL) letters on a non-illuminated background were tested. The LED version of the sign had red illuminated text illuminated internally by red LEDs; the PL version of the sign had photoluminescent white text. Significantly, these two signs were the only two positive contrast (i.e., illuminated text against a non-illuminated background) exit signs tested; the other exit signs were negative contrast signs, with illuminated or glow backgrounds and darker text. Figure 32 shows the scatter plots and trend lines for the detection distances of the internally illuminated and photoluminescent versions of the text EXIT signs. Figure 33 shows the scatter plots and trend lines for the legibility distances of these two signs.

The regression equation for detection distance of the LED text-only EXIT sign ( $R^2 = 0.83$ ) predicted detection distances of 15.7 feet at smoke opacity of 10 percent and 13.3 feet at opacity of 12 percent. Detection distances predicted for the PL version of the EXIT text sign ( $R^2 = 0.79$ ) were 10.6 feet at 10 percent smoke opacity and 8.7 feet at 12 percent opacity.

Predicted legibility distances for the LED sign ( $R^2 = .60$ ) were 14.1 feet at 10 percent opacity and 12.6 feet at 12 percent opacity. Predicted legibility distances for the PL sign ( $R^2 = .49$ ) were 9.7 feet at 10 percent opacity and 8.4 feet at 12 percent opacity.






Figure 32. Detection distances for text EXIT signs, LED and PL.





Figure 33. Legibility distances for text EXIT signs, LED and PL.

### Running Man Symbol (LED)

The running man symbol-only sign was the first sign presented to participants. Because the artificial smoke in the tunnel was densest at the start of each testing session, the average opacity at which participants viewed this sign was just over 14 percent. Additionally, since this was the first sign that participants saw, it was also the practice sign: participants learned with this


first sign what to look for and where (at least in terms of height above the floor). It is not surprising, therefore, that the observed detection and legibility distances varied somewhat more than those for most of the other exit signs (see Figure 34). The regression equation for the detection distance of the running man symbol-only sign ( $R^2 = 0.64$ ) predicted detection distances of 19.2 feet at 10 percent smoke opacity and 15.9 feet at 12 percent opacity. Legibility distances at the same two opacities were predicted as 14.9 feet and 13.0 feet ( $R^2 = 0.48$ ).




**Figure 34. Detection and legibility distances for running man symbol-only sign (LED).**

### Emergency Phone and Refuge Point Signs

The emergency phone and refuge point signs were considerably smaller than the exit signs, and the photoluminescent material was not as powerful as other photoluminescent signs used. For these reasons, the detection and legibility distances for these signs were short, and the variability of these distances resulted in very weak regression trend lines (see Figure 35 and Figure 36).




**Figure 35. Detection distances for emergency phone and refuge point signs.**



**Figure 36. Legibility distances for emergency phone and refuge point signs.**

### PL Path Marker

Detection distances predicted for the PL path marker ( $R^2 = 0.67$ ) were 12.1 feet at 10 percent smoke opacity and 10.3 feet at 12 percent opacity (see Figure 37).



**Figure 37. Detection distances for PL path marker.**

## PHOTOMETRIC MEASUREMENT AND VISIBILITY CONCLUSIONS

Smoke density/opacity was a significant factor in detection and visibility distances, as would be expected from the sharp drop in sign/marketing luminance and contrast that was seen in the photometric measurements. The internally LED-illuminated signs could all be seen from farther away than the photoluminescent signs; the regression equations for the detection and legibility distances indicate that most of the internally LED-illuminated signs could be detected and read at approximately twice the distances of the corresponding photoluminescent signs. An exception was the positive contrast PL EXIT sign, with detection and legibility distances that were between 60 and 75 percent of the distances for the LED version of the positive contrast EXIT sign, depending on the smoke opacity levels (the LED version of this sign, however, was also less bright than the LED versions of the running man signs).

Visibility testing with participants was done at an ambient lighting level of 10 lux measured at floor level, provided by overhead LED bulbs. Photometric measurements confirmed that even this low level of ambient lighting, when smoke was present, generated veiling luminance that reduced contrast ratios between the signs and the tunnel wall, and between sign legends and backgrounds. The measurements suggest that lowering overhead/ambient light level below 10 lux while providing brightly lit signs and path markers may improve visibility of the exits and exit paths in smoky conditions.

## **CHAPTER 6. CONCLUSIONS, RECOMMENDATIONS, AND SUGGESTED RESEARCH**

This study focused on providing data to help accomplish the project's primary objectives:

- Determine the messages and delivery methods (visual, audible, or both) that will encourage drivers to leave their cars and exit a tunnel on foot when conditions warrant such an evacuation.
- Determine the sign graphics and colors, sign messages, marking types and colors, and auditory messages that most effectively lead people to emergency tunnel exits.
- Determine the most visible sign and marking materials and technologies for dark and smoky conditions.

Conclusions and recommendations pertaining to each of these objectives are summarized in this chapter. More detailed recommendations are presented in a proposed set of guidelines, published as a brochure, which can be found at <http://www.trb.org/Main/Blurbs/173414.aspx>.

### **RESEARCH CONCLUSIONS**

#### **Emergency Evacuation Messages**

The literature, the focus groups, and the tunnel simulation all pointed to the value of notifying vehicle occupants of an emergency situation and providing clear directions about the appropriate course of action. The results of the tunnel emergency simulation, which presented visual and audio evidence of an unfolding fire-related emergency to participants, provided a strong indication that drivers are more likely to leave their vehicles and self-evacuate if they see or hear a message instructing them to do so.

The two messaging media tested during the tunnel simulation (DMS and audio) appeared to be equally effective in convincing participants that leaving the vehicle was the proper course of action.

#### **Emergency Exit Sign and Marking Formats**

Comprehension of the ISO 7010 running man symbol was tested in the focus groups and with the tunnel simulation participants. While a symbol-only version of the sign was understood or partially understood by approximately 86 percent of participants, most participants preferred a sign that combined the symbol with "EXIT" text. Directional signs that included the running man symbol, "EXIT" text, a directional arrow and a distance in feet were correctly interpreted by 98 percent of participants. These results indicate that a combination symbol and text sign is likely the best option for marking emergency exits in the United States, at least until the running man symbol is more widely recognized by U.S. residents.

During the tunnel simulation, the most common misconception among participants regarding the running man exit sign was that the running man symbol was next to an exit or indicated the direction of a nearby exit, versus being on the exit door itself (the text-only EXIT sign currently standard in most U.S. buildings was anticipated by most participants to be on or over the door itself). However, all signs in the simulation were placed in a frame on the wall for

visual consistency, rather than some being placed on a door; a running man sign placed on an exit door would provide visual context for this symbol that simulation participants did not have.

Seventy-five percent of participants expressed preferences for tailed directional arrows over chevron-style arrows, and a few participants did not recognize chevron-style arrows as directional symbols. Tailed arrows pointing directly left or right were clearly understood; arrows pointing directly up or down, or pointing diagonally up or down (e.g., to indicate an exit located up or down stairs), required explanation.

Of the three LED path marking formats tested, lights illuminating/strobing in a sequence that indicated a direction were the most favored by participants. Lights that flashed/strobed in unison along the path were second in preference overall, and lights that remained on (without flashing/strobing) were third.

A simulated audio beacon with a repeated “exit here” announcement was considered helpful by a majority of participants though some could not tell which direction the sound was coming from. It should be noted that the acoustics of the simulated tunnel were not the same as they would be in an actual highway tunnel.

## **Sign Technologies**

The tested photoluminescent signs were not as bright as internally illuminated signs under the test conditions, and visibility distances were shorter on average (with low levels of ambient light in white smoke). However, the PL signs tested had higher contrast ratios between the text and background compared to LED signs, as well as greater contrast ratios with the tunnel wall versus LED signs when both were tested with photometric equipment in dark conditions.

The reduction in contrast ratios for both types of sign was due in part to light scatter off smoke particles. Visibility testing was conducted in ambient light of approximately 10 lux (typical of a tunnel under emergency lighting levels). Higher ambient light levels, such as what would typically be present in non-emergency tunnel lighting, could result in increased light scatter when smoke is present; this might have the effect of further reducing the contrast ratios and therefore the visibility of signs. A strategy that merits further exploration is reducing overhead or other ambient lighting along pedestrian evacuation paths to increase the visibility and conspicuity of exit path lights and exit signs in smoky conditions. It may also be advisable to space signs more closely together or to use lighted or photoluminescent path markings to provide additional visual cues between signs.

## **RECOMMENDATIONS**

The study results highlighted the importance of communicating emergency information, including evacuation instructions when necessary, to vehicle drivers and occupants, and provided support for the use of the running man symbol on emergency exit signs. The study’s major recommendations are summarized below; these and additional recommendations are detailed further in the proposed guide.

### **Emergency Evacuation Messages**

An emergency evacuation message should contain, at minimum, the following pieces of information:

- A brief statement about the nature of the emergency, e.g., “fire in tunnel” or “vehicle fire ahead.”

- Direct instructions about the action to take, e.g., “walk to exits” or “leave vehicles, walk to exits” if evacuation on foot is warranted. An evacuation direction should be specified (e.g., upstream of the fire) if applicable.
- If slightly longer messages are possible, given the medium used, it may be beneficial to include a small amount of supplementary information. Useful supplementary information can include the identity of the person or agency making the announcement and additional instructions or guidance regarding exit locations and procedures.

## **Emergency Exit Sign and Marking Formats**

The ISO 7010 running man symbol is recommended for use on emergency exit signs for highway tunnels. An additional recommendation is to include text specifying “EXIT” with the symbol, at least until the symbol achieves wider recognition in the United States.

As specified in NFPA 502, signs indicating directions to emergency exits should be placed at least every 25 meters (82 feet) along the tunnel wall. These signs should include the running symbol and “EXIT” text, with the addition of a tailed directional arrow and the distance to the nearest exit in feet. If exits are located in two directions relative to the location of the sign, two signs should be placed side by side to indicate the directions and respective distances to the two exits.

Exit path markings are recommended to supplement directional signs in guiding pedestrians to emergency exits. Markings should be placed no higher than 1 meter (3.3 feet) from the ground or trafficway surface.

Exit doors should be marked with distinctive lighting as well as exit signs. The recommended lighting scheme is the one described by CIE 193-2010, including both illumination around the door and supplemental emergency strobe lights flashing at a rate of 1 to 2 Hz.

Auditory beacons may be beneficial as a supplemental exit door marker, depending on acoustic conditions. Auditory beacons may be used to supplement (not replace) illuminated exit door lighting and, if used, should be calibrated to be audible to listeners who are in relatively close proximity to the exit door. The recommended sound is a simple, repeated voice announcement such as “exit here,” which may be in more than one language (in addition to English).

## **Sign Technologies and Visibility**

Because of the severe degradation of sign contrast in smoke, the designed contrast ratio between sign backgrounds and legends should be as high as possible given the materials and colors used. This is one metric in which the tested PL signs scored higher than the tested LED-illuminated signs. If internally illuminated signs are used, greater contrast can be achieved by maximizing the opacity of the negative/darker elements of the sign.

Photoluminescent signs require ambient light in order to charge. If photoluminescent signs are used for emergency exits or path indicators, it is recommended that they be selected in consultation with a manufacturer that specializes in materials for tunnel environments, taking expected ambient light levels into consideration.

Depending on the available power and control infrastructure, LED lights or photoluminescent markings may be used to delineate an emergency exit path for pedestrians. LED lights that can be controlled by tunnel operators to indicate a recommended direction to an exit (e.g., by illuminating in a sequence that indicates movement in a given direction) were

considered particularly useful by most study participants, but any marker that is visible under a variety of potential emergency conditions (darkness, smoke, etc.) should be helpful to evacuees.

## **SUGGESTED RESEARCH**

Given the wide range of tunnel geometries and infrastructures, the myriad of possible emergency situations that may arise, and the evolving technologies for signs and markings, mass communications, and emergency management, the project team identified several potential issues that can be addressed in further detail and refined through further research. These issues are discussed in the following sections.

### **Emergency Announcements/Messages**

The DMS messages used in this study to provide information about the hypothetical tunnel emergency to focus group and simulation participants were two-phase messages. Two phases are the maximum currently recommended by the MUTCD for dynamic signs, though that recommendation assumes three lines of text for each phase, while the DMS used in the study was a single line of text. While there might be some benefit to providing additional information (beyond the MUTCD two-phase standard) in stopped traffic conditions, there could also be the danger that people will delay taking action if they think that further information will continue to be provided on the DMS. A short, repeated message may convince people to start moving. The question of the maximum number of message phases for both normal and emergency conditions in a highway tunnel merit additional testing in the future.

Further research is needed to examine the effects of tunnel reverberation, ambient noise from traffic and from other emergency systems (ventilation fans, fire suppression systems), and other conditions that can interfere with the intelligibility of audio announcements from loudspeakers.

While the current study focused on fire as the emergency incident, future behavioral research should examine an all-hazards approach for providing messages and advisories to drivers about other types of incidents and emergencies.

### **Sign and Marking Formats and Placement**

This study tested exit signs with 6-inch-tall text and graphics. Depending on the width of a highway tunnel, larger-scale emergency exit signs may be necessary or beneficial. A larger-scale visibility test, perhaps conducted in an actual highway tunnel or a test facility such as the Memorial Tunnel in West Virginia, would allow for a realistic comparison of different size signs.

In a two-bore tunnel with cross passages between the bores, should emergency exit signs (directing pedestrians to exit from one bore to the other via the cross passage) be placed only on the walls adjacent to the exit, or should supplemental signs be placed on walls that are opposite to exits? Signing for this and other complex tunnel geometries is another research topic that would be suitable for testing in an actual tunnel environment.

Successive signs along a tunnel passageway, for instance, distance signs showing progressively shorter distances to a tunnel exit, could not be tested within the limited space of the simulated tunnel. A larger-scale testing environment would provide the opportunity to test the effects of successive signs and markings on user comprehension and confidence regarding exit locations.

Similarly, signs showing the distances to emergency exits in two opposite directions were not tested in this study due to size constraints in the testing facility; while the study's results for



the two-directional text EXIT sign (without distances being specified) and the single-direction exit distance signs indicate that two-directional distance signs would likely be well understood, an actual test of this configuration would provide a more definitive answer.

Recent testing by the University of Greenwich in the United Kingdom found that signs with dynamic elements—specifically, signs with flashing green arrows to indicate an exit direction and signs with red X’s to indicate a route that does not lead to an exit—were well understood, were noticed by more people than static signs, and reduced evacuation time. (The Guardian, 2014) This and potentially other types of dynamic signage would be valuable to test with United States drivers.

## **IMPLEMENTATION OF RESEARCH FINDINGS AND PRODUCTS**

As stated in the introduction to this report, there is not yet a consistent format for emergency exit signs and markings for highway tunnels across the United States. Implementing the proposed guidelines into practice and incorporating them into existing standards will require input and acceptance from NFPA, as well as from professionals and professional organizations in the tunnel and roadway operations industries and in the emergency response community. This plan proposes activities to be conducted by the research team to promote the proposed guidelines, as well as products and activities that could potentially be developed as future implementation projects.

Successful implementation of the proposed guidelines should result in widespread adoption of the running man symbol + EXIT text as the accepted format for emergency exit identification in highway tunnels in the United States. The adoption of this sign format, as well as other recommended elements such as exit door and exit path markings, is likely to be gradual as new tunnels are built and existing ones are refurbished. The guidelines may also evolve as further research is conducted (as outlined in the previous section).

### **Initial Implementation—Presentations and Papers on Study Recommendations**

Implementation activities conducted by research team members will include development of papers and presentations on this research study and the proposed guidelines, to include the following:

- A brief PowerPoint presentation will be prepared, highlighting the study results and major recommendations from the proposed guidelines. Target audiences include AASHTO’s T-20 Subcommittee on Bridges and Structures, the NCUCTD Regulatory and Warning Signs Technical Committee, and one or more of NFPA’s technical committees if possible (502 Road Tunnel and Highway Fire Protection Technical Committee, 101 Safety to Life – Means of Egress, and/or 72 Signaling Systems—Public Fire Reporting Systems). The research team includes members on the AASHTO and NCUCTD technical committees, but not currently on NFPA committees, which may preclude the opportunity to present directly to that audience. This presentation can be prepared prior to the end of the current contract.
- A proposal will be submitted to present study findings and recommendations at the 2016 NFPA Conference & Expo (proposals due in September 2015).
- One or more papers will be written for submittal to the Transportation Research Board’s 2016 Annual Meeting and the Transportation Research Record (submittals due July 2015). The paper will be submitted to the AFF60 Tunnels and Underground Structures Committee for review.

- If permissions can be secured, a presentation focusing on the study recommendations will also be delivered as a webinar and/or conference presentation to the National Volunteer Fire Council, International Association of Fire Chiefs and International Association of Chiefs of Police, and/or the International Bridge, Tunnel and Turnpike Association (IBTTA).

In addition to the committee and conference presentations (if submissions are accepted for presentation), the proposed guidelines will be submitted as a potential annex to NFPA 502, through the NFPA’s online public input process.

Table 15 summarizes the implementation activities and expected milestone dates.

**Table 15. Implementation Activities by Research Team.**

<b>Implementation Activity</b>	<b>Intended Audiences</b>	<b>Target Completion Dates</b>
Prepare PowerPoint presentation summarizing study results and major recommendations	NCUTCD, AASHTO, NFPA subcommittees	<ul style="list-style-type: none"> <li>• August 1, 2015</li> </ul>
Submit paper(s) for submission to TRB	Transportation professionals	<ul style="list-style-type: none"> <li>• July 31, 2015 – submit paper for review</li> <li>• January, 2016 – present paper (if accepted)</li> </ul>
Submit proposal to present at NFPA Conference & Expo	Fire protection professionals and emergency responders	<ul style="list-style-type: none"> <li>• September 30, 2015 – submit proposal</li> <li>• June, 2016 – present (if accepted)</li> </ul>
Contact National Volunteer Fire Council, International Association of Fire Chiefs and International Association of Chiefs of Police, IBTTA	Emergency responders, tunnel operators	<ul style="list-style-type: none"> <li>• August 1, 2015 – contact organization representatives and report results to NCHRP</li> <li>• TBD (based on feedback) – conduct webinars/presentations</li> </ul>

### **Suggested Future Implementation Projects**

The following activities are suggestions for future outreach, training, and funding programs to encourage the implementation of the proposed guidelines by tunnel operators and to expand training and education regarding emergency exit signs and markings.

- Development of a module to be used with the Federal Emergency Management Agency’s (FEMA) national incident management training when the training is being delivered to responders that have tunnels in their area of responsibility.
- A web video for drivers that educates them about the importance of having a plan to self-evacuate from a highway tunnel if needed, where to look/listen for emergency announcements when inside a tunnel, and what highway tunnel emergency exit doors,

exit path markings, and exit signs look like. Examples of similar videos include a three-video series by EastLink Tunnel Safety in Australia, viewable on YouTube.

- A laminated visor card for emergency responders, illustrating the running man exit and related emergency signs and their meanings.
- A planning template for tunnel operators that includes an assessment of existing emergency exit signs and markings in a highway tunnel and an integration plan for replacement and/or additional devices.
- Establishment of a technical services contact that practitioners can use to get guidance and assistance on implementation of emergency exit signs and markings.
- A grant program to assist tunnel operators in purchasing new exit signs and conducting training for their operators and local emergency responders.

Table 16 lists the intended audiences and potential lead agencies for the suggested implementation projects.

**Table 16. Suggested Future Implementation Projects.**

<b>Implementation Project</b>	<b>Intended Audiences</b>	<b>Potential Lead Organizations/Agencies</b>
Submit recommendations to NFPA 502 via public input process.	NFPA 502 technical committee	AASHTO T-20 Committee, TRB AFF60 Committee on Tunnels and Underground Structures, or FHWA
Module for FEMA national incident management training.	Emergency responders	IBTTA
Web video on tunnel incidents and self-evacuation.	Drivers/Public	State DOTs, local transportation and/or tunnel authorities
Laminated visor card illustrating tunnel exit signs.	Emergency responders	State DOTs, local transportation and/or tunnel authorities
Sign/markings planning template.	Tunnel operators	AASHTO, FHWA
Technical services contact for guidance on implementation of emergency exit signs and markings.	Tunnel operators	FHWA, state DOTs
Grant program for new exit sign purchases and operator/responder training.	Tunnel operators	State DOTs

## REFERENCES

- Amy, J. What is photoluminescent marking? Facilities.net website, July 2008.  
<http://www.facilitiesnet.com/emergencypreparedness/article/What-is-Photoluminescent-Marking--9198> , downloaded January 2013.
- Boer, L.C. and van Wijngaarden, S.J. Directional sound evacuation from smoke-filled tunnels, TNO Human Factors, The Netherlands, First International Symposium, Prague, 2004.  
<http://www.ita-aites.org/fileadmin/filemounts/ovion/doc/safety/prague/boer.pdf>
- Boer, L.C. and van Wijngaarden, S.J. Self-explaining Sound Beacons in Evacuation, in Martens, M. (ed), *Human Factors Aspects in Tunnels: Tunnel User Behaviour and Tunnel Operators*, Ch 5. Produced as part of Workpackage 3, Human response D33, UPTUN, September 2008.  
<http://www.curnet.nl/upload/documents/UPTUN/UPTUN%20WP3%20D33%20Human%20factors%20user%20and%20operator.pdf> , downloaded January 2013.
- Carss, B. 2010. Traditional signs to exit in favor of running man, Online article, Canadian Property Management, October 2010.  
<http://www.canadianpropertymanagement.ca/TraditionalExitSignChangeToRunningMan.aspx>
- Collins, B.L., Dahir, M.S., Madrzykowski, D. Visibility of Exit Signs in Clear and Smoky Conditions. *Journal of the Illuminating Engineering Society*, Winter 1992, Volume 21, Number 1, pp. 69–84.
- Cook, G., Webber, G., Gillham, S.A., Le Scouiller, S.A., Moseley, E. The legibility and conspicuity of emergency escape route signage for people with visual impairments. *International Congress Series* 1282, 1995, pp.1016–1020.
- Eder, S., Brutting, J., Muhlberger, A., and Pauli, P. *Human Behaviour in Tunnel Accidents*. University of Wurtzberg, Germany, 2013.
- Eigentler, K. Experiences with LED-based visual guidance systems in tunnels. *Tunnelling and Underground Space Technology*, Volume 21, Issue 3–4, 2006, p. 325.
- Ellis, J., Gibson, D., and Brenkley, D. Innovative Evacuation System, in Martens, M. (ed), *Human Factors Aspects in Tunnels: Tunnel User Behaviour and Tunnel Operators*, Ch 7. Produced as part of Workpackage 3, Human response D33, UPTUN, September 2008.  
<http://www.curnet.nl/upload/documents/UPTUN/UPTUN%20WP3%20D33%20Human%20factors%20user%20and%20operator.pdf> , downloaded January 2013.
- Ernst, S., Patel, M., Capers, H., Dwyer, D., Hawkins, C., Jakovich, G.S., Lupton, W., Margro, T., Ralls, M.L., Rohena, J., and Swanson, M. *Underground transportation systems in Europe: Safety, operations, and emergency response*. Report No. FHWA-PL-06-016, Federal Highway Administration, 2006.
- Exit signs—National Lighting Product Information Program, Specifier Report Vol. 2 No. 2, January 1994

Fridolph, K., Ronchi, E., Nilsson, D., Frantzich, H. Movement speed and exit choice in smoke-filled rail tunnels. *Fire Safety Journal* 59, 2013, pp. 8–21.

The Guardian University Awards Ideas Bank 2014: Winner, University of Greenwich, Project: Active Dynamic Signage Systems. *The Guardian*, U.S. Edition online, February 18, 2014. <http://www.theguardian.com/higher-education-network/2014/feb/18/winner-university-of-greenwich-research-impact>, downloaded June 25, 2015.

Jenssen, G. *Way Finding, Signage, and Human Factors*. Presentation, NCHRP Workshop on Safety and Security in Roadway Tunnels. Irvine, California, 28–29 November 2007.

Jenssen, G., Terje, M., Bjorkli, C.A., Martens, M. *Driving Simulator Studies, Ch. 3*. Produced as part of Workpackage 3, Human response D33, UPTUN, September 2008.

Jin, Tadahisa. Studies on Human Behavior and Tenability in Fire Smoke. Howard W. Emmons Invited Plenary Lecture, 1997. <http://www.iafss.org/publications/fss/5/3/view>, downloaded February 12, 2014.

Mayer, R., Reimann, O., Lover V., Brettschneider V. and Los I. Clear announcements for Motorists: New chances for safe voice alarms in tunnels. *Official Journal of STUVA*, February 2012 (in German).

McLean, G.A. and Corbett, C.L. Comprehension of symbolic exit signs I: Effects of context. *Proceedings of the Fifth Triennial International Fire & Cabin Safety Research Conference*, 2007, Federal Aviation Administration.

Morley, F.J.J. and Corbett, A.M. An evaluation of the comprehensibility of graphical exit signs for passenger aircraft Phases 1 and 2. COA Report No. 9706, Human Factors Technology Group, College of Aeronautics, Cranfield University, Bedford, England, 1997.

Nilsson, D. Design of spoken Emergency exit messages—lessons learned from a survey and unannounced egress experiments. *Fire Engineering*. Lund University. Report 3139, 2006 (in Swedish).

Nilsson, D. Exit choice in fire emergencies: Influencing choice of exit with flashing lights. Doctoral thesis, Department of Fire Safety Engineering and Systems Safety, Lund University, 2009. <http://lup.lub.lu.se/luur/download?func=downloadFile&recordId=1370568&fileId=1415075>, downloaded January 2013.

Nilsson, D., Johansson, M., and Frantzich, H. Evacuation experiment in a road tunnel: A study of human behavior and technical installations, *Fire Safety Journal* 44, 2009, pp.458–468.

*OECD Studies in Risk Management: Norway—Tunnel Safety*. Organization for International Cooperation and Development, Paris, France, 2006.

Ronchi, E., Nilsson, D., and Gwynne, S.M.V. Modelling the Impact of Emergency Exit Signs in Tunnels. *Fire Technology* Vol. 48, 2012, 961–988.

Turner, J. The big red word vs. the little green man, *Slate Magazine*, March 8, 2010.  
[http://www.slate.com/articles/life/signs/2010/03/the\\_big\\_red\\_word\\_vs\\_the\\_little\\_green\\_man.html](http://www.slate.com/articles/life/signs/2010/03/the_big_red_word_vs_the_little_green_man.html), downloaded January 2013.

van Waterschoot, A. et al., in Martens, M. (ed), *Human Factors Aspects in Tunnels: Tunnel User Behaviour and Tunnel Operators, Ch 1*. Produced as part of Workpackage 3, Human response D33, UPTUN, September 2008.  
<http://www.curnet.nl/upload/documents/UPTUN/UPTUN%20WP3%20D33%20Human%20factors%20user%20and%20operator.pdf>, downloaded January 2013.

Windle, L. Photoluminescent Technology: Reliable Emergency Lighting in Buildings, Facilities.net website, March 2005.  
<http://www.facilitiesnet.com/emergencypreparedness/article/In-Case-of-Emergency-Show-Occupants-the-Door--2638>, downloaded January 2013.

# Appendix C

---

## Photographs

This page intentionally left blank.



## Appendix C Photographs

### Fire Detection



**Photo 1: Remains of Ventilation Control Niche. Control System has been removed.**



**Photo 2: Remains of Fire Extinguisher Niche. Fire Extinguisher has been removed.**



**Photo 3: Remains of Telephone (Left) and Traffic Control Niche (Right) at West Portal SB Barrel. Similar arrangement at all Portals.**



**Photo 4: Remains of Fire Extinguisher Niche. Note deterioration in tunnel liner wall.**

Egress



**Photo 5: Existing NB Barrel Cross Section with 2'-6" safety curbs and gated entrance to abandoned control room. Also note inoperable tunnel lights in ceiling.**



**Photo 6: Gate entrance to abandoned control room.**



Photo 7: Interior of abandoned control room.

### Emergency Vent



Photo 8: Control room showing rectangular opening for ventilation fans and 6'0" diameter ventilation shafts leading to ventilation building at top of West Rock Ridge.



**Photo 9: Control room showing rectangular opening for ventilation fans and 6'0" diameter ventilation shafts leading to ventilation building at top of West Rock Ridge.**



**Photo 10: Dual openings for ventilation fans that have been removed.**



**Photo 11: Existing 6'-0" diameter ventilation shaft. Note the evidence of leakage at joints in shaft.**



**Photo 12: Existing concrete tunnel liner. Note the deterioration and exposed rebar, all conditions that could affect the fire resistance of the existing concrete tunnel liner.**

## Electrical Systems



**Photo 13: Abandoned Electrical Junction Box with exposed wiring.**



**Photo 14: Existing PVC Conduit with duct tape repairing damage to the conduit.**



**Photo 15: Abandoned conduit with exposed wiring in control room.**



**Photo 16: Lighting in control room no longer functioning.**





**Photo 17: Conduit in SB Barrel at tunnel centerline with junction box and a run of conduit mounted to ceiling going to the lighting system.**



**Photo 18: Inoperable tunnel lighting. Note condition of concrete tunnel liner with extensive map cracking and efflorescence.**



**Photo 19: Lighting at tunnel portal.**



**Photo 20: Tunnel lighting with random luminaires no longer functioning.**



**Photo 21: Ventilation Exhaust Building at top of West Rock Ridge.**



**Photo 22: Ventilation Exhaust Building at top of West Rock Ridge.**

Electrical Cabinet




Photo 23: Automatic transfer switch





Photo 24: Automatic transfer switch



**Photo 25: 500A main circuit breakers for the two utility services**



**Photo 26: Automatic transfer switch and associated controls**



Photo 27: 120V Panelboard (Left), 480-120/240V transformer (Right)



Photo 28: Daytime lighting panelboard



Photo 29: Daytime lighting panelboard



Photo 30: Daytime lighting panelboard



**Photo 31: Electrical distribution pedestal cabinet**



**Photo 32: Corroded conduits containing lighting and Wintergreen Avenue electrical service wiring.**





**Photo 33: Additional corrosion on conduit and conduit bodies.**

# Appendix D

## Air Quality Technical Memorandum

This page intentionally left blank.

# Technical Memorandum Air Quality

## 1 Introduction

This memorandum presents the air quality analysis conducted for the proposed Project. The analysis includes a description of the existing conditions of the project site and surrounding area. Emission calculations and air quality modeling results are provided in the Appendix to this Technical Memorandum.

## 2 Criteria Air Pollutants

The following section provides a detailed description of these air pollutants, as adapted from the EPA<sup>1</sup> and Connecticut Department of Energy & Environmental Protection (CTDEEP)<sup>2</sup>.

### 2.1 Carbon Monoxide

Carbon Monoxide (CO) is a colorless, odorless and poisonous gas produced by incomplete burning of carbon in fuels. Sources include motor-vehicle exhaust, industrial processes, wood-burning stoves, or forest fires. High concentrations can be found in confined spaces such as parking garages, poorly ventilated tunnels, or traffic intersections, especially during peak hours. When CO enters the bloodstream, it reduces the delivery of oxygen to the body's organs and tissues, which negatively affects those with cardiovascular or respiratory disease.

### 2.2 Ozone

Ozone (O<sub>3</sub>) is a colorless gas that is not directly emitted into the air but created through chemical reactions between precursors of O<sub>3</sub> in the presence of sunlight. O<sub>3</sub> is a major constituent of smog. Ozone is found both at high altitude and ground level. High altitude ozone is beneficial because it shields the earth from the sun's ultraviolet radiation. Ground level ozone is harmful because it reacts with the mucus membranes of the respiratory system and causes inflammation.

Primary precursor compounds that lead to formation of O<sub>3</sub> include VOCs and NO<sub>x</sub>. Both VOCs and NO<sub>x</sub> are emitted from transportation and industrial sources. Ozone does not come directly from any source. The VOCs that form ozone come from vehicle and industrial exhaust as well as evaporation of gasoline, solvents and paints, and many other sources.

### 2.3 Sulfur Oxides

Sulfur Dioxide (SO<sub>2</sub>) is a colorless gas. It is odorless at low concentrations but pungent at very high concentrations. SO<sub>2</sub> is generated primarily by burning of fuels that contain sulfur. The largest source of SO<sub>2</sub> in the atmosphere is from oil and coal fired power plants and other industrial facilities. Smaller sources of SO<sub>2</sub> include vehicles and heavy equipment that burn fuel with a high

---

<sup>1</sup> Detailed description of the criteria air pollutants can be found on USEPA website. Source: <https://www.epa.gov/criteria-air-pollutants> (Accessed April 18, 2018)

<sup>2</sup> Pollutant description of the criteria air pollutants as found on CTDEEP website. Source: [https://www.ct.gov/deep/cwp/view.asp?a=2684&Q=321804&deepNav\\_GID=1744](https://www.ct.gov/deep/cwp/view.asp?a=2684&Q=321804&deepNav_GID=1744) (Accessed September 26, 2018)

sulfur content. Short-term exposures to SO<sub>2</sub> can harm the human respiratory system and make breathing difficult. Children, the elderly, and those who suffer from asthma are particularly sensitive to effects of SO<sub>2</sub>.

SO<sub>2</sub> emissions that lead to high concentrations of SO<sub>2</sub> in the air generally also lead to the formation of other Sulfur Oxides (SO<sub>x</sub>). SO<sub>x</sub> can react with other compounds in the atmosphere to form small particles. These particles contribute to particulate matter pollution which also contributes to negative health effects. It is also a main contributor to acid rain.

## 2.4 Nitrogen Oxides

Nitrogen Dioxide (NO<sub>2</sub>) is one of a group of highly reactive gases known as oxides of nitrogen or nitrogen oxides (NO<sub>x</sub>). Other nitrogen oxides include nitrous acid and nitric acid. NO<sub>2</sub> is used as the indicator for the larger group of nitrogen oxides. NO<sub>2</sub> is a yellowish brown, highly reactive gas that is the primary ingredient in formation of ground-level ozone. It is formed from high temperature fuel combustion such as from cars, trucks, buses, power plants, and off-road equipment. Short-term NO<sub>2</sub> exposures, ranging from 30 minutes to 24 hours, can produce adverse respiratory effects including increased asthma symptoms, more difficulty controlling asthma, and an increase in respiratory illnesses and symptoms. NO<sub>2</sub> along with other NO<sub>x</sub> reacts with other chemicals in the air to form both particulate matter and ozone.

## 2.5 Particulate Matter

Particulate Matter (PM) includes PM<sub>10</sub> which are inhalable particles, with diameter less than 10 microns and PM<sub>2.5</sub> which are fine inhalable particles, with diameters less than 2.5 microns. Most particles form in the atmosphere as a result of complex reactions of chemicals such as sulfur dioxide and nitrogen oxides, which are pollutants emitted from power plants, industries and automobiles. Particulates can damage human health and retard plant growth. Health concerns associated with suspended particulate matter focus on those particles small enough to reach the lungs when inhaled. Particulates also reduce visibility and corrode materials. The size of a particle is directly linked to its potential for causing health problems. Small particles, that is, those less than 10 microns in diameter (PM<sub>10</sub>), pose the greatest problems because of their ability to penetrate deeply into the lungs and bloodstream affecting human immune systems. Particulate matter less than 2.5 microns in diameter (PM<sub>2.5</sub>) can be emitted directly from sources (e.g., engines) or can form in the atmosphere from precursor compounds.

## 2.6 Mobile Source Air Toxics

Mobile Source Air Toxics (MSATs) are a subset of the 188 air toxics defined by the CAA. MSATs are compounds emitted from highway vehicles and non-road equipment. Some toxic compounds are present in fuel and are emitted to the air when the fuel evaporates or passes through the engine unburned. Other toxics are emitted from the incomplete combustion of fuels or as secondary combustion products. Metal air toxics also result from engine wear or from impurities in oil or gasoline. Most air toxics originate from human-made sources, including on-road mobile sources, non- road mobile sources (e.g., airplanes), area sources (e.g., dry cleaners) and stationary sources (e.g., factories or refineries).

## 3 Existing Condition Emissions

Following sections provide a summary of the modeling approach and results from the regional emissions inventory calculated for the existing condition (i.e. No Build Alternative).

### 3.1 Modeling Approach

U.S. Environmental Protection Agency's (EPA) Motor Vehicle Emissions Simulator (MOVES) model was used to develop an emission factor for all criteria air pollutants (CO, NO<sub>x</sub>, SO<sub>2</sub>, PM<sub>10</sub>, PM<sub>2.5</sub> and VOC). This analysis used the current EPA-approved version of MOVES2014a (released on November 17, 2016) to develop emission factors for different vehicle source types. A predicted peak hour volume of vehicles was used to calculate operational emissions in tons per year for the existing conditions.

A run specification (RunSpec) was created for New Haven county with "Emission Rate" as calculation type<sup>3</sup> using a national scale domain for the year 2018. The month of January, a weekday and hour 17:00-17:59 was selected for the modeled time span, and hourly time aggregation was used. Gasoline was assumed as worst-case fuel for emissions and the vehicle source types selected were Motorcycle, Light commercial truck, passenger car and passenger truck. The vehicle and fuel combinations were selected to match the types of vehicles that operate to simulate regional emissions. All five road types were selected in the MOVES Road Type panel, however, the Heroes Tunnel is assumed to be in an "Urban Restricted" road type. A separate RunSpec was created for New Haven County with "Inventory" as calculation type to obtain activity data for the different model years, which was then used to obtain a weighted emission factor in grams/miles/vehicle. The model output was selected to include model years and source types.

### 3.2 Modeling Results

Upon completion of successful execution of MOVES run, the rate per distance emissions factors were post-processed using MySQL script to obtain a "running exhaust" emission factor in grams per mile for each of the Source Types for an Urban Restricted Road Type. For this analysis operational emissions were calculated from the maximum no. of vehicles expected at a peak hour in tunnel in one direction (i.e. per barrel). Emissions of CO, NO<sub>2</sub>, VOC, SO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> represent emissions from vehicle exhaust only. Table 4 of Section 3.2.1 summarizes peak hourly operational emissions associated with existing conditions in the tunnel per barrel. Detailed MOVES output tables and calculations are provided in the Appendix, included at the end of this Technical Memorandum. A weighted emission factor in grams per mile was calculated using the sumproduct of activity (for different model years obtained from the separate RunSpec) and the rate per distance divide by sum of activity. Based on available traffic data, it is estimated that about 2,983 vehicles can be expected in the tunnel in peak hour conditions in one barrel.

---

<sup>3</sup> A RunSpec is an extensible markup language (XML) file that contains the input parameters for a model run.

# APPENDIX - MOVES RESULTS SUMMARY

Heroes Tunnel, New Haven, CT

MOVES Results Summary

Existing Conditions (For inventory year 2018, gasoline fuel type, for weekday at 17:00-17:59, at 57 mph speed (avg Speed Bin ID = 12))

Source Type ID	Source Type	Activity	Rate per distance X Activity					
			NOx	CO	SO2	PM10	PM2.5	VOC
11	Motorcycle	1,356.88	1,254.19	17,179.95	3.42	56.38	49.88	679.33
21	Passenger Car	324,853.82	48,745.70	630,177.12	609.13	3,478.27	3,076.95	6,274.39
31	Passenger Truck	195,524.25	63,957.44	624,880.85	486.24	2,932.27	2,593.94	8,571.78
32	Light Commercial Truck	48,475.87	14,850.84	145,297.78	118.60	597.03	528.15	1,843.99
<b>SUM</b>		<b>570,210.81</b>	<b>128,808.18</b>	<b>1,417,535.69</b>	<b>1,217.39</b>	<b>7,063.96</b>	<b>6,248.91</b>	<b>17,369.48</b>

	2018
Avg Vehicles in the tunnel (per barrel)	2,983
Length of tunnel	0.231 mi

Pollutant	Emission Factor (g/mi)	g/hr	Peak lb/hr per barrel
NOx	0.23	155.70	0.34
CO	2.49	1,713.47	3.78
SO2	0.00	1.47	0.003
PM10	0.01	8.54	0.02
PM2.5	0.01	7.55	0.02
VOC	0.03	21.00	0.05

Unit Conversion

1lb = 453.592 g  
 1 ton = 2000 lb  
 1 year = 8760 hours

# APPENDIX - MOVES OUTPUT

MOVESRur	iterationID	yearID	monthID	dayID	hourID	stateID	countyID	zoneID	linkID	sourceType	regClassID	fuelTypeID	modelYear	roadTypeID	ESC	engTechID	sectorID	hpID	activityTyp	activity	activityMe	activitySign
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1988	4	NULL	NULL	NULL	NULL	1	0.923808	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1989	4	NULL	NULL	NULL	NULL	1	0.94527	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1990	4	NULL	NULL	NULL	NULL	1	1.37178	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1991	4	NULL	NULL	NULL	NULL	1	1.78772	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1992	4	NULL	NULL	NULL	NULL	1	2.4386	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1993	4	NULL	NULL	NULL	NULL	1	3.1664	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1994	4	NULL	NULL	NULL	NULL	1	4.15018	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1995	4	NULL	NULL	NULL	NULL	1	3.83712	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1996	4	NULL	NULL	NULL	NULL	1	5.39972	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1997	4	NULL	NULL	NULL	NULL	1	6.33558	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1998	4	NULL	NULL	NULL	NULL	1	6.80422	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	1999	4	NULL	NULL	NULL	NULL	1	8.25878	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2000	4	NULL	NULL	NULL	NULL	1	11.3034	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2001	4	NULL	NULL	NULL	NULL	1	14.75	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2002	4	NULL	NULL	NULL	NULL	1	18.1009	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2003	4	NULL	NULL	NULL	NULL	1	21.3404	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2004	4	NULL	NULL	NULL	NULL	1	26.0378	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2005	4	NULL	NULL	NULL	NULL	1	32.215	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2006	4	NULL	NULL	NULL	NULL	1	38.7754	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2007	4	NULL	NULL	NULL	NULL	1	43.0254	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2008	4	NULL	NULL	NULL	NULL	1	51.3064	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2009	4	NULL	NULL	NULL	NULL	1	30.7848	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2010	4	NULL	NULL	NULL	NULL	1	31.812	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2011	4	NULL	NULL	NULL	NULL	1	38.0732	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2012	4	NULL	NULL	NULL	NULL	1	51.675	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2013	4	NULL	NULL	NULL	NULL	1	63.7692	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2014	4	NULL	NULL	NULL	NULL	1	80.5606	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2015	4	NULL	NULL	NULL	NULL	1	101.499	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2016	4	NULL	NULL	NULL	NULL	1	134.96	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2017	4	NULL	NULL	NULL	NULL	1	183.46	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	11	NULL	NULL	2018	4	NULL	NULL	NULL	NULL	1	338.008	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1988	4	NULL	NULL	NULL	NULL	1	530.67	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1989	4	NULL	NULL	NULL	NULL	1	403.988	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1990	4	NULL	NULL	NULL	NULL	1	497.65	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1991	4	NULL	NULL	NULL	NULL	1	607.779	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1992	4	NULL	NULL	NULL	NULL	1	746.945	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1993	4	NULL	NULL	NULL	NULL	1	937.323	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1994	4	NULL	NULL	NULL	NULL	1	1159.56	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1995	4	NULL	NULL	NULL	NULL	1	1582.89	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1996	4	NULL	NULL	NULL	NULL	1	1670.05	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1997	4	NULL	NULL	NULL	NULL	1	2204.5	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1998	4	NULL	NULL	NULL	NULL	1	2598.24	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	1999	4	NULL	NULL	NULL	NULL	1	3480.08	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2000	4	NULL	NULL	NULL	NULL	1	4855.66	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2001	4	NULL	NULL	NULL	NULL	1	5505.17	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2002	4	NULL	NULL	NULL	NULL	1	6844.57	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2003	4	NULL	NULL	NULL	NULL	1	8259.99	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2004	4	NULL	NULL	NULL	NULL	1	9463.45	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2005	4	NULL	NULL	NULL	NULL	1	11798.9	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2006	4	NULL	NULL	NULL	NULL	1	13026.6	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2007	4	NULL	NULL	NULL	NULL	1	14908.4	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2008	4	NULL	NULL	NULL	NULL	1	14300.8	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2009	4	NULL	NULL	NULL	NULL	1	12007.3	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2010	4	NULL	NULL	NULL	NULL	1	13755.1	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2011	4	NULL	NULL	NULL	NULL	1	12566.8	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2012	4	NULL	NULL	NULL	NULL	1	20815.6	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2013	4	NULL	NULL	NULL	NULL	1	23399.6	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2014	4	NULL	NULL	NULL	NULL	1	25302.5	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2015	4	NULL	NULL	NULL	NULL	1	26486.1	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2016	4	NULL	NULL	NULL	NULL	1	27817.1	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2017	4	NULL	NULL	NULL	NULL	1	28588.4	NULL	NULL
4	1	2018	1	5	18	9	9009	NULL	NULL	21	NULL	NULL	2018	4	NULL	NULL	NULL	NULL	1	28732.1	NULL	NULL



# APPENDIX - MOVES OUTPUT

MOVES	Rur	iterationID	yearID	monthID	dayID	hourID	stateID	countyID	zoneID	linkID	sourceType	regClassID	fuelTypeID	modelYear	roadTypeID	ESC	engTechID	sectorID	hpID	activityTyp	activity	activityMe	activitySign
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1988	4	NULL	NULL	NULL	NULL	1	262.816	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1989	4	NULL	NULL	NULL	NULL	1	314.655	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1990	4	NULL	NULL	NULL	NULL	1	313.931	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1991	4	NULL	NULL	NULL	NULL	1	365.094	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1992	4	NULL	NULL	NULL	NULL	1	439.671	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1993	4	NULL	NULL	NULL	NULL	1	560.247	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1994	4	NULL	NULL	NULL	NULL	1	844.775	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1995	4	NULL	NULL	NULL	NULL	1	984.685	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1996	4	NULL	NULL	NULL	NULL	1	1079.78	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1997	4	NULL	NULL	NULL	NULL	1	1550.08	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1998	4	NULL	NULL	NULL	NULL	1	1928.81	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	1999	4	NULL	NULL	NULL	NULL	1	2486.47	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2000	4	NULL	NULL	NULL	NULL	1	3029.26	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2001	4	NULL	NULL	NULL	NULL	1	3534.03	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2002	4	NULL	NULL	NULL	NULL	1	4356.76	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2003	4	NULL	NULL	NULL	NULL	1	5056.73	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2004	4	NULL	NULL	NULL	NULL	1	6305.08	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2005	4	NULL	NULL	NULL	NULL	1	6893.12	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2006	4	NULL	NULL	NULL	NULL	1	7370	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2007	4	NULL	NULL	NULL	NULL	1	7376.98	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2008	4	NULL	NULL	NULL	NULL	1	7848.73	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2009	4	NULL	NULL	NULL	NULL	1	4637.62	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2010	4	NULL	NULL	NULL	NULL	1	6490.59	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2011	4	NULL	NULL	NULL	NULL	1	7147.14	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2012	4	NULL	NULL	NULL	NULL	1	11541.4	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2013	4	NULL	NULL	NULL	NULL	1	13917.5	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2014	4	NULL	NULL	NULL	NULL	1	15504.4	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2015	4	NULL	NULL	NULL	NULL	1	17119.1	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2016	4	NULL	NULL	NULL	NULL	1	18348.7	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2017	4	NULL	NULL	NULL	NULL	1	18820	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	31	NULL	NULL	2018	4	NULL	NULL	NULL	NULL	1	19096.1	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1988	4	NULL	NULL	NULL	NULL	1	48.8675	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1989	4	NULL	NULL	NULL	NULL	1	56.1696	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1990	4	NULL	NULL	NULL	NULL	1	53.7889	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1991	4	NULL	NULL	NULL	NULL	1	49.1411	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1992	4	NULL	NULL	NULL	NULL	1	53.6956	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1993	4	NULL	NULL	NULL	NULL	1	105.487	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1994	4	NULL	NULL	NULL	NULL	1	111.398	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1995	4	NULL	NULL	NULL	NULL	1	180.068	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1996	4	NULL	NULL	NULL	NULL	1	186.558	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1997	4	NULL	NULL	NULL	NULL	1	290.173	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1998	4	NULL	NULL	NULL	NULL	1	290.679	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	1999	4	NULL	NULL	NULL	NULL	1	495.166	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2000	4	NULL	NULL	NULL	NULL	1	717.377	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2001	4	NULL	NULL	NULL	NULL	1	917.169	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2002	4	NULL	NULL	NULL	NULL	1	1169.08	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2003	4	NULL	NULL	NULL	NULL	1	1363.51	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2004	4	NULL	NULL	NULL	NULL	1	1705.95	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2005	4	NULL	NULL	NULL	NULL	1	1856.21	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2006	4	NULL	NULL	NULL	NULL	1	2006.18	NULL	NULL	
4	1	2018	1	5	18	9	9009	NULL	NULL	32	NULL	NULL	2007	4	NULL	NULL	NULL	NULL	1	1969.6	NULL	NULL	
4	1	2018	1	5	18	9	9009	NU	NULL	32	NULL	NULL	2007	4	NULL	NULL	NULL	NULL	1	1969.6	NULL	NULL	
NULL	NULL	2008	4	NULL	NULL	NULL	NULL	1	2112.12	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2009	4	NULL	NULL	NULL	NULL	1	1227.5	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2010	4	NULL	NULL	NULL	NULL	1	1704.05	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2011	4	NULL	NULL	NULL	NULL	1	1924.15	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2012	4	NULL	NULL	NULL	NULL	1	2767.26	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2013	4	NULL	NULL	NULL	NULL	1	3350.23	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2014	4	NULL	NULL	NULL	NULL	1	3754.54	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2015	4	NULL	NULL	NULL	NULL	1	4170.72	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2016	4	NULL	NULL	NULL	NULL	1	4494.79	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2017	4	NULL	NULL	NULL	NULL	1	4629.92	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	
NULL	NULL	2018	4	NULL	NULL	NULL	NULL	1	4714.32	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	

MOVEScenarioID	MOVESRunID	YearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadTypeID	avgSpeed	Temperature	relativeHumidity	ratePerDistance	Activity	Rate per Distance X Activity
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1988	4	12	33.2	59.6	18.7558	0.923808	17.33	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1989	4	12	33.2	59.6	18.7558	0.94527	17.73	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1990	4	12	33.2	59.6	18.7558	1.37178	25.73	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1991	4	12	33.2	59.6	18.7558	1.78772	33.53	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1992	4	12	33.2	59.6	18.7558	2.4386	45.74	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1993	4	12	33.2	59.6	18.7558	3.1664	59.39	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1994	4	12	33.2	59.6	21.5452	4.15018	89.42	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1995	4	12	33.2	59.6	21.5471	3.83712	82.68	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1996	4	12	33.2	59.6	21.5493	5.39972	116.36	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1997	4	12	33.2	59.6	21.5518	6.33558	136.54	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1998	4	12	33.2	59.6	21.5542	6.80422	146.66	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	1999	4	12	33.2	59.6	21.5567	8.25878	178.03	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2000	4	12	33.2	59.6	21.5591	11.3034	243.69	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2001	4	12	33.2	59.6	24.0229	14.75	354.34	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2002	4	12	33.2	59.6	24.0229	18.1009	434.84	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2003	4	12	33.2	59.6	24.0229	21.3404	512.66	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2004	4	12	33.2	59.6	17.4931	26.0378	455.48	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2005	4	12	33.2	59.6	17.4931	32.215	563.54	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2006	4	12	33.2	59.6	17.4931	38.7754	678.30	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2007	4	12	33.2	59.6	17.4931	43.0254	752.65	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2008	4	12	33.2	59.6	11.0636	51.3064	567.63	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2009	4	12	33.2	59.6	11.0636	30.7848	340.59	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2010	4	12	33.2	59.6	11.0636	31.812	351.96	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2011	4	12	33.2	59.6	11.0636	38.0732	421.23	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2012	4	12	33.2	59.6	11.0636	51.675	571.71	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2013	4	12	33.2	59.6	11.0636	63.7692	705.52	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2014	4	12	33.2	59.6	11.0636	80.5606	891.29	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2015	4	12	33.2	59.6	11.0636	101.499	1,122.94	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2016	4	12	33.2	59.6	11.0636	134.96	1,493.14	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2017	4	12	33.2	59.6	11.0636	183.46	2,029.73	
ScenarioID1	2	2018	1	5	18	90090412	2	1	11	0	0	2018	4	12	33.2	59.6	11.0636	338.008	3,739.59	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1988	4	12	33.2	59.6	8.52664	531	4,524.83	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1989	4	12	33.2	59.6	8.52664	404	3,444.66	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1990	4	12	33.2	59.6	6.96152	498	3,464.40	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1991	4	12	33.2	59.6	6.96152	608	4,231.07	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1992	4	12	33.2	59.6	6.96152	747	5,199.87	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1993	4	12	33.2	59.6	6.96152	937	6,525.19	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1994	4	12	33.2	59.6	5.8098	1,160	6,736.81	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1995	4	12	33.2	59.6	5.81033	1,583	9,197.11	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1996	4	12	33.2	59.6	4.93134	1,670	8,235.58	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1997	4	12	33.2	59.6	4.9319	2,205	10,872.37	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1998	4	12	33.2	59.6	4.93246	2,598	12,815.71	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	1999	4	12	33.2	59.6	4.91281	3,480	17,096.97	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2000	4	12	33.2	59.6	4.91337	4,856	23,857.65	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2001	4	12	33.2	59.6	3.11544	5,505	17,151.03	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2002	4	12	33.2	59.6	3.09213	6,845	21,164.30	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2003	4	12	33.2	59.6	3.14757	8,260	25,998.90	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2004	4	12	33.2	59.6	2.74249	9,463	25,953.42	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2005	4	12	33.2	59.6	2.64926	11,799	31,258.35	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2006	4	12	33.2	59.6	2.59469	13,027	33,799.99	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2007	4	12	33.2	59.6	2.51301	14,908	37,464.96	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2008	4	12	33.2	59.6	2.50665	14,301	35,847.10	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2009	4	12	33.2	59.6	2.03642	12,007	24,451.91	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2010	4	12	33.2	59.6	2.03258	13,755	27,958.34	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2011	4	12	33.2	59.6	1.91372	12,567	24,049.34	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2012	4	12	33.2	59.6	1.91372	20,816	39,835.23	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2013	4	12	33.2	59.6	1.67583	23,400	39,213.75	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2014	4	12	33.2	59.6	1.67583	25,303	42,402.69	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2015	4	12	33.2	59.6	0.915459	26,486	24,246.94	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2016	4	12	33.2	59.6	0.960132	27,817	26,708.09	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2017	4	12	33.2	59.6	0.650613	28,588	18,599.98	
ScenarioID1	2	2018	1	5	18	90090412	2	1	21	0	0	2018	4	12	33.2	59.6	0.621972	28,732	17,870.56	



# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadTypeID	avgSpeed	B temperature	relHumidit	ratePerDis	activity	Rate per Distance X Activity			
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1988	4	12	33.2	59.6	1.18915	0.923808				1.10	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1989	4	12	33.2	59.6	1.18915	0.94527				1.12	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1990	4	12	33.2	59.6	1.18915	1.37178				1.63	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1991	4	12	33.2	59.6	1.18915	1.78772				2.13	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1992	4	12	33.2	59.6	1.18915	2.4386				2.90	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1993	4	12	33.2	59.6	1.18915	3.1664				3.77	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1994	4	12	33.2	59.6	1.16975	4.15018				4.85	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1995	4	12	33.2	59.6	1.16975	3.83712				4.49	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1996	4	12	33.2	59.6	1.16975	5.39972				6.32	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1997	4	12	33.2	59.6	1.16975	6.33558				7.41	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1998	4	12	33.2	59.6	1.16975	6.80422				7.96	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	1999	4	12	33.2	59.6	1.16975	8.25878				9.66	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2000	4	12	33.2	59.6	1.16975	11.3034				13.22	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2001	4	12	33.2	59.6	1.17026	14.75				17.26	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2002	4	12	33.2	59.6	1.17026	18.1009				21.18	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2003	4	12	33.2	59.6	1.17026	21.3404				24.97	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2004	4	12	33.2	59.6	0.958744	26.0378				24.96	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2005	4	12	33.2	59.6	0.958744	32.215				30.89	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2006	4	12	33.2	59.6	0.958744	38.7754				37.18	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2007	4	12	33.2	59.6	0.958744	43.0254				41.25	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2008	4	12	33.2	59.6	0.895139	51.3064				45.93	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2009	4	12	33.2	59.6	0.895139	30.7848				27.56	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2010	4	12	33.2	59.6	0.895139	31.812				28.48	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2011	4	12	33.2	59.6	0.895139	38.0732				34.08	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2012	4	12	33.2	59.6	0.895139	51.675				46.26	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2013	4	12	33.2	59.6	0.895139	63.7692				57.08	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2014	4	12	33.2	59.6	0.895139	80.5606				72.11	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2015	4	12	33.2	59.6	0.895139	101.499				90.86	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2016	4	12	33.2	59.6	0.895139	134.96				120.81	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2017	4	12	33.2	59.6	0.895139	183.46				164.22	
ScenarioID	2	2018	1	5	18	90090412	3	1	11	0	0	2018	4	12	33.2	59.6	0.895139	338.008				338.008	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1988	4	12	33.2	59.6	1.7247	530.67				530.67	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1989	4	12	33.2	59.6	1.7247	403.988				403.988	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1990	4	12	33.2	59.6	1.69328	607.79				607.79	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1993	4	12	33.2	59.6	1.69328	937.323				1,587.15	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1994	4	12	33.2	59.6	1.52667	1159.56				1,770.27	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1995	4	12	33.2	59.6	1.52667	1582.89				2,416.55	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1996	4	12	33.2	59.6	1.14479	1670.05				1,911.86	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1997	4	12	33.2	59.6	1.14479	2204.5				2,523.69	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1998	4	12	33.2	59.6	1.14479	2598.24				2,974.44	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	1999	4	12	33.2	59.6	1.14063	3480.08				3,969.48	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2000	4	12	33.2	59.6	1.14063	4855.66				5,538.51	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2001	4	12	33.2	59.6	0.294844	5505.17				1,623.17	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2002	4	12	33.2	59.6	0.277469	6844.57				1,899.16	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2003	4	12	33.2	59.6	0.260749	8259.99				2,153.78	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2004	4	12	33.2	59.6	0.144214	9463.45				1,364.76	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2005	4	12	33.2	59.6	0.11625	11798.9				1,371.62	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2006	4	12	33.2	59.6	0.111073	13026.6				1,446.90	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2007	4	12	33.2	59.6	0.093663	14908.4				1,396.37	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2008	4	12	33.2	59.6	0.088128	14300.8				1,260.31	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2009	4	12	33.2	59.6	0.071052	12007.3				853.15	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2010	4	12	33.2	59.6	0.066325	13755.1				912.31	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2011	4	12	33.2	59.6	0.052962	12566.8				665.56	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2012	4	12	33.2	59.6	0.052962	20815.6				1,102.43	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2013	4	12	33.2	59.6	0.043312	23399.6				1,013.48	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2014	4	12	33.2	59.6	0.043312	25302.5				1,095.90	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2015	4	12	33.2	59.6	0.027547	26486.1				729.62	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2016	4	12	33.2	59.6	0.028892	27817.1				803.68	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2017	4	12	33.2	59.6	0.029147	28588.4				833.27	
ScenarioID	2	2018	1	5	18	90090412	3	1	21	0	0	2018	4	12	33.2	59.6	0.027137	28732.1				779.71	

# APPENDIX - MOVES OUTPUT

MOVEScenarioID	MOVESRur yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadType	LAvgSpeed	B temperature	relHumidit	ratePerDis	activity	Rate per Distance X Activity					
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1988	4	12	33.2	59.6	3.50034	262.816			919.95				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1989	4	12	33.2	59.6	3.5056	314.655			1,103.05				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1990	4	12	33.2	59.6	3.733	313.931			1,171.90				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1991	4	12	33.2	59.6	3.73049	365.094			1,361.98				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1992	4	12	33.2	59.6	3.73041	439.671			1,640.15				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1993	4	12	33.2	59.6	3.72696	560.247			2,088.02				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1994	4	12	33.2	59.6	3.3478	844.775			2,828.14				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1995	4	12	33.2	59.6	3.34933	984.685			3,298.04				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1996	4	12	33.2	59.6	1.86334	1079.78			2,012.00				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1997	4	12	33.2	59.6	1.84183	1550.08			2,854.98				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1998	4	12	33.2	59.6	1.82758	1928.81			3,525.05				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	1999	4	12	33.2	59.6	1.82773	2486.47			4,544.60				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2000	4	12	33.2	59.6	1.80952	3029.26			5,481.51				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2001	4	12	33.2	59.6	0.834291	3534.03			2,948.41				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2002	4	12	33.2	59.6	0.822815	4356.76			3,584.81				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2003	4	12	33.2	59.6	0.87458	5056.73			4,422.51				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2004	4	12	33.2	59.6	0.39755	6305.08			2,506.58				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2005	4	12	33.2	59.6	0.302075	6893.12			2,082.24				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2006	4	12	33.2	59.6	0.247404	7370			1,823.37				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2007	4	12	33.2	59.6	0.211708	7376.98			1,561.77				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2008	4	12	33.2	59.6	0.191319	7848.73			1,501.61				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2009	4	12	33.2	59.6	0.140579	4637.62			651.95				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2010	4	12	33.2	59.6	0.132538	6490.59			860.25				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2011	4	12	33.2	59.6	0.108909	7147.14			778.39				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2012	4	12	33.2	59.6	0.108983	11541.4			1,257.82				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2013	4	12	33.2	59.6	0.088145	13917.5			1,226.76				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2014	4	12	33.2	59.6	0.088115	15504.4			1,366.16				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2015	4	12	33.2	59.6	0.055286	17119.1			946.44				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2016	4	12	33.2	59.6	0.057632	18348.7			1,057.46				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2017	4	12	33.2	59.6	0.081288	18820			1,529.84				
ScenarioID	2	2018	1	5	18 90090412	3	1	31	0	0	2018	4	12	33.2	59.6	0.053503	19096.1			1,021.71				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1988	4	12	33.2	59.6	3.58527	48.8675			175.20				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1989	4	12	33.2	59.6	3.60217	56.1696			202.33				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1990	4	12	33.2	59.6	3.66954	53.7889			197.38				
ScenarioID	2	2018	1	5	18						90090412	3	1	32	0	0	1991	4	12	33.2	59.6	3.67845	49.1411	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1992	4	12	33.2	59.6	3.69256	53.6956	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1993	4	12	33.2	59.6	3.70382	105.487	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1994	4	12	33.2	59.6	3.31286	111.398	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1995	4	12	33.2	59.6	3.30468	180.068	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1996	4	12	33.2	59.6	1.90298	186.558	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1997	4	12	33.2	59.6	1.8853	290.173	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1998	4	12	33.2	59.6	1.79196	290.679	
ScenarioID	2	2018	1	5		ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	1999	4	12	33.2	59.6	1.80684	495.166	
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	18 90090412	2008	4	12	33.2	59.6	0.896260	9172.00	4	12	33.2	59.6	1.84754	717.377
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2002	4	12	33.2	59.6	0.837166	1169.08			978.71				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2003	4	12	33.2	59.6	0.889596	1363.51			1,212.97				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2004	4	12	33.2	59.6	0.464425	1705.95			792.29				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2005	4	12	33.2	59.6	0.370263	1856.21			687.29				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2006	4	12	33.2	59.6	0.335982	2006.18			674.04				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2007	4	12	33.2	59.6	0.273234	1969.6			538.16				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2008	4	12	33.2	59.6	0.230914	2112.12			487.72				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2009	4	12	33.2	59.6	0.141013	1227.5			173.09				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2010	4	12	33.2	59.6	0.130983	1704.05			223.20				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2011	4	12	33.2	59.6	0.113393	1924.15			218.19				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2012	4	12	33.2	59.6	0.113598	2767.26			314.36				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2013	4	12	33.2	59.6	0.090377	3350.23			302.78				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2014	4	12	33.2	59.6	0.090291	3754.54			339.00				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2015	4	12	33.2	59.6	0.055616	4170.72			231.96				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2016	4	12	33.2	59.6	0.057492	4494.79			258.42				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2017	4	12	33.2	59.6	0.083795	4629.92			387.96				
ScenarioID	2	2018	1	5	18 90090412	3	1	32	0	0	2018	4	12	33.2	59.6	0.054489	4714.32			256.88				

# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadTypeID	avgSpeedB	temperatu	relHumidit	ratePerDistance	activity	Rate per Distance X Activity
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1988	4	12	33.2	59.6	0.00200008	0.923808	0.00	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1989	4	12	33.2	59.6	0.00200008	0.94527	0.00	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1990	4	12	33.2	59.6	0.00200008	1.37178	0.00	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1991	4	12	33.2	59.6	0.00225744	1.78772	0.00	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1992	4	12	33.2	59.6	0.00228926	2.4386	0.01	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1993	4	12	33.2	59.6	0.00232108	3.1664	0.01	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1994	4	12	33.2	59.6	0.0023529	4.15018	0.01	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1995	4	12	33.2	59.6	0.00238472	3.83712	0.01	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1996	4	12	33.2	59.6	0.00241654	5.39972	0.01	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1997	4	12	33.2	59.6	0.00244837	6.33558	0.02	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1998	4	12	33.2	59.6	0.00248019	6.80422	0.02	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	1999	4	12	33.2	59.6	0.00252602	8.25878	0.02	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2000	4	12	33.2	59.6	0.00252602	11.3034	0.03	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2001	4	12	33.2	59.6	0.00252602	14.75	0.04	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2002	4	12	33.2	59.6	0.00252602	18.1009	0.05	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2003	4	12	33.2	59.6	0.00252602	21.3404	0.05	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2004	4	12	33.2	59.6	0.00252602	26.0378	0.07	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2005	4	12	33.2	59.6	0.00252602	32.215	0.08	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2006	4	12	33.2	59.6	0.00252602	38.7754	0.10	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2007	4	12	33.2	59.6	0.00252602	43.0254	0.11	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2008	4	12	33.2	59.6	0.00252602	51.3064	0.13	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2009	4	12	33.2	59.6	0.00252602	30.7848	0.08	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2010	4	12	33.2	59.6	0.00252602	31.812	0.08	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2011	4	12	33.2	59.6	0.00252602	38.0732	0.10	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2012	4	12	33.2	59.6	0.00252602	51.675	0.13	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2013	4	12	33.2	59.6	0.00252602	63.7692	0.16	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2014	4	12	33.2	59.6	0.00252602	80.5606	0.20	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2015	4	12	33.2	59.6	0.00252602	101.499	0.26	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2016	4	12	33.2	59.6	0.00252602	134.96	0.34	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2017	4	12	33.2	59.6	0.00252602	183.46	0.46	
ScenarioID	2	2018	1	5	18	90090412	31	1	11	0	0	2018	4	12	33.2	59.6	0.00252602	338.008	0.85	
ScenarioID	2	2018	1	5	18	90090412	31	1	21	0	0	1988	4	12	33.2	59.6	0.00206856	530.67	1.10	
ScenarioID	2	2018	1	5	18	90090412	31	1	21	0	0	1989	4	12	33.2	59.6	0.00208666	403.988	0.84	
ScenarioID	2	2018	1	5	18	90090412	31	1	21	0	0	1990	4	12	33.2	59.6	0.00209326	497.65	1.04	
ScenarioID	2	2018	1	5																
4	12	33.2	59.6		0.00200815	607.779					1.22									
4	12	33.2	59.6		0.00206137	746.945					1.54									
4	12	33.2	59.6		0.00203023	937.323					1.90									
4	12	33.2	59.6		0.00205735	1159.56					2.39									
4	12	33.2	59.6		0.00204306	1582.89					3.23									
4	12	33.2	59.6		0.00206911	1670.05					3.46									
4	12	33.2	59.6		0.00203923	2204.5					4.50									
4	12	33.2	59.6		0.00204819	2598.24					5.32									
4	12	33.2	59.6		0.00206596	3480.08					7.19									
4	12	33.2	59.6		0.00206596	4855.66					10.03									



# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadType	avgSpeed	B temperature	relHumidit	ratePerDis	activity	Rate per D
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1988	4	12	33.2	59.6	0.121943	0.923808	0.11	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1989	4	12	33.2	59.6	0.121943	0.94527	0.12	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1990	4	12	33.2	59.6	0.121943	1.37178	0.17	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1991	4	12	33.2	59.6	0.121943	1.78772	0.22	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1992	4	12	33.2	59.6	0.121943	2.4386	0.30	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1993	4	12	33.2	59.6	0.121943	3.1664	0.39	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1994	4	12	33.2	59.6	0.121943	4.15018	0.51	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1995	4	12	33.2	59.6	0.121943	3.83712	0.47	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1996	4	12	33.2	59.6	0.121943	5.39972	0.66	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1997	4	12	33.2	59.6	0.121943	6.33558	0.77	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1998	4	12	33.2	59.6	0.121943	6.80422	0.83	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	1999	4	12	33.2	59.6	0.121943	8.25878	1.01	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2000	4	12	33.2	59.6	0.121943	11.3034	1.38	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2001	4	12	33.2	59.6	0.118623	14.75	1.75	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2002	4	12	33.2	59.6	0.118623	18.1009	2.15	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2003	4	12	33.2	59.6	0.118623	21.3404	2.53	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2004	4	12	33.2	59.6	0.03454	26.0378	0.90	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2005	4	12	33.2	59.6	0.03454	32.215	1.11	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2006	4	12	33.2	59.6	0.03454	38.7754	1.34	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2007	4	12	33.2	59.6	0.03454	43.0254	1.49	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2008	4	12	33.2	59.6	0.03454	51.3064	1.77	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2009	4	12	33.2	59.6	0.03454	30.7848	1.06	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2010	4	12	33.2	59.6	0.03454	31.812	1.10	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2011	4	12	33.2	59.6	0.03454	38.0732	1.32	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2012	4	12	33.2	59.6	0.03454	51.675	1.78	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2013	4	12	33.2	59.6	0.03454	63.7692	2.20	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2014	4	12	33.2	59.6	0.03454	80.5606	2.78	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2015	4	12	33.2	59.6	0.03454	101.499	3.51	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2016	4	12	33.2	59.6	0.03454	134.96	4.66	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2017	4	12	33.2	59.6	0.03454	183.46	6.34	
ScenarioID	2	2018	1	5	18	90090412	100	1	11	0	0	2018	4	12	33.2	59.6	0.03454	338.008	11.67	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1988	4	12	33.2	59.6	0.152783	530.67	81.08	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1989	4	12	33.2	59.6	0.152783	403.988	61.72	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1990	4	12	33.2	59.6	0.219063	497.65	109.02	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1992	4	12	33.2	59.6	0.134515	746.945	100.48	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1993	4	12	33.2	59.6	0.134515	937.323	126.08	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1994	4	12	33.2	59.6	0.105936	1159.56	122.84	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1995	4	12	33.2	59.6	0.08434	1582.89	133.50	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1996	4	12	33.2	59.6	0.064009	1670.05	106.90	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1997	4	12	33.2	59.6	0.115539	2204.5	254.71	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1998	4	12	33.2	59.6	0.087429	2598.24	227.16	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	1999	4	12	33.2	59.6	0.045577	3480.08	158.61	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2000	4	12	33.2	59.6	0.064263	4855.66	312.04	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2001	4	12	33.2	59.6	0.03867	5505.17	212.89	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2002	4	12	33.2	59.6	0.035995	6844.57	246.37	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2003	4	12	33.2	59.6	0.022193	8259.99	183.31	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2004	4	12	33.2	59.6	0.005375	9463.45	50.86	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2005	4	12	33.2	59.6	0.005375	11798.9	63.41	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2006	4	12	33.2	59.6	0.005375	13026.6	70.01	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2007	4	12	33.2	59.6	0.005375	14908.4	80.13	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2008	4	12	33.2	59.6	0.005375	14300.8	76.86	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2009	4	12	33.2	59.6	0.004074	12007.3	48.92	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2010	4	12	33.2	59.6	0.004074	13755.1	56.04	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2011	4	12	33.2	59.6	0.003478	12566.8	43.70	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2012	4	12	33.2	59.6	0.003478	20815.6	72.39	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2013	4	12	33.2	59.6	0.002969	23399.6	69.46	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2014	4	12	33.2	59.6	0.002969	25302.5	75.11	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2015	4	12	33.2	59.6	0.002341	26486.1	62.01	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2016	4	12	33.2	59.6	0.002341	27817.1	65.12	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2017	4	12	33.2	59.6	0.002243	28588.4	64.12	
ScenarioID	2	2018	1	5	18	90090412	100	1	21	0	0	2018	4	12	33.2	59.6	0.002147	28732.1	61.68	



# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadType	LavgSpeed	Btemperatu	relHumidit	ratePerDis	activity	Rate per D
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1988	4	12	33.2	59.6	0.142469	262.816	37.44	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1989	4	12	33.2	59.6	0.142771	314.655	44.92	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1990	4	12	33.2	59.6	0.196508	313.931	61.69	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1991	4	12	33.2	59.6	0.08202	365.094	29.94	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1992	4	12	33.2	59.6	0.082034	439.671	36.07	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1993	4	12	33.2	59.6	0.082572	560.247	46.26	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1994	4	12	33.2	59.6	0.098953	844.775	83.59	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1995	4	12	33.2	59.6	0.092656	984.685	91.24	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1996	4	12	33.2	59.6	0.102582	1079.78	110.77	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1997	4	12	33.2	59.6	0.093928	1550.08	145.60	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1998	4	12	33.2	59.6	0.083917	1928.81	161.86	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	1999	4	12	33.2	59.6	0.084879	2486.47	211.05	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2000	4	12	33.2	59.6	0.074418	3029.26	225.43	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2001	4	12	33.2	59.6	0.072188	3534.03	255.11	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2002	4	12	33.2	59.6	0.040836	4356.76	177.91	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2003	4	12	33.2	59.6	0.055158	5056.73	278.92	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2004	4	12	33.2	59.6	0.008651	6305.08	54.54	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2005	4	12	33.2	59.6	0.008636	6893.12	59.53	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2006	4	12	33.2	59.6	0.008669	7370	63.89	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2007	4	12	33.2	59.6	0.008611	7376.98	63.52	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2008	4	12	33.2	59.6	0.008634	7848.73	67.77	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2009	4	12	33.2	59.6	0.007067	4637.62	32.78	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2010	4	12	33.2	59.6	0.007048	6490.59	45.74	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2011	4	12	33.2	59.6	0.006361	7147.14	45.46	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2012	4	12	33.2	59.6	0.006362	11541.4	73.43	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2013	4	12	33.2	59.6	0.005684	13917.5	79.10	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2014	4	12	33.2	59.6	0.005683	15504.4	88.11	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2015	4	12	33.2	59.6	0.003626	17119.1	62.08	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2016	4	12	33.2	59.6	0.003626	18348.7	66.53	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2017	4	12	33.2	59.6	0.003626	18820	68.24	
ScenarioID	2	2018	1	5	18	90090412	100	1	31	0	0	2018	4	12	33.2	59.6	0.003337	19096.1	63.73	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1988	4	12	33.2	59.6	0.136749	48.8675	6.68	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1989	4	12	33.2	59.6	0.137698	56.1696	7.73	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1990	4	12	33.2	59.6	0.182231	53.7889	9.80	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1992	4	12	33.2	59.6	0.074605	53.6956	4.01	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1993	4	12	33.2	59.6	0.073254	105.487	7.73	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1994	4	12	33.2	59.6	0.101171	111.398	11.27	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1995	4	12	33.2	59.6	0.086247	180.068	15.53	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1996	4	12	33.2	59.6	0.089918	186.558	16.77	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1997	4	12	33.2	59.6	0.089125	290.173	25.86	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1998	4	12	33.2	59.6	0.072943	290.679	21.20	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	1999	4	12	33.2	59.6	0.070337	495.166	34.83	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2000	4	12	33.2	59.6	0.064364	717.377	46.17	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2001	4	12	33.2	59.6	0.063115	917.169	57.89	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2002	4	12	33.2	59.6	0.036573	1169.08	42.76	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2003	4	12	33.2	59.6	0.047886	1363.51	65.29	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2004	4	12	33.2	59.6	0.008017	1705.95	13.68	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2005	4	12	33.2	59.6	0.007981	1856.21	14.81	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2006	4	12	33.2	59.6	0.008063	2006.18	16.18	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2007	4	12	33.2	59.6	0.007916	1969.6	15.59	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2008	4	12	33.2	59.6	0.007976	2112.12	16.85	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2009	4	12	33.2	59.6	0.006461	1227.5	7.93	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2010	4	12	33.2	59.6	0.006409	1704.05	10.92	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2011	4	12	33.2	59.6	0.005877	1924.15	11.31	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2012	4	12	33.2	59.6	0.005888	2767.26	16.27	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2013	4	12	33.2	59.6	0.005239	3350.23	17.55	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2014	4	12	33.2	59.6	0.005237	3754.54	19.66	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2015	4	12	33.2	59.6	0.00334	4170.72	13.93	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2016	4	12	33.2	59.6	0.00334	4494.79	15.01	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2017	4	12	33.2	59.6	0.00334	4629.92	15.46	
ScenarioID	2	2018	1	5	18	90090412	100	1	32	0	0	2018	4	12	33.2	59.6	0.003096	4714.32	14.59	

# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadType	avgSpeed	temp	relHumidit	ratePerDis	activity	Rate per D
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1988	4	12	33.2	59.6	0.107873	0.923808	0.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1989	4	12	33.2	59.6	0.107873	0.94527	0.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1990	4	12	33.2	59.6	0.107873	1.37178	0.15	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1991	4	12	33.2	59.6	0.107873	1.78772	0.19	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1992	4	12	33.2	59.6	0.107873	2.4386	0.26	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1993	4	12	33.2	59.6	0.107873	3.1664	0.34	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1994	4	12	33.2	59.6	0.107873	4.15018	0.45	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1995	4	12	33.2	59.6	0.107873	3.83712	0.41	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1996	4	12	33.2	59.6	0.107873	5.39972	0.58	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1997	4	12	33.2	59.6	0.107873	6.33558	0.68	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1998	4	12	33.2	59.6	0.107873	6.80422	0.73	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	1999	4	12	33.2	59.6	0.107873	8.25878	0.89	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2000	4	12	33.2	59.6	0.107873	11.3034	1.22	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2001	4	12	33.2	59.6	0.104936	14.75	1.55	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2002	4	12	33.2	59.6	0.104936	18.1009	1.90	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2003	4	12	33.2	59.6	0.104936	21.3404	2.24	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2004	4	12	33.2	59.6	0.030555	26.0378	0.80	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2005	4	12	33.2	59.6	0.030555	32.215	0.98	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2006	4	12	33.2	59.6	0.030555	38.7754	1.18	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2007	4	12	33.2	59.6	0.030555	43.0254	1.31	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2008	4	12	33.2	59.6	0.030555	51.3064	1.57	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2009	4	12	33.2	59.6	0.030555	30.7848	0.94	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2010	4	12	33.2	59.6	0.030555	31.812	0.97	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2011	4	12	33.2	59.6	0.030555	38.0732	1.16	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2012	4	12	33.2	59.6	0.030555	51.675	1.58	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2013	4	12	33.2	59.6	0.030555	63.7692	1.95	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2014	4	12	33.2	59.6	0.030555	80.5606	2.46	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2015	4	12	33.2	59.6	0.030555	101.499	3.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2016	4	12	33.2	59.6	0.030555	134.96	4.12	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2017	4	12	33.2	59.6	0.030555	183.46	5.61	
ScenarioID	2	2018	1	5	18	90090412	110	1	11	0	0	2018	4	12	33.2	59.6	0.030555	338.008	10.33	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1988	4	12	33.2	59.6	0.135155	530.67	71.72	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1989	4	12	33.2	59.6	0.135155	403.988	54.60	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1990	4	12	33.2	59.6	0.193788	497.65	96.44	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1992	4	12	33.2	59.6	0.118995	746.945	88.88	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1993	4	12	33.2	59.6	0.118995	937.323	111.54	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1994	4	12	33.2	59.6	0.093713	1159.56	108.67	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1995	4	12	33.2	59.6	0.074609	1582.89	118.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1996	4	12	33.2	59.6	0.056623	1670.05	94.56	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1997	4	12	33.2	59.6	0.102208	2204.5	225.32	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1998	4	12	33.2	59.6	0.077342	2598.24	200.95	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	1999	4	12	33.2	59.6	0.040318	3480.08	140.31	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2000	4	12	33.2	59.6	0.056848	4855.66	276.03	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2001	4	12	33.2	59.6	0.034208	5505.17	188.32	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2002	4	12	33.2	59.6	0.031842	6844.57	217.94	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2003	4	12	33.2	59.6	0.019632	8259.99	162.16	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2004	4	12	33.2	59.6	0.004754	9463.45	44.99	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2005	4	12	33.2	59.6	0.004754	11798.9	56.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2006	4	12	33.2	59.6	0.004754	13026.6	61.93	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2007	4	12	33.2	59.6	0.004754	14908.4	70.88	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2008	4	12	33.2	59.6	0.004754	14300.8	67.99	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2009	4	12	33.2	59.6	0.003604	12007.3	43.27	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2010	4	12	33.2	59.6	0.003604	13755.1	49.57	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2011	4	12	33.2	59.6	0.003076	12566.8	38.66	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2012	4	12	33.2	59.6	0.003076	20815.6	64.04	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2013	4	12	33.2	59.6	0.002626	23399.6	61.45	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2014	4	12	33.2	59.6	0.002626	25302.5	66.44	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2015	4	12	33.2	59.6	0.002071	26486.1	54.85	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2016	4	12	33.2	59.6	0.002071	27817.1	57.61	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2017	4	12	33.2	59.6	0.001984	28588.4	56.72	
ScenarioID	2	2018	1	5	18	90090412	110	1	21	0	0	2018	4	12	33.2	59.6	0.001899	28732.1	54.56	

# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadTypeID	avgSpeed	B temperature	relHumidit	ratePerDis	activity	Rate per D
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1988	4	12	33.2	59.6	0.126031	262.816	33.12	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1989	4	12	33.2	59.6	0.126298	314.655	39.74	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1990	4	12	33.2	59.6	0.173835	313.931	54.57	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1991	4	12	33.2	59.6	0.072556	365.094	26.49	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1992	4	12	33.2	59.6	0.072569	439.671	31.91	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1993	4	12	33.2	59.6	0.073045	560.247	40.92	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1994	4	12	33.2	59.6	0.087536	844.775	73.95	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1995	4	12	33.2	59.6	0.081965	984.685	80.71	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1996	4	12	33.2	59.6	0.090746	1079.78	97.99	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1997	4	12	33.2	59.6	0.083091	1550.08	128.80	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1998	4	12	33.2	59.6	0.074235	1928.81	143.18	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	1999	4	12	33.2	59.6	0.075086	2486.47	186.70	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2000	4	12	33.2	59.6	0.065831	3029.26	199.42	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2001	4	12	33.2	59.6	0.063859	3534.03	225.68	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2002	4	12	33.2	59.6	0.036124	4356.76	157.38	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2003	4	12	33.2	59.6	0.048794	5056.73	246.74	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2004	4	12	33.2	59.6	0.007653	6305.08	48.25	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2005	4	12	33.2	59.6	0.00764	6893.12	52.66	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2006	4	12	33.2	59.6	0.007669	7370	56.52	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2007	4	12	33.2	59.6	0.007618	7376.98	56.19	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2008	4	12	33.2	59.6	0.007638	7848.73	59.95	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2009	4	12	33.2	59.6	0.006252	4637.62	28.99	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2010	4	12	33.2	59.6	0.006235	6490.59	40.47	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2011	4	12	33.2	59.6	0.005627	7147.14	40.22	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2012	4	12	33.2	59.6	0.005628	11541.4	64.96	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2013	4	12	33.2	59.6	0.005028	13917.5	69.98	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2014	4	12	33.2	59.6	0.005027	15504.4	77.95	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2015	4	12	33.2	59.6	0.003208	17119.1	54.91	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2016	4	12	33.2	59.6	0.003208	18348.7	58.86	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2017	4	12	33.2	59.6	0.003208	18820	60.37	
ScenarioID	2	2018	1	5	18	90090412	110	1	31	0	0	2018	4	12	33.2	59.6	0.002952	19096.1	56.38	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1988	4	12	33.2	59.6	0.120971	48.8675	5.91	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1989	4	12	33.2	59.6	0.12181	56.1696	6.84	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1990	4	12	33.2	59.6	0.161205	53.7889	8.67	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1992	4	12	33.2	59.6	0.065997	53.6956	3.54	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1993	4	12	33.2	59.6	0.064802	105.487	6.84	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1994	4	12	33.2	59.6	0.089498	111.398	9.97	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1995	4	12	33.2	59.6	0.076296	180.068	13.74	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1996	4	12	33.2	59.6	0.079543	186.558	14.84	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1997	4	12	33.2	59.6	0.078841	290.173	22.88	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1998	4	12	33.2	59.6	0.064527	290.679	18.76	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	1999	4	12	33.2	59.6	0.062222	495.166	30.81	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2000	4	12	33.2	59.6	0.056938	717.377	40.85	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2001	4	12	33.2	59.6	0.055833	917.169	51.21	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2002	4	12	33.2	59.6	0.032353	1169.08	37.82	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2003	4	12	33.2	59.6	0.042361	1363.51	57.76	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2004	4	12	33.2	59.6	0.007092	1705.95	12.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2005	4	12	33.2	59.6	0.00706	1856.21	13.10	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2006	4	12	33.2	59.6	0.007132	2006.18	14.31	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2007	4	12	33.2	59.6	0.007002	1969.6	13.79	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2008	4	12	33.2	59.6	0.007056	2112.12	14.90	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2009	4	12	33.2	59.6	0.005716	1227.5	7.02	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2010	4	12	33.2	59.6	0.00567	1704.05	9.66	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2011	4	12	33.2	59.6	0.005199	1924.15	10.00	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2012	4	12	33.2	59.6	0.005202	2767.26	14.40	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2013	4	12	33.2	59.6	0.004634	3350.23	15.53	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2014	4	12	33.2	59.6	0.004633	3754.54	17.39	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2015	4	12	33.2	59.6	0.002955	4170.72	12.32	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2016	4	12	33.2	59.6	0.002954	4494.79	13.28	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2017	4	12	33.2	59.6	0.002955	4629.92	13.68	
ScenarioID	2	2018	1	5	18	90090412	110	1	32	0	0	2018	4	12	33.2	59.6	0.002739	4714.32	12.91	

# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadType	avgSpeed	B temperature	relHumidit	ratePerDis	activity	Rate per Distance X Ai
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1988	4	12	33.2	59.6	1.08433	0.923808	1.00	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1989	4	12	33.2	59.6	1.08433	0.94527	1.02	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1990	4	12	33.2	59.6	1.08712	1.37178	1.49	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1991	4	12	33.2	59.6	1.08712	1.78772	1.94	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1992	4	12	33.2	59.6	1.08712	2.4386	2.65	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1993	4	12	33.2	59.6	1.08712	3.1664	3.44	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1994	4	12	33.2	59.6	1.16357	4.15018	4.83	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1995	4	12	33.2	59.6	1.16357	3.83712	4.46	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1996	4	12	33.2	59.6	1.17126	5.39972	6.32	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1997	4	12	33.2	59.6	1.17126	6.33558	7.42	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1998	4	12	33.2	59.6	1.17126	6.80422	7.97	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	1999	4	12	33.2	59.6	1.17126	8.25878	9.67	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2000	4	12	33.2	59.6	1.17126	11.3034	13.24	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2001	4	12	33.2	59.6	1.05985	14.75	15.63	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2002	4	12	33.2	59.6	1.05985	18.1009	19.18	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2003	4	12	33.2	59.6	1.05985	21.3404	22.62	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2004	4	12	33.2	59.6	0.736379	26.0378	19.17	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2005	4	12	33.2	59.6	0.736379	32.215	23.72	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2006	4	12	33.2	59.6	0.736379	38.7754	28.55	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2007	4	12	33.2	59.6	0.736379	43.0254	31.68	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2008	4	12	33.2	59.6	0.409875	51.3064	21.03	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2009	4	12	33.2	59.6	0.409875	30.7848	12.62	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2010	4	12	33.2	59.6	0.409875	31.812	13.04	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2011	4	12	33.2	59.6	0.409875	38.0732	15.61	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2012	4	12	33.2	59.6	0.409875	51.675	21.18	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2013	4	12	33.2	59.6	0.409875	63.7692	26.14	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2014	4	12	33.2	59.6	0.409875	80.5606	33.02	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2015	4	12	33.2	59.6	0.409875	101.499	41.60	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2016	4	12	33.2	59.6	0.409875	134.96	55.32	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2017	4	12	33.2	59.6	0.409875	183.46	75.20	
ScenarioID	2	2018	1	5	18	90090412	87	1	11	0	0	2018	4	12	33.2	59.6	0.409875	338.008	138.54	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1988	4	12	33.2	59.6	0.383926	530.67	203.74	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1989	4	12	33.2	59.6	0.383926	403.988	155.10	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1990	4	12	33.2	59.6	0.254398	497.65	126.60	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1992	4	12	33.2	59.6	0.254406	746.945	190.03	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1993	4	12	33.2	59.6	0.254406	937.323	238.46	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1994	4	12	33.2	59.6	0.222156	1159.56	257.60	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1995	4	12	33.2	59.6	0.225334	1582.89	356.68	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1996	4	12	33.2	59.6	0.159449	1670.05	266.29	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1997	4	12	33.2	59.6	0.15957	2204.5	351.77	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1998	4	12	33.2	59.6	0.160146	2598.24	416.10	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	1999	4	12	33.2	59.6	0.158855	3480.08	552.83	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2000	4	12	33.2	59.6	0.160377	4855.66	778.74	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2001	4	12	33.2	59.6	0.018318	5505.17	100.84	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2002	4	12	33.2	59.6	0.017519	6844.57	119.91	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2003	4	12	33.2	59.6	0.017588	8259.99	145.28	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2004	4	12	33.2	59.6	0.014441	9463.45	136.66	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2005	4	12	33.2	59.6	0.014258	11798.9	168.23	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2006	4	12	33.2	59.6	0.014139	13026.6	184.18	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2007	4	12	33.2	59.6	0.013958	14908.4	208.09	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2008	4	12	33.2	59.6	0.013947	14300.8	199.46	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2009	4	12	33.2	59.6	0.009736	12007.3	116.90	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2010	4	12	33.2	59.6	0.009736	13755.1	133.92	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2011	4	12	33.2	59.6	0.007058	12566.8	88.69	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2012	4	12	33.2	59.6	0.007058	20815.6	146.91	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2013	4	12	33.2	59.6	0.005128	23399.6	119.98	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2014	4	12	33.2	59.6	0.005128	25302.5	129.74	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2015	4	12	33.2	59.6	0.002088	26486.1	55.30	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2016	4	12	33.2	59.6	0.00219	27817.1	60.91	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2017	4	12	33.2	59.6	0.002001	28588.4	57.19	
ScenarioID	2	2018	1	5	18	90090412	87	1	21	0	0	2018	4	12	33.2	59.6	0.001867	28732.1	53.63	

# APPENDIX - MOVES OUTPUT

MOVESce	MOVESRur	yearID	monthID	dayID	hourID	linkID	pollutantID	processID	sourceType	regClassID	SCC	fuelTypeID	modelYear	roadType	EAvgSpeed	B temperature	relHumidit	ratePerDis	activity	Rate per Distance X Ai
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1988	4	12	33.2	59.6	0.65919	262.816	173.25	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1989	4	12	33.2	59.6	0.659836	314.655	207.62	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1990	4	12	33.2	59.6	0.577905	313.931	181.42	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1991	4	12	33.2	59.6	0.579154	365.094	211.45	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1992	4	12	33.2	59.6	0.579191	439.671	254.65	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1993	4	12	33.2	59.6	0.580649	560.247	325.31	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1994	4	12	33.2	59.6	0.533376	844.775	450.58	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1995	4	12	33.2	59.6	0.533283	984.685	525.12	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1996	4	12	33.2	59.6	0.21321	1079.78	230.22	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1997	4	12	33.2	59.6	0.323422	1550.08	501.33	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1998	4	12	33.2	59.6	0.308999	1928.81	596.00	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	1999	4	12	33.2	59.6	0.297756	2486.47	740.36	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2000	4	12	33.2	59.6	0.297399	3029.26	900.90	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2001	4	12	33.2	59.6	0.091394	3534.03	322.99	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2002	4	12	33.2	59.6	0.08749	4356.76	381.17	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2003	4	12	33.2	59.6	0.096294	5056.73	486.93	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2004	4	12	33.2	59.6	0.036639	6305.08	231.01	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2005	4	12	33.2	59.6	0.027604	6893.12	190.28	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2006	4	12	33.2	59.6	0.028444	7370	209.63	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2007	4	12	33.2	59.6	0.027271	7376.98	201.18	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2008	4	12	33.2	59.6	0.02642	7848.73	207.37	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2009	4	12	33.2	59.6	0.018141	4637.62	84.13	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2010	4	12	33.2	59.6	0.018034	6490.59	117.05	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2011	4	12	33.2	59.6	0.013384	7147.14	95.66	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2012	4	12	33.2	59.6	0.013389	11541.4	154.52	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2013	4	12	33.2	59.6	0.009499	13917.5	132.21	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2014	4	12	33.2	59.6	0.009499	15504.4	147.27	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2015	4	12	33.2	59.6	0.004047	17119.1	69.29	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2016	4	12	33.2	59.6	0.004224	18348.7	77.51	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2017	4	12	33.2	59.6	0.005267	18820	99.13	
ScenarioID	2	2018	1	5	18	90090412	87	1	31	0	0	2018	4	12	33.2	59.6	0.00347	19096.1	66.26	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1988	4	12	33.2	59.6	0.68374	48.8675	33.41	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1989	4	12	33.2	59.6	0.685642	56.1696	38.51	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1990	4	12	33.2	59.6	0.593739	53.7889	31.94	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1992	4	12	33.2	59.6	0.585195	53.6956	31.42	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1993	4	12	33.2	59.6	0.581233	105.487	61.31	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1994	4	12	33.2	59.6	0.556455	111.398	61.99	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1995	4	12	33.2	59.6	0.567376	180.068	102.17	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1996	4	12	33.2	59.6	0.256134	186.558	47.78	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1997	4	12	33.2	59.6	0.360021	290.173	104.47	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1998	4	12	33.2	59.6	0.305487	290.679	88.80	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	1999	4	12	33.2	59.6	0.29033	495.166	143.76	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2000	4	12	33.2	59.6	0.28863	717.377	207.06	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2001	4	12	33.2	59.6	0.092848	917.169	85.16	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2002	4	12	33.2	59.6	0.086288	1169.08	100.88	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2003	4	12	33.2	59.6	0.094619	1363.51	129.01	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2004	4	12	33.2	59.6	0.03981	1705.95	67.91	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2005	4	12	33.2	59.6	0.031099	1856.21	57.73	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2006	4	12	33.2	59.6	0.032912	2006.18	66.03	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2007	4	12	33.2	59.6	0.029757	1969.6	58.61	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2008	4	12	33.2	59.6	0.02706	2112.12	57.15	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2009	4	12	33.2	59.6	0.016684	1227.5	20.48	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2010	4	12	33.2	59.6	0.016479	1704.05	28.08	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2011	4	12	33.2	59.6	0.012651	1924.15	24.34	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2012	4	12	33.2	59.6	0.012662	2767.26	35.04	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2013	4	12	33.2	59.6	0.008604	3350.23	28.83	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2014	4	12	33.2	59.6	0.008603	3754.54	32.30	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2015	4	12	33.2	59.6	0.003712	4170.72	15.48	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2016	4	12	33.2	59.6	0.003849	4494.79	17.30	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2017	4	12	33.2	59.6	0.004905	4629.92	22.71	
ScenarioID	2	2018	1	5	18	90090412	87	1	32	0	0	2018	4	12	33.2	59.6	0.003252	4714.32	15.33	

## Appendix E

# Carbon Monoxide (CO) Technical Memorandum

This page intentionally left blank.

# Technical Memorandum

## Carbon Monoxide Exposure Limit

### 1 Introduction

This memorandum presents the justification for the determined carbon monoxide exposure limit for the proposed project. The state of Connecticut has a single tunnel within their highway system, therefore there are no standards to aid in determining exposure limits of carbon monoxide (CO) during normal traffic operations, traffic incidents and maintenance operations. Several sources including the Occupational Safety and Health Standards (OSHA), the National Fire Protection Agency (NFPA) and other state's requirements were reviewed to determine the most appropriate guidelines to use as a design basis for the Heroes Tunnel ventilation system. Excerpts from the referenced sources are provided in attachments to this Technical Memorandum.

### 2 Standards, Codes and Evaluation Criteria

#### 2.1 Evaluation Criteria

To provide the safest possible environment in the tunnel, the exposure limits were chosen based on the longest anticipated time period an individual would be exposed to CO. In this case, that time would be during maintenance operations which typically last eight hours. Therefore, the acceptable exposure limits will be specified for an eight-hour duration.

#### 2.2 Occupational Safety and Health Administration (OSHA) Standards

The Occupational Safety and Health Administration (OSHA) provides standards to ensure workers a safe and healthful working environment. Within OSHA standard 1910.1000 – Air Contaminants, permissible exposure limits for many contaminants are listed in Table Z-1 – Limits for Air Contaminants as an 8-hour time weighted average (see Appendix attachment). The time weighted average for CO is listed as 50 parts per million (ppm).

#### 2.3 National Fire Protection Association (NFPA) Standards

The National Fire Protection Association (NFPA) offers guidance on how to eliminate fire, electrical and other related hazards. NFPA 502 – Standard for Road Tunnels, Bridges, and Other Limited Access Highways includes similar information on CO exposure limits to the OSHA standards. In Section B.2.2 (see Appendix attachment), the concentration of CO in air must average 50 ppm or less for any exposure duration over 30 minutes.

#### 2.4 National Cooperative Highway Research Program (NCHRP)

In 2009, the National Cooperative Highway Research Program (NCHRP) conducted a conference to address the need for national tunnel standards. The participants included several state departments of transportation as well as other representatives. The resulting document, NCHRP Project 20-68A, titled “Best Practices for Roadway Tunnel Design, Construction, maintenance, Inspection, and Operations” (see Appendix attachment), outlines the participants’ air quality requirements in Section 2.3.1.2. Here, a few of the departments of transportation involved, California, Colorado and Massachusetts, list their CO concentration limits. California states that at



concentrations of 60 ppm or greater, exhaust fans activate to lower the concentration of CO. Colorado's and Massachusetts' maximum CO limit is 100 ppm for any exposure time and 70 ppm for a duration of one hour, respectively.

## **2.5 LRFD Road Tunnel Design and Construction Guide Specifications (AASHTO) 2107**

Table 2.8.3.2-1 Minimum Limits for Carbon Monoxide, Oxides of Nitrogen, and Particulate Matter provides a limiting Value of 35 ppm up to 60 minutes of exposure for Carbon Monoxide. As indicated in the commentary of this section the CO limiting values are based on FHWA/EPA guidelines.

## **3 Recommendations**

Comparing the various exposure limits, the values shown in OSHA and NFPA 502 coincide with one another at a level of 50 ppm but the exposure limit for OSHA is 8 hours while NFPA 502 is any exposure over 30 minutes a much more stringent limit. The LRFD Guide Specifications level of 35 ppm for a similar exposure limit of one hour. The values from the NCHRP program are consistently higher, reaching a maximum allowable level of 100 ppm. Since the NCHRP proceedings are based on various departments' standards and are not restricted by national code, OSHA and NFPA will be the primary resource for the exposure limits in Heroes Tunnel. The criteria for this study was to determine required upgrades that meet the NFPA 502 Standards for fire protection and life safety systems. Though the LRFD Guide Specifications will be the controlling code for this facility and moving forward in design, the NFPA 502 Standard of 50 ppm for exposures over 30 minutes will be the controlling exposure level for this report. It is CDM Smith's recommendation to implement a 50 ppm limit for exposures over 30 minutes, at which the tunnel ventilation system will activate to maintain air quality at an acceptable level.

TABLE Z-1—LIMITS FOR AIR CONTAMINANTS—Continued

Substance	CAS No. (c)	ppm (a) <sup>1</sup>	mg/m <sup>3</sup> (b) <sup>1</sup>	Skin designation
Butanethiol; see Butyl mercaptan.				
2-Butanone (Methyl ethyl ketone) .....	78-93-3	200	590	
2-Butoxyethanol .....	111-76-2	50	240	X
n-Butyl-acetate .....	123-86-4	150	710	
sec-Butyl acetate .....	105-46-4	200	950	
tert-Butyl acetate .....	540-88-5	200	950	
n-Butyl alcohol .....	71-36-3	100	300	
sec-Butyl alcohol .....	78-92-2	150	450	
tert-Butyl alcohol .....	75-65-0	100	300	
Butylamine .....	109-73-9	(C)5	(C)15	X
tert-Butyl chromate (as CrO <sub>3</sub> ); see 1910.1026 <sup>6</sup> .....	1189-85-1			
n-Butyl glycidyl ether (BGE) .....	2426-08-6	50	270	
Butyl mercaptan .....	109-79-5	10	35	
p-tert-Butyltoluene .....	98-51-1	10	60	
Cadmium (as Cd); see 1910.1027 .....	7440-43-9			
Calcium carbonate .....	1317-65-3			
Total dust .....			15	
Respirable fraction .....			5	
Calcium hydroxide .....	1305-62-0			
Total dust .....			15	
Respirable fraction .....			5	
Calcium oxide .....	1305-78-8		5	
Calcium silicate .....	1344-95-2			
Total dust .....			15	
Respirable fraction .....			5	
Calcium sulfate .....	7778-18-9			
Total dust .....			15	
Respirable fraction .....			5	
Camphor, synthetic .....	76-22-2		2	
Carbaryl (Sevin) .....	63-25-2		5	
Carbon black .....	1333-86-4		3.5	
Carbon dioxide .....	124-38-9	5000	9000	
Carbon disulfide .....	75-15-0		( <sup>2</sup> )	
Carbon monoxide .....	630-08-0	50	55	
Carbon tetrachloride .....	56-23-5		( <sup>2</sup> )	
Cellulose .....	9004-34-6			
Total dust .....			15	
Respirable fraction .....			5	
Chlordane .....	57-74-9		0.5	X
Chlorinated camphene .....	8001-35-2		0.5	X
Chlorinated diphenyl oxide .....	55720-99-5		0.5	
Chlorine .....	7782-50-5	(C)1	(C)3	
Chlorine dioxide .....	10049-04-4	0.1	0.3	
Chlorine trifluoride .....	7790-91-2	(C)0.1	(C)0.4	
Chloroacetaldehyde .....	107-20-0	(C)1	(C)3	
o-Chloroacetophenone (Phenacyl chloride) .....	532-27-4	0.05	0.3	
Chlorobenzene .....	108-90-7	75	350	
o-Chlorobenzylidene malononitrile .....	2698-41-1	0.05	0.4	
Chlorobromomethane .....	74-97-5	200	1050	
2-Chloro-1,3-butadiene; see beta-Chloroprene.				
Chlorodiphenyl (42% Chlorine) (PCB) .....	53469-21-9		1	X
Chlorodiphenyl (54% Chlorine) (PCB) .....	11097-69-1		0.5	X
1-Chloro-2,3-epoxypropane; see Epichlorohydrin.				
2-Chloroethanol; see Ethylene chlorohydrin.				
Chloroethylene; see Vinyl chloride.				
Chloroform (Trichloromethane) .....	67-66-3	(C)50	(C)240	
bis(Chloromethyl) ether; see 1910.1008 .....	542-88-1			
Chloromethyl methyl ether; see 1910.1006 .....	107-30-2			
1-Chloro-1-nitropropane .....	600-25-9	20	100	
Chloropicrin .....	76-06-2	0.1	0.7	
beta-Chloroprene .....	126-99-8	25	90	X
2-Chloro-6-(trichloromethyl) pyridine .....	1929-82-4			
Total dust .....			15	
Respirable fraction .....			5	
Chromium (II) compounds.				
(as Cr) .....	7440-47-3		0.5	
Chromium (III) compounds.				
(as Cr) .....	7440-47-3		0.5	
Chromium (VI) compounds; See 1910.1026 <sup>5</sup>				
Chromium metal and insol. salts (as Cr) .....	7440-47-3		1	
Chrysene; see Coal tar pitch volatiles.				
Clopidol .....	2971-90-6			

As with toxic gases, an exposed occupant can be considered to accumulate a dose of convected heat over a period of time. The FED of convected heat accumulated per minute is the reciprocal of  $t_{conv}$ .

Convected heat accumulated per minute depends on the extent to which an exposed occupant is clothed and the nature of the clothing. For fully clothed subjects, equation B.2.1b is suggested:

$$t_{conv} = (4.1 \times 10^8) T^{-3.61} \quad [\text{B.2.1b}]$$

where:

$t_{conv}$  = time (minutes)  
 $T$  = temperature ( $^{\circ}\text{C}$ )

For unclothed or lightly clothed subjects, it might be more appropriate to use equation B.2.1c:

$$t_{conv} = (5.0 \times 10^7) T^{-3.4} \quad [\text{B.2.1c}]$$

where:

$t_{conv}$  = time (minutes)  
 $T$  = temperature ( $^{\circ}\text{C}$ )

Equations B.2.1b and B.2.1c are empirical fits to human data. It is estimated that the uncertainty is  $\pm 25$  percent.

Thermal tolerance data for unprotected human skin suggest a limit of about  $120^{\circ}\text{C}$  ( $248^{\circ}\text{F}$ ) for convected heat, above which there is, within minutes, onset of considerable pain along with the production of burns. Depending on the length of exposure, convective heat below this temperature can also cause hyperthermia.

The body of an exposed occupant can be regarded as acquiring a “dose” of heat over a period of time. A short exposure to a high radiant heat flux or temperature generally is less tolerable than a longer exposure to a lower temperature or heat flux. A methodology based on additive FEDs similar to that used with toxic gases can be applied. Providing that the temperature in the fire is stable or increasing, the total fractional effective dose of heat acquired during an exposure can be calculated using equation B.2.1d:

$$\text{FED} = \sum \left( \frac{1}{t_{rad}} + \frac{1}{t_{conv}} \right) \Delta t_i^{t_i} \quad [\text{B.2.1d}]$$

where:

FED = fraction equivalent dose

$t_{rad}$  = time (min)

$t_{conv}$  = time (min)

$\Delta t_i^{t_i}$  = change in time (min)

Note 1: In areas within an occupancy where the radiant flux to the skin is under  $2.5 \text{ kW/m}^2$ , the first term in equation B.2.1d is to be set at zero.

Note 2: The uncertainty associated with the use of equation B.2.1d would depend on the uncertainties associated with the use of the three earlier equations.

The time at which the FED accumulated sum exceeds an incapacitating threshold value of 0.3 represents the time available for escape for the chosen radiant and convective heat exposures.

Consider an example with the following characteristics:

- (1) Evacuees are lightly clothed.
- (2) There is zero radiant heat flux.
- (3) The time to FED is reduced by 25 percent to allow for uncertainties in equations B.2.1b and B.2.1c.
- (4) The exposure temperature is constant.
- (5) The FED is not to exceed 0.3.

Equations B.2.1c and B.2.1d can be manipulated to provide the following equation:

$$t_{exp} = (1.125 \times 10^7) T^{-3.4} \quad [\text{B.2.1e}]$$

where:

$t_{exp}$  = time of exposure to reach a FED of 0.3 (minutes)  
 $T$  = temperature ( $^{\circ}\text{C}$ )

This gives the results in Table B.2.1.

**B.2.2 Air Carbon Monoxide Content.** Air carbon monoxide (CO) content is as follows:

- (1) Maximum of 2000 ppm for a few seconds
- (2) Averaging 1150 ppm or less for the first 6 minutes of the exposure
- (3) Averaging 450 ppm or less for the first 15 minutes of the exposure
- (4) Averaging 225 ppm or less for the first 30 minutes of the exposure
- (5) Averaging 50 ppm or less for the remainder of the exposure

These values should be adjusted for altitudes above 984 m (3000 ft).

**B.2.3 Toxicity.** The toxicity of fire smoke should be determined by considering contributing gases, which can act cumulatively.

**Table B.2.1 Exposure Time and Incapacitation**

Exposure Temperature		Maximum Exposure Time Without Incapacitation (min)
$^{\circ}\text{C}$	$^{\circ}\text{F}$	
80	176	3.8
75	167	4.7
70	158	6.0
65	149	7.7
60	140	10.1
55	131	13.6
50	122	18.8
45	113	26.9
40	104	40.2

switching lighting technology, although it has had not found this technology to be beneficial in the past.

### **2.3.1.2 Air Quality and Opacity Air Quality Requirements**

Ventilation systems, CO/nitrogen oxides (NO<sub>x</sub>)/particulate matter (PM) monitoring systems, and fire and life-safety provisions are utilized in tunnels as needed based on design calculations of anticipated air quality exposure levels and EPA/OSHA requirements. The extent of ventilation capacity is based on tunnel length as defined by NFPA 502. Regulation varies from internal handling to reporting to local or state environmental agencies. Video is used to monitor opacity; ventilation stacks do not typically have air scrubbers.

**AKDOT&PF:** The Anton Anderson Memorial (Whittier) Tunnel is one of the first tunnels in the U.S. to use jet fans for ventilation. The AKDOT&PF monitors its CO levels due to the mix of trains and vehicles, but has no specific regulator.

**Caltrans:** Caltrans does not specify specialized air quality equipment (e.g., video imaging, laser based imaging, or newer technologies). Instead, it specifies local CO and NO<sub>x</sub> monitors located in the tunnel and dedicated to a zone. The monitors are manually calibrated, and sensors are replaced by a maintenance schedule.

Design calculations for all tunnels, including short tunnels that normally would not be expected to require ventilation, must show that CO exposure levels will not exceed the EPA maximum exposure levels during normal ADT volumes and the predicted maximum vehicle per hour traffic rate. If design calculations (i.e., computer modeling) of CO exposure levels show they could reach 50 ppm for the expected exposure time of vehicles in the tunnel, then real-time CO monitoring equipment must be installed and monitored and the contract drawings must provide for future addition of ventilation equipment. This means that sections in the structure must be blocked out for ducting and mounting of ventilation equipment, and empty power conduits to the future equipment locations must be provided. If design calculations of CO exposure levels show they could reach 120 ppm for the expected exposure time of vehicles in the tunnel, then the contract drawings must provide for the installation and operation of ventilation equipment, electrical power and controls, CO monitoring equipment, and fire/life-safety provisions.

The extent of ventilation capacity is based on the tunnel length as defined in the latest edition of NFPA 502 and as follows:

- For tunnels less than 300 feet in length, specific ventilation and fire/life-safety provisions are evaluated on a case-by-case basis, with engineering analysis required for evaluation.
- For tunnels 300 feet and greater in length, if engineering analysis indicates CO accumulations are probable, at a minimum ventilation capacity is required to dilute CO concentrations. Two-speed fans will operate at low speed when concentrations reach 60 ppm CO and high speed when concentrations reach 100 ppm CO. All other provisions of NFPA 502 apply.
- For tunnels lengths greater than 800 feet, all provisions of NFPA 502 apply, and ventilation

---

capacity must produce the critical velocity required to prevent back layering of the smoke of a design fire.

Documentation of air quality sampling is expected to be recorded and stored for historical and tort liability. Ventilation stacks (usually exhaust) do not have air scrubbers.

**Colorado DOT:** The EJMT effectively employs the original full transverse ventilation system. The HLT has not needed to run fans routinely, as the normal CO levels remain below 15 ppm.

Historically, the requirement has been a maximum 100 ppm for CO. CO ppm measurements are taken in the exhaust plenum immediately prior to being exhausted into open air. Much lower levels (i.e., 5 to 20 ppm) are typical.

The Colorado Department of Health and Environment is the regulating agency, but there is limited scrutiny due to decades without violations. CDOT does not have air scrubbers on its ventilation stacks.

**MassDOT:** MassDOT is under Massachusetts DEP air quality requirements. It follows the DEP regulated Continuous Emissions Monitoring (CEM) Program, which is unique to Boston. The CEM is a hybrid of ambient air quality monitoring and continuous emissions monitoring systems. Emissions are regulated as a direct source, similar to power plants, although vehicular exhaust is an indirect source, and monitored over time for air quality concentration with respect to time. CO and PM-10<sup>30</sup> are measured continuously, while NOx is calculated using a CO:NOx correlation. Emission limits are as follows:

- Maximum CO is 70 ppm in one hour
- Maximum NOx is 8.88 ppm in one hour
- Maximum PM-10 is 500 mg/m<sup>3</sup> in 24 hours

New state regulations on PM go from PM-10 to PM-3. The hourly average is reported at 16 locations in ventilation buildings, exhaust plenums, and entrance and exit ramps. Typical equipment components at each location are continuous CO gas analyzer, multi gas calibration unit, zero air generator, data logger, CO calibration gas, and a PM-10 sampler at four locations. CEM design and capital cost were \$2 million, with annual non labor operating costs of \$200,000, including a five year permit renewal. The CEM labor requirements to operate, maintain, and report are two environmental technicians and one senior environmental engineer. The CEM is independent of in tunnel CO monitoring.

**PennDOT:** PennDOT has done CO monitoring inside tunnels only. Air sampling is continuous, but there are no reporting requirements. PennDOT does not have air scrubbers on its ventilation stacks.

**PANY&NJ:** The PANY&NJ follows OSHA and EPA regulations and monitors CO levels

---

<sup>30</sup> PM standard that includes particles with a diameter of 10 micrometers or less

accordingly. The PANY&NJ is self regulated and does not report to external agencies. Its tunnels are equipped with CO monitors, and CO levels are monitored 24/7 via manned control rooms from which fans are adjusted accordingly. PANY&NJ also monitors NOx. It does not have air scrubbers on its ventilation stacks.

**VA CBBT:** The CBBT District effectively employs the original full transverse ventilation system in its tunnels.

**VDOT:** VDOT uses video monitoring for opacity and CO monitoring for air quality. In accordance with OSHA requirements, the maximum CO level cannot exceed 35 ppm for an 8-hour time weighted average. Air sampling is performed to determine CO levels, and regulation is performed internally by VDOT. VDOT is exempt from discharge regulations based on the Code of Virginia.

**WSDOT:** In normal operation, air is moved through the tunnel portals with a series of jet fans, so specialized technologies cannot be applied. The vertical fans will only operate during extreme congestion or during an emergency. The Puget Sound Air Quality Agency regulates air quality, and the tunnel project must meet local air quality standards, as must all transportation projects. There are regional air quality monitors. WSDOT does not have air scrubbers on its ventilation stacks and will resist installing them since they will only be used occasionally.

### ***2.3.1.3 Waterproofing Systems***

Various waterproofing systems have been used in tunnels, as described below. Tunnels that do not have waterproofing membranes have drainage systems to collect seep water.

**Caltrans:** At the Devil's Slide Tunnel and new Caldecott Tunnel, between the initial lining and the final lining, a geotextile material will be placed against a smoothed shotcrete layer and a waterproofing membrane will be placed against the final lining. This system will drain into an under drain system that will carry the water outside the tunnel and past the portals into a drainage system.

At the Doyle Drive Southbound Battery Tunnel, a geo composite drainage material will be placed at the retaining walls. A waterproofing system will be applied on the inside face of the retaining wall or tunnel walls and will drain into a sub drain system underneath the tunnel and flow out underneath the tunnel.

The Posey/Webster Tubes' precast segments were wrapped in a waterproofing material and timber lagging.

**Colorado DOT:** The Eisenhower bore of the EJMT does not have a waterproofing membrane. The Johnson bore was effectively treated with a membrane. Maintenance forces have drilled past the tunnel liner in the Eisenhower bore in the wet locations of the air ducts and have built a drainage system to collect the seep water in these locations. An extensive drainage system is in place above and below the roadway in both bores.

The HLT includes an elastomeric waterproofing membrane at spot locations with a formation drainage system.

# Appendix F


## Electrical Supporting Documents

This page intentionally left blank.



(3) 100 KVA, POLE MTD. PRI - 4160/13800, SEC - 480 Δ ( BY UI )

F.H.W.A. REGION NO.	STATE	TOWN	FED. AID PROJ. NO.	PROJ. NO.	YEAR	ROUTE NO.	SHEET NO.	TOTAL SHEETS
1	CONN.	NEW HAVEN - WOODBRIDGE		167-80	1983	15	5A	13



THIS SHEET CORRECTED

DESIGN BY  
DRAWN BY  
CHECKED BY

- NOTE:
1. RUN GROUNDS AS REQUIRED
  2. SERVICE TRANSFORMER TAPS TO BE FIELD SET TO COMPENSATE FOR VOLTAGE DROP.
  3. ALL TERMINATORS, LUGS, CONNECTORS, SPLICES TO BE APPROPRIATE FOR WIRE SIZE & USAGE.
  4. LIGHTING & OUTLETS IN CONTROL ROOM & TOWER ROOM TO BE DETERMINED IN THE FIELD.

CONNECTICUT  
DEPARTMENT OF TRANSPORTATION  
BUREAU OF HIGHWAYS  
DIVISION OF TRAFFIC

TOWNS OF NEW HAVEN & WOODBRIDGE  
WEST ROCK TUNNEL


WIRING DIAGRAM

SUBMITTED BY *[Signature]* DATE 9/83  
APPROVED BY *[Signature]* DATE 10/83  
ENG. OF TRAFFIC

REVISIONS		
NO.	DATE	DESCRIPTION
5A	7/84	


SCALE \_\_\_\_\_

© 2019 CDM SMITH ALL RIGHTS RESERVED. REUSE OF DOCUMENTS: THESE DOCUMENTS AND DESIGNS PROVIDED BY PROFESSIONAL SERVICE, INCORPORATED HEREIN, ARE THE PROPERTY OF CDM SMITH AND ARE NOT TO BE USED, IN WHOLE OR PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CDM SMITH.




RECOMMENDED  
**ONE LINE DIAGRAM**  
N.T.S.


© 2019 CDM SMITH ALL RIGHTS RESERVED. REUSE OF DOCUMENTS: THESE DOCUMENTS AND DESIGNS PROVIDED BY PROFESSIONAL SERVICE, INCORPORATED HEREIN, ARE THE PROPERTY OF CDM SMITH AND ARE NOT TO BE USED, IN WHOLE OR PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CDM SMITH.



### ALTERNATIVE ONE LINE DIAGRAMS

N.T.S.





A = Fixation Point = 520'  
 B = Adaptation Point = 35.34'  
 C = Portal  
 $\phi = 22^\circ$

a = Approach = 520'  
 b = Adaptation Distance = 35.34'  
 c = Threshold Zone = 484.66'  
 d = Transition Zone\* = 806.67'  
 c + d = 1291.33'  
 f = driver eye height = 4.76'

\*Transition zone extends beyond the length of the tunnel.

The following sections do not exist for this tunnel.

e = interior  
 g = exit zone

01 THRESHOLD 1  
GOAL 185 CD PER SQ M

382ft

02 THRESHOLD 2  
GOAL 130 CD PER SQ M

103ft

03 TRANSITION 1  
GOAL 75.3 CD PER SQ M



162ft


04 TRANSITION 2  
GOAL 30.1 CD PER SQ M

243ft

05 TRANSITION 3  
GOAL 12.3 CD PER SQ M






310ft










**NOTES:**

1. REFER TO OVERALL PLAN FOR LOCATION OF EACH CALCULATION ZONE WITHIN THE TUNNEL.
2. CALCULATION POINTS SHOW LUMINANCE (CANDELA/M<sup>2</sup>) VALUES.




© 2019 CDM SMITH ALL RIGHTS RESERVED.  
 REUSE OF DOCUMENTS: THESE DOCUMENTS AND DESIGNS PROVIDED BY PROFESSIONAL SERVICE, INCORPORATED HEREIN, ARE THE PROPERTY OF  
 CDM SMITH AND ARE NOT TO BE USED, IN WHOLE OR PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CDM SMITH.



**NOTES:**


1. REFER TO OVERALL PLAN FOR LOCATION OF EACH CALCULATION ZONE WITHIN THE TUNNEL. ONLY RELEVANT NIGHTTIME CALCULATIONS ARE SHOWN.
2. CALCULATION POINTS SHOW LUMINANCE (CANDELA/M<sup>2</sup>) VALUES.

© 2019 CDM SMITH ALL RIGHTS RESERVED.  
 REUSE OF DOCUMENTS: THESE DOCUMENTS AND DESIGNS PROVIDED BY PROFESSIONAL SERVICE, INCORPORATED HEREIN, ARE THE PROPERTY OF  
 CDM SMITH AND ARE NOT TO BE USED, IN WHOLE OR PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CDM SMITH.



**NOTES:**

1. REFER TO OVERALL PLAN FOR LOCATION OF THE CALCULATION ZONE WITHIN THE TUNNEL. ONLY A SAMPLE SECTION IS SHOWN
2. CALCULATION POINTS SHOW LUMINANCE (CANDELA/M<sup>2</sup>) VALUES.





# Summary of Scene Calculations with Product Numbers and Dimming Values







# Sample Lighting Fixture Cutsheets

# Sample Lighting Fixture Cutsheets



Consistent with LEED® goals & Green Globes™ criteria for light pollution reduction



## PRODUCT OVERVIEW



### Applications:

- Roadways
- Off ramps
- Residential streets
- Parking lots

### DIMENSIONS



Effective Projected Area (EPA): The EPA for the ATB0 is 0.76 sq. ft.  
Approx. Wt. = 14 lbs.

### STANDARDS

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at [www.designlights.org/QPL](http://www.designlights.org/QPL) to confirm which versions are qualified.

Color temperatures of  $\leq 3000\text{K}$  must be specified for International Dark-Sky Association certification.

Rated for  $-40^{\circ}\text{C}$  to  $40^{\circ}\text{C}$  ambient

CSA Certified to U.S. and Canadian standards

Complies with ANSI: C136.2, C136.10, C136.14, C136.31, C136.15, C136.37

### Features:

#### OPTICAL

**Same Light:** Performance is comparable to 70-250W HPS roadway luminaires.

**White Light:** Correlated color temperature - 4000K, 70 CRI minimum, 3000K, 70 CRI minimum or optional 5000K, 70 CRI minimum.

Unique IP66 rated LED light engines provided 0% uplight and restrict backlight to within sidewalk depth, providing optimal application coverage and optimal pole spacing. Available in Type II, III, IV, and V roadway distributions.

#### ELECTRICAL

**Expected Life:** LED light engines are rated  $>100,000$  hours at  $25^{\circ}\text{C}$ , L70. Electronic driver has an expected life of 100,000 hours at a  $25^{\circ}\text{C}$  ambient.

**Lower Energy:** Saves an expected of 40-60% over comparable HID luminaires.

**Robust Surge Protection:** Three different surge protection options provide a minimum of ANSI C136.2 10kV/5kA protection. 20kV/10kA protection is also available.

#### MECHANICAL

Includes standard AEL lineman-friendly features such as tool-less entry, 3 station terminal block and quick disconnects. Bubble level located inside the electrical compartment for easily leveling at installation.

Rugged die-cast aluminum housing and door are polyester powder-coated for durability and corrosion resistance. Rigorous five-stage pre-treating and painting process yields a finish that achieves a scribe creepage rating of 7 (per ASTM D1654) after over 5000 hours exposure to salt fog chamber (operated per ASTM B117).

Mast arm mount is adjustable for arms from 1-1/4" to 2" (1-5/8" to 2-3/8" O.D.) diameter. Provides a 3G vibration rating per ANSI C136.31

Wildlife shield is cast into the housing (not a separate piece).

#### CONTROLS

NEMA 3 pin photocontrol receptacle is standard, with the Acuity designed ANSI standard 7 pin receptacle optionally available.

Premium solid state locking style photocontrol - PCSS (10 year rated life) Extreme long life solid state locking style photocontrol - PCLL (20 year rated life).

Multi-level dimming available to provide scheduled dimming as specified by the customer.

Optional onboard Adjustable Output module allows the light output and input wattage to be modified to meet site specific requirements, and also can allow a single fixture to be flexibly applied in many different applications.

Note: Specifications subject to change without notice. Actual performance may differ as a result of end-user environment and application.

# Autobahn Series ATB0

## Roadway Lighting

### ORDERING INFORMATION

Example: ATB0 30LEDE10 MVOLT R2

Series	Performance Packages	Voltage	Optics
<b>ATB0</b> Autobahn LED Roadway	<b>10BLEDE70</b> 10B Chips, 700mA Driver <b>10BLEDE10</b> 10B Chips, 1050mA Driver <b>10BLEDE15</b> 10B Chips, 1500mA Driver <b>20BLEDE53</b> 20B Chips, 525mA Driver <b>20BLEDE70</b> 20B Chips, 700mA Driver <b>20BLEDE10</b> 20B Chips, 1050mA Driver <b>20BLEDE13</b> 20B Chips, 1300mA Driver <b>20BLEDE15</b> 20B Chips, 1500mA Driver <b>30BLEDE70</b> 30B Chips, 700mA Driver <b>30BLEDE85</b> 30B Chips, 850mA Driver <b>30BLEDE10</b> 30B Chips, 1050mA Driver <b>30BLEDE13</b> 30B Chips, 1300mA Driver <b>30BLEDE15</b> 30B Chips, 1500mA Driver	<b>MVOLT</b> Multi-volt, 120-277V <b>347</b> 347V <b>480</b> 480V	<b>R2</b> Roadway Type II <b>R3</b> Roadway Type III <b>R4</b> Roadway Type IV <b>R5</b> Roadway Type V

Options			
<u>Color Temperature (CCT)</u> <b>(Blank)</b> 4000K CCT, 70 CRI Min. <b>3K</b> 3000K CCT, 70 CRI Min. <b>5K</b> 5000K CCT, 70 CRI Min.	<b>UMS-XX</b> 8" Horizontal Arm for Square Pole, Painted to match Fixture <b>UMR-GALV</b> 8" Horizontal Arm for Round Pole, Galvanized <b>UMS-GALV</b> 8" Horizontal Arm for Square Pole, Galvanized	<u>Accessories (field installed):</u> <b>ATB0 LTS20</b> Light Trespass Shield for ATB0 LEM 20 <b>ATB0 LTS30</b> Light Trespass Shield for ATB0 LEM 30	
<u>Paint</u> <b>(Blank)</b> Gray (Standard) <b>BK</b> Black <b>BZ</b> Bronze <b>DDB</b> Dark Bronze <b>GI</b> Graphite <b>WH</b> White	<u>Controls</u> <b>(Blank)</b> 3 Pin NEMA Photocontrol Receptacle (Standard) <b>P7<sup>2</sup></b> 7 Pin Photocontrol Receptacle (Dimmable Driver Included) <b>NR</b> No Photocontrol Receptacle <b>AO<sup>3</sup></b> Field Adjustable Output <b>DM</b> 0V-10V Dimmable Driver (Controls by others) <b>ML<sup>4,5</sup></b> Multi-Level Dimming <b>PCSS<sup>1</sup></b> Solid State Lighting Photocontrol (120-277V) <b>PCLL</b> Solid State Long Life Photocontrol <b>SH</b> Shorting Cap	<b>Notes</b> 1 Not available in 347 or 480V. 2 Not available with DM, ML or NR. 3 Not available with DM or ML options. Not available with 10BLED packages. 4 Not available with AO, DM or P7 options. 5 Dimming Schedule and light level information required from the customer in order to configure product. Contact Infrastructure Technical Support to proceed.	
<u>Surge Protection</u> <b>(Blank)</b> Standard 10kV/5kA SPD <b>20</b> 20kV/10KA SPD <b>MP<sup>1</sup></b> MOV Pack <b>IL<sup>1</sup></b> SPD with Indicator Light	<u>Packaging</u> <b>(Blank)</b> Single Unit (Standard) <b>JP</b> Job Pack (42/Pallet)		
<u>Terminal Block</u> <b>(Blank)</b> Terminal Block (Standard) <b>T2</b> Wired to L1 & L2 Positions			
<u>Misc.</u> <b>BL</b> External Bubble Level <b>HS</b> House-Side Shield <b>NL</b> Nema Label <b>XL</b> Not CSA Certified <b>UMR-XX</b> 8" Horizontal Arm for Round Pole, Painted to match Fixture			



AEL Headquarters, 3825 Columbus Road, Granville, OH 43023  
 www.americanelectricalighting.com  
 © 2014-2019 Acuity Brands Lighting, Inc. All Rights Reserved. ATB0 02/21/19

**Warranty** Five-year limited warranty. Complete warranty terms located at: [www.acuitybrands.com/resources/terms-and-conditions](http://www.acuitybrands.com/resources/terms-and-conditions)  
 Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

*Please contact your sales representative for the latest product information.*



# Autobahn Series ATB0

## Roadway Lighting

### PERFORMANCE PACKAGE

Performance Package	Drive Current (mA)	Input Watts	Optic	3K (3000K CCT, 70 CRI Min.)					4K/5K (4000K/5000K CCT, 70 CRI Min.)					LLD @ 25°C		
				Lumens	LPW	B	U	G	Lumens	LPW	B	U	G	25k Hours	75k Hours	100k Hours
10B	700	25	R2	2,670	107	1	0	1	2,994	120	1	0	1	0.98	0.97	0.96
	1050	37		4,006	108	1	0	2	4,293	116	1	0	2	0.97	0.95	0.92
	1500	54		5,364	99	1	0	2	5,688	105	1	0	2	0.93	0.90	0.88
	700	25	R3	2,702	108	1	0	1	3,009	120	1	0	1	0.98	0.97	0.96
	1050	37		4,069	110	1	0	1	4,313	117	1	0	1	0.97	0.95	0.92
	1500	54		5,409	100	1	0	1	5,742	106	1	0	1	0.93	0.90	0.88
	700	25	R4	2,686	107	1	0	1	2,992	120	1	0	1	0.98	0.97	0.96
	1050	37		3,934	106	1	0	1	4,232	114	1	0	1	0.97	0.95	0.92
	1500	54		5,383	100	1	0	2	5,653	105	1	0	2	0.93	0.90	0.88
	700	25	R5	2,806	112	2	0	1	3,065	123	2	0	1	0.98	0.97	0.96
	1050	37		4,125	111	3	0	1	4,422	120	3	0	1	0.97	0.95	0.92
	1500	54		5,551	103	3	0	1	5,844	108	3	0	1	0.93	0.90	0.88
20B	525	36	R2	4,328	120	1	0	2	4,638	129	1	0	2	0.98	0.97	0.96
	700	48		5,652	118	1	0	2	5,956	124	1	0	2	0.98	0.96	0.95
	1050	71		7,948	112	2	0	2	8,506	120	2	0	2	0.97	0.95	0.92
	1300	87		9,157	105	2	0	3	9,922	114	2	0	3	0.93	0.90	0.88
	1500	99		10,288	104	2	0	3	11,038	111	2	0	3	0.93	0.90	0.88
	525	36		R3	4,436	123	1	0	1	4,704	131	1	0	1	0.98	0.97
	700	48	5,705		119	1	0	1	6,114	127	1	0	2	0.98	0.96	0.95
	1050	71	8,080		114	2	0	2	8,606	121	2	0	2	0.97	0.95	0.92
	1300	87	9,442		109	2	0	2	10,065	116	2	0	2	0.93	0.90	0.88
	1500	99	10,503		106	2	0	2	11,181	113	2	0	2	0.93	0.90	0.88
	525	36	R4		4,459	124	1	0	2	4,676	130	1	0	2	0.98	0.97
	700	48		5,766	120	1	0	2	6,022	125	1	0	2	0.98	0.96	0.95
	1050	71		8,101	114	2	0	2	8,569	121	2	0	2	0.97	0.95	0.92
	1300	87		9,321	107	2	0	2	10,053	116	2	0	2	0.93	0.90	0.88
	1500	99		10,426	105	2	0	2	11,160	113	2	0	3	0.93	0.90	0.88
	525	36		R5	4,540	126	3	0	1	4,869	135	3	0	1	0.98	0.97
	700	48	5,832		122	3	0	1	6,287	131	3	0	1	0.98	0.96	0.95
	1050	71	8,241		116	3	0	2	8,880	125	3	0	2	0.97	0.95	0.92
	1300	87	9,597		110	3	0	2	10,397	120	4	0	2	0.93	0.90	0.88
	1500	99	10,647		108	4	0	2	11,593	117	4	0	2	0.93	0.90	0.88
	700	70	R2		8,406	120	2	0	2	9,174	131	2	0	3	0.98	0.97
	850	83		9,897	119	2	0	3	10,457	126	2	0	3	0.97	0.95	0.92
	1050	105		11,806	112	2	0	3	12,414	118	2	0	3	0.97	0.95	0.92
	1300	126		13,675	109	3	0	3	14,964	119	3	0	3	0.93	0.90	0.88
1500	145	15,090		104	3	0	3	16,251	112	3	0	3	0.93	0.90	0.88	
700	70	R3		8,539	122	2	0	2	8,893	127	2	0	2	0.98	0.97	0.96
850	83		10,056	121	2	0	2	10,825	130	2	0	2	0.97	0.95	0.92	
1050	105		11,936	114	2	0	2	12,748	121	2	0	2	0.97	0.95	0.92	
1300	126		13,893	110	3	0	3	14,850	118	3	0	3	0.93	0.90	0.88	
1500	145		15,381	106	3	0	3	16,193	112	3	0	3	0.93	0.90	0.88	
700	70		R4	8,335	119	2	0	2	8,971	128	2	0	2	0.98	0.97	0.96
850	83	9,877		119	2	0	2	10,589	128	2	0	2	0.97	0.95	0.92	
1050	105	11,943		114	2	0	3	12,782	122	2	0	3	0.97	0.95	0.92	
1300	126	13,681		109	2	0	3	14,889	118	3	0	3	0.93	0.90	0.88	
1500	145	14,952		103	3	0	3	16,463	114	3	0	3	0.93	0.90	0.88	
700	70	R5		8,893	127	3	0	2	9,329	133	3	0	2	0.98	0.97	0.96
850	83		10,469	126	4	0	2	11,209	135	4	0	2	0.97	0.95	0.92	
1050	105		12,382	118	4	0	2	13,296	127	4	0	2	0.97	0.95	0.92	
1300	126		14,453	115	4	0	2	15,254	121	4	0	2	0.93	0.90	0.88	
1500	145		15,853	109	4	0	2	16,871	116	4	0	2	0.93	0.90	0.88	

Note: Individual fixture performance may vary.

ATB0 LLD Multiplier	15°C	20°C	25°C	30°C	35°C	40°C
	1.02	1.01	1	0.98	0.97	0.95

To calculate the LLD for a temperature other than 25°C, multiply the LLD @ 25°C (shown in the performance package table) by the LLD multiplier for the selected temperature.



AEL Headquarters, 3825 Columbus Road, Granville, OH 43023  
 www.americanelectricalighting.com  
 © 2014-2019 Acuity Brands Lighting, Inc. All Rights Reserved. ATB0 02/21/19

Warranty Five-year limited warranty. Complete warranty terms located at: [www.acuitybrands.com/resources/terms-and-conditions](http://www.acuitybrands.com/resources/terms-and-conditions)  
 Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications subject to change without notice.




Please contact your sales representative for the latest product information.

# Autobahn Series ATB0

## Roadway Lighting

### UMR POLE ADAPTOR

RECOMMENDED FOR USE WITH POLES OF 4" DIAMETER OR SMALLER



### UMS POLE ADAPTOR



AEL Headquarters, 3825 Columbus Road, Granville, OH 43023  
www.americanelectriclighting.com  
© 2014-2019 Acuity Brands Lighting, Inc. All Rights Reserved. ATB0 02/21/19

**Warranty** Five-year limited warranty. Complete warranty terms located at:  
[www.acuitybrands.com/resources/terms-and-conditions](http://www.acuitybrands.com/resources/terms-and-conditions)  
Actual performance may differ as a result of end-user environment and application.  
All values are design or typical values, measured under laboratory conditions at 25 °C.  
Specifications subject to change without notice.

**Please contact your sales representative for the latest product information.**

Catalog Number		<b>Tunnel Interior Lighting</b>	
Notes		Type	

## TNLED2

TunnelPass LED™ Large



### Mechanical

- Low copper content diecast aluminum A360 alloy electrical and optical housing. Diecast aluminum housing has integral heat sink fins to optimize thermal management through conductive and convection cooling.
- Stainless steel bolted or latched door closure disengages top electrical cover for easy access to LED drivers, surge protection, luminaire disconnect, and terminal block.
- Super durable TGIC thermoset powder coat finish over anodized aluminum pre-finish. Rigorous pre-treating and paint process yields over 5,000 hours salt fog rating per ASTM B117.
- Luminaire mounting brackets are of 316 grade stainless steel.
- Luminaire is IP66 rated.
- Luminaire is 3G vibration rated per ANCI C136.31.
- Luminaire is suitable for continuous row mounting as standard, with through wire raceway available as an option.
- Luminaire and through wire raceway box each have three removable brass 3/4-14NPT entries to facilitate wiring.

### Electrical

- Quick disconnect connectors for ease of installation and maintenance.
- Extreme surge protection meets 20KV/10KA per ANSI/IEEEC62.41 and is fail off.
- Three pole terminal block is standard for ease of installation.
- LED drivers meets maximum total harmonic distortion (THD) of 20% and are ROHS compliant. Minimum operating temperature is -40C. Electronic driver has an estimated minimum life of 100,000 hours at 25C.

### Optical

- PCB mounted LED technology comprised of multi-cluster LED's on a single metal core board.
- Color temperature options of 3000K, 4000K, and 5000K with CRI of 70 minimum.
- Segmented Miro 4 internal reflectors are designed for superior optical control in Counterbeam, Crossbeam, Long and Narrow.
- Borosilicate glass retractor ensures longevity and minimizes dirt depreciation and minimizes direct view of LED's, reducing glare.

### Controls

- Field Adjustable Output (AO) module - Onboard device that adjusts the light output and input wattage to meet site specific requirements. The AO module is preset at the factory to position number 8 (see chart).
- ICMNYX - Nyx Hemera internally mounted control module communicates with Nyx Hemera powerline control systems (consult factory).

### Testing/Compliance

Luminaire conforms to the following standards:

- ANSI/IEEE C62.41:2002 - Surge protection
- ANSI C82.77:2002 - Harmonic distortion limits
- ANSI C136.31 - Luminaire vibration
- ASTM B117 - Salt Spray
- FCC Title 47 CFR Part 15 - FCC EMC/EMI
- IEC 60068 - Environmental testing
- ANSI C136.27-17 - Environmental Testing (including Parsons test)
- IEC 60529 - Ingress Protection (IP)
- IEC 61000 - Electromagnetic Compatibility testing (EMC)
- IEEE 519 - Harmonic Control in Electrical Power systems
- UL 1598 - Wet Location Safety Listing
- UL 1598A - Marine Outside
- PK1-PK4 Suitable for ambient temperatures -40C to 50C
- PK5 Suitable -40C to 45C ambient
- PK6 Suitable -40C to 40C ambient
- TW Option suitable -40C to 40C ambient

### Manufacturing

- Manufactured in Crawfordsville, Indiana, ARRA compliant
- 100% electrical testing on all luminaires before shipment
- No less than five (5) years experience in manufacturing LED based products

### Warranty

5-year limited warranty. Complete warranty terms located at: [www.acuitybrands.com/resources/terms-and-conditions](http://www.acuitybrands.com/resources/terms-and-conditions)


**Note:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.



Weight = 58 lbs.  
IAH Voltage Option = 65 lbs.



**ORDERING INFORMATION**

**Example:** TNLED2 PK4 AS 40K CCB DGRA L TW AWB35 ICMNYX

Series	Lumen Package	Voltage	Color Temperature	Optics	Color	Door Closure
TNLED2 TunnelPass LED™ Large	PK1 25,700	AS Auto-Sensing Voltage (120V-277V)	30K 3,000 K CCT +/- 175	CCB Ceiling Mount Counterbeam	A As Specified	L Latched
	PK2 31,200	AH Auto-Sensing Voltage (347V-480V)	40K 4,000 K CCT +/- 275	CLN Ceiling Mount Long and Narrow	DBKA Black	S Bolted Assembly
	PK3 37,700		50K 5,000 K CCT +/- 283	WCR Wall Mount Crossbeam	DBZA Bronze	
	PK4 41,200	IAH Voltage 120V-277V (provides protection when connected to circuits supplied by 277V derived from 480V-WYE)			DGRA Gray	
	PK5 51,300				DWHA White	
	PK6 57,300				DGHA Graphite	

Options:					
BM	Box Mount	AWB00	Adjustable Wall Bracket Factory Set to 0 Degree Tilt	AO	Field adjustable output
F1	Single Fusing	AWB05	Adjustable Wall Bracket Factory Set to 5 Degree Tilt	ICMNYX	Nyx Hemera Internal Control Module, Consult Factory
F2	Double Fusing	AWB10	Adjustable Wall Bracket Factory Set to 10 Degree Tilt	DALI	DALI Driver Option, Consult Factory
TW	Through Wire	AWB15	Adjustable Wall Bracket Factory Set to 15 Degree Tilt		
		AWB20	Adjustable Wall Bracket Factory Set to 20 Degree Tilt		
		AWB25	Adjustable Wall Bracket Factory Set to 25 Degree Tilt		
		AWB30	Adjustable Wall Bracket Factory Set to 30 Degree Tilt		
		AWB35	Adjustable Wall Bracket Factory Set to 35 Degree Tilt		
		AWB40	Adjustable Wall Bracket Factory Set to 40 Degree Tilt		
		AWB45	Adjustable Wall Bracket Factory Set to 45 Degree Tilt		

**OPTIONS MATRIX** (continued next page)

Parameters		Perf Package	Optics			Color						Door Closure		Options			
		PK1-PK6	CCB	CLN	WCR	A	DBKA	DBZA	DGRA	DWHA	DGHA	L	S	BM	TW	F1	F2
LED Performance Package	PK1-PK6		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Voltage	AS	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	AH	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	IAH	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Color Temperature	30K	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	40K	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	50K	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Optics	CCB	Y		N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	CLN	Y	N		N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	WCR	Y	N	N		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Color	A	Y	Y	Y	Y		N	N	N	N	N	Y	Y	Y	Y	Y	Y
	DBKA	Y	Y	Y	Y	N		N	N	N	N	Y	Y	Y	Y	Y	Y
	DBZA	Y	Y	Y	Y	N	N		N	N	N	Y	Y	Y	Y	Y	Y
	DGRA	Y	Y	Y	Y	N	N	N		N	N	Y	Y	Y	Y	Y	Y
	DWHA	Y	Y	Y	Y	N	N	N	N		N	Y	Y	Y	Y	Y	Y
	DGHA	Y	Y	Y	Y	N	N	N	N	N		Y	Y	Y	Y	Y	Y
Door Closure	L	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y		N	Y	Y	Y	Y
	S	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N		Y	Y	Y	Y
Options	BM	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y			N	Y	Y
	TW	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N		Y	Y
	F1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y			Y
	F2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
Angle Wall Bracket	AWB00	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB05	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB10	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB15	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB20	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB25	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB30	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB35	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB40	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
	AWB45	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
Other Options	AO	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	ICMNYX	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	DALI	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

Notes  
IAH is not available in combination with ICMNYX on PK6.  
ICMNYX is available (without IAH) for all performance packages.

Y= Valid Option Combination  
N = Combination Not available

**OPTIONS MATRIX** (continued from previous page)

Parameters		Angle Wall Bracket										Other Options		
		AWB00	AWB05	AWB10	AWB15	AWB20	AWB25	AWB30	AWB35	AWB40	AWB45	AO	ICMNYX	DALI
LED Performance Package	PK1-PK6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Voltage	AS	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	AH	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	IAH	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Color Temperature	30K	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	40K	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	50K	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Optics	CCB	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	CLN	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	WCR	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Color	A	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	DBKA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	DBZA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	DGRA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	DWHA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	DGHA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Door Closure	L	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	S	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Options	BM	N	N	N	N	N	N	N	N	N	N	Y	Y	Y
	TW	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	F1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	F2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Angle Wall Bracket	AWB00		N	N	N	N	N	N	N	N	N	Y	Y	Y
	AWB05	N		N	N	N	N	N	N	N	N	Y	Y	Y
	AWB10	N	N		N	N	N	N	N	N	N	Y	Y	Y
	AWB15	N	N	N		N	N	N	N	N	N	Y	Y	Y
	AWB20	N	N	N	N		N	N	N	N	N	Y	Y	Y
	AWB25	N	N	N	N	N		N	N	N	N	Y	Y	Y
	AWB30	N	N	N	N	N	N		N	N	N	Y	Y	Y
	AWB35	N	N	N	N	N	N	N		N	N	Y	Y	Y
	AWB40	N	N	N	N	N	N	N	N		N	Y	Y	Y
	AWB45	N	N	N	N	N	N	N	N	N		Y	Y	Y
Other Options	AO	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y		N	N
	ICMNYX	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N		N
	DALI	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	

Notes  
IAH is not available in combination with ICMNYX on PK6.  
ICMNYX is available (without IAH) for all performance packages.

Y= Valid Option Combination  
N = Combination Not available

**PERFORMANCE DATA**

TNLEDMED	Input Watts	Distribution	3000K		4000K		5000K	
			Lumens	LPW	Lumens	LPW	Lumens	LPW
PK1	212	CCB	25,116	119	25,836	122	26,156	124
		CLN	25,479	120	26,209	124	26,534	125
		WCR	24,378	115	25,077	119	25,387	120
PK2	262	CCB	30,532	117	31,407	120	31,796	122
		CLN	30,973	118	31,860	122	32,255	123
		WCR	29,634	113	30,484	117	30,861	118
PK3	321	CCB	36,907	115	37,965	118	38,435	120
		CLN	37,440	117	38,513	120	38,990	122
		WCR	35,823	112	36,849	115	37,306	116
PK4	345	CCB	40,625	118	41,789	121	42,307	123
		CLN	41,211	120	42,392	123	42,917	125
		WCR	39,432	114	40,562	118	41,064	119
PK5	435	CCB	50,165	115	51,603	119	52,242	120
		CLN	50,889	117	52,348	120	52,996	122
		WCR	48,692	112	50,087	115	50,708	117
PK6	495	CCB	56,009	113	57,614	117	58,327	118
		CLN	56,817	115	58,445	118	59,169	120
		WCR	54,363	110	55,922	113	56,614	114

Package	Driver Output mA	Luminaire Input Operating Amps					
	mA	120V	208V	240V	277V	347V	480V
PK1	500	1.8	1.0	0.9	0.8	0.6	0.5
PK2	625	2.2	1.3	1.1	1.0	0.8	0.6
PK3	770	2.7	1.5	1.4	1.2	1.0	0.7
PK4	550	2.9	1.7	1.4	1.3	1.0	0.7
PK5	700	3.7	2.1	1.8	1.6	1.3	0.9
PK6	800	4.2	2.4	2.1	1.8	1.5	1.1

**LAT TABLE**

Package	LAT										
	0C	5C	10C	15C	20C	25C	30C	35C	40C	45C	50C
PK1	1.022	1.018	1.014	1.010	1.005	1.000	0.995	0.989	0.983	0.976	0.970
PK2	1.024	1.020	1.015	1.011	1.005	1.000	0.994	0.988	0.982	0.975	0.968
PK3	1.026	1.021	1.017	1.011	1.006	1.000	0.994	0.987	0.980	0.973	0.966
PK4	1.026	1.022	1.017	1.012	1.006	1.000	0.994	0.987	0.980	0.973	0.965
PK5	1.030	1.024	1.019	1.013	1.007	1.000	0.993	0.986	0.978	0.970	
PK6	1.032	1.026	1.020	1.014	1.007	1.000	0.993	0.985	0.977		

PK1-PK4 suitable for use -40C to 50C.  
 PK5 suitable for use -40C to 45C ambient.  
 PK6 suitable for use -40C to 40C ambient.  
 TW option suitable for use -40C to 40C ambient.

**LLD TABLE**


	PK1	PK2	PK3	PK4	PK5	PK6
25,000 hours	97.5%	97.5%	96.5%	97.4%	97.0%	95.6%
50,000 hours	97.1%	97.1%	94.6%	96.7%	96.0%	93.1%
75,000 hours	96.7%	96.6%	92.8%	96.0%	95.0%	90.8%
100,000 hours	96.2%	96.1%	91.0%	95.3%	94.0%	88.4%

**AO OPTION SETTINGS**


AS / IAH / AH : PK1-thru-PK6		
AO setting	Lumens %	Wattage %
8	100%	100%
7	94%	94%
6	83%	81%
5	71%	68%
4	59%	55%
3	46%	43%
2	34%	31%
1	21%	18%




**CCB: Ceiling mount counterbeam**




Recommended for divided tunnels where majority of lumens are directed towards oncoming drivers to maximize roadway luminance while controlling disability glare.




**CLN: Ceiling mount counterbeam**



Recommended for undivided tunnels where equal lumens are with and against traffic flow.



**WCR: Wall mount crossbeam**




Recommended for undivided tunnels where equal lumens are with and against traffic flow.




# TNLED2

TunnelPass LED™ Large


## SURFACE MOUNTING DETAILS



## BOX MOUNTING DETAILS



## ADJUSTABLE WALL BRACKET MOUNTING DETAILS



Catalog Number	Tunnel Interior Lighting	
Notes		Type

# TNLEDMED

TunnelPass LED™ Medium



### Mechanical

- Low copper content diecast aluminum A360 alloy electrical and optical housing. Diecast aluminum housing has integral heat sink fins to optimize thermal management through conductive and convection cooling.
- Stainless steel bolted or latched door closure disengages top electrical cover for easy access to LED drivers, surge protection, luminaire disconnect, and terminal block.
- Super durable TGIC thermoset powder coat finish over anodized aluminum pre-finish. Rigorous pre-treating and paint process yields over 5,000 hours salt fog rating per ASTM B117.
- Luminaire mounting brackets are of 316 grade stainless steel.
- Luminaire is IP66 rated.
- Luminaire is 3G vibration rated per ANCI C136.31.
- Luminaire is suitable for continuous row mounting as standard, with through wire raceway available as an option.
- Luminaire and through wire raceway box each have three removable brass 3/4-14NPT entries to facilitate wiring.

### Electrical

- Quick disconnect connectors for ease of installation and maintenance.
- Extreme surge protection meets 20KV/10KA per ANSI/IEEE C62.41 and is fail off.
- Three pole terminal block is standard for ease of installation.
- LED drivers meets maximum total harmonic distortion (THD) of 20% and are ROHS compliant. Minimum operating temperature is -40C. Electronic driver has an estimated minimum life of 100,000 hours at 25C.

### Optical

- PCB mounted LED technology comprised of multi-cluster LED's on a single metal core board.
- Color temperature options of 3000K, 4000K, and 5000K with CRI of 70 minimum.
- Segmented Miro 4 internal reflectors are designed for superior optical control in Counterbeam, Crossbeam, Long and Narrow, and Underpass optics.
- Borosilicate glass retractor ensures longevity and minimizes dirt depreciation and minimizes direct view of LED's, reducing glare.

### Controls

- Field Adjustable Output (AO) module - Onboard device that adjusts the light output and input wattage to meet site specific requirements. The AO module is preset at the factory to position number 8 (see chart).
- ICMNYX - Nyx Hemera internally mounted control module communicates with Nyx Hemera powerline control systems, MVOLT only (consult factory).
- ICMECH - Echelon internally mounted control module that communicates with Echelon powerline control systems, MVOLT only (consult factory).

### Testing/Compliance

Luminaire conforms to the following standards:

- ANSI/IEEE C62.41:2002 - Surge protection
- ANSI C82.77:2002 - Harmonic distortion limits
- ANSI C136.31 - Luminaire vibration
- ASTM B117 - Salt Spray
- FCC Title 47 CFR Part 15 - FCC EMC/EMI
- IEC 60068 - Environmental testing
- ANSI C136.27-17 - Environmental Testing (including Parsons test)
- IEC 60529 - Ingress Protection (IP)
- IEC 61000 - Electromagnetic Compatibility testing (EMC)
- IEEE 519 - Harmonic Control in Electrical Power systems
- UL 1598 - Wet Location Safety Listing
- UL 1598A - Marine Outside
- Suitable for ambient temperatures -40C to 40C

### Manufacturing

- Manufactured in Crawfordsville, Indiana, ARRA compliant
- 100% electrical testing on all luminaires before shipment
- No less than five (5) years experience in manufacturing LED based products

### Warranty

5-year limited warranty. Complete warranty terms located at: [www.acuitybrands.com/CustomerResources/Terms\\_and\\_Conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_Conditions.aspx).

**Note:** Actual performance may differ as a result of end-user environment and application.


All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.



Max Weight = 43 lbs (19.5 kg)

Max EPA = 3.2 ft² (.30 m²)



**ORDERING INFORMATION**

**Example:** TNLEDMEDPK840KMVOLTCCBDGRAL

Series	Lumen Package	Color Temperature	Voltage	Optics	Color	Door Closure
TNLEDMED TunnelPass LED™ Medium	PK1 6,000	30K 3,000 K CCT +/- 250K	MVOLT Auto-Sensing Voltage (120V-277V)	CCB Ceiling Mount Counterbeam	A As Specified	L Latched
	PK2 9,500	40K 4,000 K CCT +/- 250K	HVOLT Auto-Sensing Voltage (347V-480V)	CLN Ceiling Mount Long and Narrow	DBKA Black	S Bolted Assembly
	PK3 12,000	50K 5,000 K CCT +/- 250K		WCR Wall Mount Crossbeam	DBZA Bronze	
	PK4 15,000		UDP Wall Mount Underpass	DGRA Gray		
	PK5 18,000			DWHA White		
	PK6 21,000			DGHA Graphite		
	PK7 24,000					
	PK8 30,000					
	PK9 36,000					

Options:					
BM	Box Mount	AWB0	Adjustable Wall Bracket Factory Set to 0 Degree Tilt	ICMNYX	Nyx Hemera Internal Control Module, Consult Factory
F1	Single Fusing	AWB5	Adjustable Wall Bracket Factory Set to 5 Degree Tilt	ICMECH	Echelon Internal Control Module, Consult Factory
F2	Double Fusing	AWB10	Adjustable Wall Bracket Factory Set to 10 Degree Tilt	DALI	DALI Driver Option, Consult Factory
TW	Through Wire Box Top Mount	AWB15	Adjustable Wall Bracket Factory Set to 15 Degree Tilt		
A0	Field Adjustable Module	AWB20	Adjustable Wall Bracket Factory Set to 20 Degree Tilt		
		AWB25	Adjustable Wall Bracket Factory Set to 25 Degree Tilt		

**OPTIONS MATRIX**

Parameters	Optic				Door Closure		Options					Wall Brackets					Controls				
	CCB	CLN	WCR	UDP	L	S	BM	F1	F2	TW	AO	AWB0	AWB5	AWB10	AWB15	AWB20	AWB25	ICMNYX	ICMECH	DALI	
Lumen Package	PK1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	PK2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	PK3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	PK4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N
	PK5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N
	PK6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N
	PK7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
	PK8	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
	PK9 (*1)	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
Voltage	MVOLT	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	HVOLT	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y	
Optic	CCB		N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	CLN	N		N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	WCR	N	N		N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	UDP	N	N	N		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Door Closure	L	Y	Y	Y	Y		N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	S	Y	Y	Y	Y	N		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
Options	BM	Y	Y	Y	Y	Y	Y		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	F1	Y	Y	Y	Y	Y	Y	Y		N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	F2	Y	Y	Y	Y	Y	Y	Y	N		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	
	TW	Y	Y	Y	Y	Y	Y	Y	Y	Y		Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	AO	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y		Y	Y	Y	Y	Y	Y	N	N	N
Wall Brackets	AWB0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y		N	N	N	N	N	Y	Y	Y	
	AWB5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N		N	N	N	N	Y	Y	Y	
	AWB10	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N		N	N	N	Y	Y	Y	
	AWB15	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N		N	N	Y	Y	Y	
	AWB20	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	N		N	Y	Y	Y	
AWB25	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N		Y	Y	Y	Y	
Controls (Consult Factory)	ICMNYX	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y		N	Y	
	ICMECH	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	N		Y	
	DALI	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y		Y

Notes

\*1 PK9 has non-illuminated fail-off 20kV/10kA surge (fail off mode). PK1-thru-PK8 have 20kV/10kA fail off mode surge with indicator light.

Y = Valid Option Combination

N = Combination Not available

**PERFORMANCE DATA**

TNLEDMED	Input Watts	Distribution	3000K		4000K		5000K	
			Lumens	LPW	Lumens	LPW	Lumens	LPW
PK1	57	CCB	6,782	119	7,343	129	7,343	129
		CLN	6,333	111	6,858	120	6,858	120
		WCR	6,485	114	7,022	123	7,022	123
		UDP	6,277	110	6,797	119	6,797	119
PK2	70	CCB	9,168	131	9,928	142	9,928	142
		CLN	8,562	122	9,271	132	9,271	132
		WCR	8,767	125	9,493	136	9,493	136
		UDP	8,486	121	9,189	131	9,189	131
PK3	102	CCB	12,592	123	13,634	134	13,634	134
		CLN	11,759	115	12,733	125	12,733	125
		WCR	12,040	118	13,037	128	13,037	128
		UDP	11,655	114	12,620	124	12,620	124
PK4	125	CCB	14,897	119	16,130	129	16,130	129
		CLN	13,911	111	15,063	121	15,063	121
		WCR	14,244	114	15,424	123	15,424	123
		UDP	13,788	110	14,930	119	14,930	119
PK5	151	CCB	17,601	117	19,059	126	19,059	126
		CLN	16,437	109	17,799	118	17,799	118
		WCR	16,831	111	18,224	121	18,224	121
		UDP	16,292	108	17,641	117	17,641	117
PK6	182	CCB	19,551	107	21,170	116	21,170	116
		CLN	18,258	100	19,770	109	19,770	109
		WCR	18,695	103	20,243	111	20,243	111
		UDP	18,097	99	19,595	108	19,595	108
PK7	203	CCB	25,497	126	27,608	136	27,608	136
		CLN	23,866	118	25,842	127	25,842	127
		WCR	24,176	119	26,178	129	26,178	129
		UDP	22,935	113	24,834	122	24,834	122
PK8	246	CCB	29,801	121	32,268	131	32,268	131
		CLN	27,895	113	30,204	123	30,204	123
		WCR	28,257	115	30,597	124	30,597	124
		UDP	26,806	109	29,026	118	29,026	118
PK9	323	CCB	34,026	105	36,843	114	36,843	114
		CLN	31,849	99	34,486	107	34,486	107
		WCR	32,263	100	34,935	108	34,935	108
		UDP	30,607	95	33,141	103	33,141	103

Package	Driver Output mA	Luminaire Input Operating Amps					
	mA	120V	208V	240V	277V	347V	480V
PK1	330	0.295	0.289	0.253	0.226	0.174	0.138
PK2	420	0.586	0.349	0.302	0.267	0.207	0.159
PK3	600	0.849	0.494	0.429	0.367	0.299	0.216
PK4	730	1.042	0.617	0.534	0.465	0.388	0.299
PK5	880	1.255	0.739	0.64	0.548	0.452	0.345
PK6	1050	1.513	0.881	0.764	0.647	0.534	0.402
PK7	600	1.693	1.007	0.872	0.763	0.623	0.486
PK8	730	2.049	1.213	1.051	0.914	0.763	0.589
PK9	960	2.76	1.64	1.43	1.2	0.75	0.73

**LAT TABLE**

LAT										
0C	5C	10C	15C	20C	25C	30C	35C	40C	45C	50C
1.04	1.04	1.03	1.02	1.01	1.00	0.99	0.98	0.97	0.96	0.95

**LLD TABLE**

L70	PK1	PK2	PK3	PK4	PK5	PK6	PK7	PK8	PK9
25,000 hours		0.958			0.947		0.947	0.933	0.938
50,000 hours		0.919			0.898		0.899	0.892	0.881
75,000 hours		0.882			0.852		0.853	0.843	0.828
100,000 hours		0.847			0.809		0.810	0.797	0.777


**AO OPTION SETTINGS**

PK1			PK2			PK3-PK7			PK8			PK9		
Setting	Lumens	Wattage	Setting	Lumens	Wattage	Setting	Lumens	Wattage	Setting	Lumens	Wattage	Setting	Lumens	Wattage
8	100%	100%	8	100%	100%	8	100%	100%	8	100%	100%	8	100%	100%
7	100%	100%	7	100%	100%	7	100%	100%	7	100%	100%	7	100%	99%
6	100%	100%	6	98%	97%	6	99%	99%	6	100%	100%	6	100%	99%
5	100%	88%	5	87%	85%	5	86%	86%	5	94%	90%	5	91%	87%
4	88%	76%	4	75%	72%	4	73%	73%	4	82%	77%	4	80%	74%
3	65%	65%	3	64%	60%	3	61%	61%	3	70%	65%	3	66%	60%
2	53%	54%	2	53%	47%	2	47%	47%	2	58%	52%	2	53%	46%
1	40%	43%	1	42%	35%	1	36%	36%	1	45%	40%	1	39%	34%


**Notes**

1 MVOLT Values shown - Consult Factory for HVOLT Values.


**CCB: Ceiling mount counterbeam**




Recommended for divided tunnels where majority of lumens are directed towards oncoming drivers to maximize roadway luminance while controlling disability glare.




**CLN: Ceiling mount counterbeam**



Recommended for undivided tunnels where equal lumens are with and against traffic flow.




**UDP: Wall mount underpass**



Recommended for underpass applications where illuminance is required IES type 4 distribution.



**WCR: Wall mount crossbeam**







Recommended for undivided tunnels where equal lumens are with and against traffic flow.











**SURFACE MOUNTING DETAILS**





**BOX MOUNTING DETAILS**



**THROUGH WIRE BOX TOP MOUNTING DETAILS**



**ADJUSTABLE WALL BRACKET MOUNTING DETAILS**



# Sample Lighting Control System Cutsheets




109, St-Vallier Est, suite 100, Québec, Qc, Canada, G1K 3N9  
tel.: 418 977 7788 [www.nyx-hemera.com](http://www.nyx-hemera.com)



**Project: GENERAL SYSTEM ARCHITECTURE  
TLACS-EM**

**Client: NYX HEMERA TECHNOLOGIES**

**Drawing: 0018-D05-20000**



- NOTE:
1. SSSD - SAFE SIGHT STOPPING DISTANCE AS PER REF: ANSI/IES RP-22-11 AND CIE 88:2004.
  2. ENCLOSURE TYPE : SS316 OR PAINTED STEEL
  3. GATEWAY CONNECTION : ETHERNET; FIBER OPTIC SINGLE MODE; FIBER OPTIC MULTIMODE OR RS-485.
  4. EXTERNAL NETWORK CONNECTION: ETHERNET, FIBER OPTIC SINGLE MODE OR MULTIMODE.
  5. CAN BE IN SAME ELECTRICAL ROOM WITH LCC OR IN OTHER ADJOINING ROOM.
  6. THE LPC CAN BE IN A JUNCTION BOX(MAX.6 LPC PAR JUNCTION BOX) OR INTEGRATED WITHIN LUMINAIRES.

A	FOR INFORMATION	17/12/03	C.E.	G.D.	P.S.
REV	DESCRIPTION	DATE	BY	CHK	APP

GENERAL SYSTEM ARCHITECTURE TLACS - EM INDIVIDUAL CONTROL					
ANY DESIGNS, SKETCHES, MODELS OR SAMPLES SHALL REMAIN THE PROPERTY OF "NYX HEMERA TECHNOLOGIES INC." AND SHALL BE TREATED AS CONFIDENTIAL INFORMATION UNLESS "NYX HEMERA TECHNOLOGIES INC." HAS INDICATED IN WRITING THE USE OR DISCLOSURE OF SUCH DESIGNS, SKETCHES, MODELS AND SAMPLES, OR ANY DESIGN OR PRODUCTION TECHNIQUES REVEALED THEREBY					

DRAWN BY:	C. ENACHE	17/12/03
CHECKED BY:	G. DOGGER	17/12/03
APPROVED BY:	P. SAMSON	17/12/03
CLIENT: NYX HEMERA TECHNOLOGIES		
PROJECT No:	SCALE	DRAWING No:
0018	N/A	0018-D05-20500

**NYX HEMERA**  
Technologies Inc.

109, St-Vallier Est, suite 100, Québec, Qc, Canada, G1K 3N8  
tel.: 418 977 7788  
www.nyx-hemera.com

## TLACS' Gateway (GTW)

### General Description

The TLACS Gateway (GTW) provides a link between the LCC (Lighting Control Cabinet) and the LPC (Local Product Controller) inside the luminaires.

The GTW receives commands intended to the LPC 480 from the Lighting Control Cabinet (LCC) over either a RS-485, an Ethernet or a Fiber Optic link. It translates and transfer the command to the LPC 480 through the powerline grid.

For long distance communication, multiple GTWs can be installed in different electrical panels and connected to the LCC to reach all luminaires in the lighting circuitry. A maximum of 1000 luminaires can be connected to a Gateway.



## LCAM Tunnel Entrance Photometer

### General Description

The LCAM measures and communicates to the Lighting Control Cabinet (LCC) the level of luminance or brightness created by natural light at the tunnel entrance / exit. The tunnel light control system in turn adjust the tunnel luminaire light levels to ensure that the visual perception of drivers will be maintained, both day and night, by avoiding sudden variations in lighting levels and potential “black hole effect” when entering and exiting a tunnel.

The LCAM uses a specially designed, highly light-sensitive photocell, filtered to provide a spectral response close to the average human eye for optimal performance.

The light receptor measures the average luminance over a scalable range of 0 - 10,000 cd/m<sup>2</sup> within an acceptance angle subtending 20° as recommended by CIE 088:2044 and RP-22-11.

To ensure proper alignment of the photometer, an operator can request an image, and have it compared with a valid one taken at the installation time. An alarm can then be set up if the unit has moved and does not provide an effective reading.

### Features

- CIE and IES approved measurement technology
- Accurate measurement of tunnel entrance luminance
- Photometer alignment monitoring
- Variable viewing angle to compensate if cannot be installed at a Safe Stopping Sight Distance (SSSD) from the tunnel portal.
- Specifically designed for tunnels control system
- Rugged 316 Stainless Steel construction
- Simple installation/operation
- RS-485 communication for remote diagnostic and configuration



Specifications subject to change without notice – LCAM-DTS-EN-5.7 February 2019

## Technical Specifications

### Measurement Performance

Parameter	Units	Min	Max	Comment
<b>Detector</b>				Silicon photo diode, $\sqrt{\lambda}$ filtered
<b>Viewing Angle (FWHM)</b>	Deg	10	40	20° as standard; from 10 to 40° under request
<b>Measurement Range</b>	cd/m <sup>2</sup>	0	10,000	Range [1, 10.000] cd/m <sup>2</sup> scalable
<b>Resolution</b>	cd/m <sup>2</sup>		1	Display resolution
<b>Accuracy</b>	%			Under 3%
<b>Damping</b>	seconds	1	100	Default setting is 10s

### Power

<b>Input Voltage</b>	Vac	100	240	50/60Hz / 277/480 VAC under request
<b>Power Consumption</b>	W	6	10	Excluding washer
	W	48	52	With wiper/washer system (optional)

### Interface Options

<b>Serial Outputs</b>				ModBus RTU via RS485 (isolated) Ethernet (RJ-45) or Fiber Optic under request
<b>Analog Outputs (one)</b>	mA	0 / 2 / 4	20	Isolated and scalable (user selected)
<b>Digital Relay Contacts (four)</b>	A	0	1	@240Vac (signal levels and data valid)
<b>Network Controller Integration</b>				Internal diagnostic available when integrated with Nyx Hemera Network Controller. (Using RS485 Link)

### Physical

<b>Ingress Protection</b>			IP66	
<b>Operating Temperature</b>	°C	-40	+50	
<b>Storage Temperature</b>	°C	-40	+50	
<b>Operating Humidity</b>	%		100	Up to
<b>Regulatory Compliance</b>				2004/108/EC (Electromagnetic Radiation)/ 2006/95/EC (Low Voltage)
<b>Materials</b>				Stainless steel 316 (powder coated)
<b>Dimensions</b>	mm	463 x 162 x 122	463 x 162 x 184	Without optional wiper/washer option With optional wiper/washer option
<b>Weight</b>	kg		5.5 6.3	Without optional wiper/washer option With optional wiper/washer option
<b>Warranty</b>	Months	24		Return to base warranty. Extensions available

Specifications subject to change without notice – LCAM-DTS-EN-5.7 February 2019





## Lighting Control Cabinet – (LCC)

### General Description

The LCC is an integrated control cabinet specifically designed for tunnel lighting control. It supports multiple configurations allowing optimal solutions targeting a wide range of tunnels layouts.

The LCC can either be used in a TLACS-RDE configuration to control a group of luminaires, in a TLACS -EM configuration to individually control every luminaire or in hybrid configuration mainly supporting very long tunnels. It interfaces with Luminescence Photometer (LCAM) and the Illuminance Photometer (ILCAM).

As optional features, the LCC can include redundant Network Controller (NWC) components, a SCADA connection, a data logger to keep and historic of the operations and a 15 inches Industrial touch screen display for an easy control and operation of the lighting system through an intuitive Human Machine Interface.




Specification subject to change without notice –LCC-DV-DTS-001-EN-7.6 – May 2019



## Local Product Controller 480 (LPC 480)

The LPC 480 provides a two-way communication between luminaires and Lighting Control Cabinet (LCC) and is used to individually control and monitor luminaires. Specifically designed for 100-480 VAC tunnel installation, it can be embedded in a tunnel luminaire or installed in a junction box.

The LPC 480 is a component of Nyx Hemera's Tunnel Lighting Addressable Control System (TLACS). It communicates over power line (PL) using a proven and reliable protocol thus greatly reducing installation, deployment, and operating costs.



## Features

- Two-way powerline communication (without new wiring).
- Individually monitors and controls the luminaire with alarm reporting
- Voltage, Current, Power Factor, Power Consumption, Diagnostic and Luminaire Status reporting
- Luminaire burn hours monitoring
- LPC Internal Temperature monitoring
- Dynamic repeater function providing the optimum level of communication robustness
- Configurable fail-safe switching mode (On/Off)
- Dimming lighting stages optimisation
- Luminaire alternations support to average luminaire usage
- Control type DALI, 0-10V dimming and ON-OFF relay

Specifications subject to change without notice – LPC480-DTS-001-EN –2.7 May 2019



## Specifications


### Electrical

Item	Description
Nominal input voltage	100 to 480 VAC
Frequency	50/60 Hz
Consumption	Under 3W

### Luminaire Interface

Item	Description
Relay contact rated voltage	100 to 480 VAC
Relay contact rated current	Max 4 Amp at 100-347 VAC Max 2 Amp at 480 VAC
Relay contact form	SPST-NO
Analog interface	0-10V Dimming, maximum current: 10 mA
Digital interface	DALI

### Wiring Diagram



Specifications subject to change without notice – LPC480-DTS-001-EN –2.7 May 2019



## Environmental Conditions

Item	Description
<b>Operating temperature</b>	-40°C to 75°C
<b>Storage temperature</b>	-40°C to 85°C
<b>IP Rating</b>	IP 66
<b>Enclosure</b>	Fully potted electronics

## Standards

Item	Description
<b>Safety standards</b>	CSA 60950-1-07 Second Edition UL 60950-1, Second Edition – Certified to U.S. Standards CAN/CSA C22.2 No. 0-M91 (R2001) CAN/CSA C22.2 No. 60950-1-07, 2nd Ed. Am 2:2014 (MOD) ANSI/UL Std No. 60950-1-2014, 2nd Ed. IEC 60950-1:2005 IEC 60950-1:2005/AMD1:2009 IEC 60950-1:2005/AMD2/2013 UL 916
<b>EMC standard</b>	EN 55032 :2012/AC :2013 EN 61000-32 :2014 (Harmonics) EN 61000-3 No. -M-3 :2013 (Flicker and voltage fluctuation) FCC 47 CFR Part 15, Subpart B ICES-003 Issue 6 January 2016
<b>EMC immunity</b>	EN 55024:2010 EN 61000-4-2 (Electrostatic discharge) EN 61000-4-3 (Radiated, radio-frequency, electromagnetic field) EN 61000-4-4 (Electrical fast transient/burst) EN 61000-4-5 (Surge) EN 61000-4-6 (Conducted disturbances) EN 61000-4-11 (Voltage dips, short interruptions and voltage variations)

Specifications subject to change without notice – LPC480-DTS-001-EN –2.7 May 2019



# Appendix G

## Opinion of Probable Cost

This page intentionally left blank.

Item Description	Opinion of Probable Cost
<b>Fire Detection</b>	<b>\$400,000</b>
Fire Alarm System	\$400,000
<b>Fire Protection</b>	<b>\$720,000</b>
Dry Standpipe System 3000 lf @ \$100.00/LF	\$300,000
Fire Extinguishers and Cabinets 16 @ \$5000.00 each	\$80,000
Fire Department Connections (FDC)	\$250,930
Mounting Standpipes	\$84,000
<b>Ventilation - Central Shaft for CO</b>	<b>\$3,330,000</b>
New Center Shaft Louvres and Ducts	\$350,000
Center Shaft Fans (Axial)	\$300,000
Structural Rehabilitation to Ventilation Building	\$100,000
Mounting New Ventilation fans to top of shafts	\$50,000
Sealing cracks in existing tunnel ventilation shafts	\$2,500,000
Electrical and Lighting to Ventilation Building	\$30,000
<b>Ventilation - Jet Fans for Fire Protection</b>	<b>\$1,260,000</b>
Longitudinal Jet Fans	\$1,140,000
Mounting Longitudinal Jet Fans	\$120,000
<b>Structural Improvements</b>	<b>\$500,000</b>
New Egress Pathway	\$500,000
Protection of Existing Structural Liner	Not Included
<b>Traffic Control</b>	<b>\$540,000</b>
Sign Support Foundation (assumes 4 @ \$50,000)	\$200,000
Sign Support Structure (assumes 2 @ \$120,000)	\$240,000
Lane Use Control Sign (assumes 8 @ \$1,000)	\$8,000
Trenching & Backfilling - 2000 LF @ \$45.00/LF	\$90,000
Local Incident Management System	Not Included
Variable Message Signs Inside Tunnel	Not Included
Two-Way Emergency Radio System	Not Included
<b>Egress Signage</b>	<b>\$220,000</b>
<b>Electrical Systems - Distribution and Lighting</b>	<b>\$4,430,000</b>
2" RMC - 15,600 LF @ \$35.00/ LF	\$546,000
Wires within Conduit (assume 4 required)	\$300,000
Removal of Existing Luminaires @ \$625 each	\$195,000
Removal of Existing Conduit	\$30,000
Lighting System (Surface Mounted LED Luminaries, Emergency Egress and Pathway Lighting)	\$1,291,800
Mounting 2" RMC to Tunnel Walls	\$150,000
Mounting Tunnel Luminaires	\$130,000
Lighting Control System	\$235,200
New Power Distribution Electrical Building (all inclusive)	\$350,000
Emergency Generator - 750kW, Diesel	\$700,000
Electrical Control Communication System	\$500,000
<b>Identified Work SUBTOTAL</b>	<b>\$11,400,000</b>
<b>Minor Items (20%)</b>	<b>\$2,280,000</b>
<b>Identified Work + Minor Items Subtotal</b>	<b>\$13,680,000</b>
<b>Estimated as a % of Contract Work:</b>	
Clearing and Grubbing (0.5%)	\$79,075
Construction Staking (0.5%)	\$79,075
MP&T (6%)	\$948,902
Mobilization (6.5%)	\$1,027,977
<b>CONTRACT WORK</b>	<b>\$15,815,029</b>
<b>Contingency (20%)</b>	<b>\$3,163,006</b>
<b>ESTIMATED CONSTRUCTION COST BASE YEAR (2019)</b>	<b>\$18,978,035</b>
<b>Inflation (3.5% for 1.75 years)</b>	<b>\$1,162,405</b>
<b>ESTIMATED CONSTRUCTION COSTS WITH INFLATION</b>	<b>\$20,150,000</b>

TOTAL PROJECT COSTS	
Preliminary Design	\$450,000
Final Design	\$1,250,000
<b>ESTIMATED CONSTRUCTION COSTS WITH INFLATION</b>	<b>\$20,150,000</b>
<b>INCIDENTALS (20% of Contract Items)</b>	<b>\$3,163,006</b>
<b>TOTAL PROJECT COSTS</b>	<b>\$25,020,000</b>

## Appendix H

# FHWA Specifications for the National Tunnel Inventory



This page intentionally left blank.



# Specifications for the National Tunnel Inventory



U.S. Department of Transportation  
Federal Highway Administration

July 2015  
Publication No. FHWA-HIF-15-006

### 3.4—Mechanical Systems Section

This section defines tunnel mechanical system elements and the methodology for determining total element quantities and condition state quantities. The following elements are included.

<b>Element Type</b>	<b>Element #</b>	<b>Element Name</b>	<b>Unit of Measure</b>
Ventilation System	10200	Ventilation System	each
	10201	Fans	each
Drainage and Pumping System	10300	Drainage and Pumping System	each
	10301	Pumps	each
Emergency Generator System	10400	Emergency Generator System	each
Flood Gate	10475	Flood Gate	each

<b>Ventilation System</b>	
<u>Unit of Measure</u> Each	<u>Element Number</u> 10200
<u>Specification</u>	<u>Commentary</u>
<p>Record this element for all ventilation systems. This element describes the components that provide the supply of fresh air to the tunnel while removing stale air and contaminants.</p> <p>The total quantity for ventilation system is the sum of all the ventilation systems.</p>	<p>The ventilation system may include the following subcomponents: Fans - Fan Motors, Fan Controller, Airways, Sound Attenuators, Dampers, Damper Motor, Damper Controller, Air Quality Monitoring Equipment (CO), Control Panels and Conduit.</p> <p>Damper inspection should also include a review of the maintenance records for each piece of equipment and note any special or frequent maintenance problems.</p> <p>For this element, a separate ventilation system is considered to be one system. Tunnels with twin bores may have separate ventilation systems and would be considered as two. Some tunnels may have a ventilation system at each portal that work independently and would also be considered as two.</p>

### Condition State Definitions

<b>Defect</b>	<b>Condition State 1</b>	<b>Condition State 2</b>	<b>Condition State 3</b>	<b>Condition State 4</b>
System Condition	The system is in good condition – no notable distress.	The system is in fair condition – isolated breakdowns or deterioration.	The system is in poor condition – widespread deterioration or breakdowns reducing operational capacity, without impacting the serviceability of the element or tunnel.	The condition warrants evaluation to determine the effect on serviceability of the element or tunnel or the evaluation has determined there is an impact on the serviceability of the element or tunnel.

<b><i>Electrical Distribution System</i></b>	
<u>Unit of Measure</u> Each	<u>Element Number</u> 10500
<u>Specification</u>	<u>Commentary</u>
<p>Record this element for all electrical distribution systems. The electrical distribution system consists of the electrical equipment, wiring, conduit, and cable used for distributing electrical energy from the utility supply (service entrance) to the line terminals of utilization equipment.</p> <p>The total quantity for electrical distribution system is the sum of all the electrical distribution systems.</p>	<p>The electrical distribution system may include the following subcomponents: Switchgear, Unit Substations, Switchboard, Motor Control Centers, Starters, Transformers, Transfer Switches, Panelboards, Conduits and Raceways, and Electrical Outlets/Receptacles.</p> <p>For this element, a separate electrical distribution system is considered to be one system. Tunnels with twin bores may have separate electrical distribution systems and would be considered as two.</p>

**Condition State Definitions**

<b>Defect</b>	<b>Condition State 1</b>	<b>Condition State 2</b>	<b>Condition State 3</b>	<b>Condition State 4</b>
System Condition	The system is in good condition – no notable distress.	The system is in fair condition – isolated breakdowns or deterioration.	The system is in poor condition – widespread deterioration or breakdowns reducing operational capacity, without impacting the serviceability of the element or tunnel.	The condition warrants evaluation to determine the effect on serviceability of the element or tunnel or the evaluation has determined there is an impact on the serviceability of the element or tunnel.

<b><i>Fire Detection System</i></b>	
<u>Unit of Measure</u> Each	<u>Element Number</u> 10650
<u>Specification</u>	<u>Commentary</u>
<p>Record this element for all fire detection systems. These systems consist of control panels, initiating devices (heat and smoke detectors, pull-stations, etc.), notification appliances (strobes, horns, etc.), wiring, conduit, and cable used to detect a fire in the tunnel.</p> <p>The total quantity for fire detection system is the sum of all the fire detection systems.</p>	<p>The fire detection system may also include the following subcomponents: sensors, controls, and alarms.</p> <p>For this element, a separate fire detection system is considered to be one system. Tunnels with twin bores may have separate fire detection systems and would be considered as two.</p>

### Condition State Definitions

<b>Defect</b>	<b>Condition State 1</b>	<b>Condition State 2</b>	<b>Condition State 3</b>	<b>Condition State 4</b>
System Condition	The system is in good condition – no notable distress.	The system is in fair condition – isolated breakdowns or deterioration.	The system is in poor condition – widespread deterioration or breakdowns reducing operational capacity, without impacting the serviceability of the element or tunnel.	The condition warrants evaluation to determine the effect on serviceability of the element or tunnel or the evaluation has determined there is an impact on the serviceability of the element or tunnel.
Detection Sensor Operations (heat and smoke detectors)	All detection sensors are operational.		Detection sensors are not operational in one zone.	Detection sensors are not operational in multiple zones.

<b>Fire Protection System</b>	
<u>Unit of Measure</u> Each	<u>Element Number</u> 10700
<u>Specification</u>	<u>Commentary</u>
<p>Record this element for all fire protection systems. These systems consist of fire extinguishers, hose connections, storage tanks, fire hydrants, building sprinklers, pumping systems, piping, circulating pumps, and hose reels used as fire protection in the tunnel.</p> <p>The total quantity for fire protection system is the sum of all the fire protection systems.</p>	<p>The fire protection system may include the following subcomponents: main fire pump, pressure maintenance/jockey pump, dry pipe valve, valves and tamper switches, storage tanks, tunnel stand pipe, pressure relief and air release valves, backflow prevention, hose stations, hose reels, building sprinklers, fire department connections and fire hydrants.</p> <p>For this element, a separate fire protection system is considered to be one system. Tunnels with twin bores may have separate fire protection systems and would be considered as two.</p>

**Condition State Definitions**

<b>Defect</b>	<b>Condition State 1</b>	<b>Condition State 2</b>	<b>Condition State 3</b>	<b>Condition State 4</b>
System Condition	The system is in good condition – no notable distress.	The system is in fair condition – isolated breakdowns or deterioration.	The system is in poor condition – widespread deterioration or breakdowns reducing operational capacity, without impacting the serviceability of the element or tunnel.	The condition warrants evaluation to determine the effect on serviceability of the element or tunnel or the evaluation has determined there is an impact on the serviceability of the element or tunnel.

<b><i>Emergency Communication System</i></b>	
<u>Unit of Measure</u> Each	<u>Element Number</u> 10750
<u>Specification</u>	<u>Commentary</u>
<p>Record this element for all emergency communication systems. The components of the emergency communication system include the communication device itself (i.e. intercom, radios, cell-phone), receivers, wiring, exchange devices, etc.</p> <p>The total quantity for emergency communication system is the sum of all the emergency communication systems.</p>	<p>The emergency communications system may also include the following subcomponents: signs, controllers, speakers and audio input equipment.</p> <p>For this element, a separate emergency communication system is considered to be one system. Tunnels with twin bores may have separate emergency communication systems and would be considered as two.</p>

### **Condition State Definitions**

<b>Defect</b>	<b>Condition State 1</b>	<b>Condition State 2</b>	<b>Condition State 3</b>	<b>Condition State 4</b>
System Condition	The system is in good condition – no notable distress.	The system is in fair condition – isolated breakdowns or deterioration.	The system is in poor condition – widespread deterioration or breakdowns reducing operational capacity, without impacting the serviceability of the element or tunnel.	The condition warrants evaluation to determine the effect on serviceability of the element or tunnel or the evaluation has determined there is an impact on the serviceability of the element or tunnel.



<b>Traffic Sign</b>	
<u>Unit of Measure</u> Each	<u>Element Number</u> 10850
<u>Specification</u>	<u>Commentary</u>
<p>Record this element for all traffic signs. These elements consist of the traffic sign and supports. Signs for pedestrians, variable message signs and lane signals are not covered under this element.</p> <p>The total quantity for traffic signs is the sum of all the traffic signs.</p>	<p>The MUTCD Chapter 2 contains the requirements for the shape and wording of regulatory, warning and guide signs on a highway or road. It also contains requirements for maintaining minimum retroreflectivity of signs.</p>

### Condition State Definitions

<b>Defect</b>	<b>Condition State 1</b>	<b>Condition State 2</b>	<b>Condition State 3</b>	<b>Condition State 4</b>
Component Supports	No deficient support conditions.	Loose anchorage or component housing connection hardware.	Missing anchorage or component housing connection hardware which does not result in an unstable situation.	Failed anchorage or component connection hardware which results in an unstable situation.

# Appendix I

## 2017 In-Depth Inspection for Tunnel No. 00773

This page intentionally left blank.

**CONNECTICUT  
DEPARTMENT OF TRANSPORTATION**



**STATE PROJECT NO. 170-3413 (NHS)  
BRIDGE SAFETY INSPECTION**

**TUNNEL NO. 00773  
WEST ROCK RIDGE**

**OVER  
ROUTE 15**

**WOODBIDGE, CONNECTICUT**

**IN-DEPTH INSPECTION  
JANUARY 30, 2017**

**LAST DAY OF INSPECTION: MAY 26, 2017**



*Prepared By:*

**Michael Baker**  
INTERNATIONAL

**Michael Baker International, Inc.**  
500 Enterprise Drive, Suite 2B  
Rocky Hill, CT 06067

Structure No. 00773 Town Woodbridge

Inspectors Michael Baker International, Inc. (TK, KT) Date 1/30/2017

**TABLE OF CONTENTS**

<u>LOOSE FORMS (not bound in report)</u>	<u>No. of Sheets Enclosed</u>
Maintenance Memo .....	--
Flagging Memos .....	--
BRI-11, Seismic Screening Data Sheet .....	--
Plan Sheets: Project No. 185-90, 1947	Check here if already on file: <input type="checkbox"/>


---

<u>Bound Report Pages</u>	<u>Number of Sheets</u>
Title Cover Sheet.....	1
Table of Contents .....	1
Report Title Page.....	1
Location Map.....	1
SI & A Form and Tunnel Elements.....	5
Sketches.....	295
Photo Sheets.....	21
Back-up Material.....	11

Tunnel No. 00773, West Rock Ridge over Route 15, Woodbridge

Inspected By: Michael Baker International, Inc.

Date: 01/30/2017



*Professional Certification: I hereby certify that this report, including all of its contents, has been approved by me, and that I am a duly licensed professional engineer under the laws of the State of Connecticut.*

Signature:

License No.: CT PE 20004

Date: 06/28/2017



## LOCATION MAP

### Tunnel 00773: West Rock Ridge over Route 15



LOCATION DATA

Tunnel Number (I.1): 00773  
Tunnel Name (I.2): Heroes Tunnel  
Place Code (I.5): Woodbridge  
County Code (I.4):  
State Code (I.3): 09 Connecticut  
Hwy Agency District (I.6): New Haven  
Latitude (I.13): 41.34  
Longitude (I.14): 72.97  
Owner (C.1): State Highway Agency  
Operator (C.2): State Highway Agency  
Urban Code (C.8): New Haven

BORDER TUNNEL

State / Country Code (I.15): Not Applicable (P)  
Fin Responsibility (I.16):  
Border Number (I.17):  
Urban Code (C.8): Not Applicable (P)

TUNNEL AGE

Year Built (A.1): 1949  
Year Rehabilitated (A.2):

ROUTE DATA

Route Number (I.7): 00015  
Facility Carried (I.10): Route 15 - Heroes Tunnel  
LRS Route ID (I.11): A015  
LRS Milepost (I.12): 47.13  
Route Direction (I.8): Two route directions  
Direction of Traffic (C.3): 2-way traffic  
Total # of Lanes (A.3): 4  
AADT (A.4): 77,300  
ADTT (A.5): 0  
Year of AADT (A.6): 2015  
Detour Length (A.7): 5

GENERAL INSPECTION DATA

Load Posting Status (L.4): A - No Restriction  
Haz Mat Restriction (L.11): 1 - Yes  
Other Restriction (L.12): 1 - Yes  
Portal Island Protection (N.3): 0 - Nav prot not req.

GEOMETRY & RESTRICTION DATA

Number of Bores (S.1): 2  
Tunnel Shape (S.2): Horseshoe  
Portal Shape (S.3): Horseshoe  
Ground Conditions (S.4): Rock  
Complex (S.5): Not Complex  
Tunnel Length (G.1): 1,200  
Min Vert Clearance (G.2): 14.00  
Roadway Width (G.3): 23.50  
Left Sidewalk Width (G.4): 2.50  
Right Sidewalk Width (G.5): 2.50  
Height Restriction (L.10): Yes  
Under Nav Waterway (N.1): No navigable waterway  
Nav Waterway Clear (N.2): 0.00

LOAD RATING DATA

Load Rating Method (L.1): Not required  
Inventory Rating (L.2):  
Operating Rating (L.3):  
Posting - Gross (L.5):  
Posting - Axle (L.6):  
Posting - Type 3 (L.7):  
Posting - Type 3S2 (L.8):  
Posting - Type 3-3 (L.9):

ROUTE CLASSIFICATION

Route Type (I.9): State highway  
Service in Tunnel (A.8): Highway  
Toll (C.4): No tolls  
NHS Route (C.5): Route is on the NHS  
STRAHNET Route (C.6): Not a STRAHNET route  
Functional Class (C.7): Principal - Other

INSPECTION SCHEDULE

Routine Insp Target (D.1):  
Current Inspection Date: 2017-01-30  
Routine Insp Date (D.2):  
Routine Insp Freq (D.3): 24  
In-Depth Scheduled (D.4): 0  
Damage Inspection (D.5):  
Special Scheduled (D.6): 0



Tomasz Kurasz

Element Number	Str Unit	Total	CS1	CS2	CS3	CS4
<b>Structure Unit:</b>						
10001	Cast-in-Place Conc Tunnel	124,425.00	99,732.00 (80%)	7,468.00 (6%)	17,029.00 (14%)	196.00 (0%)
<p>The overall condition of the tunnel is poor (NBI rating = 4). The concrete tunnel liner has hollow areas up to 71 square feet (Southbound tunnel ceiling at between STA's 710+00 and 710+25) and spalls with and without exposed rebar up to 120 SF x 3" deep (Northbound tunnel ceiling at STA 719+00). There are other smaller but deeper spalls, up to 63 square feet x 7" deep (Southbound tunnel ceiling between STA 719+50 – 719+75). Numerous spalls have adjacent hollow areas and/or the concrete inside the spall is hollow at some locations. Also, spalls have de-bonded rebar at isolated locations and/or isolated rebar with up to 50% section loss (estimated). There are random areas with efflorescence, punky concrete and light to severe scale. There are isolated drilled core holes in the ceiling and isolated locations with embedded remnants of the wood forms. There are random linear cracks and areas of map cracking. The linear cracks are open up to 0.125", have random efflorescence, water leakage and/or adjacent minor spalling. Both tunnels have longitudinal hairline cracking with random efflorescence along the crown throughout (only shown on field sketches if crack has efflorescence, rust or is 0.012" wide or more). There are numerous previously patched transverse cracks in the ceiling. Some of these cracks extend all the way through the walls to sidewalks. These cracks have typically re-opened, have up to heavy efflorescence and/or water leakage. There are other concrete patches throughout. These patches have areas of punky concrete, cracking, efflorescence, leakage, hollow areas, varying degrees of scale and spalls. There are transverse construction joints spaced at +/-40 feet and longitudinal construction joints between the ceiling and wall portions of the liner. Along joints, there are cracks, up to heavy scale, spalls with and without exposed rebar, hollow areas and areas of up to heavy efflorescence. All hollow areas are marked. All loose concrete has been removed. See field sheets 7-295 and photos 4-16 &amp; 39.</p>						
80000	Leakage	163.00	0.00 (0%)	23.00 (14%)	56.00 (34%)	84.00 (52%)
82100	Delamination / Spall / Pa	19,212.00	0.00 (0%)	4,926.00 (26%)	14,174.00 (74%)	112.00 (1%)
82101	Exposed Rebar	66.00	0.00 (0%)	28.00 (42%)	38.00 (58%)	0.00 (0%)
82102	Efflorescence / Staining	1,427.00	0.00 (0%)	1,292.00 (91%)	135.00 (10%)	0.00 (0%)
82103	Cracking (Concrete Liner)	3,825.00	0.00 (0%)	1,199.00 (31%)	2,626.00 (69%)	0.00 (0%)
10031	Concrete Cross Passage	48.00	33.00 (69%)	15.00 (31%)	0.00 (0%)	0.00 (0%)
<p>This item is being used to describe the machinery control room. The control room has efflorescence, spalling up to 2" deep and hollow areas covering up to 50% of the exterior walls/liner surface. The interior tile walls have damaged tiles and up to 2' diameter holes (possibly from removal of the ventilation system). All internal doors are missing. All fans, duct work and components of electrical/fire detection systems are removed. Water drains down the concrete lined vertical vent shafts in the ceiling and ponds on the room floor. There is random construction debris on the floor (from ventilation system removal) and minor spalling. The iron bar picket fence at the entrance to the control room in the tunnel has up to heavy laminated rust with up to 50% section loss to components. The concrete fence bases have spalls up to 8 square feet x full depth with exposed rebar. See field sheet 5 and photos 25-28.</p>						
82100	Delamination / Spall / Pa	15.00	0.00 (0%)	15.00 (100%)	0.00 (0%)	0.00 (0%)
10055	Masonry Portal	8,500.00	6,483.00 (76%)	1,965.00 (23%)	52.00 (1%)	0.00 (0%)

Tomasz Kurasz

The reinforced concrete portal walls with stone masonry fascia have random areas with cracked joint mortar, isolated vertical hairline cracks and minor chips in the stones. Approximately 20% (average) of mortar in the portal walls has separations, is deteriorated and/or is missing up to 8" deep (worst along the top of the wall/below the cap stones, no loose stones). There are random areas of vegetation growth in the joints typically near the top of the walls, random areas of efflorescence from the mortar joints and surface staining at the stones. Three cap stones at the south portal over the southbound tunnel are horizontally misaligned/pushed toward the roadway up to 1.5" due to a tree/vegetation growth behind and against these stones, pushing them outward. Isolated arch ring stones have horizontal hairline cracks (non-structural) with isolated rust staining. The south portal ring for the northbound tunnel has an 18" long x 1" wide x 6" deep spall/void. There is heavy efflorescence build up along the longitudinal joints between the three arch rings and random missing mortar along these joints up to 1' deep, typically worst at the arch bases. Random areas along the joints have deteriorated/punky joint material. The vertical joints between the portal walls and joints with wingwalls have random loose/missing joint filler up to full height. There are isolated locations with vegetation/vine growth in these vertical joints that spreads onto the portal walls. The concrete backside of the portal walls visible at the upper portions have random hairline cracking with and without efflorescence. Wingwalls are in similar condition as portal walls. There are chain-link fences behind the portal walls on top. The north fence is missing sections at the west end. Also, the concrete post bases are partially exposed due to apparent past erosion. Fence appears secure. Area adjacent to the fence is paved. See field sheets 3-4 and photos 2-3 and 17-20.

82102	Efflorescence / Staining	300.00	0.00 (0%)	250.00 (83%)	50.00 (17%)	0.00 (0%)
84000	Mortar Breakdown	1,700.00	0.00 (0%)	1,700.00 (100%)	0.00 (0%)	0.00 (0%)
84001	Split/Spall	2.00	0.00 (0%)	0.00 (0%)	2.00 (100%)	0.00 (0%)
84002	Masonry Displacement	15.00	0.00 (0%)	15.00 (100%)	0.00 (0%)	0.00 (0%)
10111	Concrete Slab-on-Grade	56,400.00	54,830.00 (97%)	1,570.00 (3%)	0.00 (0%)	0.00 (0%)
	Not visible; paved over. Condition states are based on condition of the bituminous wearing surface. See "Asphalt Wearing Surface" item. See field sheet 7.					
82109	Cracking (RC)	1,570.00	0.00 (0%)	1,570.00 (100%)	0.00 (0%)	0.00 (0%)
10158	Asphalt Wearing Surface	56,400.00	54,830.00 (97%)	1,570.00 (3%)	0.00 (0%)	0.00 (0%)
	The asphalt wearing surface has random transverse cracks, typically corresponding to locations of the construction joints at the liner. Random cracks have adjacent areas with breaking up bituminous and/or potholes up to 18" x 4" x 2" deep. See field sheet 7 and photo 21.					
85003	General Condition (WS)	1,551.00	0.00 (0%)	1,551.00 (100%)	0.00 (0%)	0.00 (0%)
86004	Effectiveness (WS)	19.00	0.00 (0%)	19.00 (100%)	0.00 (0%)	0.00 (0%)
10161	Concrete Traffic Barrier	4,740.00	4,388.00 (93%)	46.00 (1%)	306.00 (7%)	0.00 (0%)
	Concrete safety walks are rated under this item. The concrete safety walks have light scale, minor chipping, sand/debris accumulation and hairline cracks. There are random transverse cracks up to 1" wide, and spalls up to 5" deep (Northbound tunnel, east wall at STA 712+37). At random locations PVC wall weeps drain on the safety walk causing deterioration. There are random bituminous patches at the locations where the utility access covers used to be. The safety walks typically have spalling along these patches, as well as along plates/utility covers along the safety walks and curbs. See field sheets 7, 56-151 & 200-295 and photos 22-24.					
82100	Delamination / Spall / Pa	140.00	0.00 (0%)	2.00 (1%)	138.00 (99%)	0.00 (0%)
82109	Cracking (RC)	212.00	0.00 (0%)	44.00 (21%)	168.00 (79%)	0.00 (0%)
10200	Ventilation System	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)

Tomasz Kurasz

The tunnel had a forced air ventilation system. The system was/is located in the control room at mid-length of the tunnels and consisted of four, 72" diameter fans, four electric motors (to control the fans), four, six foot diameter steel ducts (from fans to concrete shafts), four, 6 foot diameter x 180' high vertical concrete lined shafts (one per each fan), and an octagonal shaped exhaust house on top of the tunnel. The ventilation system was originally activated by removing any of the fire extinguishers from the tunnel walls and/or by elevated levels of the carbon monoxide inside the tunnel detected by carbon monoxide detectors located along tunnel walls. The fans, ducts, fire extinguishers and carbon monoxide detection devices are missing/have been removed in the past. Water is draining down the vent shafts and ponding on the control room floor. Ventilation house: There is a reinforced concrete with stone masonry fascia ventilation house on top of West Rock. The copper roof material is missing (daylight is visible from inside). Water seeps between wood roof planks and ponds on floor. The steel roof overhang has up to heavy rust and up to ½" impacted rust at the sheet metal splices. The aluminum louvers are mostly missing at the back side of the house, and the exposed steel chain-link fences/screens behind the louvers have up to 2 square foot openings. The steel entry door has up to heavy rust and was open at the time of inspection. There is steel grating on top of the vent shafts covered with tarp. The tarp is secured with timber planks. There is random timber and other debris inside the vent house. The access ladder and fall protection barrier along the entrance opening in the floor have up to heavy rust. Additionally, the steel fall protection barrier is missing/rusted out at one side. The roof-supporting beams have up to moderate rust. The concrete perimeter wall inside vent house has random graffiti and honeycombing w/exposed rebar. There is isolated bird debris inside. See field sheets 5-6 and photos 25-32.

86007	System Condition	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
10201	Fans	4.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	4.00 (100%)
	Originally, there were four 72" diameter fans (two per each tunnel) controlled by electric motors. These fans were located in the control room located at mid-length of the tunnel. The fans were activated by removal of any fire extinguisher from the tunnel wall and/or by elevated levels of the carbon monoxide gas in the tunnels. All fans are missing/have been removed in the past. See field sheets 5-6 and photos 25-27.					
86017	Fan Operation	4.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	4.00 (100%)
10300	Drainage and Pumping S:	2.00	0.00 (0%)	2.00 (100%)	0.00 (0%)	0.00 (0%)
	The drainage systems consist of an 8" diameter precast concrete pipe embedded in the inboard sidewalks and a 15" diameter precast concrete pipe embedded along the outboard sidewalks. There are 2.5" diameter steel weeps that extend from wall bases and drain into these pipes. These pipes and weeps are not visible. There are catch basins along the outboard sidewalks that feed into the 15" diameter pipe. There are random locations with PVC weeps along the wall bases that drain on top of the sidewalks (some are filled with dirt). These appear to be a retrofit. Random locations with active leakage and evidence of past leakage along the walls and weeps filled with dirt suggest that the drainage system is partially dysfunctional. There is a total of 2 fully clogged and 2 partially clogged (30%) catch basins in the northbound tunnel only. All catch basins in the southbound tunnel are clear. The previously reported catch basins along the access road (Baldwin Drive) were not seen. See field sheets 56-151 & 200-295 and photos 33-34.					
86007	System Condition	2.00	0.00 (0%)	2.00 (100%)	0.00 (0%)	0.00 (0%)
10500	Electrical Distribution Sys	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
	Originally, there were electrical distribution systems embedded below the sidewalks. These systems supplied power to the fire detection and fire protection systems, tunnel emergency lightning and wall phones. The electrical distribution systems are missing have been removed in the past. There are random bituminous filled utility access openings in the sidewalks (previously having steel plate cover). There are junction boxes with conduits ached to both portal walls. These junction boxes have missing covers and exposed wires. The steel conduits have up to laminated rust and rusted through holes exposing wires. PVC conduits have isolated broken areas with exposed wires. It is not clear if these conduits and junction boxes are functional and if they are part of the tunnel lightning system. There are disconnected junction boxes with opened access doors and exposed wires inside the control room. These boxes appear to be a part of the previous ventilation and fire detection system. See field sheets 5-6 & 8-295 and photos 35-39.					
10600	Tunnel Lighting System	2.00	0.00 (0%)	2.00 (100%)	0.00 (0%)	0.00 (0%)
	The tunnel lighting system consists of electrical conduits with junction boxes supplying power to the tunnel lights and light bulbs. The conduits along the southbound tunnel west wall have random locations with rusted out/missing supports and/or are disconnected at the couplers (no exposed wires). There are approximately of 30 locations with rusted out utility supports and/or disconnected utilities at the couplers. There is a total of 58 light fixtures with nonfunctioning light bulbs in both tunnels. Also, approximately 62 lights have broken lenses. See field sheets 8-295 and photos 4, 5, 8, 10 & 40.					

Tomasz Kurasz

86007	System Condition	1.00	0.00 (0%)	1.00 (100%)	0.00 (0%)	0.00 (0%)
10601	Tunnel Lighting Fixture	306.00	306.00 (100%)	0.00 (0%)	0.00 (0%)	0.00 (0%)
	There are light fixtures along the ceiling crown in both tunnels. These lights have random missing junction box covers exposing wires. See field sheets 8-55 & 152-199 and photos 4, 5, 8, 10 & 40.					
86008	Component Supports	1.00	1.00 (100%)	0.00 (0%)	0.00 (0%)	0.00 (0%)
86009	Component Housing or E	1.00	1.00 (100%)	0.00 (0%)	0.00 (0%)	0.00 (0%)
10650	Fire Detection System	2.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	2.00 (100%)
	The fire detection system originally consisted of carbon monoxide sensors located in designated wall niches in both tunnels (four total), carbon monoxide recorder and analyzer controls located in the control room (two total), and emergency caution and stop lights along tunnel walls. The carbon monoxide detectors activated control room vent fans for the concerned tunnel and turned on the traffic lights to caution if the carbon monoxide levels in that tunnel were elevated. In the case the carbon monoxide levels would continue to rise and be at very high levels, these detectors would activate vent fans in both tunnels and change the traffic lights to stop. All carbon monoxide detectors and recorder control and analyzers are missing/have been removed in the past. See field sheets 5, 6, 56-151 & 200-295 and photos 37-38 & 42.					
86007	System Condition	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
86014	Detection Sensor (Operat	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
10700	Fire Protection System	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
	The fire protection system originally consisted of fire extinguishers located in designated wall niches at equal intervals in each tunnel (four extinguishers total). Removal of any fire extinguisher would have automatically changed the traffic light in the tunnel concerned to caution and started the ventilating fans in the control room for that tunnel. Also, there were additional fire extinguishers attached to the walls in the control room (six total). All fire extinguishers are missing/have been removed in the past. See field sheets 5, 6, 56-151 & 200-295 and photo 14.					
10750	Emergency Communicati	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
	The emergency communication system originally consisted of telephone units located in designated wall niches in each tunnel (two phones in each tunnel). The telephones are missing/have been removed in the past. See field sheets 5, 6, 56-151 & 200-295 and photos 25 & 41.					
86007	System Condition	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)
10850	Traffic Sign	12.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	12.00 (100%)
	Caution and stop emergency lights are rated under this element. The caution and stop emergency lights were initially installed for emergency use along the tunnel walls. Removal of any fire extinguisher and/or elevated levels of carbon monoxide in the tunnel (detected by the Fire Detection System) would have automatically changed the traffic lights in the tunnel concerned to caution. High levels of the carbon monoxide would change the light to stop. All traffic lights are missing/have been removed in the past. See field sheets 5, 6, 56-151 & 200-295 and photo 41.					
86008	Component Supports	1.00	0.00 (0%)	0.00 (0%)	0.00 (0%)	1.00 (100%)

